

PowerBook Duo 270c

Features

Power and speed

33-MHz 68030 microprocessor

33-MHz 68882 math coprocessor

· 4MB of RAM, expandable to 32MB

Display
 Bright, backlit, active-matrix display
 8.4-in. diagonal

Two display modes: 640 by 400 with thousands of colors; 640 by 480 with 256 colors

Battery life

· 2 to 4 hours on a single charge

Expansion

- Built-in high-speed serial port for peripheral devices, including LocalTalk network and printers
- Slots for internal modem and RAM

Docking connector
 Optional PowerBook Express Modem

Features Built Into Every PowerBook

Runs thousands of Macintosh

applications Easy to set up, learn, use, and expand

System software

System software version 7, with multitasking, file sharing, Balloon Help, TrueType fonts, and more

Networking

Built-in LocalTalk networking

File sharing without a dedicated server

Compatibility

Reads and writes Macintosh, Windows, MS-DOS, OS/2, and ProDOS floppy disk formats with appropriate software

For users looking for light weight and small size in a powerful notebook computer, the Apple PowerBook Duo System is an excellent choice. The PowerBook Duo offers high-speed processors, active matrix screens, large RAM expansion, and desktop expansion—features normally found only on much larger, heavier systems-all in a package that weighs less than 5 pounds.

The PowerBook Duo 270c is Apple's top-of-the-line color PowerBook Duo computer and is the industry's first 16-bit color notebook. Its 8.4-inch, backlit, active-matrix display lets you work with your files in thousands of colors, providing the best screen image, performance, and color available in a notebook computer. Yet the PowerBook Duo 270c weighs just 4.8 pounds and fits easily into a briefcase.


The PowerBook Duo 270c is as powerful as many desktop computers because it combines the power of a 33-megahertz 68030 microprocessor with an additional math coprocessor. It also supports up to 32 megabytes of RAM, so you can work with multiple applications simultaneously.

With the PowerBook Duo 270c, you'll find all the connections you need to work anywhere—on the road, in a conference room, or at your desk. AppleTalk networking is built in, so you can connect to all the resources in an AppleTalk network, such as electronic mail, printers, and file servers. Add a modem and AppleTalk Remote Access software to gain full access to AppleTalk networks practically anywhere in the world.

The PowerBook Duo 270c can meet all your computing needs no matter where you are. It includes a standard-size keyboard, full-page-width display, and built-in trackball.

When you're back at the office, simply slide your PowerBook Duo notebook into any PowerBook Duo Dock. Instantly you're working with a complete Macintosh desktop system. There's nothing to reconfigure, no switches to flip, and no cables to connect.

The PowerBook Duo system lets you decide which capabilities of a desktop system you want, letting you invest in exactly the setup that suits your needs.





PowerBook Duo 270c

Ordering Information

PowerBook Duo 270c 4/240 Order No. M1752LL/A

- PowerBook Duo 270c computer with 4MB of RAM and internal 240MB hard disk
- Battery and AC adapter System software version 7.1
- Complete setup, learning, and reference documentation
- Limited warranty

Optional PowerBook Duo 270

configuration
Order No. M2124LL/A

PowerBook Duo 270c computer with 12MB of RAM and internal PowerBook Duo Express Modem with Express Fax software

PowerBook Duo 4MB Memory Expansion Kit* Order No. M4184LL/A

PowerBook Duo 8MB Memory Expansion Kit* Order No. M4185LL/A

PowerBook Duo Fax/Data Modem (U.S., Canada, Japan) Order No. M0970LL/A

Express Modem for PowerBook Duo* (U.S., Canada, Japan) Order No. M4186LL/A

PowerBook Duo Rechargeable Battery Order No. M1835LL/A

PowerBook Duo AC Adapter Order No. M4174LL/A

PowerBook Duo Battery Recharger Order No. M4176LL/A

Apple HDI-30 SCSI Disk Adapter Order No. M2539LL/A

Apple HDI-30 SCSI System Cable Order No. M2538LL/A

*Dealer installation recommended

Technical Specifications

Microprocessor

- Motorola 68030, running at 33 MHz
- 68882 math coprocessor, running at 33 MHz

Memory

- Comes with 4MB of RAM
- Expands to up to 32MB of RAM with the addition of PowerBook Duo 4MB or 8MB Memory Expansion Kits, or third-party memory expansion cards

Disk storage
• One internal 240MB hard disk

- Display

 8.4-in. diagonal

 Backlit, active-matrix, color liquid crystal display,
- 640 by 480 pixels Two display modes: 640 by 400 with thousands of colors; 640 by 480 with 256 colors
- LED indicator when computer is in sleep mode

- Battery
 Nickel-metal-hydride High Capacity Type II battery provides 2 to 4 hours of computer use before
 Thereign is necessary. recharging is necessary

 EverWatch Battery Saver technology

Keyboard

- Built-in, 2.4-mm travel, 18-mm pitch
- Two-level tilt adjustment
- LED light when caps lock is engaged

19-mm diameter, dual-button trackball

CMOS custom-integrated circuit with long-life lithium battery

Microphone

Built-in omnidirectional electret; output voltage of 4 mV, peak-to-peak, at normal volume

- Power adapter port
- To the result of the result of
- modems, and other devices

 Port for optional internal modem

File-transfer options

- LocalTalk cables and System 7 file sharing Serial cable and System 7 file sharing Fax/data modem and AppleTalk Remote Access software
- Duo MiniDock with external Apple SuperDrive, SCSI disk adapter, and HDI-30 SCSI system cables Duo Dock internal Apple SuperDrive, optional internal hard drive, and HDI-30 SCSI system cable

Docking options

- PowerBook Duo Dock
 PowerBook Duo MiniDock
- PowerBook Floppy Adapter
 Docking systems from third-party vendors

· Optional internal PowerBook Express Modern sends and receives data at 14,400 bps and sends and receives faxes at 9,600 bps. Includes Express Fax software.

Magnesium subframe

Provides structural rigidity and heat sink

Sound generator

- Built-in speaker
 Apple Sound Chip provides monophonic 8-bit sound and is capable of driving stereo headphones or other stereo equipment with the same signal supplied to both channels through any optional PowerBook Duo Dock or PowerBook Duo Mini Dock

4-voice sound with 8-bit analog-to-digital conversion recording, sampled at 11 or 22 kHz

Disability access
CloseView, Easy Access, and visible-beep included with system software. These built-in solutions and third-party options provide alternative input and output devices for people with disabilities.

- Electrical requirements
 Line voltage: 85 to 270 VAC, RMS single phase, automatically configured
 Frequency: 47 to 63 Hz, single phase
 Power: 25 W maximum

ADB power requirements

Maximum current draw for all ADB devices is 100
A with Powerbook Duo MiniDock or PowerBook Floppy
Adapter or 500 mA with PowerBook Duo Dock (a maximum of three ADB devices is recommended)

Environmental requirements

- Operating temperature: 50° to 104° F (10° to 40°
- Storage temperature: -13° to 140° F (-25° to 60°
- Relative humidity: 20% to 80% noncondensing Operating altitude: 0 to 10,000 ft. (0 to 3,048 m) Maximum storage altitude: 15,000 ft. (4,722 m)

- Size and weight
 Thickness: 1.5 in. (3.8 cm)
- Width: 10.9 in. (27.7 cm) Depth: 8.5 in. (21.6 cm) Weight: 4.8 lb. (2.2 kg)

Apple Computer, Inc. 20525 Mariani Avenue Cupertino, CA 95014 (408) 996-1010 TIX 171-576

© 1993 Apple Computer, Inc. All rights reserved. Apple, the Apple logo, AppleTalk, LocalTalk, Macintosh, and ProDOS are trudemarks of Apple Computer, Inc., registered in the U.S. and other countries. Apple Desktop Bus, Apple SuperDrive, Balloon Help, PowerBook, PowerBook Duo, and TrueType are trademarks of Apple Computer, Inc. MS-DOS is a registered trademark of Microsoft Corporation. OS/2 is a trademark of International Business Machines Corporation. Mention of non-Apple products is for informational purposes only and constitutes neither an endorsement nor a recommendation. Apple assumes no responsibility with regard to the selection, performance, or use of these products. All understandings, agreements, or warranties, if any, take place directly between the vendors and the prospective users. September 1993. Product specifications are subject to change without notice. Printed in U.S.A. 1.0544LL/A