

The printing solution that's fast, flexible and built to last.



IBM 4230 and 4232 Serial Matrix Printer



Highlights

- ***Low-cost, flexible, heavy-duty dot matrix printing solution***
- ***Customizable operator panel***
- ***Flexible forms handling capabilities***
- ***Automatic forms loading and thickness adjustment***
- ***Very quiet for office use***

The IBM® 4230 and 4232 Serial Matrix Printers offer high speed, exceptional reliability and rugged durability which make them the right choice for the most demanding print environments and applications.

Enhanced productivity

With features such as auto-forms load, innovative forms handling, customizable operator panels and menu selections, IBM 4230 and 4232 printers can improve productivity and virtually eliminate user frustration, paper jamming and costly paper loss.

The customizable operator panel option allows you to easily lock out specific buttons or make them active again depending on your specific environment. Custom setup profiles allow users to store and retrieve as many as four different menus of printer setup values. This means users can switch instantly from one application to another, thereby improving user productivity and eliminating adjustment errors.

Printing where you need it

At only 53 dBA, the IBM 4230 and 4232 print more quietly than many laser printers, making them suitable for virtually any business environment. And with their small footprints, the printers can be placed wherever a need for printing exists. The printers offer either a coaxial, twinaxial, coaxial/ASCII, twinaxial/ASCII or ASCII-only attachment, maximizing flexibility while providing a wide range of printer placement options.

Versatile forms handling

The ability to use cutsheet paper allows for the advantage of NLQ printing on letter-head paper for business correspondence applications. The automatic forms thickness adjustment feature saves users from having to manually adjust the printhead gap and helps ensure consistent, high-quality forms printing and improved printhead reliability.

Worldwide service and support

In addition to the standard warranty, IBM offers comprehensive service and support that is available 24x7x365. Call (800) 358-6661 or contact your local IBM Printing Systems representative for details.

Designed specifically for the 4230/4232, IBM printer ribbons can help maximize printer performance.



© International Business Machines Corporation 2001

IBM Printing Systems
Dept. HT7/001H
P.O. Box 1900
Boulder, Colorado 80301-9191

Printed in the United States of America
9-01
All Rights Reserved

References in this publication to IBM products or services do not imply that IBM intends to make them available outside the United States.

IBM hardware products are manufactured from new parts, or new and used parts. Regardless, our warranty terms apply.

Visit the IBM Printing Systems Web site at ibm.com/printers for more information.

The IBM home page can be found on the Internet at ibm.com

IBM 4230/4232 Serial Matrix Printers at a glance

For expanded specifications visit: ibm.com/printers/4230 and ibm.com/printers/4232

Print Speed	4230 Model xx	4230 Model xx2	4230 Model xx3	4232
—Fast draft mode:	375	480	600	600
—DP mode:	300	400	400	400
—DP text mode:	150	200	200	200
—NLQ mode:	75	100	100	100

Print Options

Vertical spacing:	—6 or 8 lines per inch (lpi) selectable from operator panel for text
Horizontal spacing:	—10, 12, 15, 16.7, 17.1 and 20 characters per inch —Proportional spacing is available in DP text and NLQ modes
Maximum print line:	—13.6"
Bar codes:	—Postnet, UPC-A, UPC-E, EAN-13, Code 3 of 9, Code 128, Interleaved 2 of 5, Codabar, MSL, Industrial 2 of 5 and Matrix 2 of 5

Paper Handling

- Operator-changeable forms modules:
- Continuous forms up to six parts
 - Cutsheet
 - Pull tractor support for batch printing
 - Document-on-demand/zero tear-off
 - Automatic forms loading and thickness adjustment

Paper Sizes

Continuous forms:	—3" to 15" Width	—3" to 14" Length
Cutsheet forms:	—3" to 15" Width	—5" to 14" Length

Interfaces

4232 Serial (RS-232C, RS-422A) and Parallel (Centronics Parallel) available
4230 Serial, Parallel, Twinax and Coax SCS or IPDS
4230, 4232 Ethernet via IBM's Network Print Server

Physical Characteristics	Depth	Height	Width	Weight
	15.6" (396mm)	12.4" (315mm)	26.75" (655mm)	45 lbs. (20.4kg)

Power Requirements

—100-127 V, 1-phase, 200-240V, 1-phase			
Consumption:	Idle:	Max.	Typical
120 VAC 60 HZ	40 Watts	90 Watts	90 Watts
220 VAC 50 HZ	40 Watts	90 Watts	90 Watts

Environmental Conditions

Noise emission:	—Printing: 53 dBA	—idling: 30 dBA
-----------------	-------------------	-----------------

Supplies

- Ribbon cartridges
- Auto-inking ribbon, P/N-1040580, 15-million character life
 - High-yield ribbon, P/N-1040440, 6-million character life

The following terms are trademarks of IBM Corporation in the United States or other countries or both: IBM.

Other company, product and service names may be trademarks or service marks of others.