

IBM Infoprint 2000 Advanced Function Printing System



Highlights

- **Up to 110 impressions per minute print speed at 600 dpi resolution**
- **Supports 240, 300 and 600 dpi native AFP/IPDS printing**
- **Powerful IBM @server pSeries technology with easy-to-use Java-based operator interface**
- **Up to 8000-sheet input capacity and output capacity**

Help your enterprise become more e-business ready with the IBM® Infoprint® 2000 Advanced Function Printing System, which extends the capabilities of a proven, high-production digital system. A powerful IBM server and new controller accelerate information flow and can help improve organizational efficiency — reliably and cost effectively.

Boost your output power

Operate and compete at a new level. The Infoprint 2000 AFP System offers instantaneous delivery of information, global data access, secure output and reliable job completion. Reliability enhancements help ensure maximum throughput and uptime.

By combining advanced hardware and software components, the Infoprint 2000 offers you a complete native Advanced Function Printing™ (AFP™) solution that delivers exceptional flexibility and control. The solution includes an IBM @server pSeries™-based Advanced Function Common Control Unit™ (AFCCU™), AFP architecture, Intelligent Printer Data Stream™ (IPDS™) and a powerful print engine. AFP and IPDS provide essential e-business capabilities of electronic document creation and manipulation as well as bi-directional communications. You also receive built-in support for SNMP and stapling, and the capability of intermixing color documents with monochrome printing.¹

It's not about the document, it's about your information

Capitalize on new technology

At its best, technology provides strategic operational advantages. The Infoprint 2000 was built from the ground up as a fully digital production system.

A user-friendly Java™-based console features an innovative touch-screen interface, and includes keyboard and mouse support. And to help ensure that your output provides benchmark quality, the Infoprint 2000 operates at 600 dpi resolution with automatic 240/300 dpi conversion.

Enhance productivity and quality

Imagine complex jobs that run at close to rated speed, superior halftones and robust collation and stapling that require minimal operator intervention. The feature-rich, fine-tuned Infoprint 2000 sets a new standard for high-speed, benchmark-quality printing:

- *Electronic, system-based data storage and management*
- *Variable intensity printhead*
- *High-resolution "Write Black" imaging technology*

- *Short, straight paper path*
- *Vacuum feed adjustment for paper weight*
- *Active registration*
- *Automated image quality adjustment*
- *Trayless duplexing*

Do more with IBM Infoprint Manager

Streamline print management and free your staff to concentrate on more important operational issues.

With Infoprint Manager, you can:

- *Submit jobs electronically*
- *Reduce incompatibility issues by processing input from multiple datastreams (PostScript®, PCL, AFP, PDF, TIFF and more)*
- *Maintain productivity by distributing automatically different job types and job sizes to appropriate output devices*
- *Save user time and reduce costs associated with job resends with automatic page- and job-level recovery*
- *Store, retrieve, view and manage text, graphics, images and more. Then, deliver output via hardcopy, fax, e-mail and the Internet at e-business speed.*

Worldwide service and support

In addition to the standard warranty, preventive maintenance and remote diagnostics offered with the Infoprint 2000, IBM offers customizable, comprehensive, global service and support including 7x24 coverage. Call (800) 358-6661, option 3, or contact your local IBM Printing Systems representative for details.

Maximize performance with IBM supplies and paper

Optimize your Infoprint 2000 with genuine IBM supplies and paper. Contact IBM at ibmprint@us.ibm.com or your local dealer for details.

For more information

To learn more about the Infoprint 2000 and its ability to help you become more e-business ready, contact your local IBM sales representative or visit ibm.com/printers

Hardware Components	System Control Subsystem (printer controller)		
	—IBM @server pSeries	—333 MHz	—256 MB RAM
	—9.1 GB hard disk	—32x CD-ROM	—3.5" 1.44 MB Floppy Disk Drive
	—MIP Interface Board	—Ethernet Hub	—Modem 56 KB (Remote Diagnostics)
	—T55 15" Flat Panel Monitor	—Powerful Graphics Adapter	
	Marking Image Processor (MIP)		
	—512 MB RAM	—AFCCU/Marking Engine Interface	
	Marking Engine		
	—Electrophotographic/LED	—Small Particle Development	—Heat Fusing
Print Speed Per Minute (up to)	—110 impressions per minute (letter/A4, legal), 55 impressions per minute (11x17/A3)		
Usage (max/mo. in millions)	—Up to 2 million 8.5 x 11 impressions per month ²		
Paper Handling	Standard input capacity	—Two 1000-sheet trays	—One 2000-sheet tray
	Optional paper supply module	—Two 1000-sheet trays	—One 2000-sheet tray
	Optional post fuse inserter¹ input module	—Two 1000-sheet trays	—One 2000-sheet tray
	Standard output capacity	—One 500-sheet top tray exit	
		—One 3000-sheet stacker with stapling capability (up to 102 sheets)	
	Optional output high-capacity stacker	—One 5000-sheet stacker (face-down delivery with straight or offset stacking)	
Media Sizes	—8 x 10 (letter) ¹	—8.5 x 10 (letter) ¹	—8 x 10.5 (letter)
	—8.5 x 11 (standard letter)	—8.5 x 14 (legal)	—9 x 11 (letter tab)
	—9 x 12 (manual)	—9 x 14 (legal tab)	—11 x 17 (standard ledger) ³
	—14 x 17 (ledger) ⁴	—12 x 18 (ledger) ⁵	—14 x 18 (ledger) ⁵
	—210 mm x 297 mm (A4)	—225 mm x 297 mm (A4 tab)	—215 mm x 305 mm (RA4) ¹
	—420 mm x 297 mm (A3) ³	—430 x 305 mm (RA3) ⁴	
Media Types/Weights	—16 lb. bond to 110 lb. index (60 g/m ² to 200 g/m ²)		
	—Xerographic bond, rag bond, ledger grain long, dual purpose, cover stock, recycled and short/long grain stocks		
Environmental Conditions	Permitted ranges:	—Temperature—60° to 90° F (15.5° C to 32.2° C), Humidity—5% to 90% RH	
	Optimal ranges:	—Temperature—70° F (21.1° C), Humidity—50% RH	
	Acoustics	—85 dbA (operating), 73 dbA (idle)	
Print Language Support	Standard	—IPDS	
	With Infoprint Manager	—PostScript, PCL, PDF, GIF, JPEG, TIFF, LCDS/Metacode with Xport on Infoprint Manager/AIX [®]	
Software Support	PSF™ for OS/390®, PSF/400®, PSF/MVS®, PSF/VSE™, PSF/VM®, Network Printer Manager (NPM), Infoprint Manager for Microsoft® Windows® NT®/2000 and Infoprint Manager for AIX		
Attachments	Ethernet, Token Ring, ESCON®, FICON™ ¹ , S/370™ Parallel Channel, FDDI and SNA		

Physical Characteristics	(sizes & weights)			
	<i>Height</i>	<i>Depth</i>	<i>Length</i>	<i>Weight</i>
Marking Engine	64 in. (162.6 cm)	47 in. (119.4 cm)	67 in. (170.2 cm)	1500 lbs. (567.3 kg)
Standard Finisher	61.5 in. (156.2 cm)	34 in. (86.4 cm)	22 in. (53.3 cm)	650 lbs. (294.7 kg)
MIP	26 in. (66 cm)	20.5 in. (51 cm)	18 in. (45.7 cm)	120 lbs. (54.4 kg)
Paper Supply Module	45 in. (114.3 cm)	33.5 in. (83.8 cm)	31 in. (78.7 cm)	545 lbs. (247.4 kg)
Optional High-Capacity Stacker	49.5 in. (125.7 cm)	31.6 in. (78.7 cm)	33 in. (84.8 cm)	450 lbs. (203.7 kg)
Post Fuse Inserter ¹	59 in. (149.9 cm)	33.5 in. (83.8 cm)	31 in. (78.7 cm)	545 lbs. (247.4 kg)
Control Unit Enclosure ¹	46.3 in. (117.6 cm)	34.5 in. (87.7 cm)	23.6 in. (60 cm)	180 lbs. (81.9 kg)

Power Requirements	Marking Engine/Paper Supply/Finisher	
	—AC Power	—60 Hz, 120/208-127/208 volts, 24 amps
	Stacker	
	—AC Power	—60 Hz, 120 volts, 4 amps
	Convenience Outlet (AFCCU, switch, monitor, modem)	
	—AC Power	—60 Hz, 120 volts, 15 amps
For information regarding 50 Hz support for the Infoprint 2000, please contact your sales representative.		

¹ Not currently available; please contact your sales representative to ascertain availability.

² IBM does not recommend reaching this monthly maximum on a consistent basis.

³ Only for use in the middle and lower drawers of the standard paper supply module, the optional paper supply module, and the post fuse inserter.

⁴ Only for use in the middle and lower drawers of the standard paper supply module, the optional paper supply module, and the post fuse inserter. Not currently available; please contact your sales representative to ascertain availability.

⁵ Only for use in the middle drawers of the standard paper supply module, the optional paper supply module, and the post fuse inserter. Not currently available; please contact your sales representative to ascertain availability.

The following are trademarks or registered trademarks of IBM Corporation in the United States and/or other countries: Advanced Function Common Control Unit, AFCCU, Advanced Function Printing, AFP, AIX, the e-business logo, ESCON, the eServer logo, FICON, IBM, Infoprint, Intelligent Printer Data Stream, IPDS, MVS, OS/390, Print Services Facility, pSeries, PSF, PSF/400, S/370, VM and VSE.

Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

Microsoft, Windows and Windows NT are trademarks of Microsoft Corporation in the United States, other countries, or both.

PostScript is a registered trademark of Adobe Systems Incorporated.

Other company, product and service names may be trademarks or service marks of others.

IBM hardware is manufactured from new parts, or new and used parts. Regardless, our warranty terms apply.

References in this publication to IBM products or services do not imply that IBM intends to make them available in all countries in which IBM operates.



© International Business Machines Corporation 2001

IBM Printing Systems
Dept. HT7/001H
P.O. Box 1900
Boulder, CO 80301-9191

Printed in the United States of America
9-01
All Rights Reserved

Visit the IBM Printing Systems Web site at ibm.com/printers

The IBM home page can be found on the Internet at ibm.com

