

DB2  
for Linux, UNIX, and Windows



Version 9 Release 7



**Developing Perl, PHP, Python, and Ruby on Rails Applications**  
**Updated July, 2012**



DB2  
for Linux, UNIX, and Windows



Version 9 Release 7



**Developing Perl, PHP, Python, and Ruby on Rails Applications**  
**Updated July, 2012**

**Note**

Before using this information and the product it supports, read the general information under Appendix B, "Notices," on page 81.

**Edition Notice**

This document contains proprietary information of IBM. It is provided under a license agreement and is protected by copyright law. The information contained in this publication does not include any product warranties, and any statements provided in this manual should not be interpreted as such.

You can order IBM publications online or through your local IBM representative.

- To order publications online, go to the IBM Publications Center at [www.ibm.com/shop/publications/order](http://www.ibm.com/shop/publications/order)
- To find your local IBM representative, go to the IBM Directory of Worldwide Contacts at [www.ibm.com/planetwide](http://www.ibm.com/planetwide)

To order DB2 publications from DB2 Marketing and Sales in the United States or Canada, call 1-800-IBM-4YOU (426-4968).

When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© Copyright IBM Corporation 2006, 2012.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

---

# Contents

## Chapter 1. Developing Perl Applications 1

Programming considerations for Perl . . . . .	1
Perl downloads and related resources . . . . .	1
Database connections in Perl . . . . .	2
Fetching results in Perl . . . . .	3
Parameter markers in Perl . . . . .	4
SQLSTATE and SQLCODE variables in Perl . . . . .	4
Perl Restrictions . . . . .	5
pureXML and Perl . . . . .	5
Running Perl sample programs . . . . .	7
Executing routines from Perl applications. . . . .	8

## Chapter 2. Developing PHP applications 9

PHP application development for IBM data servers . . . . .	9
PHP downloads and related resources . . . . .	10
Setting up the PHP environment . . . . .	10
Application development in PHP (ibm_db2) . . . . .	14
Application development in PHP (PDO). . . . .	30

## Chapter 3. Developing Python applications . . . . . 43

Python, SQLAlchemy and Django Framework application development for IBM data servers. . . . .	43
Python downloads and related resources . . . . .	43
Setting up the Python environment for IBM data servers . . . . .	44
Application development in Python with ibm_db . . . . .	47

## Chapter 4. Developing Ruby on Rails applications . . . . . 59

The IBM_DB Ruby driver and Rails adapter . . . . .	59
Getting started with IBM data servers on Rails . . . . .	59
Installing the IBM_DB adapter and driver as a Ruby gem . . . . .	60

Configuring Rails application connections to IBM data servers . . . . .	64
IBM Ruby driver and trusted contexts . . . . .	65
IBM_DB Rails adapter dependencies and consequences . . . . .	66
The IBM_DB Ruby driver and Rails adapter are not supported on JRuby . . . . .	66
ActiveRecord-JDBC versus IBM_DB adapter . . . . .	67
Heap size considerations with DB2 on Rails . . . . .	67

## Appendix A. Overview of the DB2 technical information . . . . . 69

DB2 technical library in hardcopy or PDF format. . . . .	69
Ordering printed DB2 books. . . . .	72
Displaying SQL state help from the command line processor . . . . .	73
Accessing different versions of the DB2 Information Center . . . . .	73
Displaying topics in your preferred language in the DB2 Information Center . . . . .	74
Updating the DB2 Information Center installed on your computer or intranet server . . . . .	74
Manually updating the DB2 Information Center installed on your computer or intranet server . . . . .	76
DB2 tutorials . . . . .	77
DB2 troubleshooting information . . . . .	78
Terms and Conditions . . . . .	78

## Appendix B. Notices . . . . . 81

## Index . . . . . 85



---

# Chapter 1. Developing Perl Applications

---

## Programming considerations for Perl

Perl Database Interface (DBI) is an open standard application programming interface (API) that provides database access for client applications written in Perl. Perl DBI defines a set of functions, variables, and conventions that provide a platform-independent database interface.

You can use the IBM® DB2® Database Driver for Perl DBI (the DBD::DB2 driver) available from <http://www.ibm.com/software/data/db2/perl> along with the Perl DBI Module available from <http://www.perl.com> to create DB2 applications that use Perl.

Because Perl is an interpreted language and the Perl DBI module uses dynamic SQL, Perl is an ideal language for quickly creating and revising prototypes of DB2 applications. The Perl DBI module uses an interface that is quite similar to the CLI and JDBC interfaces, which makes it easy for you to port your Perl prototypes to CLI and JDBC.

Most database vendors provide a database driver for the Perl DBI module, which means that you can also use Perl to create applications that access data from many different database servers. For example, you can write a Perl DB2 application that connects to an Oracle database using the DBD::Oracle database driver, fetch data from the Oracle database, and insert the data into a DB2 database using the DBD::DB2 database driver.

For information about supported database servers, installation instructions, and prerequisites, see <http://www.ibm.com/software/data/db2/perl>

## Perl downloads and related resources

Several resources are available to help you develop Perl applications that access IBM data servers.

*Table 1. Perl downloads and related resources*

<b>Downloads</b>	
Perl Database Interface (DBI) Module	<a href="http://www.perl.com">http://www.perl.com</a>
DBD::DB2 driver	<a href="http://www.ibm.com/software/data/db2/perl">http://www.ibm.com/software/data/db2/perl</a>
IBM Data Server Driver Package (DS Driver)	<a href="http://www.ibm.com/software/data/support/data-server-clients/index.html">http://www.ibm.com/software/data/support/data-server-clients/index.html</a>
<b>API documentation</b>	
DBI API documentation	<a href="http://search.cpan.org/~timb/DBI/DBI.pm">http://search.cpan.org/~timb/DBI/DBI.pm</a>
<b>Related resources</b>	
DB2 Perl Database Interface for LUW technote, including readme and installation instructions	<a href="http://www.ibm.com/software/data/db2/perl">http://www.ibm.com/software/data/db2/perl</a>
Perl driver bug reporting system	<a href="http://rt.cpan.org/">http://rt.cpan.org/</a>
Reporting bugs to the Open Source team at IBM	<a href="mailto:opendev@us.ibm.com">opendev@us.ibm.com</a>

## Database connections in Perl

The DBD::DB2 driver provides support for standard database connection functions defined by the DBI API.

To enable Perl to load the DBI module, you must include the following line in your application:

```
use DBI;
```

The DBI module automatically loads the DBD::DB2 driver when you create a database handle using the **DBI->connect** statement with the following syntax:

```
my $dbh = DBI->connect('dbi:DB2:dsn', $userID, $password);
```

where:

### **\$dbh**

represents the database handle returned by the connect statement

### **dsn**

for local connections, represents a DB2 alias cataloged in your DB2 database directory

for remote connections, represents a complete connection string that includes the host name, port number, protocol, user ID, and password for connecting to the remote host

### **\$userID**

represents the user ID used to connect to the database

### **\$password**

represents the password for the user ID used to connect to the database

For more information about the DBI API, see <http://search.cpan.org/~timb/DBI/DBI.pm>.

## Example

*Example 1:* Connect to a database on the local host (client and server are on the same workstation)

```
use DBI;
```

```
$DATABASE = 'dbname';  
$USERID = 'username';  
$PASSWORD = 'password';
```

```
my $dbh = DBI->connect("dbi:DB2:$DATABASE", $USERID, $PASSWORD, {PrintError => 0})  
or die "Couldn't connect to database: " . DBI->errstr;
```

```
$dbh->disconnect;
```

*Example 2:* Connect to a database on the remote host (client and server are on different workstations)

```
use DBI;
```

```
$DSN="DATABASE=sample; HOSTNAME=host; PORT=60000; PROTOCOL=TCPIP; UID=username;  
PWD=password";
```



```

my $dbh = DBI->connect("dbi:DB2:$DSN", $USERID, $PASSWORD, {PrintError => 0})
or die "Couldn't connect to database: " . DBI->errstr;

$dbh->disconnect;

```

## Fetching results in Perl

The Perl DBI module provides methods for connecting to a database, preparing and issuing SQL statements, and fetching rows from result sets.

### About this task

This procedure fetches results from an SQL query.

**Restriction:** Because the Perl DBI module supports only dynamic SQL, you cannot use host variables in your Perl DB2 applications.

### Procedure

To fetch results:

1. Create a database handle by connecting to the database with the DBI->connect statement.
2. Create a statement handle from the database handle. For example, you can return the statement handle \$sth from the database handle by calling the prepare method and passing an SQL statement as a string argument, as demonstrated in the following Perl statement:

```

my $sth = $dbh->prepare(
    'SELECT firstme, lastname
    FROM employee '
);

```

3. Issue the SQL statement by calling the execute method on the statement handle. A successful call to the execute method associates a result set with the statement handle. For example, you can run the statement prepared in the previous example by using the following Perl statement:

```

#Note: $rc represents the return code for the execute call
my $rc = $sth->execute();

```

4. Fetch a row from the result set associated with the statement handle by calling the fetchrow method. The Perl DBI returns a row as an array with one value per column. For example, you can return all of the rows from the statement handle in the previous example by using the following Perl statement:

```

while (($firstme, $lastname) = $sth->fetchrow()) {
    print "$firstme $lastname\n";
}

```

### Example

The following example shows how to connect to a database and issue a SELECT statement from an application written in Perl.

```

#!/usr/bin/perl
use DBI;

my $database='dbi:DB2:sample';
my $user='';
my $password='';

my $dbh = DBI->connect($database, $user, $password)
or die "Can't connect to $database: $DBI::errstr";

```

```

my $sth = $dbh->prepare(
    q{ SELECT firstnme, lastname
        FROM employee }
    )
    or die "Can't prepare statement: $DBI::errstr";

my $rc = $sth->execute
    or die "Can't execute statement: $DBI::errstr";

print "Query will return $sth->{NUM_OF_FIELDS} fields.\n\n";
print "$sth->{NAME}->[0]: $sth->{NAME}->[1]\n";

while (($firstnme, $lastname) = $sth->fetchrow()) {
    print "$firstnme: $lastname\n";
}

# check for problems that might have terminated the fetch early
warn $DBI::errstr if $DBI::err;

$sth->finish;
$dbh->disconnect;

```

## Parameter markers in Perl

The Perl DBI module supports executing a prepared statement that includes parameter markers for variable input. To include a parameter marker in an SQL statement, use the question mark (?) character or a colon followed by a name (:name).

The following Perl code creates a statement handle that accepts a parameter marker for the WHERE clause of a SELECT statement. The code then executes the statement twice using the input values 25000 and 35000 to replace the parameter marker.

```

my $sth = $dbh->prepare(
    'SELECT firstnme, lastname
     FROM employee
     WHERE salary > ?'
    );

my $rc = $sth->execute(25000);

.
.
.

my $rc = $sth->execute(35000);

```

## SQLSTATE and SQLCODE variables in Perl

The Perl DBI module provides methods for returning the SQLSTATE and SQLCODE associated with a Perl DBI database or statement handle.

To return the SQLSTATE associated with a Perl DBI database handle or statement handle, call the state method. For example, to return the SQLSTATE associated with the database handle \$dbh, include the following Perl statement in your application:

```
my $sqlstate = $dbh->state;
```

To return the SQLCODE associated with a Perl DBI database handle or statement handle, call the err method. To return the message for an SQLCODE associated with a Perl DBI database handle or statement handle, call the errstr method. For

example, to return the SQLCODE associated with the database handle \$dbhhandle, include the following Perl statement in your application:

```
my $sqlcode = $dbhhandle->err;
```

## Perl Restrictions

Some restrictions apply to the support that is available for application development in Perl.

The Perl DBI module supports only dynamic SQL. When you must execute a statement multiple times, you can improve the performance of your Perl applications by issuing a **prepare** call to prepare the statement.

Perl does not support multiple-thread database access.

For current information on the restrictions of the version of the DBD::DB2 driver that you install on your workstation, refer to the CAVEATS file in the DBD::DB2 driver package.

## pureXML and Perl

The DBD::DB2 driver supports DB2 pureXML<sup>®</sup>. Support for pureXML allows more direct access to your data through the DBD::DB2 driver and helps to decrease application logic by providing more transparent communication between your application and database.

With pureXML support, you can directly insert XML documents into your DB2 database. Your application no longer needs to parse XML documents because the pureXML parser is automatically run when you insert XML data into the database. Having document parsing handled outside your application improves application performance and reduces maintenance efforts. Retrieval of XML stored data with the DBD::DB2 driver is easy as well; you can access the data using a BLOB or record.

For information about the DB2 Perl Database Interface and how to download the latest DBD::DB2 driver, see <http://www.ibm.com/software/data/db2/perl>.

## Example

The following example is a Perl program that uses pureXML:

```
#!/usr/bin/perl
use DBI;
use strict ;

# Use DBD:DB2 module:
#   to create a simple DB2 table with an XML column
#   Add one row of data
#   retrieve the XML data as a record or a LOB (based on $datatype).

# NOTE: the DB2 SAMPLE database must already exist.

my $database='dbi:DB2:sample';
my $user='';
my $password='';

my $datatype = "record" ;
# $datatype = "LOB" ;

my $dbh = DBI->connect($database, $user, $password)
    or die "Can't connect to $database: $DBI::errstr";
```

```

# For LOB datatype, LongReadLen = 0 -- no data is retrieved on initial fetch
$dbh->{LongReadLen} = 0 if $datatype eq "LOB" ;

# SQL CREATE TABLE to create test table
my $stmt = "CREATE TABLE xmlTest (id INTEGER, data XML)";
my $sth = $dbh->prepare($stmt);
$sth->execute();

#insert one row of data into table
insertData() ;

# SQL SELECT statement returns home phone element from XML data
$stmt = qq(
    SELECT XMLQUERY ( '
    \d/*:customerinfo/*:phone[\@type = "home"] '
    passing data as "d")
    FROM xmlTest
) ;

# prepare and execute SELECT statement
$sth = $dbh->prepare($stmt);
$sth->execute();

# Print data returned from select statement
if($datatype eq "LOB") {
    printLOB() ;
}
else {
    printRecord() ;
}

# Drop table
$stmt = "DROP TABLE xmlTest" ;
$sth = $dbh->prepare($stmt);
$sth->execute();

warn $DBI::errstr if $DBI::err;

$sth->finish;
$dbh->disconnect;

#####

sub printRecord {
    print "output data as as record\n" ;

    while( my @row = $sth->fetchrow )
    {
        print $row[0] . "\n";
    }

    warn $DBI::errstr if $DBI::err;
}

sub printLOB {
    print "output as Blob data\n" ;

    my $offset = 0;
    my $buff="";
    $sth->fetch();
    while( $buff = $sth->blob_read(1,$offset,1000000)) {
        print $buff;
    }
}

```

```

    $offset+=length($buff);
    $buff="";
}
warn $DBI::errstr if $DBI::err;
}

sub insertData {

    # insert a row of data
    my $xmlInfo = qq(\
<customerinfo xmlns="http://posample.org" Cid="1011">
  <name>Bill Jones</name>
  <addr country="Canada">
    <street>5 Redwood</street>
    <city>Toronto</city>
    <prov-state>Ontario</prov-state>
    <pcode-zip>M6W 1E9</pcode-zip>
  </addr>
  <phone type="work">416-555-9911</phone>
  <phone type="home">416-555-1212</phone>
</customerinfo>
\');

    my $catID = 1011 ;

    # SQL statement to insert data.
    my $Sql = qq(
    INSERT INTO xmlTest (id, data)
      VALUES($catID, $xmlInfo )
    );

    $sth = $dbh->prepare( $Sql )
      or die "Can't prepare statement: $DBI::errstr";

    my $rc = $sth->execute
      or die "Can't execute statement: $DBI::errstr";

    # check for problems
    warn $DBI::errstr if $DBI::err;
}

```

## Running Perl sample programs

Perl sample programs are available that demonstrate how to build a Perl application.

### Before you begin

Before running the Perl sample programs, you must install the latest DB2::DB2 driver for Perl DBI. For information about how to obtain the latest driver, see <http://www.ibm.com/software/data/db2/perl>.

### About this task

The Perl sample programs for DB2 database are available in the `sqlib/samples/perl` directory.

### Procedure

To run the Perl interpreter on a Perl sample program on the command line:

Enter the interpreter name and the program name (including the file extension):

- If connecting locally on the server:  

```
perl dbauth.pl
```
- If connecting from a remote client:  

```
perl dbauth.pl sample <userid> <password>
```

Some of the sample programs require you to run support files. For example, the `tbse1` sample program requires several tables that are created by the `tbse1create.db2` CLP script. The `tbse1init` script (UNIX), or the `tbse1init.bat` batch file (Windows), first calls `tbse1drop.db2` to drop the tables if they exist, and then calls `tbse1create.db2` to create them. Therefore, to run the `tbse1` sample program, you would issue the following commands:

- If connecting locally on the server:  

```
tbse1init
perl tbse1.pl
```
- If connecting from a remote client:  

```
tbse1init
perl tbse1.pl sample <userid> <password>
```

**Note:** For a remote client, you need to modify the connect statement in the `tbse1init` or `tbse1init.bat` file to hardcode your user ID and password: `db2 connect to sample user <userid> using <password>`

## Executing routines from Perl applications

DB2 client applications can access routines (stored procedures and user-defined functions) that are created by supported host languages or by SQL procedures. For example, the sample program `spclient.pl` can access the SQL procedures `spserver` shared library, if it exists in the database.

### Before you begin

To build a host language routine, you must have the appropriate compiler set up on the server. SQL procedures do not require a compiler. The shared library can be built on the server only, and not from a remote client.

### Procedure

To create SQL procedures in a shared library and then access the procedures from a Perl application:

1. Create and catalog the SQL procedures in the library. For example, go to the `samples/sqlpl` directory on the server, and run the following commands to create and catalog the SQL procedures in the `spserver` library:  

```
db2 connect to sample
db2 -td@ -vf spserver.db2
```
2. Go back to the `perl samples` directory (this can be on a remote client workstation), and run the Perl interpreter on the client program to access the `spserver` shared library:
  - If connecting locally on the server:  

```
perl spclient
```
  - If connecting from a remote client:  

```
perl spclient sample <userid> <password>
```

---

## Chapter 2. Developing PHP applications

---

### PHP application development for IBM data servers

PHP: Hypertext Preprocessor (PHP) is an interpreted programming language that is widely used for developing Web applications. PHP has become a popular language for Web development because it is easy to learn, focuses on practical solutions, and supports the most commonly required functionality in Web applications.

PHP is a modular language that enables you to customize the available functionality through the use of extensions. These extensions can simplify tasks such as reading, writing, and manipulating XML, creating SOAP clients and servers, and encrypting communications between server and browser. The most popular extensions for PHP, however, provide read and write access to databases so that you can easily create a dynamic database-driven Web site.

IBM provides the following PHP extensions for accessing IBM data server databases:

#### **ibm\_db2**

A procedural application programming interface (API) that, in addition to the normal create, read, update, and write database operations, also offers extensive access to the database metadata. You can compile the `ibm_db2` extension with either PHP 4 or PHP 5. This extension is written, maintained, and supported by IBM.

#### **pdo\_ibm**

A driver for the PHP Data Objects (PDO) extension that offers access to IBM data server databases through the standard object-oriented database interface introduced in PHP 5.1.

These extensions are included as part of the IBM Data Server Driver Package (DS Driver) of Version 1.7.0. This version or a later version is supported to connect to IBM DB2 Version 9.7 for Linux, UNIX, and Windows. You can check the version of `ibm_db2` extension by issuing the following command:

```
php --re ibm_db2
```

The most recent versions of `ibm_db2` and `pdo_ibm` are also available from the PHP Extension Community Library (PECL) at <http://pecl.php.net/>.

PHP applications can access the following IBM data server databases:

- IBM DB2 Version 9.1 for Linux, UNIX, and Windows, Fix Pack 2 and later
- IBM DB2 Universal Database™ (DB2 UDB) Version 8 for Linux, UNIX, and Windows, Fixpak 15 and later
- Remote connections to IBM DB2 Universal Database on i5/OS® V5R3
- Remote connections to IBM DB2 for IBM i 5.4 and later
- Remote connections to IBM DB2 for z/OS®, Version 8 and Version 9

A third extension, Unified ODBC, has historically offered access to DB2 database systems. For new applications, however, you should use either `ibm_db2` and `pdo_ibm` because they offer significant performance and stability benefits over

Unified ODBC. The `ibm_db2` extension API makes porting an application that was previously written for Unified ODBC almost as easy as globally changing the `odbc_` function name to `db2_` throughout the source code of your application.

## PHP downloads and related resources

Many resources are available to help you develop PHP applications for IBM data servers.

Table 2. PHP downloads and related resources

Downloads	
Complete PHP source code <sup>1</sup>	<a href="http://www.php.net/downloads.php">http://www.php.net/downloads.php</a>
<code>ibm_db2</code> and <code>pdo_ibm</code> from the PHP Extension Community Library (PECL)	<a href="http://pecl.php.net/">http://pecl.php.net/</a>
IBM Data Server Driver Package (DS Driver)	<a href="http://www.ibm.com/software/data/support/data-server-clients/index.html">http://www.ibm.com/software/data/support/data-server-clients/index.html</a>
Zend Server	<a href="http://www.zend.com/en/products/server/downloads">http://www.zend.com/en/products/server/downloads</a>
Documentation	
<i>PHP Manual</i>	<a href="http://www.php.net/docs.php">http://www.php.net/docs.php</a>
<code>ibm_db2</code> API documentation	<a href="http://www.php.net/ibm_db2">http://www.php.net/ibm_db2</a>
PDO API documentation	<a href="http://php.net/manual/en/book.pdo.php">http://php.net/manual/en/book.pdo.php</a>
Related resources	
PHP Web site	<a href="http://www.php.net/">http://www.php.net/</a>

1. Includes Windows binaries. Most Linux distributions come with PHP already precompiled.

## Setting up the PHP environment

You can set up the PHP environment on Linux, UNIX, or Windows operating systems by installing a precompiled binary version of PHP and enabling support for IBM data servers.

### About this task

For the easiest installation and configuration experience on Linux, UNIX, or Windows operating systems, you can download and install Zend Server for use in production systems at <http://www.zend.com/en/products/server/downloads>. Packaging details are available at <http://www.zend.com/en/products/server/editions>.

On Windows, precompiled binary versions of PHP are available for download from <http://www.php.net/downloads.php>. Most Linux distributions include a precompiled version of PHP. On UNIX operating systems that do not include a precompiled version of PHP, you can compile your own version of PHP.

For more information about installing and configuring PHP, see <http://www.php.net/manual/en/install.php>.

### Setting up the PHP environment on Windows

Before you can connect to an IBM data server and execute SQL statements, you need to set up the PHP environment.



## Before you begin

You must have the following software installed on your system:

- An Apache HTTP Server
- One of the following client types: IBM Data Server Driver Package, IBM Data Server Client, or IBM Data Server Driver for ODBC and CLI

## About this task

This procedure manually installs a precompiled binary version of PHP and enables support for IBM data servers on Windows.

## Procedure

To set up the PHP environment on Windows:

1. Download the latest version of the PHP zip package (as of now PHP 5.3.x) from <http://windows.php.net/download/> and the collection of PECL modules from <http://php.net/releases/index.php>. The PECL collection modules are available only for PHP versions 5.2.x. Please note that Non Thread Safe build of PHP is recommended when you are not using PHP as an Apache module.
2. Extract the PHP zip package into an installation directory.
3. Extract the collection of PECL modules zip package into the `\ext\` subdirectory of your PHP installation directory.
4. Create a new file named `php.ini` in your installation directory by making a copy of the `php.ini-recommended` file.
5. Open the `php.ini` file in a text editor and add the following lines.
  - To enable the PDO extension and `pdo_ibm` driver:  
`extension=php_pdo.dll`  
`extension=php_pdo_ibm.dll`
  - To enable the `ibm_db2` extension:  
`extension=php_ibm_db2.dll`
6. If you are using Apache HTTP Server 2.x., enable PHP support by adding the following lines to your `httpd.conf` file, in which `phpdir` refers to the PHP installation directory:  

```
LoadModule php5_module 'phpdir/php5apache2_2.dll'  
AddType application/x-httpd-php .php  
PHPIniDir 'phpdir'
```
7. Restart the Apache HTTP Server to enable the changed configuration.

## Results

**Note:** If you encounter message DB21085I or SQL09054, you can do one of the following:

- Rebuild PHP in 64 bit mode
- Set the `PHP_IBM_DB2_LIB` and `PHP_PDO_IBM_LIB` variables to use `lib32` instead of default `lib64`, and update `LD_LIBRARY_PATH` to point to `lib32`.

The PHP extensions are now installed on your system and ready to use.

## What to do next

Connect to the data server and begin executing SQL statements.

## Setting up the PHP environment on Linux or UNIX

Before you can connect to an IBM data server and execute SQL statements, you must set up the PHP environment.

### Before you begin

DB2 supports database access for client applications written in the PHP programming language using either or both of the `ibm_db2` extension and the `pdo_ibm` driver for the PHP Data Objects (PDO) extension.

You must have the following software and files installed on your system:

- The Apache HTTP Server
- The gcc compiler and the following development packages: `apache-devel`, `autoconf`, `automake`, `bison`, `flex`, `gcc`, and `libxml2-devel` package
- If you are connecting from PHP to a DB2 database server on a remote machine, then you need one of the following DB2 clients on the machine where you are installing, running or executing PHP, such as IBM Data Server Driver Package, IBM Data Server Client, or IBM Data Server Driver for ODBC and CLI.
- If you are connecting from PHP to a DB2 server on the local machine, you don't need to install any DB2 client.

### About this task

This procedure manually compiles and installs PHP from source with support for DB2 on Linux or UNIX.

### Procedure

To set up the PHP environment on Linux or UNIX:

1. Download the latest version of the PHP tarball from <http://www.php.net>. The latest version of PHP at the time of writing is PHP 5.3.x.
2. Untar the file by issuing the following command:  

```
tar -xjf php-5.x.x.tar.bz2
```
3. Change directories to the newly created `php-5.x.x` directory.
4. Configure the makefile by issuing the `configure` command. Specify the features and extensions you want to include in your custom version of PHP. A typical configure command includes the following options:

```
./configure --enable-cli --disable-cgi --with-apxs2=/usr/sbin/apxs2  
--with-zlib --with-pdo-ibm=<sqllib> --with-IBM_DB2=<sqllib>
```

The configure options have the following effects:

**--enable-cli**

Enables the command line mode of PHP access.

**--disable-cgi**

Disables the Common Gateway Interface (CGI) mode of PHP access.

**--with-apxs2=/usr/sbin/apxs2**

Enables the Apache 2 dynamic server object (DSO) mode of PHP access.

**--with-zlib**

Enables zlib compression support.

### **--with-pdo-ibm=<sqllib>**

Enables the pdo\_ibm driver using the CLI library to access database systems. The <sqllib> setting refers to the directory in which DB2 is installed.

If the source code of pdo\_ibm extensions are not in the ext/ directory under PHP source, this flag will not be valid. To use --with-pdo-ibm, you must have the pdo\_ibm directory, containing source code of pdo\_ibm in the ext/ subdirectory.

### **--with-IBM\_DB2=<sqllib>**

Enables the IBM\_DB2 driver using the library to access database systems. The <sqllib> setting refers to the directory in which DB2 is installed.

If the source code of IBM\_DB2 extension is not in the ext/ directory under PHP source, this flag will not be valid. To use this configure option, you must have the ibm\_db2 directory, containing source code of ibm\_db2 in the ext/ subdirectory.

5. Compile the files by issuing the make command.
6. Install the files by issuing the make install command. Depending on how you configured the PHP installation directory using the configure command, you might need root authority to successfully issue this command. This should install the executable files and update the Apache HTTP Server configuration to support PHP.
7. Install the ibm\_db2 extension by issuing the following command as a user with root authority:

```
pecl install ibm_db2
```

This command downloads, configures, compiles, and installs the ibm\_db2 extension for PHP. It is recommended to use the latest extension. However, you can also use the ibm\_db2 extension which is included as part of the DB2 products.

8. Copy the php.ini-development or php.ini-production file to the configuration file path for your new PHP installation. To determine the configuration file path, issue the php -i command and look for the php.ini keyword. Rename the file to php.ini.
9. Open the new php.ini file in a text editor and add the following lines, where *instance* refers to the name of the DB2 instance on Linux or UNIX.

- To enable the pdo\_ibm extension and set the environment:

```
extension=pdo_ibm.so  
PDO_IBM.db2_instance_name=instance
```

- To enable the ibm\_db2 extension and set the DB2 environment:

```
extension=ibm_db2.so  
ibm_db2.instance_name=instance
```

Where the extension variable should be specified as a relative path from the extension directory, which is specified in extension\_dir variable. For example, if the extension\_dir is \$HOME/usr/php/ext and the extension is at \$HOME/user/sqllib/php32, the entry will look like: extension=../../sqllib/php32/ibm\_db2\_5.2.1.so

10. Before you run any PHP script that connects to DB2, you need to ensure that the IBM DB2 PHP drivers (PDO\_IBM/IBM\_DB2) can access the CLI driver libdb2.so, which is part of your DB2 Server setup or DB2 client setup. Failing to do so will result in a missing libraries - libdb2.so.1 error when you run your PHP script. On Linux, you do this by adding the folder where the

libdb2.so file resides to the `LD_LIBRARY_PATH` environmental variable for the userid under which PHP is going to be run.

When using IBM Data Server Driver Package, libdb2.so is located in the `odbc_cli_driver/linux/clidriver/lib` directory.

In the DB2 server installation, libdb2.so is located in the `sql1lib/lib` directory.

11. Restart the Apache HTTP Server to enable the changed configuration.

## Results

**Note:** If you encounter message DB21085I or SQL09054, you can do one of the following:

- Rebuild PHP in 64 bit mode
- Set the `PHP_IBM_DB2_LIB` and `PHP_PDO_IBM_LIB` variables to use lib32 instead of default lib64, and update `LD_LIBRARY_PATH` to point to lib32.

## Application development in PHP (ibm\_db2)

The `ibm_db2` extension provides a variety of useful PHP functions for accessing and manipulating data in an IBM data server database. The extension includes functions for connecting to a database, executing and preparing SQL statements, fetching rows from result sets, calling stored procedures, handling errors, and retrieving metadata.

### Connecting to an IBM data server database in PHP (ibm\_db2)

Before you can issue SQL statements to create, update, delete, or retrieve data, you need to connect to a database from your PHP application. You can use the `ibm_db2` API to connect to an IBM data server database through either a cataloged connection or a direct TCP/IP connection. To improve performance, you can also create a persistent connection.

### Before you begin

Before connecting to an IBM data server database through the `ibm_db2` extension, you must set up the PHP environment on your system and enable the `ibm_db2` extension.

### Procedure

To return a connection resource that you can use to call SQL statements, call one of the following connection functions:

Table 3. `ibm_db2` connection functions

Function	Description
<code>db2_connect</code>	Creates a non-persistent connection.
<code>db2_pconnect</code>	Creates a persistent connection. A persistent connection remains open between PHP requests, which allows subsequent PHP script requests to reuse the connection if they have an identical set of credentials.

The database values that you pass as arguments to these functions can specify either a cataloged database name or a complete database connection string for a direct TCP/IP connection. You can specify optional arguments that control when transactions are committed, the case of the column names that are returned, and the cursor type.

If the connection attempt fails, you can retrieve diagnostic information by calling

the `db2_conn_error` or `db2_stmt_errormsg` function.

When you create a connection by calling the `db2_connect` function, PHP closes the connection to the database when one of the following events occurs:

- You call the `db2_close` function for the connection
- You set the connection resource to `NULL`
- The PHP script finishes

When you create a connection by calling the `db2_pconnect` function, PHP ignores any calls to the `db2_close` function for the specified connection resource, and keeps the connection to the database open for subsequent PHP scripts.

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.

## Example

Connect to a cataloged database.

```
<?php
$database = "sample";
$user = "db2inst1";
$password = "";

$conn = db2_connect($database, $user, $password);

if ($conn) {
    echo "Connection succeeded.";
    db2_close($conn);
}
else {
    echo "Connection failed.";
}
?>
```

## What to do next

If the connection attempt is successful, you can use the connection resource when you call `ibm_db2` functions that execute SQL statements. Next, prepare and execute SQL statements.

### Trusted contexts in PHP applications (`ibm_db2`):

Starting in Version 9.5 Fix Pack 3 (or later), the `ibm_db2` extension supports trusted contexts by using connection string keywords.

Trusted contexts provide a way of building much faster and more secure three-tier applications. The user's identity is always preserved for auditing and security purposes. When you need secure connections, trusted contexts improve performance because you do not have to get new connections.

## Example

Enable trusted contexts, switch users, and get the current user ID.

```
<?php
$database = "SAMPLE";
$hostname = "localhost";
$port = 50000;
$authID = "db2inst1";
$auth_pass = "ibmdb2";

$tc_user = "tcuser";
$tc_pass = "tcpassword";

$dsn = "DATABASE=$database;HOSTNAME=$hostname;PORT=$port;PROTOCOL=TCPIP;UID=$authID;PWD=$auth_pass";
$options = array ("trustedcontext" => DB2_TRUSTED_CONTEXT_ENABLE);

$tc_conn = db2_connect($dsn, "", "", $options);
if ($tc_conn) {
    echo "Explicit Trusted Connection succeeded.\n";
}
```

```

if(db2_get_option($tc_conn, "trustedcontext") {
    $userBefore = db2_get_option($tc_conn, "trusted_user");

    //Do some work as user 1.

    //Switching to trusted user.
    $parameters = array("trusted_user" => $tc_user, "trusted_password" => $tcuser_pass);
    $res = db2_set_option ($tc_conn, $parameters, 1);

    $userAfter = db2_get_option($tc_conn, "trusted_user");
    //Do more work as trusted user.

    if($userBefore != $userAfter) {
        echo "User has been switched." . "\n";
    }
}

db2_close($tc_conn);
}
else {
    echo "Explicit Trusted Connection failed.\n";
}
?>

```

## Executing SQL statements in PHP (ibm\_db2)

After connecting to a database, use functions available in the `ibm_db2` API to prepare and execute SQL statements. The SQL statements can contain static text, XQuery expressions, or parameter markers that represent variable input.

### Executing a single SQL statement in PHP (ibm\_db2):

To prepare and execute a single SQL statement that accepts no input parameters, use the `db2_exec` function. A typical use of the `db2_exec` function is to set the default schema for your application in a common include file or base class.

### Before you begin

To avoid the security threat of SQL injection attacks, use the `db2_exec` function only to execute SQL statements composed of static strings. Interpolation of PHP variables representing user input into the SQL statement can expose your application to SQL injection attacks.

Obtain a connection resource by calling one of the connection functions in the `ibm_db2` API.

### Procedure

To prepare and execute a single SQL statement, call the `db2_exec` function, passing the following arguments:

#### *connection*

A valid database connection resource returned from the `db2_connect` or `db2_pconnect` function.

#### *statement*

A string that contains the SQL statement. This string can include an XQuery expression that is called by the `XMLQUERY` function.

#### *options*

Optional: An associative array that specifies statement options:

#### **DB2\_ATTR\_CASE**

For compatibility with database systems that do not follow the SQL standard, this option sets the case in which column names will be returned to the application. By default, the case is set to `DB2_CASE_NATURAL`, which returns column names as they are returned by the database. You can set this parameter to `DB2_CASE_LOWER` to force column names to lower case, or to `DB2_CASE_UPPER` to force column names to upper case.

#### **DB2\_ATTR\_CURSOR**

This option sets the type of cursor that `ibm_db2` returns for result sets. By

default, `ibm_db2` returns a forward-only cursor (`DB2_FORWARD_ONLY`) which returns the next row in a result set for every call to `db2_fetch_array`, `db2_fetch_assoc`, `db2_fetch_both`, `db2_fetch_object`, or `db2_fetch_row`. You can set this parameter to `DB2_SCROLLABLE` to request a scrollable cursor so that the `ibm_db2` fetch functions accept a second argument specifying the absolute position of the row that you want to access within the result set.

If the function call succeeds, it returns a statement resource that you can use in subsequent function calls related to this query.

If the function call fails (returns `False`), you can use the `db2_stmt_error` or

`db2_stmt_errormsg` function to retrieve diagnostic information about the error.

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.

### Example

*Example 1:* Executing a single SQL statement.

```
<?php
$conn = db2_connect("sample", "db2inst1", "");
$sql = "SELECT * FROM DEPT";
$stmt = db2_exec($conn, $sql);
db2_close($conn);
?>
```

*Example 2:* Executing an XQuery expression

```
<?php
$xmlquery = '$doc/customerinfo/phone';
$stmt = db2_exec($conn, "select xmlquery('$xmlquery'
PASSING INFO AS \"doc\") from customer");?>
```

### What to do next

If the SQL statement selected rows using a scrollable cursor, or inserted, updated, or deleted rows, you can call the `db2_num_rows` function to return the number of rows that the statement returned or affected. If the SQL statement returned a result set, you can begin fetching rows.

### Preparing and executing SQL statements with variable input in PHP (`ibm_db2`):

To prepare and execute an SQL statement that includes variable input, use the `db2_prepare`, `db2_bind_param`, and `db2_execute` functions. Preparing a statement improves performance because the database server creates an optimized access plan for data retrieval that it can reuse if the statement is executed again.

### Before you begin

Obtain a connection resource by calling one of the connection functions in the `ibm_db2` API.

### Procedure

To prepare and execute an SQL statement that includes parameter markers:

1. Call the `db2_prepare` function, passing the following arguments:

*connection*

A valid database connection resource returned from the `db2_connect` or `db2_pconnect` function.

*statement*

A string that contains the SQL statement, including question marks (?) as parameter markers for any column or predicate values that require variable input. This string can include an XQuery expression that is called the XMLQUERY function. You can only use parameter markers as a place holder for column or predicate values. The SQL compiler is unable to create an access plan for a statement that uses parameter markers in place of column names, table names, or other SQL identifiers.

*options*

Optional: An associative array that specifies statement options:

**DB2\_ATTR\_CASE**

For compatibility with database systems that do not follow the SQL standard, this option sets the case in which column names will be returned to the application. By default, the case is set to DB2\_CASE\_NATURAL, which returns column names as they are returned by the database. You can set this parameter to DB2\_CASE\_LOWER to force column names to lower case, or to DB2\_CASE\_UPPER to force column names to upper case.

**DB2\_ATTR\_CURSOR**

This option sets the type of cursor that `ibm_db2` returns for result sets. By default, `ibm_db2` returns a forward-only cursor (DB2\_FORWARD\_ONLY) which returns the next row in a result set for every call to `db2_fetch_array`, `db2_fetch_assoc`, `db2_fetch_both`, `db2_fetch_object`, or `db2_fetch_row`. You can set this parameter to DB2\_SCROLLABLE to request a scrollable cursor so that the `ibm_db2` fetch functions accept a second argument specifying the absolute position of the row that you want to access within the result set.

If the function call succeeds, it returns a statement handle resource that you can use in subsequent function calls that are related to this query.

If the function call fails (returns False), you can use the `db2_stmt_error` or `db2_stmt_errormsg` function to retrieve diagnostic information about the error.

- Optional: For each parameter marker in the SQL string, call the `db2_bind_param` function, passing the following arguments. Binding input values to parameter markers ensures that each input value is treated as a single parameter, which prevents SQL injection attacks against your application.

*stmt*

A prepared statement returned by the call to the `db2_prepare` function.

*parameter-number*

An integer that represents the position of the parameter marker in the SQL statement.

*variable-name*

A string that specifies the name of the PHP variable to bind to the parameter specified by *parameter-number*.

- Call the `db2_execute` function, passing the following arguments:

*stmt*

A prepared statement returned by the `db2_prepare` function.

*parameters*

Optional: An array that contains the values to use in place of the parameter markers, in order.

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.



## Example

Prepare and execute a statement that includes variable input.

```
$sql = "SELECT firstme, lastname FROM employee WHERE bonus > ? AND bonus < ?";
$stmt = db2_prepare($conn, $sql);
if (!$stmt) {
    // Handle errors
}

// Explicitly bind parameters
db2_bind_param($stmt, 1, $_POST['lower']);
db2_bind_param($stmt, 2, $_POST['upper']);

db2_execute($stmt);
// Process results

// Invoke prepared statement again using dynamically bound parameters
db2_execute($stmt, array($_POST['lower'], $_POST['upper']));
```

## What to do next

If the SQL statement returns one or more result sets, you can begin fetching rows from the statement resource.

## Inserting large objects in PHP (ibm\_db2):

When you insert a large object into the database, rather than loading all of the data for a large object into a PHP string and passing it to the IBM data server database through an INSERT statement, you can insert large objects directly from a file on your PHP server.

## Before you begin

Obtain a connection resource by calling one of the connection functions in the `ibm_db2` API.

## Procedure

To insert a large object into the database directly from a file:

1. Call the `db2_prepare` function to prepare an INSERT statement with a parameter marker that represents the large object column.
2. Set the value of a PHP variable to the path and name of the file that contains the data for the large object. The path can be relative or absolute, and is subject to the access permissions of the PHP executable file.
3. Call the `db2_bind_param` function to bind the parameter marker to the variable. The third argument to this function is a string representing the name of the PHP variable that holds the path and name of the file. The fourth argument is `DB2_PARAM_FILE`, which tells the `ibm_db2` extension to retrieve the data from a file.
4. Call the `db2_execute` function to issue the INSERT statement.

## Example

Insert a large object into the database.

```

$stmt = db2_prepare($conn, "INSERT INTO animal_pictures(picture) VALUES (?");
$picture = "/opt/albums/spook/grooming.jpg";
$rc = db2_bind_param($stmt, 1, "picture", DB2_PARAM_FILE);
$rc = db2_execute($stmt);

```

## Reading query result sets

### Fetching rows or columns from result sets in PHP (ibm\_db2):

After executing a statement that returns one or more result sets, use one of the functions available in the `ibm_db2` API to iterate through the returned rows of each result set. If your result set includes columns that contain extremely large data, you can retrieve the data on a column-by-column basis to avoid using too much memory.

#### Before you begin

You must have a statement resource returned by either the `db2_exec` or `db2_execute` function that has one or more associated result sets.

#### Procedure

To fetch data from a result set:

1. Fetch data from a result set by calling one of the fetch functions.

Table 4. *ibm\_db2* fetch functions

Function	Description
<code>db2_fetch_array</code>	Returns an array, indexed by column position, representing a row in a result set. The columns are 0-indexed.
<code>db2_fetch_assoc</code>	Returns an array, indexed by column name, representing a row in a result set.
<code>db2_fetch_both</code>	Returns an array, indexed by both column name and position, representing a row in a result set
<code>db2_fetch_row</code>	Sets the result set pointer to the next row or requested row. Use this function to iterate through a result set.
<code>db2_fetch_object</code>	Returns an object with properties representing columns in the fetched row. The properties of the object map to the names of the columns in the result set.

These functions accept the following arguments:

*stmt*

A valid statement resource.

*row\_number*

The number of the row that you want to retrieve from the result set. Row numbering begins with 1. Specify a value for this optional parameter if you requested a scrollable cursor when you called the `db2_exec` or `db2_prepare` function. With the default forward-only cursor, each call to a fetch method returns the next row in the result set.

2. Optional: If you called the `db2_fetch_row` function, for each iteration over the result set, retrieve a value from the specified column by calling the `db2_result`

function. You can specify the column by either passing an integer that represents the position of the column in the row (starting with 0), or a string that represents the name of column.

3. Continue fetching rows until the fetch function returns False, which indicates that you have reached the end of the result set.

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.

### Example

*Example 1:* Fetch rows from a result set by calling the `db2_fetch_object` function

```
<?php
$conn = db2_connect("sample", "db2inst1", "");
$sql = 'SELECT FIRSTNME, LASTNAME FROM EMPLOYEE WHERE EMPNO = ?';
$stmt = db2_prepare($conn, $sql);
db2_execute($stmt, array('000010'));
while ($row = db2_fetch_object($stmt)) {
    print "Name:
        {$row->FIRSTNME} {$row->LASTNAME}

    ";
}
db2_close($conn);
?>
```

*Example 2:* Fetch rows from a result set by calling the `db2_fetch_row` function

```
<?php
$conn = db2_connect("sample", "db2inst1", "");
$sql = 'SELECT FIRSTNME, LASTNAME FROM EMPLOYEE WHERE EMPNO = ?';
$stmt = db2_prepare($conn, $sql);
db2_execute($stmt, array('000010'));
while (db2_fetch_row($stmt)) {
    $fname = db2_result($stmt, 0);
    $lname = db2_result($stmt, 'LASTNAME');
    print "
    Name: $fname $lname

    ";
}
db2_close($conn);
?>
```

*Example 3:* Fetch rows from a result set by calling the `db2_fetch_both` function

```
<?php
$conn = db2_connect("sample", "db2inst1", "");
$sql = 'SELECT FIRSTNME, LASTNAME FROM EMPLOYEE WHERE EMPNO = ?';
$stmt = db2_prepare($conn, $sql);
db2_execute($stmt, array('000010'));
while ($row = db2_fetch_both($stmt)) {
    print "
    NAME: $row[0] $row[1]

    ";
    print "
    NAME: " . $row['FIRSTNME'] . " " . $row['LASTNAME'] . "

    ";
}
db2_close($conn);
?>
```

## What to do next

When you are ready to close the connection to the database, call the `db2_close` function. If you attempt to close a persistent connection that you created by using `db2_pconnect`, the close request returns `TRUE`, and the IBM data server client connection remains available for the next caller.

## Fetching large objects in PHP (ibm\_db2):

When you fetch a large object from a result set, rather than treating the large object as a PHP string, you can save system resources by fetching large objects directly into a file on your PHP server.

## Before you begin

Obtain a connection resource by calling one of the connection functions in the `ibm_db2` API.

## Procedure

To fetch a large object from the database directly into a file:

1. Create a PHP variable representing a stream. For example, assign the return value from a call to the `fopen` function to a variable.
2. Create a `SELECT` statement by calling the `db2_prepare` function.
3. Bind the output column for the large object to the PHP variable representing the stream by calling the `db2_bind_param` function. The third argument to this function is a string representing the name of the PHP variable that holds the path and name of the file. The fourth argument is `DB2_PARAM_FILE`, which tells the `ibm_db2` extension to write the data into a file.
4. Issue the SQL statement by calling the `db2_execute` function.
5. Retrieve the next row in the result set by calling an `ibm_db2` fetch function (for example, `db2_fetch_object`).

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.

## Example

Fetch a large object from the database.

```
$stmt = db2_prepare($conn, "SELECT name, picture FROM animal_pictures");
$picture = fopen("/opt/albums/spook/grooming.jpg", "wb");
$rc = db2_bind_param($stmt, 1, "nickname", DB2_CHAR, 32);
$rc = db2_bind_param($stmt, 2, "picture", DB2_PARAM_FILE);
$rc = db2_execute($stmt);
$rc = db2_fetch_object($stmt);
```

## Calling stored procedures in PHP (ibm\_db2)

To call a stored procedure from a PHP application, you prepare and execute an SQL `CALL` statement. The procedure that you call can include input parameters (IN), output parameters (OUT), and input and output parameters (INOUT).

## Before you begin

Obtain a connection resource by calling one of the connection functions in the `ibm_db2` API.

## Procedure

To call a stored procedure:

1. Call the `db2_prepare` function, passing the following arguments:

*connection*

A valid database connection resource returned from `db2_connect` or `db2_pconnect`.

*statement*

A string that contains the SQL CALL statement, including parameter markers (?) for any input or output parameters

*options*

Optional: A associative array that specifies the type of cursor to return for result sets. You can use this parameter to request a scrollable cursor on database servers that support this type of cursor. By default, a forward-only cursor is returned.

2. For each parameter marker in the CALL statement, call the `db2_bind_param` function, passing the following arguments:

*stmt*

The prepared statement returned by the call to the `db2_prepare` function.

*parameter-number*

An integer that represents the position of the parameter marker in the SQL statement.

*variable-name*

The name of the PHP variable to bind to the parameter specified by *parameter-number*.

*parameter-type*

A constant that specifies whether to bind the PHP variable to the SQL parameter as an input parameter (`DB2_PARAM_INPUT`), an output parameter (`DB2_PARAM_OUTPUT`), or a parameter that accepts input and returns output (`DB2_PARAM_INPUT_OUTPUT`).

This step binds each parameter marker to the name of a PHP variable that will hold the output.

3. Call the `db2_execute` function, passing the prepared statement as an argument.

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.

## Example

Prepare and execute an SQL CALL statement.

```
$sql = 'CALL match_animal(?, ?)';
$stmt = db2_prepare($conn, $sql);

$second_name = "Rickety Ride";
$weight = 0;

db2_bind_param($stmt, 1, "second_name", DB2_PARAM_INOUT);
db2_bind_param($stmt, 2, "weight", DB2_PARAM_OUT);

print "Values of bound parameters _before_ CALL:\n";
print " 1: {$second_name} 2: {$weight}\n";

db2_execute($stmt);
```

```
print "Values of bound parameters _after_ CALL:\n";
print " 1: {$second_name} 2: {$weight}\n";
```

## What to do next

If the procedure call returns one or more result sets, you can begin fetching rows from the statement resource.

### Retrieving multiple result sets from a stored procedure in PHP (ibm\_db2):

When a single call to a stored procedure returns more than one result set, you can use the `db2_next_result` function of the `ibm_db2` API to retrieve the result sets.

### Before you begin

You must have a statement resource returned by the `db2_exec` or `db2_execute` function that has multiple result sets.

### Procedure

To retrieve multiple result sets:

1. Fetch rows from the first result set returned from the procedure by calling one of the following `ibm_db2` fetch functions, passing the statement resource as an argument. (The first result set that is returned from the procedure is associated with the statement resource.)

Table 5. *ibm\_db2* fetch functions

Function	Description
<code>db2_fetch_array</code>	Returns an array, indexed by column position, representing a row in a result set. The columns are 0-indexed.
<code>db2_fetch_assoc</code>	Returns an array, indexed by column name, representing a row in a result set.
<code>db2_fetch_both</code>	Returns an array, indexed by both column name and position, representing a row in a result set
<code>db2_fetch_row</code>	Sets the result set pointer to the next row or requested row. Use this function to iterate through a result set.
<code>db2_fetch_object</code>	Returns an object with properties representing columns in the fetched row. The properties of the object map to the names of the columns in the result set.

2. Retrieve the subsequent result sets by passing the original statement resource as the first argument to the `db2_next_result` function. You can fetch rows from the statement resource until no more rows are available in the result set.

The `db2_next_result` function returns `False` when no more result sets are available or if the procedure did not return a result set.

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.

## Example

Retrieve multiple result sets from a stored procedure.

```
$stmt = db2_exec($conn, 'CALL multiResults()');

print "Fetching first result set\n";
while ($row = db2_fetch_array($stmt)) {
    // work with row
}

print "\nFetching second result set\n";
$result_2 = db2_next_result($stmt);
if ($result_2) {
    while ($row = db2_fetch_array($result_2)) {
        // work with row
    }
}

print "\nFetching third result set\n";
$result_3 = db2_next_result($stmt);
if ($result_3) {
    while ($row = db2_fetch_array($result_3)) {
        // work with row
    }
}
```

## What to do next

When you are ready to close the connection to the database, call the `db2_close` function. If you attempt to close a persistent connection that you created by using `db2_pconnect`, the close request returns `TRUE`, and the persistent IBM data server client connection remains available for the next caller.

## Commit modes in PHP applications (ibm\_db2)

You can control how groups of SQL statements are committed by specifying a commit mode for a connection resource. The `ibm_db2` extension supports two commit modes: `autocommit` and `manual commit`.

You must use a regular connection resource returned by the `db2_connect` function to control database transactions in PHP. Persistent connections always use `autocommit` mode.

### autocommit mode

In `autocommit` mode, each SQL statement is a complete transaction, which is automatically committed. `Autocommit` mode helps prevent locking escalation issues that can impede the performance of highly scalable Web applications. By default, the `ibm_db2` extension opens every connection in `autocommit` mode.

You can turn on `autocommit` mode after disabling it by calling `db2_autocommit($conn, DB2_AUTOCOMMIT_ON)`, where `conn` is a valid connection resource.

Calling the `db2_autocommit` function might affect the performance of your PHP scripts because it requires additional communication between PHP and the database management system.

### manual commit mode

In `manual commit` mode, the transaction ends when you call the `db2_commit` or `db2_rollback` function. This means that all statements

executed on the same connection between the start of a transaction and the call to the commit or rollback function are treated as a single transaction.

Manual commit mode is useful if you might have to roll back a transaction that contains one or more SQL statements. If you issue SQL statements in a transaction, and the script ends without explicitly committing or rolling back the transaction, the `ibm_db2` extension automatically rolls back any work performed in the transaction.

You can turn off autocommit mode when you create a database connection by using the "AUTOCOMMIT" => `DB2_AUTOCOMMIT_OFF` setting in the `db2_connect` options array. You can also turn off autocommit mode for an existing connection resource by calling `db2_autocommit($conn, DB2_AUTOCOMMIT_OFF)`, where `conn` is a valid connection resource.

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.

### Example

End the transaction when `db2_commit` or `db2_rollback` is called.

```
$conn = db2_connect('SAMPLE', 'db2inst1', 'ibmdb2', array(
    'AUTOCOMMIT' => DB2_AUTOCOMMIT_ON));

// Issue one or more SQL statements within the transaction
$result = db2_exec($conn, 'DELETE FROM TABLE employee');
if ($result === FALSE) {
    print '<p>Unable to complete transaction!</p>';
    db2_rollback($conn);
}
else {
    print '<p>Successfully completed transaction!</p>';
    db2_commit($conn);
}
```

### Error-handling functions in PHP applications (ibm\_db2)

Sometimes errors happen when you attempt to connect to a database or issue an SQL statement. The username or password might be incorrect, a table or column name might be misspelled, or the SQL statement might be invalid. The `ibm_db2` API provides error-handling functions to help you recover gracefully from these situations.

#### Connection errors

Use one of the following functions to retrieve diagnostic information if a connection attempt fails.

Table 6. `ibm_db2` functions for handling connection errors

Function	Description
<code>db2_conn_error</code>	Retrieves the SQLSTATE returned by the last connection attempt
<code>db2_conn_errormsg</code>	Retrieves a descriptive error message appropriate for an application error log

#### SQL errors

Use one of the following functions to retrieve diagnostic information if an attempt to prepare or execute an SQL statement or to fetch a result from a result set fails.



Table 7. *ibm\_db2* functions for handling SQL errors

Function	Description
db2_stmt_error	Retrieves the SQLSTATE returned by the last attempt to prepare or execute an SQL statement or to fetch a result from a result set
db2_stmt_errormsg	Retrieves a descriptive error message appropriate for an application error log

For more information about the *ibm\_db2* API, see <http://www.php.net/docs.php>.

**Tip:** To avoid security vulnerabilities that might result from directly displaying the raw SQLSTATE returned from the database, and to offer a better overall user experience in your Web application, use a switch structure to recover from known error states or return custom error messages. For example:

```
switch($this->state):
    case '22001':
        // More data than allowed for the defined column
        $message = "You entered too many characters for this value.";
        break;
```

## Example

*Example 1:* Handle connection errors

```
$connection = db2_connect($database, $user, $password);
if (!$connection) {
    $this->state = db2_conn_error();
    return false;
}
```

*Example 2:* Handle SQL errors

```
$stmt = db2_prepare($connection, "DELETE FROM employee
WHERE firstnme = ?");
if (!$stmt) {
    $this->state = db2_stmt_error();
    return false;
}
```

*Example 3:* Handle SQL errors that result from executing prepared statements

```
$success = db2_execute($stmt, array('Dan'));
if (!$success) {
    $this->state = db2_stmt_error($stmt);
    return $false;
}
```

## Database metadata retrieval functions in PHP (*ibm\_db2*)

You can use functions in the *ibm\_db2* API to retrieve metadata for databases served by DB2 Database for Linux, UNIX, and Windows, IBM Cloudscape, and, through DB2 Connect™, DB2 for z/OS and DB2 for i.

Some classes of applications, such as administration interfaces, must dynamically reflect the structure and SQL objects contained in arbitrary databases. One approach to retrieving metadata about a database is to issue SELECT statements directly against the system catalog tables; however, the schema of the system catalog tables might change between versions of DB2, or the schema of the system catalog tables on DB2 Database for Linux, UNIX, and Windows might differ from the schema of the system catalog tables on DB2 for z/OS. Rather than laboriously

maintaining these differences in your application code, you can use PHP functions available in the `ibm_db2` extension to retrieve database metadata.

Before calling these functions, you must set up the PHP environment and have a connection resource returned by the `db2_connect` or `db2_pconnect` function.

**Important:** Calling metadata functions uses a significant amount of space. If possible, cache the results of your calls for use in subsequent calls.

*Table 8. `ibm_db2` metadata retrieval functions*

Function	Description
<code>db2_client_info</code>	Returns a read-only object with information about the IBM data server client
<code>db2_column_privileges</code>	Returns a result set listing the columns and associated privileges for a table
<code>db2_columns</code>	Returns a result set listing the columns and associated metadata for a table
<code>db2_foreign_keys</code>	Returns a result set listing the foreign keys for a table
<code>db2_primary_keys</code>	Returns a result set listing the primary keys for a table
<code>db2_procedure_columns</code>	Returns a result set listing the parameters for one or more stored procedures
<code>db2_procedures</code>	Returns a result set listing the stored procedures registered in the database
<code>db2_server_info</code>	Returns a read-only object with information about the database management system software and configuration
<code>db2_special_columns</code>	Returns a result set listing the unique row identifiers for a table
<code>db2_statistics</code>	Returns a result set listing the indexes and statistics for a table
<code>db2_table_privileges</code>	Returns a result set listing tables and their associated privileges in the database

Most of the `ibm_db2` database metadata retrieval functions return result sets with columns defined for each function. To retrieve rows from the result sets, use the `ibm_db2` functions that are available for this purpose.

The `db2_client_info` and `db2_server_info` functions directly return a single object with read-only properties. You can use the properties of these objects to create an application that behaves differently depending on the database management system to which it connects. For example, rather than encoding a limit of the lowest common denominator for all possible database management systems, a Web-based database administration application built on the `ibm_db2` extension could use the `db2_server_info()->MAX_COL_NAME_LEN` property to dynamically display text fields for naming columns with maximum lengths that correspond to the maximum length of column names on the database management system to which it is connected.

For more information about the `ibm_db2` API, see <http://www.php.net/docs.php>.

## Example

*Example 1:* Display a list of columns and associated privileges for a table

```
<?php
$conn = db2_connect('sample', 'db2inst1', 'ibmdb2');

if ($conn) {
    $stmt = db2_column_privileges($conn, NULL, NULL, 'DEPARTMENT');
    $row = db2_fetch_array($stmt);
    print $row[2] . "\n";
    print $row[3] . "\n";
    print $row[7];
    db2_close($conn);
}
else {
    echo db2_conn_errormsg();
    printf("Connection failed\n\n");
}
?>
```

*Example 2:* Display a list of primary keys for a table

```
<?php
$conn = db2_connect('sample', 'db2inst1', 'ibmdb2');

if ($conn) {
    $stmt = db2_primary_keys($conn, NULL, NULL, 'DEPARTMENT');
    while ($row = db2_fetch_array($stmt)) {
        echo "TABLE_NAME:\t" . $row[2] . "\n";
        echo "COLUMN_NAME:\t" . $row[3] . "\n";
        echo "KEY_SEQ:\t" . $row[4] . "\n";
    }

    db2_close($conn);
}
else {
    echo db2_conn_errormsg();
    printf("Connection failed\n\n");
}
?>
```

*Example 3:* Display a list of parameters for one or more stored procedures

```
<?php
$conn = db2_connect('sample', 'db2inst1', 'ibmdb2');

if ($conn) {
    $stmt = db2_procedures($conn, NULL, 'SYS%', '%');

    $row = db2_fetch_assoc($stmt);
    var_dump($row);

    db2_close($conn);
}
else {
    echo "Connection failed.\n";
}
?>
```

*Example 4:* Display a list of the indexes and statistics for a table

```
<?php
$conn = db2_connect('sample', 'db2inst1', 'ibmdb2');

if ($conn) {
    echo "Test DEPARTMENT table:\n";
    $result = db2_statistics($conn, NULL, NULL, "EMPLOYEE", 1);
}
```

```

while ($row = db2_fetch_assoc($result)) {
    var_dump($row);
}

echo "Test non-existent table:\n";
$result = db2_statistics($conn,NULL,NULL,"NON_EXISTENT_TABLE",1);
$row = db2_fetch_array($result);
if ($row) {
    echo "Non-Empty\n";
} else {
    echo "Empty\n";
}

db2_close($conn);
}
else {
    echo 'no connection: ' . db2_conn_errormsg();
}
?>

```

*Example 5:* Display a list of tables and their associated privileges in the database

```

<?php
$conn = db2_connect('sample', 'db2inst1', 'ibmdb2');

if ($conn) {
    $stmt = db2_table_privileges($conn, NULL, "%%", "DEPARTMENT");
    while ($row = db2_fetch_assoc($stmt)) {
        var_dump($row);
    }
    db2_close($conn);
}
else {
    echo db2_conn_errormsg();
    printf("Connection failed\n\n");
}
?>

```

## Application development in PHP (PDO)

The PDO\_IBM extension provides a variety of useful PHP functions for accessing and manipulating data through the standard object-oriented database interface introduced in PHP 5.1. The extension includes functions for connecting to a database, executing and preparing SQL statements, fetching rows from result sets, managing transactions, calling stored procedures, handling errors, and retrieving metadata.

### Connecting to an IBM data server database with PHP (PDO)

Before you can issue SQL statements to create, update, delete, or retrieve data, you must connect to a database. You can use the PHP Data Objects (PDO) interface for PHP to connect to an IBM data server database through either a cataloged connection or a direct TCP/IP connection. To improve performance, you can also create a persistent connection.

### Before you begin

You must set up the PHP 5.1 (or later) environment on your system and enable the PDO and PDO\_IBM extensions.

## About this task

This procedure returns a connection object to an IBM data server database. This connection stays open until you set the PDO object to NULL, or the PHP script finishes.

## Procedure

To connect to an IBM data server database:

1. Create a connection to the database by calling the PDO constructor within a `try{}` block. Pass a *DSN* value that specifies `ibm:` for the PDO\_IBM extension, followed by either a cataloged database name or a complete database connection string for a direct TCP/IP connection.
  - (Windows): By default, the PDO\_IBM extension uses connection pooling to minimize connection resources and improve connection performance.
  - (Linux and UNIX): To create a persistent connection, pass `array(PDO::ATTR_PERSISTENT => TRUE)` as the *driver\_options* (fourth) argument to the PDO constructor.
2. Optional: Set error handling options for the PDO connection in the fourth argument to the PDO constructor:
  - By default, PDO sets an error message that can be retrieved through `PDO::errorInfo()` and an `SQLCODE` that can be retrieved through `PDO::errorCode()` when any error occurs; to request this mode explicitly, set `PDO::ATTR_ERRMODE => PDO::ERRMODE_SILENT`
  - To issue a PHP `E_WARNING` when any error occurs, in addition to setting the error message and `SQLCODE`, set `PDO::ATTR_ERRMODE => PDO::ERRMODE_WARNING`
  - To throw a PHP exception when any error occurs, set `PDO::ATTR_ERRMODE => PDO::ERRMODE_EXCEPTION`
3. Catch any exception thrown by the `try{}` block in a corresponding `catch {}` block.

For more information about the PDO API, see <http://php.net/manual/en/book.pdo.php>.

## Example

Connect to an IBM data server database over a persistent connection.

```
try {
    $connection = new PDO("ibm:SAMPLE", "db2inst1", "ibmdb2", array(
        PDO::ATTR_PERSISTENT => TRUE,
        PDO::ATTR_ERRMODE => PDO::ERRMODE_EXCEPTION)
    );
}
catch (Exception $e) {
    echo($e->getMessage());
}
```

## What to do next

Next, you prepare and execute SQL statements.

## Executing SQL statements in PHP (PDO)

After connecting to a database, use methods available in the PDO API to prepare and execute SQL statements. The SQL statements can contain static text or parameter markers that represent variable input.

## Executing a single SQL statement in PHP (PDO):

To prepare and execute a single SQL statement that accepts no input parameters, use the PDO::exec or PDO::query method. Use the PDO::exec method to execute a statement that returns no result set. Use the PDO::query method to execute a statement that returns one or more result sets.

### Before you begin

**Important:** To avoid the security threat of SQL injection attacks, use the PDO::exec or PDO::query method only to execute SQL statements composed of static strings. Interpolation of PHP variables representing user input into the SQL statement can expose your application to SQL injection attacks.

Obtain a connection object by calling the PDO constructor.

### Procedure

To prepare and execute a single SQL statement that accepts no input parameters, call one of the following methods:

- To execute an SQL statement that returns no result set, call the PDO::exec method on the PDO connection object, passing in a string that contains the SQL statement. For example, a typical use of PDO::exec is to set the default schema for your application in a common include file or base class.

If the SQL statement succeeds (successfully inserts, modifies, or deletes rows), the PDO::exec method returns an integer value representing the number of rows that were inserted, modified, or deleted.

To determine if the PDO::exec method failed (returned FALSE or 0), use the === operator to strictly test the returned value against FALSE.

- To execute an SQL statement that returns one or more result sets, call the PDO::query method on the PDO connection object, passing in a string that contains the SQL statement. For example, you might want to call this method to execute a static SELECT statement.

If the method call succeeds, it returns a PDOStatement resource that you can use in subsequent method calls.

If the method call fails (returns FALSE), you can use the PDO::errorCode and PDO::errorInfo method to retrieve diagnostic information about the error. For more information about the PDO API, see <http://php.net/manual/en/book.pdo.php>.

### Example

*Example 1:* Call the PDO::exec method to set the default schema for your application

```
$conn = new PDO('ibm:SAMPLE', 'db2inst1', 'ibmdb2');
$result = $conn->exec('SET SCHEMA myapp');
if ($result === FALSE) {
    print "Failed to set schema: " . $conn->errorMsg();
}
```

*Example 2:* Call the PDO::query method to issue an SQL SELECT statement

```
$conn = new PDO('ibm:SAMPLE', 'db2inst1', 'ibmdb2');
$result = $conn->query('SELECT firstme, lastname FROM employee');
if (!$result) {
    print "<p>Could not retrieve employee list: " . $conn->errorMsg(). "</p>";
}
```

```

}
while ($row = $conn->fetch()) {
    print "<p>Name: {$row[0] $row[1]}</p>";
}

```

## What to do next

If you called the PDO::query method to create a PDOStatement object, you can begin retrieving rows from the object by calling the PDOStatement::fetch or PDOStatement::fetchAll method.

## Preparing and executing SQL statements in PHP (PDO):

To prepare and execute an SQL statement that includes variable input, use the PDO::prepare, PDOStatement::bindParam, and PDOStatement::execute methods. Preparing a statement improves performance because the database server creates an optimized access plan for data retrieval that it can reuse if the statement is executed again.

### Before you begin

Obtain a connection object by calling the PDO constructor.

### Procedure

To prepare and execute an SQL statement that includes parameter markers:

1. Call the PDO::prepare method, passing the following arguments:

#### *statement*

A string that contains the SQL statement, including question marks (?) or named variables (:name) as parameter markers for any column or predicate values that require variable input. You can only use parameter markers as a place holder for column or predicate values. The SQL compiler is unable to create an access plan for a statement that uses parameter markers in place of column names, table names, or other SQL identifiers. You cannot use both question mark (?) parameter markers and named parameter markers (:name) in the same SQL statement.

#### *driver\_options*

Optional: An array that contains statement options:

#### **PDO::ATTR\_CURSOR**

This option sets the type of cursor that PDO returns for result sets. By default, PDO returns a forward-only cursor (PDO::CURSOR\_FWDONLY), which returns the next row in a result set for every call to PDOStatement::fetch(). You can set this parameter to PDO::CURSOR\_SCROLL to request a scrollable cursor.

If the function call succeeds, it returns a PDOStatement object that you can use in subsequent method calls that are related to this query.

If the function call fails (returns False), you can use the PDO::errorCode or PDO::errorInfo method to retrieve diagnostic information about the error.

2. Optional: For each parameter marker in the SQL string, call the PDOStatement::bindParam method, passing the following arguments. Binding input values to parameter markers ensures that each input value is treated as a single parameter, which prevents SQL injection attacks against your application.

#### *parameter*

A parameter identifier. For question mark parameter markers (?), this is an

integer that represents the 1-indexed position of the parameter in the SQL statement. For named parameter markers (:name), this is a string that represents the parameter name.

#### *variable*

The value to use in place of the parameter marker

3. Call the PDOStatement::execute method, optionally passing an array that contains the values to use in place of the parameter markers, either in order for question mark parameter markers, or as a :name => value associative array for named parameter markers.

For more information about the PDO API, see <http://php.net/manual/en/book.pdo.php>.

### **Example**

Prepare and execute a statement that includes variable input.

```
$sql = "SELECT firstme, lastname FROM employee WHERE bonus > ? AND bonus < ?";
$stmt = $conn->prepare($sql);
if (!$stmt) {
    // Handle errors
}

// Explicitly bind parameters
$stmt->bindParam(1, $_POST['lower']);
$stmt->bindParam(2, $_POST['upper']);

$stmt->execute($stmt);

// Invoke statement again using dynamically bound parameters
$stmt->execute($stmt, array($_POST['lower'], $_POST['upper']));
```

### **What to do next**

If the SQL statement returns one or more result sets, you can begin fetching rows from the statement resource by calling the PDOStatement::fetch or PDOStatement::fetchAll method.

### **Inserting large objects in PHP (PDO):**

When you insert a large object into the database, rather than loading all of the data for a large object into a PHP string and passing it to the IBM data server database through an INSERT statement, you can insert large objects directly from a file on your PHP server.

### **Before you begin**

Obtain a connection object by calling the PDO constructor.

### **Procedure**

To insert a large object into the database directly from a file:

1. Call the PDO::prepare method to create a PDOStatement object from an INSERT statement with a parameter marker that represents the large object column.
2. Create a PHP variable that represents a stream (for example, by assigning the value returned by the fopen function to variable).



3. Call the `PDOStatement::bindParam` method, passing the following arguments to bind the parameter marker to the PHP variable that represents the stream of data for the large object:

*parameter*

A parameter identifier. For question mark parameter markers (?), this is an integer that represents the 1-indexed position of the parameter in the SQL statement. For named parameter markers (:name), this is a string that represents the parameter name.

*variable*

The value to use in place of the parameter marker

*data\_type*

The PHP constant, `PDO::PARAM_LOB`, which tells the PDO extension to retrieve the data from a file.

4. Call the `PDOStatement::execute` method to issue the INSERT statement.

### Example

Insert a large object into the database.

```
$stmt = $conn->prepare("INSERT INTO animal_pictures(picture) VALUES (?)");  
$picture = fopen("/opt/albums/spook/grooming.jpg", "rb");  
$stmt->bindParam(1, $picture, PDO::PARAM_LOB);  
$stmt->execute();
```

## Reading query result sets

### Fetching rows or columns from result sets in PHP (PDO):

After executing a statement that returns one or more result sets, use one of the methods available in the PDO API to iterate through the returned rows. The PDO API also provides methods that allow you to fetch a single column from one or more rows in the result set.

### Before you begin

You must have a statement resource returned by either the `PDO::query` or `PDOStatement::execute` method that has one or more associated result sets.

### Procedure

To fetch data from a result set:

1. Fetch data from a result set by calling one of the following fetch methods:
  - To return a single row from a result set as an array or object, call the `PDOStatement::fetch` method.
  - To return all of the rows from the result set as an array of arrays or objects, call the `PDOStatement::fetchAll` method.

By default, PDO returns each row as an array indexed by the column name and 0-indexed column position in the row. To request a different return style, specify one of the following constants as the first parameter when you call the `PDOStatement::fetch` method:

#### **PDO::FETCH\_ASSOC**

Returns an array indexed by column name as returned in your result set.

**PDO::FETCH\_BOTH (default)**

Returns an array indexed by both column name and 0-indexed column number as returned in your result set

**PDO::FETCH\_BOUND**

Returns TRUE and assigns the values of the columns in your result set to the PHP variables to which they were bound with the `PDOStatement::bindParam` method.

**PDO::FETCH\_CLASS**

Returns a new instance of the requested class, mapping the columns of the result set to named properties in the class.

**PDO::FETCH\_INTO**

Updates an existing instance of the requested class, mapping the columns of the result set to named properties in the class.

**PDO::FETCH\_LAZY**

Combines `PDO::FETCH_BOTH` and `PDO::FETCH_OBJ`, creating the object variable names as they are accessed.

**PDO::FETCH\_NUM**

Returns an array indexed by column number as returned in your result set, starting at column 0.

**PDO::FETCH\_OBJ**

Returns an anonymous object with property names that correspond to the column names returned in your result set.

If you requested a scrollable cursor when you called the `PDO::query` or `PDOStatement::execute` method, you can pass the following optional parameters that control which rows are returned to the caller:

- One of the following constants that represents the fetch orientation of the fetch request:

**PDO::FETCH\_ORI\_NEXT (default)**

Fetches the next row in the result set.

**PDO::FETCH\_ORI\_PRIOR**

Fetches the previous row in the result set.

**PDO::FETCH\_ORI\_FIRST**

Fetches the first row in the result set.

**PDO::FETCH\_ORI\_LAST**

Fetches the last row in the result set.

**PDO::FETCH\_ORI\_ABS**

Fetches the absolute row in the result set. Requires a positive integer as the third argument to the `PDOStatement::fetch` method.

**PDO::FETCH\_ORI\_REL**

Fetches the relative row in the result set. Requires a positive or negative integer as the third argument to the `PDOStatement::fetch` method.

- An integer requesting the absolute or relative row in the result set, corresponding to the fetch orientation requested in the second argument to the `PDOStatement::fetch` method.
2. Optional: Fetch a single column from one or more rows in a result set by calling one of the following methods:
    - To return a single column from a single row in the result set:

Call the `PDOStatement::fetchColumn` method, specifying the column you want to retrieve as the first argument of the method. Column numbers start at 0. If you do not specify a column, the `PDOStatement::fetchColumn` returns the first column in the row.

- To return an array that contains a single column from all of the remaining rows in the result set:

Call the `PDOStatement::fetchAll` method, passing the `PDO::FETCH_COLUMN` constant as the first argument, and the column you want to retrieve as the second argument. Column numbers start at 0. If you do not specify a column, calling `PDOStatement::fetchAll(PDO::FETCH_COLUMN)` returns the first column in the row.

For more information about the PDO API, see <http://php.net/manual/en/book.pdo.php>.

### Example

Return an array indexed by column number.

```
$stmt = $conn->query("SELECT firstnme, lastname FROM employee");
while ($row = $stmt->fetch(PDO::FETCH_NUM)) {
    print "Name: <p>{$row[0] $row[1]}</p>";
}
```

### What to do next

When you are ready to close the connection to the database, set the PDO object to `NULL`. The connection closes automatically when the PHP script finishes.

### Fetching large objects in PHP (PDO):

When you fetch a large object from a result set, rather than treating the large object as a PHP string, you can save system resources by fetching large objects directly into a file on your PHP server.

### Before you begin

Obtain a connection object by calling the PDO constructor.

### Procedure

To fetch a large object from the database directly into a file:

1. Create a PHP variable representing a stream. For example, assign the return value from a call to the `fopen` function to a variable.
2. Create a `PDOStatement` object from an SQL statement by calling the `PDO::prepare` method.
3. Bind the output column for the large object to the PHP variable representing the stream by calling the `PDOStatement::bindColumn` method. The second argument is a string representing the name of the PHP variable that holds the path and name of the file. The third argument is a PHP constant, `PDO::PARAM_LOB`, which tells the PDO extension to write the data into a file. You must call the `PDOStatement::bindColumn` method to assign a different PHP variable for every column in the result set.
4. Issue the SQL statement by calling the `PDOStatement::execute` method.

5. Call `PDOStatement::fetch(PDO::FETCH_BOUND)` to retrieve the next row in the result set, binding the column output to the PHP variables that you associated when you called the `PDOStatement::bindColumn` method.

### Example

Fetch a large object from the database directly into a file.

```
$stmt = $conn->prepare("SELECT name, picture FROM animal_pictures");
$picture = fopen("/opt/albums/spook/grooming.jpg", "wb");
$stmt->bindColumn('NAME', $nickname, PDO::PARAM_STR, 32);
$stmt->bindColumn('PICTURE', $picture, PDO::PARAM_LOB);
$stmt->execute();
$stmt->fetch(PDO::FETCH_BOUND);
```

### Calling stored procedures in PHP (PDO)

To call a stored procedure from a PHP application, you execute an SQL CALL statement. The procedure that you call can include input parameters (IN), output parameters (OUT), and input and output parameters (INOUT).

### Before you begin

Obtain a connection object by calling the PDO constructor.

### About this task

This procedure prepares and executes an SQL CALL statement. For more information, also see the topic about preparing and executing SQL statements.

### Procedure

To call a stored procedure:

1. Call the `PDO::prepare` method to prepare a CALL statement with parameter markers that represent the OUT and INOUT parameters.
2. For each parameter marker in the CALL statement, call the `PDOStatement::bindParam` method to bind each parameter marker to the name of the PHP variable that will hold the output value of the parameter after the CALL statement has been issued. For INOUT parameters, the value of the PHP variable is passed as the input value of the parameter when the CALL statement is issued.

- a. Set the third parameter, *data\_type*, to one of the following `PDO::PARAM_*` constants that specifies the type of data being bound:

**PDO::PARAM\_NULL**

Represents the SQL NULL data type.

**PDO::PARAM\_INT**

Represents SQL integer types.

**PDO::PARAM\_LOB**

Represents SQL large object types.

**PDO::PARAM\_STR**

Represents SQL character data types.

For an INOUT parameter, use the bitwise OR operator to append `PDO::PARAM_INPUT_OUTPUT` to the type of data being bound.

- b. Set the fourth parameter, *length*, to the maximum expected length of the output value.

3. Call the `PDOStatement::execute` method, passing the prepared statement as an argument.

For more information about the PDO API, see <http://php.net/manual/en/book.pdo.php>.

### Example

Prepare and execute an SQL CALL statement.

```
$sql = 'CALL match_animal(?, ?)';
$stmt = $conn->prepare($sql);

$second_name = "Rickety Ride";
$weight = 0;

$stmt->bindParam(1, $second_name, PDO::PARAM_STR|PDO::PARAM_INPUT_OUTPUT, 32);
$stmt->bindParam(2, $weight, PDO::PARAM_INT, 10);

print "Values of bound parameters _before_ CALL:\n";
print " 1: {$second_name} 2: {$weight}\n";

$stmt->execute();

print "Values of bound parameters _after_ CALL:\n";
print " 1: {$second_name} 2: {$weight}\n";
```

### Retrieving multiple result sets from a stored procedure in PHP (PDO):

When a single call to a stored procedure returns more than one result set, you can use the `PDOStatement::nextRow` method of the PDO API to retrieve the result sets.

#### Before you begin

You must have a `PDOStatement` object returned by calling a stored procedure with the `PDO::query` or `PDOStatement::execute` method.

#### Procedure

To retrieve multiple result sets:

1. Fetch rows from the first result set returned from the procedure by calling one of the following PDO fetch methods. (The first result set that is returned from the procedure is associated with the `PDOStatement` object returned by the CALL statement.)
  - To return a single row from a result set as an array or object, call the `PDOStatement::fetch` method.
  - To return all of the rows from the result set as an array of arrays or objects, call the `PDOStatement::fetchAll` method.

Fetch rows from the `PDOStatement` object until no more rows are available in the first result set.

2. Retrieve the subsequent result sets by calling the `PDOStatement::nextRowset` method to return the next result set. You can fetch rows from the `PDOStatement` object until no more rows are available in the result set.

The `PDOStatement::nextRowset` method returns `False` when no more result sets are available or the procedure did not return a result set.

For more information about the PDO API, see <http://php.net/manual/en/book.pdo.php>.

## Example

Retrieve multiple result sets from a stored procedure.

```
$sql = 'CALL multiple_results()';
$stmt = $conn->query($sql);
do {
    $rows = $stmt->fetchAll(PDO::FETCH_NUM);
    if ($rows) {
        print_r($rows);
    }
} while ($stmt->nextRowset());
```

## What to do next

When you are ready to close the connection to the database, set the PDO object to NULL. The connection closes automatically when the PHP script finishes.

## Commit modes in PHP (PDO)

You can control how groups of SQL statements are committed by specifying a commit mode for a connection resource. The PDO extension supports two commit modes: autocommit and manual commit.

### autocommit mode

In autocommit mode, each SQL statement is a complete transaction, which is automatically committed. Autocommit mode helps prevent locking escalation issues that can impede the performance of highly scalable Web applications. By default, the PDO extension opens every connection in autocommit mode.

### manual commit mode

In manual commit mode, the transaction begins when you call the `PDO::beginTransaction` method, and it ends when you call either the `PDO::commit` or `PDO::rollback` method. This means that any statements executed (on the same connection) between the start of a transaction and the call to the commit or rollback method are treated as a single transaction.

Manual commit mode is useful if you might have to roll back a transaction that contains one or more SQL statements. If you issue SQL statements in a transaction and the script ends without explicitly committing or rolling back the transaction, PDO automatically rolls back any work performed in the transaction.

After you commit or rollback the transaction, PDO automatically resets the database connection to autocommit mode.

For more information about the PDO API, see <http://php.net/manual/en/book.pdo.php>.

## Example

End the transaction when `PDO::commit` or `PDO::rollback` is called.

```
$conn = new PDO('ibm:SAMPLE', 'db2inst1', 'ibmdb2', array(
    PDO::ATTR_ERRMODE => PDO::ERRMODE_EXCEPTION));
// PDO::ERRMODE_EXCEPTION means an SQL error throws an exception
try {
    // Issue these SQL statements in a transaction within a try{} block
    $conn->beginTransaction();

    // One or more SQL statements
```

```

    $conn->commit();
}
catch (Exception $e) {
    // If something raised an exception in our transaction block of statements,
    // roll back any work performed in the transaction
    print '<p>Unable to complete transaction!</p>';
    $conn->rollBack();
}

```

## Handling errors and warnings in PHP (PDO)

Sometimes errors happen when you attempt to connect to a database or issue an SQL statement. The password for your connection might be incorrect, a table you referred to in a SELECT statement might not exist, or the SQL statement might be invalid. PDO provides error-handling methods to help you recover gracefully from these situations.

### Before you begin

You must set up the PHP environment on your system and enable the PDO and PDO\_IBM extensions.

### About this task

PDO gives you the option of handling errors as warnings, errors, or exceptions. However, when you create a new PDO connection object, PDO always throws a PDOException object if an error occurs. If you do not catch the exception, PHP prints a backtrace of the error information that might expose your database connection credentials, including your user name and password.

This procedure catches a PDOException object and handles the associated error.

### Procedure

1. To catch a PDOException object and handle the associated error:
  - a. Wrap the call to the PDO constructor in a try block.
  - b. Following the try block, include a catch block that catches the PDOException object.
  - c. Retrieve the error message associated with the error by invoking the Exception::getMessage method on the PDOException object.
2. To retrieve the SQLSTATE associated with a PDO or PDOStatement object, invoke the errorCode method on the object.
3. To retrieve an array of error information associated with a PDO or PDOStatement object, invoke the errorInfo method on the object. The array contains a string representing the SQLSTATE as the first element, an integer representing the SQL or CLI error code as the second element, and a string containing the full text error message as the third element.

For more information about the PDO API, see <http://php.net/manual/en/book.pdo.php>.





---

## Chapter 3. Developing Python applications

---

### Python, SQLAlchemy and Django Framework application development for IBM data servers

Python is a general purpose, high level scripting language that is well suited for rapid application development. Python emphasizes code readability and supports a variety of programming paradigms, including procedural, object-oriented, aspect-oriented, meta, and functional programming. The Python language is managed by the Python Software Foundation.

The following extensions are available for accessing IBM data server databases from a Python application:

#### **ibm\_db**

This API is defined by IBM and provides the best support for advanced features. In addition to issuing SQL queries, calling stored procedures, and using pureXML, you can access metadata information.

#### **ibm\_db\_dbi**

This API implements Python Database API Specification v2.0. Because the `ibm_db_dbi` API conforms to the specification, it does not offer some of the advanced features that the `ibm_db` API supports. If you have an application with a driver that supports Python Database API Specification v2.0, you can easily switch to `ibm_db`. The `ibm_db` and `ibm_db_dbi` APIs are packaged together.

#### **ibm\_db\_sa**

This adaptor supports SQLAlchemy, which offers a flexible way to access IBM data servers. SQLAlchemy is a popular open source Python SQL toolkit and object-to-relational mapper (ORM).

#### **ibm\_db\_django**

This adaptor enables access to IBM data servers from Django. Django is a popular web framework used to build high-performing, elegant Web applications quickly.

Python applications can access the following IBM data server databases:

- IBM DB2 Version 9.1 for Linux, UNIX, and Windows, Fix Pack 2 and later
- IBM DB2 Universal Database (DB2 UDB) Version 8 for Linux, UNIX, and Windows, Fixpak 15 and later
- Remote connections to IBM DB2 Universal Database on i5/OS V5R3, with PTF SI27358 (includes SI27250)
- Remote connections to IBM DB2 for IBM i 5.4 and later, with PTF SI27256
- Remote connections to IBM DB2 for z/OS, Version 8 and Version 9
- IBM Informix® Dynamic Server v11.10 and later

### Python downloads and related resources

Many resources are available to help you develop Python applications for IBM data servers.

Table 9. Python downloads and related resources

<b>Downloads</b>	
Python (Includes Windows binaries. Most Linux distributions come with Python already precompiled.)	<a href="http://www.python.org/download/">http://www.python.org/download/</a>
SQLAlchemy	<a href="http://www.sqlalchemy.org/download.html">http://www.sqlalchemy.org/download.html</a>
Django	<a href="http://www.djangoproject.com/download/">http://www.djangoproject.com/download/</a>
ibm_db and ibm_db_dbi extensions (including source code)	<a href="http://pypi.python.org/pypi/ibm_db/">http://pypi.python.org/pypi/ibm_db/</a>
	<a href="http://code.google.com/p/ibm-db/downloads/list">http://code.google.com/p/ibm-db/downloads/list</a>
ibm_db_sa adapter for SQLAlchemy 0.4	<a href="http://code.google.com/p/ibm-db/downloads/list">http://code.google.com/p/ibm-db/downloads/list</a>
	<a href="http://pypi.python.org/pypi/ibm_db_sa">http://pypi.python.org/pypi/ibm_db_sa</a>
ibm_db_django adaptor for Django 1.0.x and 1.1	<a href="http://code.google.com/p/ibm-db/downloads/list">http://code.google.com/p/ibm-db/downloads/list</a>
	<a href="http://pypi.python.org/pypi/ibm_db_django">http://pypi.python.org/pypi/ibm_db_django</a>
setuptools program	<a href="http://pypi.python.org/pypi/setuptools">http://pypi.python.org/pypi/setuptools</a>
IBM Data Server Driver Package (DS Driver)	<a href="http://www.ibm.com/software/data/support/data-server-clients/index.html">http://www.ibm.com/software/data/support/data-server-clients/index.html</a>
<b>API documentation</b>	
ibm_db API documentation	<a href="http://code.google.com/p/ibm-db/wiki/APIs">http://code.google.com/p/ibm-db/wiki/APIs</a>
<i>Python Database API Specification v2.0</i>	<a href="http://www.python.org/dev/peps/pep-0249/">http://www.python.org/dev/peps/pep-0249/</a>
<b>SQLAlchemy documentation</b>	
<i>Quick Getting Started Steps for ibm_db_sa</i>	<a href="http://code.google.com/p/ibm-db/wiki/README">http://code.google.com/p/ibm-db/wiki/README</a>
<i>SQLAlchemy Documentation</i>	<a href="http://www.sqlalchemy.org/docs/index.html">http://www.sqlalchemy.org/docs/index.html</a>
<b>Django documentation</b>	
<i>Getting Started steps for ibm_db_django</i>	<a href="http://code.google.com/p/ibm-db/wiki/ibm_db_django_README">http://code.google.com/p/ibm-db/wiki/ibm_db_django_README</a>
<i>Django Documentation</i>	<a href="http://www.djangoproject.com">http://www.djangoproject.com</a>
<b>Additional resources</b>	
Python Programming Language Web site	<a href="http://www.python.org/">http://www.python.org/</a>
The Python SQL Toolkit and Object Relational Mapper Web site	<a href="http://www.sqlalchemy.org/">http://www.sqlalchemy.org/</a>

## Setting up the Python environment for IBM data servers

Before you can connect to an IBM data server and execute SQL statements, you must set up the Python environment by installing the `ibm_db` (Python) and, optionally, the `ibm_db_sa` (SQLAlchemy) or `ibm_db_django` (Django) packages on your system.

### Before you begin

You must have the following software installed on your system:

- Python 2.5 or later, excluding Python 3.X. For Linux operating systems, you also require the `python2.5-dev` package.
- `setuptools`, a program available at <http://pypi.python.org/pypi/setuptools>. You can use this program to download, build, install, upgrade, and uninstall Python packages.
- If you are connecting from Python to a DB2 database server on a remote machine, then you need one of the following DB2 clients on the machine where you are installing, running or executing Python: IBM Data Server Driver Package, IBM Data Server Client, or IBM Data Server Driver for ODBC and CLI.
- If you are connecting from Python to a DB2 database server on the local machine, you don't need to install a DB2 database client.

## Procedure

To set up the Python environment:

1. Set up your Linux or Windows environment by using one of the following approaches:

To install the latest DB2 Python drivers and framework adaptors, obtain them from the community. The community versions always contain up-to-date fixes, the latest of which sometimes might not be available in the drivers/adapters shipped in the DB2 installation.

- If you have Internet access, issue one of the following commands:
  - To install `ibm_db`: `easy_install ibm_db`
  - To install both `ibm_db_sa` and `ibm_db`: `easy_install ibm_db_sa`
  - To install `ibm_db_django`: `easy_install ibm_db_django`

This step installs the eggs under the `site-packages` directory where `setuptools` is installed.

- If you do not have Internet access, copy the appropriate egg file for your system from <http://code.google.com/p/ibm-db/downloads/list>, and issue the following command:

```
easy_install egg_file_name
```

where `egg_file_name` is the path to the egg file. For example, issue the following command:

```
easy_install /home/user/ibm_db-xx-py2.5-linux-i386.egg
```

- To install from community source-code, download the source code from [http://pypi.python.org/pypi/ibm\\_db/](http://pypi.python.org/pypi/ibm_db/). Then build and install the driver. The instructions for building and installing the driver are in the `README` file that is included with the driver source code.
- If you want to install the DB2 Python drivers and framework adaptors that are available in your DB2 image, go to the egg file's directory in the DB2 installation, for example: `/home/user/sqlllib/python64/`. Then issue one of the following commands:
  - To install `ibm_db`: `easy_install ibm_db_egg_file_name` for example; `easy_install ibm_db-xx-py2.5-linux-x86_64.egg`
  - To install `ibm_db_sa`: `easy_install ibm_db_sa_egg_file_name` for example; `easy_install ibm_db_sa-xx-py2.5.egg`
  - To install `ibm_db_django`: `easy_install ibm_db_django_egg_file_name` for example; `easy_install ibm_db_django-xx-py2.5.egg`

This step installs the eggs under the `site-packages` directory where `setuptools` is installed.

2. Create an environment variable named **PYTHONPATH**, and set it to the path where you installed the `ibm_db` egg, as shown in the following examples:
  - On Windows operating systems: `PYTHONPATH=setuptools_install_path\site-packages\ibm_db-xx.egg`
  - On Linux (BASH shell): `export PYTHONPATH=setuptools_install_path/site-packages/ibm_db-xx.egg`

3. Before you run any Python script that connects to DB2, you need to ensure that the IBM DB2 Python driver can access the CLI driver called `libdb2.so`, which is part of your DB2 Server setup or DB2 client setup. Failing to do so will result in a 'missing libraries - libdb2.so.1' error when you run your Python program. On Linux, you do this by adding the folder where the `libdb2.so` file resides to the **LD\_LIBRARY\_PATH** environmental variable for the userid under which Python is going to be run.

When using IBM Data Server Driver Package, `libdb2.so` is located in the `odbc_cli_driver/linux/clidriver/lib` directory.

In the DB2 server installation, `libdb2.so` is located in the `sqllib/lib` directory.

4. From the command prompt, test your setup by typing `python` to launch the Python interpreter and entering code similar to that shown in the following examples:

- To test `ibm_db`:

```
import ibm_db
ibm_db_conn = ibm_db.connect('dsn=database', 'user', 'password')
import ibm_db_dbi
conn = ibm_db_dbi.Connection(ibm_db_conn)
conn.tables('SYSCAT', '%')
```

- To test `ibm_db_sa`:

```
import sqlalchemy
from sqlalchemy import *
import ibm_db_sa.ibm_db_sa
db2 = sqlalchemy.create_engine('ibm_db_sa://user:password@host.name.com:50000/database')
metadata = MetaData()
users = Table('users', metadata,
              Column('user_id', Integer, primary_key = True),
              Column('user_name', String(16), nullable = False),
              Column('email_address', String(60), key='email'),
              Column('password', String(20), nullable = False)
             )
metadata.bind = db2
metadata.create_all()
users_table = Table('users', metadata, autoload=True, autoload_with=db2)
users_table
```

- To test `ibm_db_django`:

- a. Create a new Django project:

```
django-admin.py startproject myproj
```

- b. Edit the `settings.py` file to configure access to DB2. Use any editor available on the system. An example on nix would be:

```
$ cd myproj
$ vi settings.py
```

```
DATABASE_ENGINE = 'ibm_db_django'
DATABASE_NAME = 'mydb'
DATABASE_USER = 'db2inst1'
DATABASE_PASSWORD = 'ibmdb2'
DATABASE_HOST = 'localhost'
DATABASE_PORT = '50000'
```

- c. Add the following lines in the tuple `INSTALLED_APPS` section of the `settings.py` file.

```
'django.contrib.flatpages',
'django.contrib.redirects',
'django.contrib.comments',
'django.contrib.admin',
```

d. Run a test suite to confirm the configuration is correct:

```
python manage.py test
```

## Results

The Python packages are now installed on your system and ready to use.

## What to do next

Connect to the data server, and begin issuing SQL statements.

## Application development in Python with `ibm_db`

The `ibm_db` API provides a variety of useful Python functions for accessing and manipulating data in an IBM data server database, including functions for connecting to a database, preparing and issuing SQL statements, fetching rows from result sets, calling stored procedures, committing and rolling back transactions, handling errors, and retrieving metadata.

### Connecting to an IBM data server database in Python

Before you can execute SQL statements to create, update, delete, or retrieve data, you must connect to a database. You can use the `ibm_db` API to connect to a database through either a cataloged or uncataloged connection. To improve performance, you can also create a persistent connection.

#### Before you begin

- Set up the Python environment.
- Issue the following from your Python script: `import ibm_db`.

#### Procedure

To return a connection resource that you can use to call SQL statements, call one of the following functions:

Table 10. `ibm_db` connection functions

Function	Description
<code>ibm_db.connect</code>	Creates a nonpersistent connection.
<code>ibm_db.pconnect</code>	Creates a persistent connection. A persistent connection remains open after the initial Python script request, which allows subsequent Python requests to reuse the connection if they have an identical set of credentials.

The database value that you pass as an argument to these functions can be either a cataloged database name or a complete database connection string for a direct TCP/IP connection. You can specify optional arguments that control the timing of committing transactions, the case of the column names that are returned, and the cursor type.

If the connection attempt fails, you can retrieve diagnostic information by calling the `ibm_db.conn_error` or `ibm_db.conn_errormsg` function.

For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

## Example

*Example 1:* Connect to a local or cataloged database

Approach 1:

```
import ibm_db
conn = ibm_db.connect("dsn=name","username","password")
```

Approach 2:

```
import ibm_db
conn = ibm_db.connect("name","username","password")
```

*Example 2:* Connect to a cataloged or uncataloged database

```
import ibm_db
ibm_db.connect("DATABASE=name;HOSTNAME=host;PORT=60000;PROTOCOL=TCPIP;UID=username;
              PWD=password;", "", "")
```

## What to do next

If the connection attempt is successful, you can use the connection resource when you call `ibm_db` functions that execute SQL statements. Next, you prepare and execute SQL statements.

## Executing SQL statements in Python

After connecting to a database, use functions available in the `ibm_db` API to prepare and execute SQL statements. The SQL statements can contain static text, XQuery expressions, or parameter markers that represent variable input.

### Preparing and executing a single SQL statement in Python:

To prepare and execute a single SQL statement, use the `ibm_db.exec_immediate` function. To avoid the security threat of SQL injection attacks, use the `ibm_db.exec_immediate` function only to execute SQL statements composed of static strings. Interpolation of Python variables representing user input into the SQL statement can expose your application to SQL injection attacks.

### Before you begin

Obtain a connection resource by calling one of the connection functions in the `ibm_db` API.

### Procedure

To prepare and execute a single SQL statement, call the `ibm_db.exec_immediate` function, passing the following arguments:

#### *connection*

A valid database connection resource returned from the `ibm_db.connect` or `ibm_db.pconnect` function.

#### *statement*

A string that contains the SQL statement. This string can include an XQuery expression that is called by the `XMLQUERY` function.

#### *options*

Optional: A dictionary that specifies the type of cursor to return for result sets. You can use this parameter to request a scrollable cursor for database servers that support this type of cursor. By default, a forward-only cursor is returned.

If the function call fails (returns False), you can use the `ibm_db.stmt_error` or `ibm_db.stmt_errormsg` function to retrieve diagnostic information about the error. If the function call succeeds, you can use the `ibm_db.num_rows` function to return the number of rows that the SQL statement returned or affected. If the SQL statement returns a result set, you can begin fetching the rows. For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

## Example

*Example 1:* Execute a single SQL statement

```
import ibm_db
conn = ibm_db.connect("dsn=name","username","password")
stmt = ibm_db.exec_immediate(conn, "UPDATE employee SET bonus = '1000' WHERE job = 'MANAGER'")
print "Number of affected rows: ", ibm_db.num_rows(stmt)
```

*Example 2:* Execute an XQuery expression

```
import ibm_db
conn = ibm_db.connect("dsn=name","username","password")
if conn:
    sql = "SELECT XMLSERIALIZE(XMLQUERY('for $i in $t/address where $i/city = \"01athe\" return <zip>
        {$i/zip/text()}</zip>' passing c.xmlcol as \"t\") AS CLOB(32k)) FROM xml_test c WHERE id = 1")
    stmt = ibm_db.exec_immediate(conn, sql)
    result = ibm_db.fetch_both(stmt)
    while( result ):
        print "Result from XMLSerialize and XMLQuery:", result[0]
    result = ibm_db.fetch_both(stmt)
```

## What to do next

If the SQL statement returns one or more result sets, you can begin fetching rows from the statement resource.

## Preparing and executing SQL statements with variable input in Python:

To prepare and execute an SQL statement that includes variable input, use the `ibm_db.prepare`, `ibm_db.bind_param`, and `ibm_db.execute` functions. Preparing a statement improves performance because the database server creates an optimized access plan for data retrieval that it can reuse if the statement is executed again.

## Before you begin

Obtain a connection resource by calling one of the connection functions in the `ibm_db` API.

## Procedure

To prepare and execute an SQL statement that includes parameter markers:

1. Call the `ibm_db.prepare` function, passing the following arguments:

### *connection*

A valid database connection resource returned from the `ibm_db.connect` or `ibm_db.pconnect` function.

### *statement*

A string that contains the SQL statement, including question marks (?) as parameter markers for column or predicate values that require variable input. This string can include an XQuery expression that is called by the XMLQUERY function.

### *options*

Optional: A dictionary that specifies the type of cursor to return for result

sets. You can use this parameter to request a scrollable cursor for database servers that support this type of cursor. By default, a forward-only cursor is returned.

If the function call succeeds, it returns a statement handle resource that you can use in subsequent function calls that are related to the query.

If the function call fails (returns False), you can use the `ibm_db.stmt_error` or `ibm_db.stmt_errormsg` function to retrieve diagnostic information about the error.

- Optional: For each parameter marker in the SQL string, call the `ibm_db.bind_param` function, passing the following arguments. Binding input values to parameter markers ensures that each input value is treated as a single parameter, which prevents SQL injection attacks.

*stmt*

The prepared statement returned by the call to the `ibm_db.prepare` function.

*parameter-number*

An integer that represents the position of the parameter marker in the SQL statement.

*variable*

The value to use in place of the parameter marker.

- Call the `ibm_db.execute` function, passing the following arguments:

*stmt*

A prepared statement returned from `ibm_db.prepare`.

*parameters*

A tuple of input parameters that match parameter markers contained in the prepared statement.

For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

## Example

Prepare and execute a statement that includes variable input.

```
import ibm_db
conn = ibm_db.connect("dsn=name","username","password")
sql = "SELECT EMPNO, LASTNAME FROM EMPLOYEE WHERE EMPNO > ? AND EMPNO < ?"
stmt = ibm_db.prepare(conn, sql)
max = 50
min = 0
# Explicitly bind parameters
ibm_db.bind_param(stmt, 1, min)
ibm_db.bind_param(stmt, 2, max)
ibm_db.execute(stmt)
# Process results

# Invoke prepared statement again using dynamically bound parameters
param = max, min,
ibm_db.execute(stmt, param)
```

## What to do next

If the SQL statement returns one or more result sets, you can begin fetching rows from the statement resource.



## Fetching rows or columns from result sets in Python

After executing a statement that returns one or more result sets, use one of the functions available in the `ibm_db` API to iterate through the returned rows. If your result set includes columns that contain extremely large data (such as BLOB or CLOB data), you can retrieve the data on a column-by-column basis to avoid using too much memory.

### Before you begin

You must have a statement resource returned by either the `ibm_db.exec_immediate` or `ibm_db.execute` function that has one or more associated result sets.

### Procedure

To fetch data from a result set:

1. Fetch data from a result set by calling one of the fetch functions.

Table 11. *ibm\_db* fetch functions

Function	Description
<code>ibm_db.fetch_tuple</code>	Returns a tuple, indexed by column position, representing a row in a result set. The columns are 0-indexed.
<code>ibm_db.fetch_assoc</code>	Returns a dictionary, indexed by column name, representing a row in a result set.
<code>ibm_db.fetch_both</code>	Returns a dictionary, indexed by both column name and position, representing a row in a result set.
<code>ibm_db.fetch_row</code>	Sets the result set pointer to the next row or requested row. Use this function to iterate through a result set.

These functions accept the following arguments:

*stmt*

A valid statement resource.

*row\_number*

The number of the row that you want to retrieve from the result set.

Specify a value for this parameter if you requested a scrollable cursor when you called the `ibm_db.exec_immediate` or `ibm_db.prepare` function. With the default forward-only cursor, each call to a fetch method returns the next row in the result set.

2. Optional: If you called the `ibm_db.fetch_row` function, for each iteration through the result set, retrieve a value from a specified column by calling the `ibm_db.result` function. You can specify the column by passing either an integer that represents the position of the column in the row (starting with 0) or a string that represents the name of the column.
3. Continue fetching rows until the fetch method returns `False`, which indicates that you have reached the end of the result set.  
For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

### Example

*Example 1:* Fetch rows from a result set by calling the `ibm_db.fetch_both` function

```

import ibm_db

conn = ibm_db.connect( "dsn=name", "username", "password" )
sql = "SELECT * FROM EMPLOYEE"
stmt = ibm_db.exec_immediate(conn, sql)
dictionary = ibm_db.fetch_both(stmt)
while dictionary != False:
    print "The ID is : ", dictionary["EMPNO"]
    print "The Name is : ", dictionary[1]
    dictionary = ibm_db.fetch_both(stmt)

```

*Example 2:* Fetch rows from a result set by calling the `ibm_db.fetch_tuple` function

```

import ibm_db

conn = ibm_db.connect( "dsn=name", "username", "password" )
sql = "SELECT * FROM EMPLOYEE"
stmt = ibm_db.exec_immediate(conn, sql)
tuple = ibm_db.fetch_tuple(stmt)
while tuple != False:
    print "The ID is : ", tuple[0]
    print "The name is : ", tuple[1]
    tuple = ibm_db.fetch_tuple(stmt)

```

*Example 3:* Fetch rows from a result set by calling the `ibm_db.fetch_assoc` function

```

import ibm_db

conn = ibm_db.connect( "dsn=name", "username", "password" )
sql = "SELECT * FROM EMPLOYEE"
stmt = ibm_db.exec_immediate(conn, sql)
dictionary = ibm_db.fetch_assoc(stmt)
while dictionary != False:
    print "The ID is : ", dictionary["EMPNO"]
    print "The name is : ", dictionary["FIRSTNAME"]
    dictionary = ibm_db.fetch_assoc(stmt)

```

*Example 4:* Fetch columns from a result set

```

import ibm_db

conn = ibm_db.connect( "dsn=name", "username", "password" )
sql = "SELECT * FROM EMPLOYEE"
stmt = ibm_db.exec_immediate(conn, sql)
while ibm_db.fetch_row(stmt) != False:
    print "The Employee number is : ", ibm_db.result(stmt, 0)
    print "The Name is : ", ibm_db.result(stmt, "NAME")

```

## What to do next

When you are ready to close the connection to the database, call the `ibm_db.close` function. If you attempt to close a persistent connection that you created with `ibm_db.pconnect`, the close request returns `True`, and the connection remains available for the next caller.

## Calling stored procedures in Python

To call a stored procedure from a Python application, you prepare and execute an SQL `CALL` statement. The procedure that you call can include input parameters (IN), output parameters (OUT), and input and output parameters (INOUT).

## Before you begin

Obtain a connection resource by calling one of the connection functions in the `ibm_db` API.

## Procedure

To call a stored procedure:

1. Call the `ibm_db.prepare` function, passing the following arguments:

*connection*

A valid database connection resource returned from `ibm_db.connect` or `ibm_db.pconnect`.

*statement*

A string that contains the SQL CALL statement, including parameter markers (?) for any input or output parameters.

*options*

Optional: A dictionary that specifies the type of cursor to return for result sets. You can use this parameter to request a scrollable cursor for database servers that support this type of cursor. By default, a forward-only cursor is returned.

2. For each parameter marker in the CALL statement, call the `ibm_db.bind_param` function, passing the following arguments:

*stmt*

The prepared statement returned by the call to the `ibm_db.prepare` function.

*parameter-number*

An integer that represents the position of the parameter marker in the SQL statement.

*variable*

The name of the Python variable that will hold the output.

*parameter-type*

A constant that specifies whether to bind the Python variable to the SQL parameter as an input parameter (`SQL_PARAM_INPUT`), an output parameter (`SQL_PARAM_OUTPUT`), or a parameter that accepts input and returns output (`SQL_PARAM_INPUT_OUTPUT`).

This step binds each parameter marker to the name of a Python variable that will hold the output.

3. Call the `ibm_db.execute` function, passing the prepared statement as an argument.

For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

## Example

Prepare and execute an SQL CALL statement.

```
import ibm_db

conn = ibm_db.connect("dsn=sample","username","password")
if conn:
    sql = 'CALL match_animal(?, ?, ?)'
    stmt = ibm_db.prepare(conn, sql)

    name = "Peaches"
    second_name = "Rickety Ride"
    weight = 0
    ibm_db.bind_param(stmt, 1, name, ibm_db.SQL_PARAM_INPUT)
    ibm_db.bind_param(stmt, 2, second_name, ibm_db.SQL_PARAM_INPUT_OUTPUT)
    ibm_db.bind_param(stmt, 3, weight, ibm_db.SQL_PARAM_OUTPUT)
```

```

print "Values of bound parameters _before_ CALL:"
print " 1: %s 2: %s 3: %d\n" % (name, second_name, weight)

if ibm_db.execute(stmt):
    print "Values of bound parameters _after_ CALL:"
    print " 1: %s 2: %s 3: %d\n" % (name, second_name, weight)

```

## What to do next

If the procedure call returns one or more result sets, you can begin fetching rows from the statement resource.

## Retrieving multiple result sets from a stored procedure in Python

When a single call to a stored procedure returns more than one result set, you can use the `ibm_db.next_result` function of the `ibm_db` API to retrieve the result sets.

## Before you begin

You must have a statement resource returned by the `ibm_db.exec_immediate` or `ibm_db.execute` function that has multiple result sets.

## Procedure

To retrieve multiple result sets:

1. Fetch rows from the first result set returned from the procedure by calling one of the following `ibm_db` fetch functions, passing the statement resource as an argument. (The first result set that is returned from the procedure is associated with the statement resource.)

Table 12. *ibm\_db* fetch functions

Function	Description
<code>ibm_db.fetch_tuple</code>	Returns a tuple, indexed by column position, representing a row in a result set. The columns are 0-indexed.
<code>ibm_db.fetch_assoc</code>	Returns a dictionary, indexed by column name, representing a row in a result set.
<code>ibm_db.fetch_both</code>	Returns a dictionary, indexed by both column name and position, representing a row in a result set.
<code>ibm_db.fetch_row</code>	Sets the result set pointer to the next row or requested row. Use this function to iterate through a result set.

2. Retrieve the subsequent result sets by passing the original statement resource as the first argument to the `ibm_db.next_result` function. You can fetch rows from the statement resource until no more rows are available in the result set.
 

The `ibm_db.next_result` function returns `False` when no more result sets are available or if the procedure did not return a result set.

For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

## Example

Retrieve multiple result sets from a stored procedure.

```

import ibm_db
conn = ibm_db.connect( "dsn=sample", "user", "password" )
if conn:
    sql = 'CALL sp_multi()'
    stmt = ibm_db.exec_immediate(conn, sql)
    row = ibm_db.fetch_assoc(stmt)
    while row != False :
        print "The value returned : ", row
        row = ibm_db.fetch_assoc(stmt)

    stmt1 = ibm_db.next_result(stmt)
    while stmt1 != False:
        row = ibm_db.fetch_assoc(stmt1)
        while row != False :
            print "The value returned : ", row
            row = ibm_db.fetch_assoc(stmt1)
        stmt1 = ibm_db.next_result(stmt)

```

## What to do next

When you are ready to close the connection to the database, call the `ibm_db.close` function. If you attempt to close a persistent connection that you created by using `ibm_db.pconnect`, the close request returns `True`, and the IBM data server client connection remains available for the next caller.

## Commit modes in Python applications

You can control how groups of SQL statements are committed by specifying a commit mode for a connection resource. The `ibm_db` API supports the following two commit modes: `autocommit` and `manual commit`.

### autocommit mode

In `autocommit` mode, each SQL statement is a complete transaction, which is automatically committed. `Autocommit` mode helps prevent locking escalation issues that can impede the performance of highly scalable Web applications. By default, the `ibm_db` API opens every connection in `autocommit` mode.

You can turn on `autocommit` mode after disabling it by calling `ibm_db.autocommit(conn, ibm_db.SQL_AUTOCOMMIT_ON)`, where `conn` is a valid connection resource.

Calling the `ibm_db.autocommit` function might affect the performance of your Python scripts because it requires additional communication between Python and the database management system.

### manual commit mode

In `manual commit` mode, the transaction ends when you call the `ibm_db.commit` or `ibm_db.rollback` function. This means that all statements executed on the same connection between the start of a transaction and the call to the `commit` or `rollback` function are treated as a single transaction.

`Manual commit` mode is useful if you might have to roll back a transaction that contains one or more SQL statements. If you execute SQL statements in a transaction and the script ends without explicitly committing or rolling back the transaction, the `ibm_db` extension automatically rolls back any work performed in the transaction.

You can turn off `autocommit` mode when you create a database connection by using the `{ ibm_db.SQL_ATTR_AUTOCOMMIT: ibm_db.SQL_AUTOCOMMIT_OFF }` setting in the `ibm_db.connect` or `ibm_db.pconnect` options array. You can

also turn off autocommit mode for a connection resource by calling `ibm_db.autocommit(conn, ibm_db.SQL_AUTOCOMMIT_OFF)`, where `conn` is a valid connection resource.

For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

## Example

Turn off autocommit mode and end the transaction when `ibm_db.commit` or `ibm_db.rollback` is called.

```
import ibm_db

array = { ibm_db.SQL_ATTR_AUTOCOMMIT : ibm_db.SQL_AUTOCOMMIT_OFF }
conn = ibm_db.pconnect("dsn=SAMPLE", "user", "password", array)
sql = "DELETE FROM EMPLOYEE"
try:
    stmt = ibm_db.exec_immediate(conn, sql)
except:
    print "Transaction couldn't be completed."
    ibm_db.rollback(conn)
else:
    ibm_db.commit(conn)
    print "Transaction complete."
```

## Error-handling functions in Python

Sometimes errors happen when you attempt to connect to a database or issue an SQL statement. The username or password might be incorrect, a table or column name might be misspelled, or the SQL statement might be invalid. The `ibm_db` API provides error-handling functions to help you recover gracefully from these situations.

### Connection errors

Use one of the following functions to retrieve diagnostic information if a connection attempt fails.

Table 13. `ibm_db` functions for handling connection errors

Function	Description
<code>ibm_db.conn_error</code>	Retrieves the SQLSTATE returned by the last connection attempt
<code>ibm_db.conn_errormsg</code>	Retrieves a descriptive error message appropriate for an application error log

### SQL errors

Use one of the following functions to retrieve diagnostic information if an attempt to prepare or execute an SQL statement or to fetch a result from a result set fails.

Table 14. `ibm_db` functions for handling SQL errors

Function	Description
<code>ibm_db.stmt_error</code>	Retrieves the SQLSTATE returned by the last attempt to prepare or execute an SQL statement or to fetch a result from a result set

Table 14. *ibm\_db* functions for handling SQL errors (continued)

Function	Description
<code>ibm_db.stmt_errormsg</code>	Retrieves a descriptive error message appropriate for an application error log

For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

## Example

*Example 1:* Handle connection errors

```
import ibm_db
try:
    conn = ibm_db.connect("dsn=sample","user","password")
except:
    print "no connection:", ibm_db.conn_errormsg()
else:
    print "The connection was successful"
```

*Example 2:* Handle SQL errors

```
import ibm_db
conn = ibm_db.connect( "dsn=sample", "user", "password")
sql = "DELETE FROM EMPLOYEE"
try:
    stmt = ibm_db.exec_immediate(conn, sql)
except:
    print "Transaction couldn't be completed:" , ibm_db.stmt_errormsg()
else:
    print "Transaction complete."
```

## Database metadata retrieval functions in Python

You can use functions in the `ibm_db` API to retrieve metadata for IBM databases.

Before calling these functions, you must set up the Python environment, issue `import_db` in your Python script, and obtain a connection resource by calling the `ibm_db.connect` or `ibm_db.pconnect` function.

**Important:** Calling metadata functions uses a significant amount of space. If possible, cache the results of your calls for use in subsequent calls.

Table 15. *ibm\_db* metadata retrieval functions

Function	Description
<code>ibm_db.client_info</code>	Returns a read-only object with information about the IBM data server client
<code>ibm_db.column_privileges</code>	Returns a result set listing the columns and associated privileges for a table
<code>ibm_db.columns</code>	Returns a result set listing the columns and associated metadata for a table
<code>ibm_db.foreign_keys</code>	Returns a result set listing the foreign keys for a table
<code>ibm_db.primary_keys</code>	Returns a result set listing the primary keys for a table
<code>ibm_db.procedure_columns</code>	Returns a result set listing the parameters for one or more stored procedures

Table 15. *ibm\_db* metadata retrieval functions (continued)

Function	Description
<code>ibm_db.procedures</code>	Returns a result set listing the stored procedures registered in a database
<code>ibm_db.server_info</code>	Returns a read-only object with information about the IBM data server
<code>ibm_db.special_columns</code>	Returns a result set listing the unique row identifier columns for a table
<code>ibm_db.statistics</code>	Returns a result set listing the index and statistics for a table
<code>ibm_db.table_privileges</code>	Returns a result set listing the tables in a database and the associated privileges

For more information about the `ibm_db` API, see <http://code.google.com/p/ibm-db/wiki/APIs>.

## Example

*Example 1:* Display information about the IBM data server client

```
import ibm_db

conn = ibm_db.connect("dsn=sample", "user", "password")
client = ibm_db.client_info(conn)

if client:
    print "DRIVER_NAME: string(%d) \"%s\" " % (len(client.DRIVER_NAME), client.DRIVER_NAME)
    print "DRIVER_VER: string(%d) \"%s\" " % (len(client.DRIVER_VER), client.DRIVER_VER)
    print "DATA_SOURCE_NAME: string(%d) \"%s\" " % (len(client.DATA_SOURCE_NAME), client.DATA_SOURCE_NAME)
    print "DRIVER_ODBC_VER: string(%d) \"%s\" " % (len(client.DRIVER_ODBC_VER), client.DRIVER_ODBC_VER)
    print "ODBC_VER: string(%d) \"%s\" " % (len(client.ODBC_VER), client.ODBC_VER)
    print "ODBC_SQL_CONFORMANCE: string(%d) \"%s\" " % (len(client.ODBC_SQL_CONFORMANCE), client.ODBC_SQL_CONFORMANCE)
    print "APPL_CODEPAGE: int(%s) " % client.APPL_CODEPAGE
    print "CONN_CODEPAGE: int(%s) " % client.CONN_CODEPAGE
    ibm_db.close(conn)
else:
    print "Error."
```

*Example 2:* Display information about the IBM data server

```
import ibm_db

conn = ibm_db.connect("dsn=sample", "user", "password")
server = ibm_db.server_info(conn)

if server:
    print "DBMS_NAME: string(%d) \"%s\" " % (len(server.DBMS_NAME), server.DBMS_NAME)
    print "DBMS_VER: string(%d) \"%s\" " % (len(server.DBMS_VER), server.DBMS_VER)
    print "DB_NAME: string(%d) \"%s\" " % (len(server.DB_NAME), server.DB_NAME)
    ibm_db.close(conn)
else:
    print "Error."
```



---

## Chapter 4. Developing Ruby on Rails applications

---

### The IBM\_DB Ruby driver and Rails adapter

With the introduction of support for the Ruby on Rails framework, Rails applications can now access data on IBM data servers.

Collectively known as the IBM\_DB gem, the IBM\_DB Ruby driver and Rails adapter allows Ruby applications to access the following database management systems:

- DB2 Version 9 for Linux, UNIX, and Windows
- DB2 Universal Database (DB2 UDB) Version 8 for Linux, UNIX, and Windows
- DB2 UDB Version 5, Release 1 (and later) for AS/400® and iSeries®, through DB2 Connect
- DB2 for z/OS, Version 8 and Version 9, through DB2 Connect
- Informix Dynamic Server, Version 11.10 and later

**Note:** Client applications should use IBM Data Server Driver Version 9.5 or later when accessing Informix Dynamic Server Version 11.10. Previous versions are not supported. Client applications can also use IBM Data Server Runtime Client or IBM Data Server Client.

The IBM\_DB Ruby driver can be used to connect to and access data from the IBM data servers mentioned above. The IBM\_DB Ruby adapter allows any database-backed Rails application to interface with IBM data servers.

For more information about IBM Ruby projects and the RubyForge open source community, refer to the following web site: <http://rubyforge.org/projects/rubyibm/>

For a list of installation requirements for DB2 database products, see <http://publib.boulder.ibm.com/infocenter/db2luw/v9r7/topic/com.ibm.db2.luw.qb.server.doc/doc/r0025127.html>

For a list of installation requirements for IBM Informix Dynamic Server, see [http://publib.boulder.ibm.com/infocenter/idshelp/v111/topic/com.ibm.expr.doc/ids\\_in\\_004x.html](http://publib.boulder.ibm.com/infocenter/idshelp/v111/topic/com.ibm.expr.doc/ids_in_004x.html)

For information about downloading an IBM Data Server Driver Package (DS Driver), refer to the following web site: <http://www.ibm.com/software/data/support/data-server-clients/index.html>.

### Getting started with IBM data servers on Rails

To start developing Ruby on Rails applications with IBM data servers, you must set up the Rails environment with IBM data servers. To get started, you can download the free version of DB2 and start developing Rails applications using DB2.

## Before you begin

To ensure that numeric values in quotations are handled correctly, you must use Version 9.1 Fix Pack 2 (or later) of one of the following client types: IBM Data Server Driver Package, IBM Data Server Client, or IBM Data Server Driver for ODBC and CLI.

## Procedure

To set up your environment and get started with IBM\_DB:

1. Download and install DB2 or IBM Informix from <http://www.ibm.com/software/data/servers/>.
2. Download and install the latest version of Ruby from <http://www.ruby-lang.org/en/downloads/>.
3. Install the Rails gem and its dependencies by issuing the following gem install command:

```
gem install rails --include-dependencies
```

## What to do next

You are now ready to install the IBM\_DB Ruby driver and Rails adapter as a gem. If you want, you can also set up an integrated development environment (IDE) for Rails.

## Setting up an integrated development environment for Rails

Rails requires no special file formats or integrated development environments (IDEs); you can get started with a command line prompt and a text editor. However, various IDEs are now available with Rails support, such as RadRails, which is a Rails environment for Eclipse.

## About this task

For more information about RadRails, see <http://www.radrails.org/>.

## Procedure

To set up an Eclipse based IDE for Ruby on Rails (RoR) development:

1. Install Eclipse from <http://www.eclipse.org/downloads/>.
2. Install the following Eclipse plug-ins from the following Eclipse remote update sites:
  - a. Ruby Development Tools from <http://rubyclipse.sourceforge.net/download.rdt.html>
  - b. RubyRails IDE feature from <http://radrails.sourceforge.net/update>
  - c. Subclipse plug-in from <http://subclipse.tigris.org/update>

## Installing the IBM\_DB adapter and driver as a Ruby gem

Ruby Gems is the standard packaging and installation framework for libraries and applications in the Ruby runtime environment. A single file for each bundle is called a gem, which complies to the package format. This package is then distributed and stored in a central repository, allowing simultaneous deployment of multiple versions of the same library or application.

## About this task

If you are connecting from Ruby to a DB2 database server on a remote machine, then you need one of the following DB2 clients on the machine where you are installing, running or executing Ruby: IBM Data Server Driver Package or IBM Data Server Runtime Client or IBM Data Server Client.

If you are connecting from Ruby/Ruby on Rails to a DB2 database server on the local machine, you don't need to install a DB2 database client.

Similar to package management and bundles (.rpm, .deb) used in Linux distributions, these gems can also be queried, installed, uninstalled, and manipulated through the gem end-user utility.

The gem utility can seamlessly query the remote RubyForge central repository and look up and install any of the many readily available utilities. When the IBM\_DB gem is installed, this functionality is immediately accessible from any script (or application) in the Ruby runtime environment, through:

```
require 'ibm_db'
```

or on Windows:

```
require 'mswin32/ibm_db'
```

## Procedure

To install the IBM\_DB adapter and driver as a Ruby gem:

1. On Linux, UNIX, and Mac OS X platforms, set environment variables and optionally source the DB2 profile:
  - a. Issue the following commands to set the environment variables

**IBM\_DB\_INCLUDE** and **IBM\_DB\_LIB**:

```
$ export IBM_DB_INCLUDE=DB2HOME/include
$ export IBM_DB_LIB=DB2HOME/lib
```

where *DB2HOME* is the directory where the IBM data server is installed. For example:

```
$ export IBM_DB_INCLUDE=/home/db2inst1/sqllib/include
$ export IBM_DB_LIB=/home/db2inst1/sqllib/lib
```

If you are using `ibm_db` 1.0.0 or earlier, instead of setting `IBM_DB_INCLUDE`, you must set the environment variable `IBM_DB_DIR` to *DB2HOME*.

### More about setting environment variables:

Depending on the architecture for which the IBM data server is installed, the `lib` directory under *DB2HOME* is a link to either `lib32` or `lib64`. You can set `IBM_DB_LIB` according to the architecture for which Ruby is compiled. For a 32-bit architecture, set `IBM_DB_LIB` to the `lib32` directory under *DB2HOME*. For a 64-bit architecture set `IBM_DB_LIB` to the `lib64` directory under *DB2HOME*.

### Note:

In IBM Data Server Driver Package, *DB2HOME* refers to the directory in which the client package is untarred, for example, the `odbc_cli_driver/linux/clidriver` directory.

In the DB2 server installation, *DB2HOME* refers to the `sqllib` directory under your DB2 instance.

2. On all supported platforms, issue the following gem command to install the IBM\_DB adapter and driver:  

```
$ gem install ibm_db
```
3. Before running any ruby script that connects to DB2, you need to ensure that the IBM DB2 Ruby driver can access the CLI driver `libdb2.so`, which is part of your DB2 Server setup or DB2 client setup. Failing to do so will result in a `missing libraries - libdb2.so.1` error when you run your Ruby program. You do this by adding the folder where the `libdb2.so` file resides to the **LD\_LIBRARY\_PATH** environmental variable on Linux or AIX® platforms for the `userid` under which Ruby will be run.

When using IBM Data Server Driver Package, the `libdb2.so` file is in the `odbc_cli_driver/linux/clidriver/lib` directory.

In the DB2 server installation, `libdb2.so` is in the `sqllib/lib/` directory.

**Note:** For a 32-bit architecture, set **LD\_LIBRARY\_PATH** to the `lib32` directory under *DB2HOME*. For a 64-bit architecture set **LD\_LIBRARY\_PATH** to the `lib64` directory under *DB2HOME*.

## Results

The IBM\_DB gem is now installed on your workstation.

## Verifying installation of the IBM\_DB gem with DB2 Express-C

To verify installation of the IBM\_DB gem with DB2 Express-C, you connect to the database, issue a `SELECT` statement, and then fetch the first row of the result set.

## Procedure

Use the following commands to install and verify the installation of the IBM\_DB gem with Ruby-1.8.6 patch level 111 on a Windows or Linux operating system. The output of the commands is also shown.

- To perform the installation, issue the command **gem install ibm\_db**. For example:

```
D:\>gem install ibm_db
Select which gem to install for your platform (i386-mswin32)
1. ibm_db 1.0.1 (ruby)
2. ibm_db 1.0.1 (mswin32)
2. ibm_db 1.0.0 (ruby)
3. ibm_db 1.0.0 (mswin32)
4. Skip this gem
5. Cancel installation
> 2
Successfully installed ibm_db-1.0.0-mswin32
Installing ri documentation for ibm_db-1.0.0-mswin32...
Installing RDoc documentation for ibm_db-1.0.0-mswin32...
```

**Note:** The examples in this topic include version information to demonstrate the installation. However, when you run the installation, you can choose from the two latest versions of the gem that are available.

The IBM\_DB gem is now installed on your machine.

- To verify the installation, run the following commands.

You can follow this process to verify installation against IBM Informix, DB2 Database for Linux, UNIX, and Windows, IBM DB2 for IBM i, and DB2 for z/OS. You can use DB2 Connect to access IBM DB2 for IBM i and DB2 for z/OS data servers.

```
C:\>irb
irb(main):001:0> require 'mwin32/ibm_db' (if using Linux based
platform then issue require 'ibm_db')
=>true
irb(main):002:0> conn = IBM_DB::connect
'devdb','username','password' (Here 'devdb' is the database cataloged in
client's database directory)
=> #<IBM_DB::Connection:0x2dddf40>
irb(main):003:0> stmt = IBM_DB::exec conn,'select * from cars'
=> #<IBM_DB::Statement:0x2beaabc>
irb(main):004:0> IBM_DB::fetch_assoc stmt (will fetch the first row of
the result set)
```

## What to do next

If these commands run successfully, the gem is installed correctly, and you can begin building Rails applications.

## Verifying installation with IBM data servers on Rails applications

To verify that the IBM\_DB driver and adapter are installed correctly, you test IBM\_DB driver access by connecting to an IBM data server and issuing a SELECT statement, and then you test IBM\_DB adapter access by building and running a sample Rails application.

## Procedure

To verify installation:

1. Install the latest version of the IBM\_DB gem.
2. Test IBM\_DB driver access.

For example, to test the access to an i5 data server through the IBM\_DB driver (and underlying DB2 Connect and IBM Data Server Driver for ODBC and CLI):

```
D:\ws\RoR\TeamRoom>irb
irb(main):001:0> require 'mwin32/ibm_db'
=> true
irb(main):002:0> conn = IBM_DB::connect 'testdb', 'user', 'pass'
=> #<IBM_DB::Connection:0x2f79d40>
irb(main):003:0> stmt = IBM_DB::exec conn, 'select * from qsys2.qsqptab1'
=> #<IBM_DB::Statement:0x2f762f8>
irb(main):004:0> IBM_DB::fetch_assoc stmt
```

3. Test IBM\_DB adapter access.

To test access to an IBM data server through the IBM\_DB adapter, follow the steps below to build a sample Rails application.

- a. Create a new Rails application by issuing the following command:

```
C:\>rails newapp --database=ibm_db
create
create app/controllers
create app/helpers
create app/models
create app/views/layouts
create config/environments
create config/initializers
create db
[.....]
```

```

create log/server.log
create log/production.log
create log/development.log
create log/test.log

```

- b. Change to the newly created directory, newapp:

```
C:\>cd newapp
```

- c. Configure connections for the Rails application by editing the database.yml file. For more information, see “Configuring Rails application connections to IBM data servers.”

If you are using a version prior to Rails 2.0, you need to register the IBM\_DB adapter to the list of connection adapters in the Rails framework by manually adding `ibm_db` to the list of connection adapters in `<RubyHome>\gems\1.8\gems\activerecord-1.15.6\lib\active_record.rb` at approximately line 77:

```
RAILS_CONNECTION_ADAPTERS = %w( mysql postgresql sqlite firebird
sqlserver db2 oracle sybase openbase frontbase ibm_db )
```

- d. Create a model and scaffold by issuing the following command:

```
C:\>ruby script/generate scaffold Tool name:string model_num:integer
exists app/models/
exists app/controllers/
[...]
create db/migrate
create db/migrate/20080716103959_create_tools.rb
```

- e. Issue the Rails migrate command to create the table (tools) in the database (devdb):

```
C:\> rake db:migrate
(in C:/ruby trials/newapp)
== 20080716111617 CreateTools: migrating
=====
-- create_table(:tools)
-> 0.5320s
== 20080716111617 CreateTools: migrated (0.5320s)
```

The Rails application can now access the Tools table and perform operations on it.

- f. Issue the following command to test the application:

```
C:\ruby trials\newapp>ruby script/console
Loading development environment (Rails 2.1.0)
>> tool = Tool.new
=> #<Tool id: nil, name: nil, model_num: nil, created_at: nil,
updated_at: nil>
>> tool.name = 'chistel'
=> "chistel"
>> tool.model_num = '007'
=> "007"
>> tool.save
=> true
>> Tool.find :all
=> [#<Tool id: 100, name: "chistel", model_num: 7, created_at:
"2008-07-16 11:29:35", updated_at: "2008-07-16 11:29:35">]
>>
```

## Configuring Rails application connections to IBM data servers

You configure database connections for a Rails application by specifying connection details in the database.yml file.

### Procedure

To configure host data server connections for a Rails application:

Edit the database configuration details in `rails_application_path\config\database.yml`, and specify the following connection attributes:

```
# The IBM_DB Adapter requires the native Ruby driver (ibm_db)
# for IBM data servers (ibm_db.so).
# +config+ the hash passed as an initializer argument content:
# == mandatory parameters
# adapter:      'ibm_db'           // IBM_DB Adapter name
# username:     'db2user'         // data server (database) user
# password:     'secret'          // data server (database) password
# database:     'DEVDB'           // remote database name (or catalog entry alias)
# == optional (highly recommended for data server auditing and monitoring purposes)
# schema:      'rails123'        // name space qualifier
# account:     'tester'          // OS account (client workstation)
# app_user:    'test11'          // authenticated application user
# application: 'rtests'          // application name
# workstation: 'plato'           // client workstation name
# == remote TCP/IP connection (required when no local database catalog entry available)
# host:        'Socrates'        // fully qualified hostname or IP address
# port:        '50000'           // data server TCP/IP port number
#
# When schema is not specified, the username value is used instead.
```

**Note:** Changes to connection information in this file are applied when the Rails environment is initialized during server startup. Any changes that you make after initialization do not affect the connections that are created.

Schema, account, app\_user, application and workstation are not supported for IBM Informix.

## IBM Ruby driver and trusted contexts

The IBM\_DB Ruby driver supports trusted contexts by using connection string keywords.

Trusted contexts provide a way of building much faster and more secure three-tier applications. The user's identity is always preserved for auditing and security purposes. When you require secure connections, trusted contexts improve performance because you do not have to get new connections.

### Example

The following example establishes a trusted connection and switches the user on the same connection.

```
def trusted_connection(database,hostname,port,auth_user,auth_pass,tc_user,tc_pass)
  dsn = "DATABASE=#{database};HOSTNAME=#{hostname};PORT=#{port};PROTOCOL=TCP;UID=#{auth_user};PWD=#{auth_pass};"
  conn_options = {IBM_DB::SQL_ATTR_USE_TRUSTED_CONTEXT => IBM_DB::SQL_TRUE}
  tc_options = {IBM_DB::SQL_ATTR_TRUSTED_CONTEXT_USERID => tc_user, IBM_DB::SQL_ATTR_TRUSTED_CONTEXT_PASSWORD => tc_pass}
  tc_conn = IBM_DB.connect dsn, '', '', conn_options
  if tc_conn
    puts "Trusted connection established successfully."
    val = IBM_DB.get_option tc_conn, IBM_DB::SQL_ATTR_USE_TRUSTED_CONTEXT, 1
    if val
      userBefore = IBM_DB.get_option tc_conn, IBM_DB::SQL_ATTR_TRUSTED_CONTEXT_USERID, 1
      #do some work as user 1
      #....
      #....
      #switch the user
      result = IBM_DB.set_option tc_conn, tc_options, 1
      userAfter = IBM_DB.get_option tc_conn, IBM_DB::SQL_ATTR_TRUSTED_CONTEXT_USERID, 1
      if userBefore != userAfter
        puts "User has been switched."
        #do some work as user 2
        #....
        #....
      end
    end
  end
  IBM_DB.close tc_conn
end
```

```

else
  puts "Attempt to connect failed due to: #{IBM_DB.conn_errormsg}"
end
end
end

```

## IBM\_DB Rails adapter dependencies and consequences

The IBM\_DB adapter (`ibm_db_adapter.rb`) has a direct dependency on the IBM\_DB driver, which uses IBM Data Server Driver for ODBC and CLI to connect to IBM data servers. The IBM Call Level Interface (CLI) is a callable SQL interface to IBM data servers, which is Open Database Connectivity (ODBC) compliant.

This dependency has several ramifications for the IBM\_DB adapter and driver.

- Installation of IBM Data Server Driver for ODBC and CLI, which meets the IBM\_DB requirement, is required.

IBM Data Server Driver for ODBC and CLI is included with a full DB2 database install, or you can obtain it separately

**Note:** The IBM Data Server Driver for ODBC and CLI is included in the following client packages:

- IBM Data Server Client
- IBM Data Server Runtime Client
- IBM Data Server Driver Package
- Driver behavior can be modified outside of a Rails application by using CLI keywords.

Certain transactional behavior can be altered outside the Rails application by using these CLI keywords. For example, CLI keywords can be used to set the current schema or alter transactional elements such as turning off autocommit behavior. For more information about CLI keywords, see the following links:

For Version 9: <http://publib.boulder.ibm.com/infocenter/db2luw/v9/index.jsp?topic=/com.ibm.db2.udb.apdv.cli.doc/doc/r0007964.htm>

For Version 9.5: <http://publib.boulder.ibm.com/infocenter/db2luw/v9r5/topic/com.ibm.db2.luw.apdv.cli.doc/doc/r0007964.html>

For Version 9.7: <http://publib.boulder.ibm.com/infocenter/db2luw/v9r7/topic/com.ibm.db2.luw.apdv.cli.doc/doc/r0007964.html>

- Any diagnostic gathering requires CLI driver tracing.

Because all requests through the IBM\_DB driver are implemented through IBM Data Server Driver for ODBC and CLI, the CLI trace facility can identify problems for applications that use the IBM\_DB adapter and driver.

A CLI trace captures all of the API calls made by an application to the IBM Data Server Driver for ODBC and CLI (including all input parameters), and it captures all of the values returned from the driver to the application. It is an interface trace that captures how an application interacts with the IBM Data Server Driver for ODBC and CLI and offers information about the inner workings of the driver.

## The IBM\_DB Ruby driver and Rails adapter are not supported on JRuby

The IBM\_DB adapter is not supported on JRuby.

The IBM\_DB adapter is not supported on JRuby because (as stated in the JRuby Wiki, "Getting Started"): "Many Gems will work fine in JRuby, however some Gems build native C libraries as part of their install process. These Gems will not



work in JRuby unless the Gem has also provided a Java equivalent to the native library." For more information, see <http://kenai.com/projects/jruby/pages/GettingStarted>.

The IBM\_DB adapter relies on the IBM\_DB Ruby driver (C extension) and the IBM Data Server Driver for ODBC and CLI to access databases on IBM data servers. Alternatively, you can either use the regular C implementation of Ruby, or use JDBC\_adapter to access databases.

## ActiveRecord-JDBC versus IBM\_DB adapter

Update 0.6.0 and later of the IBM\_DB gem provides a slightly different handling of the required numeric values quoting.

While the previous version of the adapter was attempting to screen out such usage of quotation marks on numeric values to conform to DB2 data server expectations on different platforms, the new implementation replaces the workaround with a permanent fix in the IBM data server client. This not only enables IBM data servers across platforms but provides a more reliable handling of all Rails APIs that could escape previous screening. The workaround provided by the previous version of the adapter is by its nature quite brittle, due to fluid developments in the Rails framework components (ActiveRecord). It is also known that certain Rails APIs managed to escape the screening of those overridden methods, so the workaround used in the ActiveRecord-JDBC adapter might require handling of some additional cases.

The JRuby runtime does not benefit from the same fix due to its inner specific interaction with the data servers. IBM DB2 for IBM i does not exhibit this issue (fixed in V5R3 and V5R4) and the same is true regarding IBM Informix. For the time being, until JRuby and ActiveRecord-JDBC adapter matures, the best alternative is to use the "classic Ruby" (C implementation) and the IBM\_DB adapter/driver. A fix in the ActiveRecord-JDBC adapter could also be considered, which could emulate the previous handling that the IBM\_DB adapter was providing.

## Heap size considerations with DB2 on Rails

Rails applications on DB2 require the **app1heapsz** database configuration parameter to be set to values above 1024.

You must set this parameter for each database for which you will be running DB2 on Rails applications. Use the following command to update the **app1heapsz** parameter:

```
db2 update db cfg for database_name using APPLHEAPSZ 1024
```

To enable this parameter, you must restart your DB2 instance.



---

## Appendix A. Overview of the DB2 technical information

DB2 technical information is available through the following tools and methods:

- DB2 Information Center
  - Topics (Task, concept and reference topics)
  - Help for DB2 tools
  - Sample programs
  - Tutorials
- DB2 books
  - PDF files (downloadable)
  - PDF files (from the DB2 PDF DVD)
  - printed books
- Command line help
  - Command help
  - Message help

**Note:** The DB2 Information Center topics are updated more frequently than either the PDF or the hardcopy books. To get the most current information, install the documentation updates as they become available, or refer to the DB2 Information Center at [ibm.com](http://ibm.com).

You can access additional DB2 technical information such as technotes, white papers, and IBM Redbooks® publications online at [ibm.com](http://ibm.com). Access the DB2 Information Management software library site at <http://www.ibm.com/software/data/sw-library/>.

### Documentation feedback

We value your feedback on the DB2 documentation. If you have suggestions for how to improve the DB2 documentation, send an email to [db2docs@ca.ibm.com](mailto:db2docs@ca.ibm.com). The DB2 documentation team reads all of your feedback, but cannot respond to you directly. Provide specific examples wherever possible so that we can better understand your concerns. If you are providing feedback on a specific topic or help file, include the topic title and URL.

Do not use this e-mail address to contact DB2 Customer Support. If you have a DB2 technical issue that the documentation does not resolve, contact your local IBM service center for assistance.

---

## DB2 technical library in hardcopy or PDF format

The following tables describe the DB2 library available from the IBM Publications Center at [www.ibm.com/e-business/linkweb/publications/servlet/pbi.wss](http://www.ibm.com/e-business/linkweb/publications/servlet/pbi.wss). English Version 9.7 manuals in PDF format can be downloaded from [www.ibm.com/support/docview.wss?uid=swg27015148](http://www.ibm.com/support/docview.wss?uid=swg27015148) and translated DB2 manuals in PDF format can be downloaded from [www.ibm.com/support/docview.wss?uid=swg27015149](http://www.ibm.com/support/docview.wss?uid=swg27015149).

Although the tables identify books available in print, the books might not be available in your country or region.

The form number increases each time a manual is updated. Ensure that you are reading the most recent version of the manuals, as listed below.

**Note:** The *DB2 Information Center* is updated more frequently than either the PDF or the hard-copy books.

*Table 16. DB2 technical information*

<b>Name</b>	<b>Form Number</b>	<b>Available in print</b>	<b>Last updated</b>
<i>Administrative API Reference</i>	SC27-2435-03	Yes	July, 2012
<i>Administrative Routines and Views</i>	SC27-2436-03	No	July, 2012
<i>Call Level Interface Guide and Reference, Volume 1</i>	SC27-2437-03	Yes	July, 2012
<i>Call Level Interface Guide and Reference, Volume 2</i>	SC27-2438-03	Yes	July, 2012
<i>Command Reference</i>	SC27-2439-03	Yes	July, 2012
<i>Data Movement Utilities Guide and Reference</i>	SC27-2440-01	Yes	July, 2012
<i>Data Recovery and High Availability Guide and Reference</i>	SC27-2441-03	Yes	July, 2012
<i>Database Administration Concepts and Configuration Reference</i>	SC27-2442-03	Yes	July, 2012
<i>Database Monitoring Guide and Reference</i>	SC27-2458-03	Yes	July, 2012
<i>Database Security Guide</i>	SC27-2443-02	Yes	July, 2012
<i>DB2 Text Search Guide</i>	SC27-2459-03	Yes	July, 2012
<i>Developing ADO.NET and OLE DB Applications</i>	SC27-2444-02	Yes	July, 2012
<i>Developing Embedded SQL Applications</i>	SC27-2445-02	Yes	July, 2012
<i>Developing Java Applications</i>	SC27-2446-03	Yes	July, 2012
<i>Developing Perl, PHP, Python, and Ruby on Rails Applications</i>	SC27-2447-02	No	July, 2012
<i>Developing User-defined Routines (SQL and External)</i>	SC27-2448-02	Yes	July, 2012
<i>Getting Started with Database Application Development</i>	GI11-9410-02	Yes	July, 2012

Table 16. DB2 technical information (continued)

<b>Name</b>	<b>Form Number</b>	<b>Available in print</b>	<b>Last updated</b>
<i>Getting Started with DB2 Installation and Administration on Linux and Windows</i>	GI11-9411-00	Yes	August, 2009
<i>Globalization Guide</i>	SC27-2449-00	Yes	August, 2009
<i>Installing DB2 Servers</i>	GC27-2455-03	Yes	July, 2012
<i>Installing IBM Data Server Clients</i>	GC27-2454-02	No	July, 2012
<i>Message Reference Volume 1</i>	SC27-2450-01	No	August, 2009
<i>Message Reference Volume 2</i>	SC27-2451-01	No	August, 2009
<i>Net Search Extender Administration and User's Guide</i>	SC27-2469-02	No	September, 2010
<i>Partitioning and Clustering Guide</i>	SC27-2453-02	Yes	July, 2012
<i>pureXML Guide</i>	SC27-2465-02	Yes	July, 2012
<i>Query Patroller Administration and User's Guide</i>	SC27-2467-00	No	August, 2009
<i>Spatial Extender and Geodetic Data Management Feature User's Guide and Reference</i>	SC27-2468-02	No	July, 2012
<i>SQL Procedural Languages: Application Enablement and Support</i>	SC27-2470-03	Yes	July, 2012
<i>SQL Reference, Volume 1</i>	SC27-2456-03	Yes	July, 2012
<i>SQL Reference, Volume 2</i>	SC27-2457-03	Yes	July, 2012
<i>Troubleshooting and Tuning Database Performance</i>	SC27-2461-03	Yes	July, 2012
<i>Upgrading to DB2 Version 9.7</i>	SC27-2452-03	Yes	July, 2012
<i>Visual Explain Tutorial</i>	SC27-2462-00	No	August, 2009
<i>What's New for DB2 Version 9.7</i>	SC27-2463-03	Yes	July, 2012
<i>Workload Manager Guide and Reference</i>	SC27-2464-03	Yes	July, 2012
<i>XQuery Reference</i>	SC27-2466-01	No	November, 2009

Table 17. DB2 Connect-specific technical information

Name	Form Number	Available in print	Last updated
<i>Installing and Configuring DB2 Connect Personal Edition</i>	SC27-2432-03	Yes	July, 2012
<i>Installing and Configuring DB2 Connect Servers</i>	SC27-2433-03	Yes	July, 2012
<i>DB2 Connect User's Guide</i>	SC27-2434-02	Yes	September, 2010

Table 18. Information Integration technical information

Name	Form Number	Available in print	Last updated
<i>Information Integration: Administration Guide for Federated Systems</i>	SC19-1020-02	Yes	August, 2009
<i>Information Integration: ASNCLP Program Reference for Replication and Event Publishing</i>	SC19-1018-04	Yes	August, 2009
<i>Information Integration: Configuration Guide for Federated Data Sources</i>	SC19-1034-02	No	August, 2009
<i>Information Integration: SQL Replication Guide and Reference</i>	SC19-1030-02	Yes	August, 2009
<i>Information Integration: Introduction to Replication and Event Publishing</i>	GC19-1028-02	Yes	August, 2009

## Ordering printed DB2 books

### About this task

If you require printed DB2 books, you can buy them online in many but not all countries or regions. You can always order printed DB2 books from your local IBM representative. Keep in mind that some softcopy books on the *DB2 PDF Documentation DVD* are unavailable in print. For example, neither volume of the *DB2 Message Reference* is available as a printed book.

Printed versions of many of the DB2 books available on the DB2 PDF Documentation DVD can be ordered for a fee from IBM. Depending on where you are placing your order from, you may be able to order books online, from the IBM Publications Center. If online ordering is not available in your country or region, you can always order printed DB2 books from your local IBM representative. Note that not all books on the DB2 PDF Documentation DVD are available in print.

**Note:** The most up-to-date and complete DB2 documentation is maintained in the DB2 Information Center at <http://publib.boulder.ibm.com/infocenter/db2luw/v9r7>.

To order printed DB2 books:

### Procedure

- To find out whether you can order printed DB2 books online in your country or region, check the IBM Publications Center at <http://www.ibm.com/shop/publications/order>. You must select a country, region, or language to access publication ordering information and then follow the ordering instructions for your location.
- To order printed DB2 books from your local IBM representative:
  1. Locate the contact information for your local representative from one of the following websites:
    - The IBM directory of world wide contacts at [www.ibm.com/planetwide](http://www.ibm.com/planetwide)
    - The IBM Publications website at <http://www.ibm.com/shop/publications/order>. You will need to select your country, region, or language to the access appropriate publications home page for your location. From this page, follow the "About this site" link.
  2. When you call, specify that you want to order a DB2 publication.
  3. Provide your representative with the titles and form numbers of the books that you want to order. For titles and form numbers, see “DB2 technical library in hardcopy or PDF format” on page 69.

---

## Displaying SQL state help from the command line processor

DB2 products return an SQLSTATE value for conditions that can be the result of an SQL statement. SQLSTATE help explains the meanings of SQL states and SQL state class codes.

### Procedure

To start SQL state help, open the command line processor and enter:

```
? sqlstate or ? class code
```

where *sqlstate* represents a valid five-digit SQL state and *class code* represents the first two digits of the SQL state.

For example, ? 08003 displays help for the 08003 SQL state, and ? 08 displays help for the 08 class code.

---

## Accessing different versions of the DB2 Information Center

### About this task

For DB2 Version 9.8 topics, the *DB2 Information Center* URL is <http://publib.boulder.ibm.com/infocenter/db2luw/v9r8/>.

For DB2 Version 9.7 topics, the *DB2 Information Center* URL is <http://publib.boulder.ibm.com/infocenter/db2luw/v9r7/>.

For DB2 Version 9.5 topics, the *DB2 Information Center* URL is <http://publib.boulder.ibm.com/infocenter/db2luw/v9r5/>.

For DB2 Version 9.1 topics, the *DB2 Information Center* URL is <http://publib.boulder.ibm.com/infocenter/db2luw/v9/>.

For DB2 Version 8 topics, go to the *DB2 Information Center* URL at:  
<http://publib.boulder.ibm.com/infocenter/db2luw/v8/>.

---

## Displaying topics in your preferred language in the DB2 Information Center

### About this task

The DB2 Information Center attempts to display topics in the language specified in your browser preferences. If a topic has not been translated into your preferred language, the DB2 Information Center displays the topic in English.

### Procedure

- To display topics in your preferred language in the Internet Explorer browser:
  1. In Internet Explorer, click the **Tools** —> **Internet Options** —> **Languages...** button. The Language Preferences window opens.
  2. Ensure your preferred language is specified as the first entry in the list of languages.
    - To add a new language to the list, click the **Add...** button.

**Note:** Adding a language does not guarantee that the computer has the fonts required to display the topics in the preferred language.
    - To move a language to the top of the list, select the language and click the **Move Up** button until the language is first in the list of languages.
  3. Refresh the page to display the DB2 Information Center in your preferred language.
- To display topics in your preferred language in a Firefox or Mozilla browser:
  1. Select the button in the **Languages** section of the **Tools** —> **Options** —> **Advanced** dialog. The Languages panel is displayed in the Preferences window.
  2. Ensure your preferred language is specified as the first entry in the list of languages.
    - To add a new language to the list, click the **Add...** button to select a language from the Add Languages window.
    - To move a language to the top of the list, select the language and click the **Move Up** button until the language is first in the list of languages.
  3. Refresh the page to display the DB2 Information Center in your preferred language.

### Results

On some browser and operating system combinations, you must also change the regional settings of your operating system to the locale and language of your choice.

---

## Updating the DB2 Information Center installed on your computer or intranet server

A locally installed DB2 Information Center must be updated periodically.



## Before you begin

A DB2 Version 9.7 Information Center must already be installed. For details, see the “Installing the DB2 Information Center using the DB2 Setup wizard” topic in *Installing DB2 Servers*. All prerequisites and restrictions that applied to installing the Information Center also apply to updating the Information Center.

## About this task

An existing DB2 Information Center can be updated automatically or manually:

- Automatic updates - updates existing Information Center features and languages. An additional benefit of automatic updates is that the Information Center is unavailable for a minimal period of time during the update. In addition, automatic updates can be set to run as part of other batch jobs that run periodically.
- Manual updates - should be used when you want to add features or languages during the update process. For example, a local Information Center was originally installed with both English and French languages, and now you want to also install the German language; a manual update will install German, as well as, update the existing Information Center features and languages. However, a manual update requires you to manually stop, update, and restart the Information Center. The Information Center is unavailable during the entire update process.

This topic details the process for automatic updates. For manual update instructions, see the “Manually updating the DB2 Information Center installed on your computer or intranet server” topic.

## Procedure

To automatically update the DB2 Information Center installed on your computer or intranet server:

1. On Linux operating systems,
  - a. Navigate to the path where the Information Center is installed. By default, the DB2 Information Center is installed in the `/opt/ibm/db2ic/V9.7` directory.
  - b. Navigate from the installation directory to the `doc/bin` directory.
  - c. Run the `update-ic` script:  
`update-ic`
2. On Windows operating systems,
  - a. Open a command window.
  - b. Navigate to the path where the Information Center is installed. By default, the DB2 Information Center is installed in the `<Program Files>\IBM\DB2 Information Center\Version 9.7` directory, where `<Program Files>` represents the location of the Program Files directory.
  - c. Navigate from the installation directory to the `doc\bin` directory.
  - d. Run the `update-ic.bat` file:  
`update-ic.bat`

## Results

The DB2 Information Center restarts automatically. If updates were available, the Information Center displays the new and updated topics. If Information Center

updates were not available, a message is added to the log. The log file is located in `doc\eclipse\configuration` directory. The log file name is a randomly generated number. For example, `1239053440785.log`.

---

## Manually updating the DB2 Information Center installed on your computer or intranet server

If you have installed the DB2 Information Center locally, you can obtain and install documentation updates from IBM.

### About this task

Updating your locally-installed *DB2 Information Center* manually requires that you:

1. Stop the *DB2 Information Center* on your computer, and restart the Information Center in stand-alone mode. Running the Information Center in stand-alone mode prevents other users on your network from accessing the Information Center, and allows you to apply updates. The Workstation version of the DB2 Information Center always runs in stand-alone mode. .
2. Use the Update feature to see what updates are available. If there are updates that you must install, you can use the Update feature to obtain and install them

**Note:** If your environment requires installing the *DB2 Information Center* updates on a machine that is not connected to the internet, mirror the update site to a local file system using a machine that is connected to the internet and has the *DB2 Information Center* installed. If many users on your network will be installing the documentation updates, you can reduce the time required for individuals to perform the updates by also mirroring the update site locally and creating a proxy for the update site.

If update packages are available, use the Update feature to get the packages. However, the Update feature is only available in stand-alone mode.

3. Stop the stand-alone Information Center, and restart the *DB2 Information Center* on your computer.

**Note:** On Windows 2008, Windows Vista (and higher), the commands listed later in this section must be run as an administrator. To open a command prompt or graphical tool with full administrator privileges, right-click the shortcut and then select **Run as administrator**.

### Procedure

To update the *DB2 Information Center* installed on your computer or intranet server:

1. Stop the *DB2 Information Center*.
  - On Windows, click **Start > Control Panel > Administrative Tools > Services**. Then right-click **DB2 Information Center** service and select **Stop**.
  - On Linux, enter the following command:  

```
/etc/init.d/db2icdv97 stop
```
2. Start the Information Center in stand-alone mode.
  - On Windows:
    - a. Open a command window.
    - b. Navigate to the path where the Information Center is installed. By default, the *DB2 Information Center* is installed in the

*Program\_Files\IBM\DB2 Information Center\Version 9.7* directory, where *Program\_Files* represents the location of the Program Files directory.

c. Navigate from the installation directory to the `doc\bin` directory.

d. Run the `help_start.bat` file:

```
help_start.bat
```

• On Linux:

a. Navigate to the path where the Information Center is installed. By default, the *DB2 Information Center* is installed in the `/opt/ibm/db2ic/V9.7` directory.

b. Navigate from the installation directory to the `doc/bin` directory.

c. Run the `help_start` script:

```
help_start
```

The systems default Web browser opens to display the stand-alone Information Center.

3. Click the **Update** button (🔄). (JavaScript must be enabled in your browser.)

On the right panel of the Information Center, click **Find Updates**. A list of updates for existing documentation displays.

4. To initiate the installation process, check the selections you want to install, then click **Install Updates**.

5. After the installation process has completed, click **Finish**.

6. Stop the stand-alone Information Center:

• On Windows, navigate to the installation directory's `doc\bin` directory, and run the `help_end.bat` file:

```
help_end.bat
```

**Note:** The `help_end` batch file contains the commands required to safely stop the processes that were started with the `help_start` batch file. Do not use `Ctrl-C` or any other method to stop `help_start.bat`.

• On Linux, navigate to the installation directory's `doc/bin` directory, and run the `help_end` script:

```
help_end
```

**Note:** The `help_end` script contains the commands required to safely stop the processes that were started with the `help_start` script. Do not use any other method to stop the `help_start` script.

7. Restart the *DB2 Information Center*.

• On Windows, click **Start > Control Panel > Administrative Tools > Services**. Then right-click **DB2 Information Center** service and select **Start**.

• On Linux, enter the following command:

```
/etc/init.d/db2icdv97 start
```

## Results

The updated *DB2 Information Center* displays the new and updated topics.

---

## DB2 tutorials

The DB2 tutorials help you learn about various aspects of DB2 products. Lessons provide step-by-step instructions.

## Before you begin

You can view the XHTML version of the tutorial from the Information Center at <http://publib.boulder.ibm.com/infocenter/db2help/>.

Some lessons use sample data or code. See the tutorial for a description of any prerequisites for its specific tasks.

## DB2 tutorials

To view the tutorial, click the title.

### “pureXML” in *pureXML Guide*

Set up a DB2 database to store XML data and to perform basic operations with the native XML data store.

### “Visual Explain” in *Visual Explain Tutorial*

Analyze, optimize, and tune SQL statements for better performance using Visual Explain.

---

## DB2 troubleshooting information

A wide variety of troubleshooting and problem determination information is available to assist you with using DB2 database products.

### DB2 documentation

Troubleshooting information can be found in the *Troubleshooting and Tuning Database Performance* or the Database fundamentals section of the *DB2 Information Center*. The troubleshooting information contains topics that can help you isolate and identify problems with DB2 diagnostic tools and utilities. There are also solutions to some of the most common problems and advice on how to solve problems you might encounter with your DB2 database products.

### IBM Support Portal

See the IBM Support Portal if you are experiencing problems and want help finding possible causes and solutions. The Technical Support site has links to the latest DB2 publications, TechNotes, Authorized Program Analysis Reports (APARs or bug fixes), fix packs, and other resources. You can search through this knowledge base to find possible solutions to your problems.

Access the IBM Support Portal at [http://www.ibm.com/support/entry/portal/Overview/Software/Information\\_Management/DB2\\_for\\_Linux\\_UNIX\\_and\\_Windows](http://www.ibm.com/support/entry/portal/Overview/Software/Information_Management/DB2_for_Linux_UNIX_and_Windows).

---

## Terms and Conditions

Permissions for the use of these publications is granted subject to the following terms and conditions.

**Personal use:** You may reproduce these Publications for your personal, non commercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these Publications, or any portion thereof, without the express consent of IBM.

**Commercial use:** You may reproduce, distribute and display these Publications solely within your enterprise provided that all proprietary notices are preserved.

You may not make derivative works of these Publications, or reproduce, distribute or display these Publications or any portion thereof outside your enterprise, without the express consent of IBM.

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the Publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the Publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.



---

## Appendix B. Notices

This information was developed for products and services offered in the U.S.A. Information about non-IBM products is based on information available at the time of first publication of this document and is subject to change.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information about the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing  
IBM Corporation  
North Castle Drive  
Armonk, NY 10504-1785  
U.S.A.

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing  
Legal and Intellectual Property Law  
IBM Japan, Ltd.  
1623-14, Shimotsuruma, Yamato-shi  
Kanagawa 242-8502 Japan

**The following paragraph does not apply to the United Kingdom or any other country/region where such provisions are inconsistent with local law:**

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions; therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements, changes, or both in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those

websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licenses of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information that has been exchanged, should contact:

IBM Canada Limited  
U59/3600  
3600 Steeles Avenue East  
Markham, Ontario L3R 9Z7  
CANADA

Such information may be available, subject to appropriate terms and conditions, including, in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement, or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems, and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements, or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility, or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information may contain examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious, and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

#### COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating



platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work must include a copyright notice as follows:

© (*your company name*) (*year*). Portions of this code are derived from IBM Corp. Sample Programs. © Copyright IBM Corp. *\_enter the year or years\_*. All rights reserved.

## Trademarks

IBM, the IBM logo, and [ibm.com](http://ibm.com)<sup>®</sup> are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at [www.ibm.com/legal/copytrade.shtml](http://www.ibm.com/legal/copytrade.shtml).

The following terms are trademarks or registered trademarks of other companies

- Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.
- Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle, its affiliates, or both.
- UNIX is a registered trademark of The Open Group in the United States and other countries.
- Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.
- Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.



---

# Index

## A

- ActiveRecord-JDBC adapter
  - IBM\_DB adapter comparison 67
- application design
  - prototyping in Perl 1
- autocommit function (ibm\_db) 55

## B

- bind\_param function (ibm\_db)
  - calling 49, 52
- books
  - ordering 72

## C

- CALL statement
  - PHP 22, 38
  - Python 52
- client\_info function (ibm\_db) 57
- close function (ibm\_db)
  - fetching from result sets 51
  - retrieving multiple result sets 54
- column\_privileges function (ibm\_db) 57
- columns function (ibm\_db) 57
- commit function (ibm\_db) 55
- commit modes
  - PHP applications 25, 40
  - Python applications 55
- conn\_error function (ibm\_db) 56
- conn\_errormsg function (ibm\_db) 56
- connect function (ibm\_db) 47
- connect method (Perl DBI) 2
- connections
  - Rails applications 64

## D

- DB2 Information Center
  - languages 74
  - updating 75, 76
  - versions 73
- db2\_autocommit function (ibm\_db2) 25
- db2\_bind\_param function (ibm\_db2)
  - calling stored procedures 22
  - executing SQL statements with variable input 17
  - inserting large objects 19
  - preparing SQL statements with variable input 17
- db2\_client\_info function (ibm\_db2) 27
- db2\_close function (ibm\_db2) 20
- db2\_column\_privileges function (ibm\_db2) 27
- db2\_columns function (ibm\_db2) 27
- db2\_commit function (ibm\_db2) 25
- db2\_conn\_error function (ibm\_db2) 26
- db2\_conn\_errormsg function (ibm\_db2) 26
- db2\_connect function (ibm\_db2) 14
- db2\_exec function (ibm\_db2) 16
- db2\_execute function (ibm\_db2)
  - calling stored procedures 22

- db2\_execute function (ibm\_db2) (*continued*)
  - executing SQL statements 17
  - inserting large objects 19
- db2\_fetch\_array function (ibm\_db2)
  - fetching data from a result set 20
  - retrieving multiple result sets 24
- db2\_fetch\_assoc function (ibm\_db2)
  - fetching data from a result set 20
  - retrieving multiple result sets 24
- db2\_fetch\_both function (ibm\_db2)
  - fetching data from a result set 20
  - retrieving multiple result sets 24
- db2\_fetch\_object function (ibm\_db2) 22
  - fetching data from a result set 20
- db2\_fetch\_row function (ibm\_db2)
  - fetching data from a result set 20
  - retrieving multiple result sets 24
- db2\_foreign\_keys function (ibm\_db2) 27
- db2\_next\_result function (ibm\_db2)
  - retrieving multiple result sets 24
- db2\_pconnect function (ibm\_db2) 14
- db2\_prepare function (ibm\_db2)
  - calling stored procedures 22
  - inserting large objects 19
  - preparing SQL statements 17
- db2\_primary\_keys function (ibm\_db2) 27
- db2\_procedure\_columns function (ibm\_db2) 27
- db2\_procedures function (ibm\_db2) 27
- db2\_result function (ibm\_db2) 20
- db2\_rollback function (ibm\_db2) 25
- db2\_server\_info function (ibm\_db2) 27
- db2\_special\_columns function (ibm\_db2) 27
- db2\_statistics function (ibm\_db2) 27
- db2\_stmt\_error function (ibm\_db2) 26
- db2\_stmt\_errormsg function (ibm\_db2) 26
- db2\_table\_privileges function (ibm\_db2) 27
- DB2::DB2 driver
  - downloads 1
  - pureXML support 5
  - resources 1
- disconnect method (Perl DBI) 2
- Django
  - IBM data server environment setup 44
- documentation
  - overview 69
  - PDF files 69
  - printed 69
  - terms and conditions of use 78
- dynamic SQL
  - Perl support 1

## E

- err method 4
- errors
  - Perl 4
  - PHP 26, 41
  - Python 56
- errstr method 4
- exec\_immediate function (ibm\_db) 48

- execute function (ibm\_db)
  - calling stored procedures 52
  - executing SQL statements with variable input 49
- execute method (Perl DBI) 3

## F

- fetch\_assoc function (ibm\_db)
  - fetching columns 51
  - fetching multiple result sets 54
  - fetching rows 51
- fetch\_both function (ibm\_db)
  - fetching columns 51
  - fetching multiple result sets 54
  - fetching rows 51
- fetch\_row function (ibm\_db)
  - fetching columns 51
  - fetching multiple result sets 54
  - fetching rows 51
- fetch\_tuple function (ibm\_db)
  - fetching columns 51
  - fetching multiple result sets 54
  - fetching rows 51
- fetchrow method (Perl DBI) 3
- foreign\_keys function (ibm\_db) 57
- functions

### PHP

- db2\_autocommit 25
- db2\_bind\_param 17, 19, 22
- db2\_client\_info 27
- db2\_close 20, 24
- db2\_column\_privileges 27
- db2\_columns 27
- db2\_commit 25
- db2\_conn\_error 26
- db2\_conn\_errormsg 26
- db2\_connect 14
- db2\_exec 16
- db2\_execute 17, 19, 22
- db2\_fetch\_array 20, 24
- db2\_fetch\_assoc 20, 24
- db2\_fetch\_both 20, 24
- db2\_fetch\_object 20, 22
- db2\_fetch\_row 20, 24
- db2\_foreign\_keys 27
- db2\_next\_result 24
- db2\_pconnect 14
- db2\_prepare 17, 19, 22
- db2\_primary\_keys 27
- db2\_procedure\_columns 27
- db2\_procedures 27
- db2\_result 20
- db2\_rollback 25
- db2\_server\_info 27
- db2\_special\_columns 27
- db2\_statistics 27
- db2\_stmt\_error 26
- db2\_stmt\_errormsg 26
- db2\_table\_privileges 27

### Python

- ibm\_db.autocommit 55
- ibm\_db.bind\_param 49, 52
- ibm\_db.client\_info 57
- ibm\_db.close 51, 54
- ibm\_db.column\_privileges 57
- ibm\_db.columns 57
- ibm\_db.commit 55

## functions (continued)

### Python (continued)

- ibm\_db.conn\_error 56
- ibm\_db.conn\_errormsg 56
- ibm\_db.connect 47
- ibm\_db.exec\_immediate 48
- ibm\_db.execute 49, 52
- ibm\_db.fetch\_assoc 51, 54
- ibm\_db.fetch\_both 51, 54
- ibm\_db.fetch\_row 51, 54
- ibm\_db.fetch\_tuple 51, 54
- ibm\_db.foreign\_keys 57
- ibm\_db.next\_result 54
- ibm\_db.pconnect 47
- ibm\_db.prepare 49, 52
- ibm\_db.primary\_keys 57
- ibm\_db.procedure\_columns 57
- ibm\_db.procedures 57
- ibm\_db.result 51
- ibm\_db.rollback 55
- ibm\_db.server\_info 57
- ibm\_db.special\_columns 57
- ibm\_db.statistics 57
- ibm\_db.stmt\_error 56
- ibm\_db.stmt\_errormsg 56
- ibm\_db.table\_privileges 57

## H

### help

- configuring language 74
- SQL statements 73

### host variables

- Perl 3

## I

### ibm\_db API

- details 43
- overview 47

### IBM\_DB Ruby driver and Rails adapter

- ActiveRecord-JDBC adapter comparison 67
- dependencies 66
- details 59
- environment setup 60
- installation verification
  - DB2 Express-C 62
  - IBM data servers 63
- integrated development environment setup 60
- JRuby support 66
- Ruby gem installation 61
- trusted contexts 65

### ibm\_db\_dbi API

- details 43

### ibm\_db\_sa adaptor

- details 43

### ibm\_db2 API

- details 9
- PHP application development 14
- trusted contexts 15

## J

### JRuby

- IBM\_DB Ruby driver and Rails adapter 66

## L

- large objects (LOBs)
  - fetching
    - PHP 22, 37
  - inserting
    - PHP 19, 34

## M

- metadata
  - retrieval
    - PHP 27
    - Python 57
- methods
  - Perl
    - connect 2
    - disconnect 2
    - err 4
    - errstr 4
    - execute 3
    - fetchrow 3
    - prepare 3
    - state 4
  - PHP
    - PDO::beginTransaction 40
    - PDO::commit 40
    - PDO::exec 32
    - PDO::prepare 33, 34, 38
    - PDO::query 32
    - PDO::rollBack 40
    - PDOStatement::bindColumn 37
    - PDOStatement::bindParam 33, 34, 38
    - PDOStatement::execute 33, 34, 38
    - PDOStatement::fetch 35, 37, 39
    - PDOStatement::fetchAll 35, 39
    - PDOStatement::fetchColumn 35
    - PDOStatement::nextRowset 39

## N

- next\_result function (ibm\_db) 54
- notices 81

## O

- ordering DB2 books 72

## P

- parameter markers
  - Perl 4
- pconnect function (ibm\_db) 47
- pdo\_ibm
  - details 9
  - developing PHP applications 30
- PDO::beginTransaction method (PDO) 40
- PDO::commit method (PDO) 40
- PDO::exec method (PDO) 32
- PDO::prepare method (PDO) 33, 34, 38
- PDO::query method (PDO) 32
- PDO::rollBack method (PDO) 40
- PDOStatement::bindColumn method (PDO) 37
- PDOStatement::bindParam method (PDO) 33, 34, 38
- PDOStatement::execute method (PDO) 33, 34, 38
- PDOStatement::fetch method (PDO) 35, 37, 39

- PDOStatement::fetchAll method (PDO) 35, 39
- PDOStatement::fetchColumn method (PDO) 35
- PDOStatement::nextRowset method (PDO) 39

## Perl

- connecting to a database 2
- documentation 1
- downloads 1
- drivers 1
- errors 4
- fetching rows 3
- methods
  - connect 2
  - disconnect 2
  - err 4
  - errstr 4
  - execute 3
  - fetchrow 3
  - prepare 3
  - state 4
- overview 1
- parameter markers 4
- problem reporting 1
- pureXML support 5
- restrictions 5
- sample programs 7
- SQLCODEs 4
- SQLSTATEs 4

## PHP

- application development 9, 14
- connecting to database 14, 30
- database metadata retrieval 27
- developing applications with PDO 30
- documentation 10
- downloads 10
- error handling 26, 41
- extensions for IBM data servers 9
- fetching large objects 22, 37
- fetching rows 20, 35
- functions
  - db2\_autocommit 25
  - db2\_bind\_param 22
  - db2\_client\_info 27
  - db2\_close 20, 24
  - db2\_column\_privileges 27
  - db2\_columns 27
  - db2\_commit 25
  - db2\_conn\_error 26
  - db2\_conn\_errormsg 26
  - db2\_connect 14
  - db2\_exec 16
  - db2\_execute 22
  - db2\_fetch\_array 20, 24
  - db2\_fetch\_assoc 20, 24
  - db2\_fetch\_both 20, 24
  - db2\_fetch\_object 20, 22
  - db2\_fetch\_row 20, 24
  - db2\_foreign\_keys 27
  - db2\_next\_result 24
  - db2\_pconnect 14
  - db2\_prepare 22
  - db2\_primary\_keys 27
  - db2\_procedure\_columns 27
  - db2\_procedures 27
  - db2\_result 20
  - db2\_rollback 25
  - db2\_server\_info 27
  - db2\_special\_columns 27

- PHP (*continued*)
  - functions (*continued*)
    - db2\_statistics 27
    - db2\_stmt\_error 26
    - db2\_stmt\_errormsg 26
    - db2\_table\_privileges 27
  - IBM data server environment setup (Windows) 11
  - ibm\_db2 API
    - connecting to a database 14
    - overview 14
  - large objects 19, 34
  - methods
    - PDO::beginTransaction 40
    - PDO::commit 40
    - PDO::exec 32
    - PDO::prepare 33, 34, 38
    - PDO::query 32
    - PDO::rollBack 40
    - PDOStatement::bindColumn 37
    - PDOStatement::bindParam 33, 34, 38
    - PDOStatement::execute 33, 34, 38
    - PDOStatement::fetch 35, 37, 39
    - PDOStatement::fetchAll 35, 39
    - PDOStatement::fetchColumn 35
    - PDOStatement::nextRowset 39
  - PDO\_IBM extension
    - connecting to database 30
    - issuing SQL statements 32
  - procedures 22, 38
  - setup
    - Linux 12
    - overview 10
    - UNIX 12
  - SQL statements 16, 17, 19, 20, 32, 33, 34, 35, 37
  - stored procedures
    - calling 22, 38
    - retrieving results 24, 39
  - transactions 25, 40
  - trusted contexts
    - overview 15
  - prepare function (ibm\_db) 49, 52
  - prepare method (Perl DBI) 3
  - primary\_keys function (ibm\_db) 57
  - problem determination
    - information available 78
    - tutorials 78
  - procedure\_columns function (ibm\_db) 57
  - procedures
    - PHP 22, 38
    - Python 52
  - procedures function (ibm\_db) 57
  - pureXML
    - DB2::DB2 driver 5
- Python
  - API documentation 44
  - application development 43, 47
  - connecting to database 47
  - database metadata retrieval 57
  - downloading extensions 44
  - error handling 56
  - extensions for IBM data servers 43
  - fetching rows 51
  - functions
    - ibm\_db.autocommit 55
    - ibm\_db.bind\_param 49, 52
    - ibm\_db.client\_info 57
    - ibm\_db.close 51, 54

- Python (*continued*)
  - functions (*continued*)
    - ibm\_db.column\_privileges 57
    - ibm\_db.columns 57
    - ibm\_db.commit 55
    - ibm\_db.conn\_error 56
    - ibm\_db.conn\_errormsg 56
    - ibm\_db.connect 47
    - ibm\_db.exec\_immediate 48
    - ibm\_db.execute 49, 52
    - ibm\_db.fetch\_assoc 51, 54
    - ibm\_db.fetch\_both 51, 54
    - ibm\_db.fetch\_row 51, 54
    - ibm\_db.fetch\_tuple 51, 54
    - ibm\_db.foreign\_keys 57
    - ibm\_db.next\_result 54
    - ibm\_db.pconnect 47
    - ibm\_db.prepare 49, 52
    - ibm\_db.primary\_keys 57
    - ibm\_db.procedure\_columns 57
    - ibm\_db.procedures 57
    - ibm\_db.result 51
    - ibm\_db.rollback 55
    - ibm\_db.server\_info 57
    - ibm\_db.special\_columns 57
    - ibm\_db.statistics 57
    - ibm\_db.stmt\_error 56
    - ibm\_db.stmt\_errormsg 56
    - ibm\_db.table\_privileges 57
  - IBM data server environment setup 44
  - ibm\_db 47
  - procedures 52
  - SQL statements 48, 49
  - stored procedures
    - calling 52
    - retrieving results 54
  - transactions 55

## R

- RadRails
  - IBM data server on Rails setup 60, 61
- Rails adapter
  - dependencies 66
  - details 59
  - getting started 60
  - IBM\_DB adapter and driver installation 61
  - installation verification
    - DB2 Express-C 62
    - IBM data servers 63
  - integrated development environment setup 60
  - JRuby support 66
- Rails applications
  - connection configuration 64
  - result function (ibm\_db) 51
  - rollback function (ibm\_db) 55
- rows
  - fetching
    - Perl 3
    - PHP 20, 35
    - Python 51
- Ruby driver
  - details 59
  - getting started 60
  - IBM\_DB adapter and driver installation 61
  - installation verification
    - DB2 Express-C 62

- Ruby driver (*continued*)
  - installation verification (*continued*)
    - IBM data servers 63
  - integrated development environment setup 60
  - JRuby support 66
  - trusted contexts 65
- Ruby on Rails
  - heap size issues 67

## S

- samples
  - Perl 7
- server\_info function (ibm\_db) 57
- special\_columns function (ibm\_db) 57
- SQL statements
  - help
    - displaying 73
  - PHP 16, 17, 19, 20, 32, 33, 34, 35, 37
  - Python 48, 49
- SQLAlchemy
  - adapter for IBM data servers 43
  - downloading extension 44
  - IBM data server environment setup 44
- state method 4
- static SQL
  - unsupported in Perl 5
- statistics function (ibm\_db) 57
- stmt\_error function (ibm\_db) 56
- stmt\_errormsg function (ibm\_db) 56
- stored procedures
  - PHP
    - calling 22, 38
    - retrieving results 24, 39
  - Python
    - calling 52
    - retrieving results 54

## T

- table\_privileges function (ibm\_db) 57
- terms and conditions
  - publications 78
- transactions
  - PHP 25, 40
  - Python 55
- troubleshooting
  - online information 78
  - tutorials 78
- trusted contexts
  - IBM\_DB Ruby driver support
    - details 65
  - PHP applications 15
- tutorials
  - list 77
  - problem determination 78
  - troubleshooting 78
  - Visual Explain 77

## U

- updates
  - DB2 Information Center 75, 76









Printed in USA

SC27-2447-02



Spine information:

DB2 for Linux, UNIX, and Windows

Version 9 Release 7

Developing Perl, PHP, Python, and Ruby on Rails Applications

