



IBM eServer iSeries

IBM server™ & TotalStorage™
UNIVERSITY 2003

iSeries: SCON Technologies - LPAR, and Windows Integration


Session IT-17

Kyle W. Wurgler

IBM & IBM Business Partner Use Only Until Announced

© 2002 IBM Corporation

iSeries Server Consolidation



* Statement of Direction

iSeries offers application flexibility

iSeries innovative technology can lower cost of management

iSeries provides enterprise IT management made simple



Video Clip

*Statement of Direction: This presentation contains IBM plans and directions. Such plans are subject to change without notice.

Agenda - Discussions on the following


- **Is it really just another Windows Server or something IBM made?**
- **Common components and functions**
- **How do I demo this stuff ?**
- **How do I architect and size a Windows SCON opportunity ?**
- **Tips and Techniques for success**
- **What did our reference customers do ?**
- **Where do I find helpful information ?**

Common Components and Functions

Windows and Linux common components

- **Network Server Description - NWSD**
- **Storage as a SAN**
 - ▶ **Storage spaces**
- **Virtualization**
 - ▶ **Server as a set of object(s)**
 - ▶ **Not just hardware**
- **Backup and Recovery**

iSeries Storage Virtualization



- ▶ Storage Space Objects provide basis for leveraging iSeries architecture to deliver benefits to Windows 2000 Server and Linux Servers
 - ▶ Performance
 - ▶ Consolidated Backup
 - ▶ Hot Spare
 - ▶ Testing
 - ▶ Addition of disk space dynamically

V5R2 Virtual Ethernet - less network traffic

Fast, More Secure, Flexible Communications Inside the iSeries

Virtual Ethernet Communication


- 1Gb Connections with no LAN Adapters/Switches
- Provides communications between OS/400, Linux, and Windows
- Up to 16 Virtual LANs may be defined
- Up to 5 of the 16 Connections may be used by one IXS / IXA
 - One Connection is automatically configured for Point to Point Communications with OS/400

Performance Improvements

- Windows App to OS/400 App / Linux App
- Windows File Level Back Up to OS/400 Tape
- Windows to Windows Communication

Support

- iSeries 270, 8xx
- OS/400 V5R2 in IXS or IXA owning partition



RZAHQ016-3

So now what ?

Server consolidation is not about combining many servers into a single footprint

- Blade servers and SANs provide a great way to get multiple servers into a rack

Server consolidation is about combining many functions into a single footprint

The real questions are "Where is the best place for the function?" and "What platform provides the best manageability?"

We need to get our customers thinking about function.

How do we help the customer leverage the "Processor activation for Linux" and "included IXS" in the Enterprise Package of the high-end systems?

Function Matrix

	OS/400	Windows	Linux
LDAP	Supported	Supported	Supported
File / Print	Supported	Supported	Supported
Domain Controller		Supported	Supported - Samba
Active Directory		Supported	Future - Samba v3
Windows Apps - Terminal Server		Supported	* Some functions via office replacement
FTP	Supported	add-on	Supported
WebServer	Apache	IIS	Apache+
e-mail	SMTP, MSF, Domino Add-on	* Add-on	SendMail - Base Full-Function add-ons
Proxy	HTTP, FTP (within HTTP) gopher	Supported	Squid
WINS		Supported	Part of Samba
DNS	DDNS, Bind 8.3, Bind 4.2	Supported	Bind 8 Update to Bind 9 available

Function Matrix

	OS/400	Windows	Linux
DHCP	Supported	Supported	Supported
NFS	Supported	* Add-on	Supported
User Admin. Functions	iSeries Navigator - Propagates Windows Domain	Native	Native / WebMin
Single-Server / Multifunction	Supported	VMWare	Supported
Database	DB2 UDB/400	SQL Server Access	mySQL postgreSQL DB2 UDB (future) ODBC/JDBC Access to DB2 UDB/400
Application Server	WAS 5 (express / standard) TOMCAT ? BEA Web-Logic	.NET	WAS (future) TOMCAT JSERV Ressin

What to demo ?

iSeries Adds Value to Windows Servers - So What ?

User Administration

Networking

Disk Management

Backup

Testing

Reliability

Availability

Remote Server Admin

The screenshot displays the iSeries Navigator application window. The title bar reads "iSeries Navigator". The menu bar includes "File", "Edit", "View", and "Help". The toolbar contains icons for various actions like cut, copy, paste, delete, and refresh. The main area is divided into two panes. The left pane, titled "Environment: My Connections", shows a tree view with "Asj1" expanded to "Windows Administration". The right pane, titled "Asj1: Windows Administration", shows a table of tasks:

Name	Description
Integrated xSeries Servers	Manage Windows Integrated xSeries
Disk Drives	Manage Windows Disk Drives
User Enrollment	Manage Windows User Enrollment

At the bottom, there are two task lists. The left list, "My Tasks - Asj1", includes "Add a connection" and "Install additional components". The right list, "Windows Administration tasks", includes "Configure system as Dir", "Create a new disk drive", "Start all Windows server", "Run Windows command", "Shut down all Windows", and "Help for related tasks". The status bar at the bottom indicates "1 - 3 of 3 objects".

Videos available on the web

VIDEOS are now available for download from iSeries University TechEd Theater

<http://www.ibm.com/eserver/iseries/education/theater.html>

iSeries - xSeries Integration

featuring: Craig Johnson and Kyle Wurgler, iSeries Product Marketing Management

iSeries Windows Integration products, the Integrated xSeries Server and Integrated xSeries Adapter, are designed to extend the value of iSeries to Windows servers. This video reviews the IBM eServer solution, its benefits, and results customers are seeing. Included with the video are a series of demonstrations that highlight the advanced user, storage, and server management functions provided by IBM.

Linux on iSeries

featuring: Craig Johnson, iSeries Product Marketing Management

Customers are looking to Linux to deliver low cost and reliable solutions - from infrastructure to e-Business. This video reviews the iSeries support for Linux, solutions available, and reasons why customers are implementing Linux on iSeries.

User Administration

Problem

- ▶ Multiple system user management

iSeries Solution

- ▶ Adding OS/400 Users and Groups to Windows 2000 Server Domains and Synchronizing Passwords

Benefit

- ▶ Can reduce costs with integrated user management



Video Clip

The screenshot shows the iSeries Navigator interface. The left pane displays a tree view of 'My Connections' with 'Users' selected under 'User Enrollment'. The right pane shows a table of users for 'Asj1: Users' on 'Server: Nt2k'.

Windows User	Enrollment Status	Enrolled Groups	Description
Annasue	Enrolled		Anna Sue F
Ggaylord	Enrolled	Ntadmins	George Gay
Krisd	Enrolled	Ntadmins	Kris Davis
Ntmrkt1	Enrolled	Ntmrkt	
Schuster	Enrolled	Ntadmins	Bob Schust
Tgrube	Enrolled	Ntadmins	Todd Grube
Wurgler	Enrolled	Ntadmins	Kyle Wurgle

1 - 7 of 7 objects

Networking - V5R2

Problem


- ▶ Upgrading network infrastructure to support high-speed application communication is expensive in terms of time, resources and equipment

iSeries Solution

- ▶ Virtual Ethernet at OS/400 V5R2 provides 1 Gb Connections with no LAN Adapters/Switches
- ▶ Windows to Windows to OS/400 to Linux
- ▶ Up to 5 Connections per IXS / IXA

Benefit

- ▶ Extremely secure and reliable server communication over high-performance connections
- ▶ Can reduce network traffic and exposure to "sniffing"



RZAHQ016-3

Disk Management

Problem

- ▶ Storage management across the server farm

iSeries Solution

- ▶ Flexible Virtual Disks from 1 MB to 64 GB.
- ▶ Up to 2 TB per Windows server
- ▶ Hot add of iSeries Storage Space to Windows 2000 Server

Benefit

- ▶ Can reduce costs with flexible, centralized storage management

New Disk - Asj1

Disk drive name: Proddata1

Description: Data Drive for Prod1 Server

Initialize disk with data from another disk


Source disk: [Dropdown]

Capacity: 500 MB

Disk pool: Disk pool 1

OK Cancel Help ?



iSeries Storage Virtualization for Windows 2000 Server



- ▶ Storage Space Objects provide basis for leveraging iSeries architecture to deliver benefits to Windows 2000 Server
 - ▶ Performance
 - ▶ Consolidated Backup
 - ▶ Hot Spare
 - ▶ Testing

iSeries Storage Consolidation Advantages


Consolidated Storage




Server 1 Server 2 Server 3

Every server's
data is spread on
all drives

iSeries



Leveraging all
available
resources



Server 1 Server 2 Server 3

All disk is
virtual

Backup

Problem


- ▶ Managing heterogeneous backups

iSeries Solution

- ▶ Save OS/400 and Windows storage spaces to iSeries tape drives

Benefit

- ▶ Can reduce costs by leveraging iSeries resources and skills



Testing

Problem

- ▶ Adequately testing Microsoft Service Packs, Application Fixes, device drivers before they are placed in production

iSeries Solution

- ▶ Logical Servers allows testing with the production image and hardware

Benefit

- ▶ Can reduce the outages caused by change

The screenshot shows the iSeries Navigator interface. The main window displays a tree view of the environment 'My Connections' with a sub-tree for 'Asj1: Integrated xSeries Servers'. The right pane shows a table of Windows servers with the following data:

Windows Server	Status	Domain	Description
Nttse	Shut down	Ntassc	Windows 2000 -lin04 +
Nt2k	Started	Ntassc	Windows 2000 Server -
Nt2kx	Shut down	Extest	Win2000 Exchange Ser
Nt6000r	Shut down	Ntassc	Windows 2000 on Exter
W2kext1	Shut down	Ntassc	External Server 1- W2K
W2kext2	Shut down	Ntassc	External Server 2- W2K

The bottom pane shows 'My Tasks - Asj1' with tasks such as 'Add a connection', 'Install additional components', 'Configure system as D', 'Start all Windows serv', 'Shut down all Window', 'Create a new disk driv', 'Run Windows comman', and 'Help for related tasks'.

Reliability

Problem


- ▶ Different hardware and device drivers can cause server instability

iSeries Solution

- ▶ IBM provides a consistent set of disk, tape, CD, and LAN hardware and device drivers that are tested to work together

Benefit

- ▶ Greater consistency can lead to better reliability



Availability - One iSeries Server

Problem


- ▶ Providing an effective and efficient availability solution

iSeries Solution

- ▶ Hot Spare allows one xSeries server to provide a backup to several production servers

Benefit

- ▶ Efficient availability solution for planned or unplanned server outages



Availability - Microsoft Cluster Service (V5R2)

Switch Disk Cluster


- Dynamically Switch Storage Spaces Between Windows Servers
- Up to 4 IXS or IXA Server Nodes per Cluster
- 16 New 1 MB to 64 GB Shared Storage Spaces

Availability Improvements

- Planned or unplanned outages

Requirements

- iSeries 270, 820, 830, 840, or 890
- OS/400 V5R2
- Windows 2000 Advanced Server for 2 Node Support
- Windows 2003 Enterprise for 4 Node Support*



* Planned for 1H 2003 dependent on Microsoft delivery

Availability - One Computer Room

Problem


- ▶ Providing an effective and efficient availability solution

Solution

- ▶ iSeries switch disk support with Independent ASP

Benefit

- ▶ Solution for planned or unplanned server outages



Availability - Multiple Locations

Problem


- ▶ Provide effective disaster recovery solution

Solution

- ▶ Lakeview Technologies' Mimix for Windows

Benefit

- ▶ Replication solution for planned or unplanned site outages



Remote Server Administration

Problem


- ▶ Managing heterogeneous server environments installed in remote offices

iSeries Solution

- ▶ With iSeries Navigator user, storage, backup administration for remote iSeries with integrated xSeries servers can be done centrally
- ▶ iSeries Navigator for Wireless provides access from cell phones

Benefit


- ▶ Can reduce costs by centrally managing remote servers



How to architect a solution ?

iSeries Server Consolidation Example


Before



- ✗ Multiple Windows servers
- ✗ Moving to Windows 2000
- ✗ Growing operations costs and limited staff
- ✗ Poor availability
- ✗ Storage management is out of control
- ✗ Multiple, inconsistent backups
- ✗ Aging capacity in a variety of places
- ✗ Servers coming off maintenance
- ✗ No test environment

After

(2) xSeries 360 & Integrated xSeries Adapter (IXA)



- ✓ Operations simplified
 - ★ Flexible, centralized storage management
 - ★ xSeries scalability delivers consolidation
- ✓ Outages reduced
 - ★ xSeries Enterprise X Architecture
 - ★ Test environment reduces impact of change
- ✓ Software costs reduced
 - ★ Linux OpenSource solutions

Decision Process

- **Inventory existing functions**
- **Determine platform that function is currently implemented on**
- **Inventory existing skills and skill availability**
- **Determine customer preference (if any) for platform**
- **Consider strengths / limitations of individual functions/platforms**
- **When the function is available on all platforms need to look at what sub-components are needed when considering the decision.**

Take an Inventory of the Existing Environment

Windows/Linux

For each server:

- ▶ size of processor and number of processors
- ▶ CPU utilization
- ▶ applications/services installed
- ▶ hard disk size, protection and utilization
- ▶ I/O rates (# of disk operations per second)
- ▶ high availability schemes used
- ▶ number of users

iSeries

For each server:

- ▶ model and processor feature
- ▶ release level
- ▶ # of disk arms
- ▶ # I/O towers
- ▶ tape device
- ▶ available slots
- ▶ CPU utilization
- ▶ disk capacity and utilization

i.e.. rack config info

Best Server Replacement Targets

You need to look for server functions that match the benefits

- ▶ mission critical, line of business applications
 - hot spare, testing, backup and recovery

- ▶ heavy I/O applications
 - storage Virtualization

- ▶ like to like function servers (file servers)
 - storage Virtualization, latest xSeries technology

- ▶ infrastructure servers (DNS, DHCP, WINS, DC)
 - storage Virtualization, latest xSeries technology, user admin.

Strategies

- **One recommended strategy would be to start with a pilot to help customer through the issues and decision making (for Linux purposes).**
 - ▶ **User Administration will be single biggest concern/prohibiter to moving to Linux**

- **Rather than bring in new function to existing infrastructure - consider new function for implementation in Linux or IXS/IXA.**

Highlight Exclusive Benefits - apply to situation

- ▶ User Administration - IXS/IXA
 - manage users

- ▶ Virtual Gigabit Ethernet
 - Less network traffic

- ▶ Storage Virtualization
 - iSeries as a SAN

- ▶ Testing
 - flexibility, reliability

- ▶ Hot Spare
 - availability option

iSeries Windows Server Integration

iSeries and Windows Environment

90+% of iSeries customers also have Windows™ servers

Windows servers typically used for infrastructure applications

Number of Windows servers continues to grow, along with management costs

Number of NT Servers in iSeries Accounts

Number of Servers	% of Customers
1-5	57%
6-10	14%
11-20	10%
21-200	17%
201+	2%

IBM IT Trends Survey - 4Q 2001, 100-999 Employee Site Data

Integrated xSeries Solution Positioning

1 GHz Integrated xSeries Server (IXS)

- Customers implementing on NT 4.0 / Windows 2000
- Customers implementing on OS/400 V5R1
- Price sensitive customers who do not need extra processing power and/or 1 GB memory

1.6 GHz Integrated xSeries Server (IXS)

- Customers on or moving to Windows 2000 Server and OS/400 V5R2
- Integrated Ethernet 10/100 - Less slots used !!

Integrated xSeries Adapter (IXA) and xSeries Servers

- Customers on or moving to Windows 2000 and OS/400 V5R1/V5R2
- Customers who need 2-8 way Intel processing power
- Customers who need flexibility to add additional PCI cards in their Intel servers
- Customers with no remaining slots in CEC or expansion towers for IXS
- One Integrated xSeries Adapter per xSeries server attached

www.ibm.com/eserver/series/windowsintegration

Intel Processor Considerations - what solution(s)

IXS vs. IXA

- ▶ uni-processor vs. multiprocessor
- ▶ adapter requirements (IXS NIC only)
- ▶ available slots in iSeries & I/O towers
- ▶ which side of the house talking to
 - iSeries side more accepting of IXS
 - Windows side more accepting of IXA
- ▶ memory requirements (IXS 4 Gig limit)

IXS - Which model ?

IXA - Which xSeries ?

Integrated xSeries Server Price/Performance Improvements

V5R1 Example:

1 GHz with 512 MB Memory

	1.0 GHz	Now
Integrated xSeries Server	\$ 2,800	\$ 1,300
Ethernet LAN	900	600
512 MB Memory	1,610	720
Keyboard/Mouse	90	90
Extension Cables	110	110
	\$ 5,510	\$ 2,820



V5R2 Example:

1 GHz vs. 1.6 GHz IXS & 1 GB Memory

	1 GHz	Now 1.6 GHz
Integrated xSeries Server	\$ 2,800	\$ 1,900
Ethernet LAN	900	Included
1 GB Memory	3,300	1,450
Keyboard/Mouse	90	90
Extension Cables	110	110
	\$ 7,200	\$ 3,550



xSeries Examples for Windows 2000 Server Deployment

1.0 GHz Integrated xSeries Server

- Intel Pentium III processor, 512 MB Memory
- 10/100 Mbps Ethernet Adapter
- File/Print serving, DNS/DHCP
- Development/test

< \$3,000

1.6 GHz Integrated xSeries Server

- Intel Xeon processor, 1 GB Memory
- Built-in 10/100 Mbps Ethernet Adapter
- Citrix server, Exchange Server

< \$4,000

x235 with Integrated xSeries Adapter

- 1.8 GHz Intel Xeon processor, 1 GB Memory
- 2-way capable, built-in 10/100/1000 Mbps Ethernet Adapter
- SQL Server, Windows 2000 Server applications

< \$6,000

xSeries Servers Supported with IXA - MUST Understand xSeries advantages !

x360

- ▶ 1-4 way server
- ▶ 1.4 to 1.6 GHz
- ▶ 3U Rack server



Enterprise X-Architecture

First servers with new Intel Xeon™ MP™ Processors
 Active™ Memory (hot-swap and hot-add)
 Active™ PCI-X
 XpandOnDemand™ Scalability
 RXE-100 Remote Expansion Enclosure
 Xcel4™ Server Accelerator Cache

x440

- ▶ 1-8 way server
- ▶ 1.4 to 1.6 GHz
- ▶ 4U Rack server



x255

- ▶ 1-4 way server
- ▶ 1.4 to 1.6 GHz
- ▶ Tower or 7U Rack server



X-Architecture Technology

Chipkill™ memory
 Active™ PCI & PCI-X
 Light Path Diagnostics™
 Extensive Predictive Failure Analysis
 Redundant Components
 IBM Director

x235

- ▶ 1-2 way server
- ▶ 1.8 to 2.4 GHz
- ▶ Tower server



iSeries Considerations - What happens on iSeries

CPW

Disk Ops/sec (1)	400	800	1,600	3,200
HSL (MB/sec)	3	6	13	26
CPW	41	81	152	300
Disk Arms (2)	7	10	18	40

HSL

Model	Loop	Max IXA	Max iSeries Towers	Max IXA per Loop	Max I/O and IXA per loop	Max I/O and IXA
270	1	2	1	2	3	3
820	1	8	5	8	9	9
830	4	16	13	8 Loop1 = 1	9	21
840	8	32	23	8	9	39
800	1	3	1	3	4	4
810	1	7	4	7	8	8
825	3	18	18	8	9	27
870	8	60	47	8	6	60
890	14	60	47	8	9	60

iSeries Considerations - continued

Available slots

- ▶ predefined slots available in each CEC and I/O tower

Model	Max IXS	Model	Max IXS
		800	4
270	3	810	13
820	12	825	36
830	28	870	48
840	32	890	48

Model	Max IXA	Model	Max IXA
		800	3
270	2	810	7
820	8	825	18
830	16	870	60
840	32	890	60

Disk arms

- ▶ for every 100 disk ops per sec you need at least 1 arm
- ▶ minimum 3 arms to start with

Performance is based on measurements and projections using standard IBM benchmarks in a controlled environment. The actual throughput or performance that any user will experience will vary depending upon considerations such as the amount of multiprogramming in the user's job stream, the I/O configuration, the storage configuration, and the workload processed. Therefore, no assurance can be given that an individual user will achieve throughput or performance improvements equivalent to the ratios stated here.

Tips & Techniques

Pre-install Checklist - Windows Integration

- ▶ *Do you have a supported xSeries model?- goto www.ibm.com/eserver/series/windowsintegration/daxsmodels.html*
- ▶ *Does the xSeries model require a Remote Supervisor Adapter (RSA) option (P.N. 09N7585) to attach to iSeries?*
 - ▶ *X235 & X255 require a RSA*
 - ▶ *X440, X360, X250, X350 & NetFinity 7100 & 7600 DO NOT require a RSA*
- ▶ *What will the HSL loop configuration be?*
 - ▶ *Is this a new loop?*
 - ▶ *If existing loop, do you have capacity on the loop?*
 - ▶ *If other I/O towers on loop, make sure you place xSeries in middle of loop.*
 - ▶ *Do not place next to Migration towers.*
- ▶ *Do you have the necessary HSL & SPCN cables?*
 - ▶ *If a new loop, you will need an HSL cable for each IXA + 1.*
 - ▶ *If adding to an existing loop you will need an HSL cable for each IXA.*
 - ▶ *If placing xSeries in a rack, get the shortest HSL cables, 3m (1460 feature) for between the IXAs.*
 - ▶ *You may need longer HSL cables to and from iSeries to IXAs.*
 - ▶ *You will need a SPCN cable for each IXA.*
 - ▶ *If placing xSeries in a rack, get the shortest SPCN cables, 2m (1463 feature) for between IXAs.*
 - ▶ *You may need longer SPCN cables to and from iSeries to IXAs*

Pre-install Checklist (continued)

► Software

- OS/400 V5R1 minimum for IXA support
- OS/400 V5R2 required for new 1.6 GHz IXS
- 5722WSV LPP
 - Base required
 - Option 2 required for Windows 2000 server
- OS/400 Cums and PTFs (include Windows Integration Service Packs) goto www.ibm.com/eserver/series/windowsintegration/ntsrvc.htm
- Microsoft Windows 2000 Server or Advanced Server
- Microsoft Windows Service Packs supported goto www.ibm.com/eserver/series/windowsintegration/ntsrvc.htm
- OS/400 Backup Performance update information for V5R1
<http://www-1.ibm.com/servers/eserver/series/windowsintegration/savbackupperf.html>

xSeries Server Preparation

- ▶ *The boot fail counter and virus detection need to be turned off before installing the IXA card. This is done from Setup utility.*
- ▶ *Upgrade xSeries server BIOS to the latest level goto www.pc.ibm.com/support to get latest BIOS.*
- ▶ *Upgrade xSeries Advanced Systems Management Firmware goto www.pc.ibm.com/support to get latest version of firmware.*

IXA Card Installation

- ▶ *Make sure power is unplugged from xSeries Server*
- ▶ *IXA card must be placed in correct slot for each supported xSeries Server goto iSeries PCI Card Installation Instructions to find current instructions.*
- ▶ *Jumpers need to be set for certain models of xSeries Servers to provide 3.3v standby power, goto iSeries PCI Card Installation Instructions to find current instructions goto <http://publib.boulder.ibm.com/series/v5r2/ic2924/info/rzame/eng47451.pdf>.*

- ▶ *Power down iSeries*
- ▶ *Connect HSL & SPCN cables to IXA*
 - *Keep all SPCN, HSL and Interconnect cables 6" away from any power source or power cables*
- ▶ *Reconnect xSeries power cables*
- ▶ *Power on iSeries, do NOT power on xSeries server, it will be powered on by iSeries*

- ▶ *You will notice the LED's on the IXA flashing, BE PATIENT - SPCN code is being downloaded, then xSeries Server will be powered on. This can take up to 1/2 hour.*
- ▶ *After iSeries & xSeries are powered on, you may want to have the SPCN network renumbered by doing an option 33 from the OPs Panel. This can be done from any point in time.*

References

New Reference Accounts - IXS/IXA

- ▶ Marshall Erdman Inc.
- ▶ Wesco Aircraft
- ▶ Coleman Cable
- ▶ IU Medical Group
- ▶ Chick Sporting Goods
- ▶ Huhtamaki
- ▶ Banco do Brasil

Wesco Aircraft



Background

- ▶ Wesco Aircraft is one of the largest distributors of aerospace fasteners, bearings, fittings, and installation tooling

Objectives

- ▶ Improve management for Exchange, SQL Server and File servers
- ▶ Reduce costs for PC server farm
- ▶ Improve availability
- ▶ Consolidate AS/400 JD Edwards servers and 31 PC servers

Solution

- ▶ 2 iSeries with LPAR and Clustering
- ▶ 8 xSeries attached to iSeries with IXA
- ▶ Switch disk clustering

Benefits

- ▶ Total cost of server administration is down over 20%
- ▶ Windows server storage is much easier to manage
- ▶ Testing of new applications is more flexible
- ▶ Better utilization rates compared to their stand-alone servers



xSeries
Exchange & SQL

xSeries
File & Print



Banco Do Brasil

Background

- ▶ Banco Do Brasil is the largest bank in South America

Objectives

- ▶ Centralize IT service and delivery
- ▶ Exploit open source software
- ▶ IT Europe had 8 branches with 250 users, 8 NT networks, and 41 NT Servers

Solution

- ▶ iSeries Model 820 Offering for Linux
- ▶ SuSE SLES 7
- ▶ 3 Integrated xSeries Servers
- ▶ 4 Integrated xSeries Adapters
- ▶ Replacing NT applications with Linux

Benefits

- ▶ Centralized storage
- ▶ Reduced Administration and support
- ▶ More reliable IT service
- ▶ Software license savings

BANCO DO BRASIL



more information needed ?

For More Information - Windows Integration

iSeries Windows Integration Web Site:

- ▶ <http://www-1.ibm.com/servers/eserver/series/windowsintegration/>
- ▶ Product information
- ▶ Service information (PTF's)
- ▶ Library

iSeries InfoCenter:

- ▶ <http://publib.boulder.ibm.com/pubs/html/as400/infocenter.htm>
- ▶ Articles on Windows NT and Windows 2000 on the IXS/IXA

Redbooks:

- ▶ <http://www.redbooks.ibm.com>
- ▶ AS/400 - Implementing Windows NT on the Integrated NetFinity Server SG24-2164
- ▶ Consolidating Windows 2000 Servers in iSeries SG24-6056
- ▶ Direct Attach xSeries for the IBM iSeries Server: A Guide to Implementing xSeries Servers in iSeries - SG24-6222

Contacts:

- ▶ Server Consolidation Segment Manager: George Gaylord ... ggaylord@us.ibm.com
- ▶ Advanced Technical Support: Bob Schuster ... raschus@us.ibm.com
- ▶ Product Manager: Kyle Wurgler ... wurgler@us.ibm.com

More information - Education and Service

Implementing Windows Server on iSeries (Course Code S6225)

Gain the skills needed to install, configure, manage and support Microsoft Windows Server on the iSeries Integrated xSeries Server and Direct Attached xSeries Server via Integrated xSeries Adapter. Learn the concepts, terminology and hardware that is related to the iSeries Integrated Windows environment. Through lecture topics and hands-on exercises, explore installation requirements and procedures, TCP/IP communication configuration including Gigabit Virtual LAN, storage space and combined user id administration, device sharing, backup and restore procedures, problem determination techniques and look at high availability options. For additional information or to view schedules and enroll, go to the following url: <http://www-3.ibm.com/servlet/com.ibm.ls.lsow.servlets.CourseDescriptionServlet?coursecode=S6225>

iSeries Windows Integration QuickStart

This services offering will get your company's integrated Windows environment up and running quickly. The engagement will be 1 & ½ days at a fixed price of \$2500. You will be able to choose 12 hours of material from an ala carte menu of choices. Some example choices will be Installing Windows Server, High Availability options, Planning and Allocating storage to Windows servers, Strategic Planning of your integrated Windows environment or Backup and Recovery options. You will get the expertise you need to have a successful implementation. For additional information or to schedule this service, send an e-mail with your request to the following address; E-mail: intwin@us.ibm.com
Phone: 1-507-253-9018

end-to-end Technical Support ...the Key Links

How to engage Technical Sales Support

- ✓ External Support:
 - ✓ <http://www.ibm.com/support>
- ✓ Sizing Tool - <http://www.ibm.com/servlet/EstimatorServlet>



<http://www-1.ibm.com/servers/eserver/series/education/key.html>

<http://publib.boulder.ibm.com/pubs/html/as400/infocenter.html>



IBM @server iSeries University

<http://www.ibm.com/servers/eserver/series/education/>



Redbooks

<http://www.redbooks.ibm.com>

IBM @server iSeries Technology Center

<http://www.ibm.com/servers/eserver/series/service/itc/educ.htm>



Partners In Education
Educating at the speed of change

IBM @server iSeries Support

Served by Lotus® Domino™ with iSeries® power

<http://www.ibm.com/eserver/series/support>

<http://www-1.ibm.com/servers/eserver/series/education/pie/>

Trademarks and Disclaimer

© Copyright International Business Machines Corporation 2001

References in this document to IBM products or services do not imply that IBM intends to make them available in every country.

The following terms are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both:

AS/400	IBM Logo	pSeries
AS/400e	iSeries	zSeries
e-Business logo	OS/400	eServer
IBM	xSeries	

Lotus, Freelance, and Word Pro are trademarks of Lotus Development Corporation in the United States, other countries, or both.

Tivoli and NetView are trademarks of Tivoli Systems Inc. in the United States, other countries, or both.

C-bus is a trademark of Corollary, Inc. in the United States, other countries, or both.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

PC Direct is a trademark of Ziff Communications Company in the United States, other countries, or both and is used by IBM Corporation under license.

ActionMedia, LANDesk, MMX, Pentium and ProShare are trademarks of Intel Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

SET and the SET Logo are trademarks owned by SET Secure Electronic Transaction LLC.

Other company, product and service names may be trademarks or service marks of others.

Information is provided "AS IS" without warranty of any kind.

All customer examples described are presented as illustrations of how those customers have used IBM products and the results they may have achieved. Actual environmental costs and performance characteristics may vary by customer.

Information in this presentation concerning non-IBM products was obtained from a supplier of these products, published announcement material, or other publicly available sources and does not constitute an endorsement of such products by IBM. Sources for non-IBM list prices and performance numbers are taken from publicly available information, including vendor announcements and vendor worldwide homepages. IBM has not tested these products and cannot confirm the accuracy of performance, capability, or any other claims related to non-IBM products. Questions on the capability of non-IBM products should be addressed to the supplier of those products.

All statements regarding IBM future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. Contact your local IBM office or IBM authorized reseller for the full text of the specific Statement of Direction.

Some information in this presentation addresses anticipated future capabilities. Such information is not intended as a definitive statement of a commitment to specific levels of performance, function or delivery schedules with respect to any future products. Such commitments are only made in IBM product announcements. The information is presented here to communicate IBM's current investment and development activities as a good faith effort to help with our customers' future planning.

Performance is based on measurements and projections using standard IBM benchmarks in a controlled environment. The actual throughput or performance that any user will experience will vary depending upon considerations such as the amount of multiprogramming in the user's job stream, the I/O configuration, the storage configuration, and the workload processed. Therefore, no assurance can be given that an individual user will achieve throughput or performance improvements equivalent to the ratios stated here.

Photographs shown are of engineering prototypes. Changes may be incorporated in production models.