

Gentran Integration Suite

System Maintenance Checklist

Release 4.3

Sterling Commerce
An IBM Company

Contents

| | |
|---|----------|
| System Maintenance Checklist..... | 3 |
| Gentran Integration Suite System Maintenance Overview..... | 6 |
| Sample Cluster Test Business Process..... | 7 |

System Maintenance Checklist

| System Maintenance Checklist | | | | |
|------------------------------|--|---------------------------------------|--------------------|--|
| 1. | Ensure the following Business Process Schedules are enabled and that they are running at their scheduled increments: | | | |
| | Schedule | Business Process to Review for Errors | Schedule Increment | Business Process Objective |
| | Schedule_BPRecovery | recovery.bpm1 | Every 45 minutes | Finish without error. |
| | Schedule_IndexBusinessProcessService | Schedule_IndexBusinessProcessService | Every 10 minutes | Process less than 5,000 and finish without error. |
| | Schedule_PurgeService | Schedule_PurgeService | Every 10 minutes | Finish without error. |
| | Schedule_BackupService | Schedule_BackupService | Once per day | <p>Set Maximum Number of Days per Backup Set to something larger than the oldest message in the system.</p> <p>By default, backup is configured to backup 2 days of data at a time, starting with the oldest data in the system.</p> <p>Ensure it finishes without error and the Cutoff Date is not in the past.</p> |
| | Schedule_AssociateBPsToDocs | Schedule_AssociateBPsToDocs | Every 30 minutes | Process less than 1,000 and finish without error. |

| System Maintenance Checklist | | | | |
|------------------------------|---|---|--------------------|---------------------------------|
| | Schedule | Business Process to Review for Errors | Schedule Increment | Business Process Objective |
| | Schedule_BPExpirator | TimeoutEvent | Every 15 minutes | Finish without error. |
| | ScheduleBPLinkagePurgeService | ScheduleBPLinkagePurgeService | Once per day | Finish without error. |
| | Schedule_MailboxEvaluateAllAutomaticRules or Schedule_MailboxEvaluateAllAutomaticRulesSubMin | Schedule_MailboxEvaluateAllAutomaticRules or Schedule_MailboxEvaluateAllAutomaticRulesSubMin | Every 1 minute | Finish without error (if used). |
| 2 | <p>Ensure all the business processes are moved out and being recovered. Review the state of your business processes:</p> <ul style="list-style-type: none"> • Active • Halted • Halting • Waiting • Waiting On IO • Interrupted Man • Interrupted Auto <p>Navigate to Administration Menu > Operations > System > Troubleshooter. Click Business Process Usage.</p> | | | |
| 3 | <p>Ensure all the necessary controllers are active.</p> <p>Navigate to Administration Menu > Operations > System > Troubleshooter. Click Controllers.</p> | | | |
| 4 | <p>Review the JDBC pool sizes to ensuring the database does not exceed the maximum size defined in jdbc.properties by the *.maxsize setting.</p> <p>Navigate to Administration Menu > Operations > System > Troubleshooter. Click Database Usage.</p> | | | |
| 5 | <p>Ensure all necessary adapters are enabled.</p> <p>Navigate to Administration Menu > Operations > System > Troubleshooter. Click Adapters.</p> | | | |
| 6 | <p>Ensure all necessary perimeter servers are enabled.</p> <p>Navigate to Administration Menu > Operations > System > Troubleshooter. Click Perimeter Server Status.</p> | | | |
| 7 | <p>Review business process life span settings to ensure they are correct. Settings include:</p> <ul style="list-style-type: none"> • How long the business process should remain in the system • How long trackable business process information remains in the system • How long business process (instances) should remain in system • Should expired business processes be archived or purged <p>Navigate to Operations > Archive Manager.</p> | | | |
| 8 | <p>Monitor table row counts through DBStats report (with increased load, increased counts are expected).</p> | | | |
| 9 | <p>Review logs for problems by looking for any of the following:</p> <ul style="list-style-type: none"> • ERROR | | | |

| System Maintenance Checklist | |
|-------------------------------------|--|
| | <ul style="list-style-type: none"> • OutofMemory • Exception (in some cases) |
| 10 | <p>Review the system for thread dumps and heap dumps.</p> <ul style="list-style-type: none"> • On IBM JDK Linux systems such as AIX, Red Hat Linux and Suse Linux, routinely check for the existence of thread dumps and heap dumps. Presence of these files indicates there is an issue. If the following files are found, they will need investigation. <ul style="list-style-type: none"> • For UNIX, check for javacore* and hprof*.* files in the <code>/install_dir/install/noapp/bin</code> directory. • For Windows, check for javacore in the <code>\install_dir\install\noapp\bin</code> and hprof files in the <code>noapp.exe.log</code> file. |
| 11 | <p>Review the system for spikes in load and ensure that no back log occurs that is sustained for hours in the queues.</p> <p>Navigate to http://server:port/queueWatcher.</p> |
| 12 | <p>Verify Cluster Information, perform a simple communication test to verify the nodes are communicating properly using sample BP (add for extra nodes as needed).</p> <p>For more information, see the <i>Sample Cluster Test Business Process</i>.</p> |

Gentran Integration Suite System Maintenance Overview

It is very important to review the daily operations of your Gentran Integration Suite. You should use the *System Maintenance Checklist* on a daily basis to ensure that your system is operating properly.

Use the System Maintenance Checklist to:

- Ensure that business processes are running and completing within your Service Level Agreement (SLA)
- Ensure that scheduled are enabled and running on time without error
- Ensure business process life spans are set correctly
- Ensure your controllers are active
- Ensure that your adapters are enabled
- Determine if the database is growing out of control
- Review Queuewatcher for spikes in load and ensure that no back log occurs that is sustained for hours in the queues
- Review log monitoring
- Review thread dumps and thread counts
- If you have a cluster, verify cluster nodes are communicating properly

The *System Maintenance Checklist* is intended to be used by the Gentran Integration Suite Administrator.

Sample Cluster Test Business Process

You can use the following example business process to test your cluster environment.

```
<process name="Cluster_Mandatory12121212">
  <rule name="queuesRemaining">
    <condition>queueCounter<10</condition>
  </rule>
  <sequence name="wrapper">
    <assign name="Assign" to="queueCounter">1</assign>
    <sequence name="main">
      <choice name="starter">
        <select>
          <case ref="queuesRemaining" activity="sub"/>
          <case ref="queuesRemaining" negative="true" activity="complete"/>
        </select>
        <sequence name="sub">
          <operation name="Execution Control Service">
            <participant name="ExecutionControlService"/>
            <output message="ExecCtrlServiceTypeInputMessage">
              <assign to="queueName" from="queueCounter"></assign>
              <assign to="." from="*"/></assign>
            </output>
            <input message="inmsg">
              <assign to="." from="*"/></assign>
            </input>
          </operation>
          <sequence name="block">
        <operation name="Sleepy1">
          <participant name="TestSleepService"/>
          <output message="Xout">
            <assign to="SLEEP_INTERVAL">1</assign>
            <assign to="mandatoryNode">node1</assign>
            <assign to="." from="*"/></assign>
          </output>
          <input message="Xin">
            <assign to="." from="*"/></assign>
          </input>
        </operation>
      <operation name="Sleepy2">
```

```

<participant name="TestSleepService" />
<output message="Xout">
    <assign to="SLEEP_INTERVAL">1</assign>
    <assign to="mandatoryNode">node2</assign>
    <assign to=".." from="*"></assign>
</output>
<input message="Xin">
    <assign to=".." from="*"></assign>
</input>
</operation>
<operation name="Sleepy3">
    <participant name="TestSleepService" />
    <output message="Xout">
        <assign to="SLEEP_INTERVAL">1</assign>
        <assign to="mandatoryNode">node1</assign>
        <assign to=".." from="*"></assign>
    </output>
    <input message="Xin">
        <assign to=".." from="*"></assign>
    </input>
</operation>
<operation name="Sleepy4">
    <participant name="TestSleepService" />
    <output message="Xout">
        <assign to="SLEEP_INTERVAL">1</assign>
        <assign to="mandatoryNode">node2</assign>
        <assign to=".." from="*"></assign>
    </output>
    <input message="Xin">
        <assign to=".." from="*"></assign>
    </input>
</operation>
<operation name="Sleepy5">
    <participant name="TestSleepService" />
    <output message="Xout">
        <assign to="SLEEP_INTERVAL">1</assign>
        <assign to="mandatoryNode">node1</assign>
        <assign to=".." from="*"></assign>
    </output>
    <input message="Xin">
        <assign to=".." from="*"></assign>
    </input>
</operation>

<operation name="Sleepy6">
    <participant name="TestSleepService" />
    <output message="Xout">
        <assign to="SLEEP_INTERVAL">1</assign>
        <assign to="mandatoryNode">node2</assign>
        <assign to=".." from="*"></assign>
    </output>
    <input message="Xin">
        <assign to=".." from="*"></assign>
    </input>

```

```

</operation>
<operation name="Sleepy7">
  <participant name="TestSleepService"/>
  <output message="Xout">
    <assign to="SLEEP_INTERVAL">1</assign>
    <assign to="mandatoryNode">node1</assign>
    <assign to="." from="*"></assign>
  </output>
  <input message="Xin">
    <assign to="." from="*"></assign>
  </input>
</operation>
<operation name="Sleepy8">
  <participant name="TestSleepService"/>
  <output message="Xout">
    <assign to="SLEEP_INTERVAL">1</assign>
    <assign to="mandatoryNode">node2</assign>
    <assign to="." from="*"></assign>
  </output>
  <input message="Xin">
    <assign to="." from="*"></assign>
  </input>
</operation>
</sequence>
<assign name="Assign" to="queueCounter" from="queueCounter + 1"></assign>

  <repeat name="repeater" ref="main" />
</sequence>
<sequence name="complete">
  <operation name="Sleep Service">
    <participant name="SleepService"/>
    <output message="SleepServiceInputMessage">
      <assign to="SLEEP_INTERVAL">2</assign>
      <assign to="." from="*"></assign>
    </output>
    <input message="inmsg">
      <assign to="." from="*"></assign>
    </input>
  </operation>
</sequence>
</choice>
</sequence>
</sequence>
</process>

```