

Sterling Integrator®

System Administration

Version 5.0



Contents

- License Information.....4**
 - License Information.....4
 - View License Information4
 - Change the IP Address.....4
- Support Tools.....6**
 - Support Tool.....6
 - Support Case Tool.....6
 - Create a Support Case.....6
 - SQL Manager Tool.....8
 - Perform SQL Query from SQL Manager.....8
 - Export SQL Query Results from SQL Manager.....8
- Back Up and Restore.....9**
 - Sterling Integrator Back Up and Restore.....9
 - Back Up Sterling Integrator.....9
 - Restore Sterling Integrator.....10
 - Restore Sterling Integrator after a Planned Database Outage.....10
- Miscellaneous.....11**
 - Start and Stop Commands.....11
 - Customize Date and Time Formats.....11
 - Configure Keystore Pathname or Password.....12
- System Log Messages.....13**
 - System Log Messages.....13
 - Format of Error Codes Without Parameters.....13
 - Format of Error Codes With Parameters.....14
 - ASC X12 Deenveloping System Log Messages.....15
 - ASC X12 Enveloping System Log Messages.....19
 - Block Processor Translation System Log Messages.....21
 - Document Extraction System Log Messages.....23
 - EDI Control Report System Log Messages.....26
 - EDIFACT Deenveloping System Log Messages.....27
 - EDIFACT Enveloping System Log Messages.....31
 - EDI Encoding System Log Messages.....33
 - EDI Enveloping System Log Messages.....34
 - EDI Post-processing System Log Messages.....36
 - EDI Report System Log Messages.....41
 - Field Processor Translation System Log Messages.....41
 - Generate 997 System Log Messages.....42
 - Generate TA1 Acknowledgement System Log Messages.....42
 - Generic Deenveloping System Log Messages.....43
 - Generic Enveloping System Log Messages.....44
 - JDBC Translation System Log Messages.....46
 - Overdue Acknowledgement System Log Messages.....47
 - Reconcile 997 Acknowledgement System Log Messages.....47

Reconcile CONTRL Acknowledgement System Log Messages.....	48
Report Translation System Log Messages.....	50
Standards Translation System Log Messages.....	50
TA1 Acknowledgement Reconciliation System Log Messages.....	51
Translation Engine System Log Messages.....	52
Translation Object System Log Messages.....	54
Translation Rules System Log Messages.....	54
Translation Storage System Log Messages.....	56
Typing Service System Log Messages.....	58
Utility Translation System Log Messages.....	59
XML Encoding Translation System Log Messages.....	64
System Maintenance.....	66
System Maintenance.....	66
Copyright.....	67

License Information

License Information

See the Sterling Integrator Installation or Upgrade documentation for system license information.

View License Information

You may find it useful to list and view the following information about currently installed licenses:

- License status - Valid or invalid.
- Component name - Component that the license is valid for.
- IP address - IP address that the license is valid on.
- Valid dates - Start and end dates that the license is valid.

To list all installed licenses:

1. Select **System > B2B Console**.
2. Select **Operations > System > Licenses**.
3. On the Licenses page, under List, next to List All Licenses, click **Go!**
4. All of the installed licenses are listed.
5. To refresh the license page, click **Reload Licenses**.

Change the IP Address

If you install Sterling Total Payments on a different server with a different IP address, you must change the IP address on the Self-Service Licensing site and download a new license. If you use the previous license file that contains the previous IP address, an IP address conflict occurs and Sterling Total Payments does not operate.

To change the IP address in the license file:

1. Select **System > B2B Console**.

2. Select **Operations > System > Licenses**.
3. Next to List All Licenses, click **Go!**
4. Click **Self-Service Licensing Site**.
5. Click **Next**.
6. Click **Next**.
7. Type your CD-Key in the CD-Key field and select Server Details listed on the left side of the Product CD-Entry page.
8. Change the IP Address.
9. Select **Review and Download Package License File** listed on the left side of the page.
10. On the Review and Download Package License File page click **Finish and Download** at the bottom of the page.
11. Click **Save** in the File Download dialog box.
12. Accept the default location for the license file or navigate to the location where the license file is stored.

Note: You recorded the path to the license file on the Preinstallation Task and Installation Information Worksheet during installation.

13. Close the Self-Service Licensing site to return to the License page.
14. Click **Return** on the License page.
15. Next to Update License, click **Go!**
16. On the New License File page, in the License Key File field, type the location of the license file, or click **Browse** to browse to the file and click **Next**.
17. Click **Finish**.

Support Tools

Support Tool

Sterling Integrator provides you with a support case and an SQL manager tool to help you communicate with and troubleshoot operational issues with Sterling Commerce Customer Support.

A support case is a situation where you call Sterling Commerce Customer Support for help. Sterling Commerce Customer Support opens a support case to record all activities through resolution.

Support Case Tool

See the Sterling Integrator Installation or Upgrade documentation for the appropriate command format.

The Support Case tool enables you to create and add information to a support case directly from the Sterling Integrator interface. This reduces the communications effort between you and Sterling Commerce Customer Support.

After you have created a support case, you can attach database queries, system information, properties files and other information to help communicate issues to Sterling Commerce Customer Support. The information is bundled together using the PackageSupportInfo business process, which creates a .jar file, a compressed java file much like a .zip file, and then sends the .jar file to Sterling Commerce Customer Support using the FTP adapter.

The .jar file is also stored in your *install_dir/supportcasejars* directory under the following name formats:

c#case_no#filename.jar, if you selected support case.

s#case_no#filename.jar, if you selected support request.

Create a Support Case

Using the support case tool should be reserved for the system administrator or the system administrator's delegate. You must have permissions to the Support Case tool to use it.

Before you begin to use the Support Case Tool:

- Have the support case or support request number you are referencing available.

- Create a support case on the Sterling SOD site, if you do not have a support case or support request number.

To use the Support Case Tool:

1. From the Administration menu, select Operations > System > Support Tools > Support Case.
2. On the Case Details page, in the Case Number field, type the case number of the support case you are referencing.

Case Number is a required field and cannot accept special characters.

Note: If you do not have a case number assigned, click Sterling SOD site to go to the Sterling Commerce Support on Demand site and create a new case.

3. Select whether the case number you are referencing is a:
 - Support Case – References a case number. Case numbers begin with the letter c.
 - Support Request – References a support request number. Support Request numbers begin with the letters sr.
4. In the Output Jar Name field, type the filename that becomes the bundled .jar file when you complete this procedure. For example, if you type Sterling in the Output Jar Name field, the bundled .jar file becomes Sterling.jar when you finish this procedure.
5. Select the FTP check box if you want to send the case information to Sterling Commerce Customer Support.
6. In the Steps To reproduce field, type the steps to reproduce the issue that led to the support case.
Provide detailed information including all steps leading up to the issue and any error messages received in this field to help support provide a quicker resolution to your issue.
This information is available in the support .jar file in the StepsToReproduce.txt file.
7. In the Description field, type a description for the support case.
This information is available in the support .jar file in the ProblemDescription.txt file.
8. Click Next.
9. On the Case Data page, in the Data File field, type the path or browse to the location of the data file you want to attach to the case.
The data files you upload are available in the support .jar file in the SuppCase.jar file.
10. In the Description field, type a brief, unique description of the file being attached.
11. Click Attach.

Note: You can attach multiple files in multiple formats in one support case bundle. Repeat steps 9 through 11 to attach multiple files.

12. On the Confirm page, complete the following actions:
Providing the system information and properties files in the .jar bundle provides the greatest amount of information about your system and situation to Sterling Commerce Customer Support and helps to expedite the case to resolution.
 - a) Select the Include System Information to include information about the server, memory and other components in the bundle.
 - b) Select the Include Property Files to include properties files from your Sterling Integrator installation.
 - c) Review the information and click Finish.

The information is bundled into the .jar file you named in the Output Jar Name field. If you selected the option, the information is sent to Sterling Commerce Customer Support.

SQL Manager Tool

The SQL Manager tool in Sterling Integrator enables Sterling Commerce Customer Support to search your Sterling Integrator database for information that may help in resolving your support case.

Caution: Use this tool only when Sterling Commerce Customer Support directs you to use it and when a support representative guides you through the process. You can make permanent changes to your database, which may result in damage to your Sterling Integrator configuration and loss of data.

Note: If you are manually entering the date in MySQL, do not enter a date with all zeroes, for example, 0000-00-00 00:00:00. Enter a valid date or NULL.

Perform SQL Query from SQL Manager

To complete a query using the SQL Manager:

1. From the **Administration Menu**, select **Operations > System > Support Tools > SQL Manager**.
2. Enter your SQL query and click **Execute**.

The query results display directly under the SQL Manager tool.

You can use the **Command History** link at the top of the SQL Manager tool to view the commands you have entered during the most current session. You can copy and paste the commands from the history page to the SQL Manager. Once you log out, or your session times out, all previous command history entries are lost.

Export SQL Query Results from SQL Manager

After you work with Sterling Commerce Customer Support to complete your query, you can export the results in different formats to send them to Sterling Commerce Customer Support or for archival purposes.

To export the query results from the SQL Manager:

1. In the SQL Manager tool, complete your query.
2. At the top-center of the results table, next to Export, click the format for the file:
 - xls – Microsoft Excel spreadsheet file
 - csv – Comma separated values file
 - xml – XML file
3. In the File Download window, click **Save** and select the location to save the file to.

You can now e-mail the file to Sterling Commerce Customer Support or attach the file to your case opened using the Support Case tool in Sterling Integrator.

Back Up and Restore

Sterling Integrator Back Up and Restore

It is good practice to back up Sterling Integrator on a regular basis to protect your data in the event of hardware failure, system failure or a catastrophic event.

The Back Up and Restore tasks contain general instructions. Your installation may require other steps not identified in the tasks. These are system level instructions. Ensure that you have sufficient access and file permissions before attempting to back up or restore Sterling Integrator. If you encounter problems with these tasks contact Sterling Commerce Customer Support.

Back Up Sterling Integrator

You may find it useful to list and view the following information about currently installed licenses:

To back up Sterling Integrator, perform the following steps:

1. Back up the database used with Sterling Integrator. If you are using MySQL, this is part of the Sterling Integrator installation directory structure. Take the following precautions:

- If you are using MySQL, stop Sterling Integrator before backing up the file system.
- If you are using another database, perform one of the following:

Stop Sterling Integrator before backing up the database.

Use a database backup tool that allows you to back up the database while it is live. Never attempt to back up a live database otherwise.

2. Back up the entire Sterling Integrator installation directory, include all files and subdirectories.

Note: Be sure to include any service configurations that point to directories that are not within the installation directories. These include:

- Command Line Adapter - `install_dir/client/cmdline/CLA2Client.jar`
 - Command Line Adapter2 - `install_dir/client/cmdline2/CLA2Client.jar`
-

3. Back up external resources, including any external locations used by any service configurations. For example:
 - Collection/extraction directories for FSA instances
 - Document directory for File System storage
 - Resources such as scripts, etc.
4. If you use perimeter services, perform the following steps:
 - a) Back up your *perimeter.properties* file.
 - b) For perimeter services in the DMZ, record your installation parameters. You will need them during the restore process. Alternatively, back up the installation directory.
 - c) Back up DMZ deployments and resources.

Restore Sterling Integrator

If you restore a system because of total failure, review the following requirements:

- The system must be restored with the same IP address.
- The user account must match the system that failed.
- The JDK on the new system must be the exact same version and installed in the same location.

To restore Sterling Integrator, perform the following steps:

1. Restore the database used with Sterling Integrator.

Note: If you are using MySQL, this is part of the Sterling Integrator installation directory structure.

2. Restore the Sterling Integrator installation directory, including all files and subdirectories, to the same directory path where it was originally installed.
3. Restore external resources to the same directory path where they were originally installed.

Note: The host information (IP address or hostname) must remain the same on the restored system.

4. (Windows only) From the installation directory, install windows services by running the *command installWindowsService.cmd*.
5. If you use perimeter services, perform the following steps:
 - a) Restore your *perimeter.properties* file.
 - b) Restore DMZ deployments and resources, if required and perimeter services installations. Use the installation parameters you recorded during the back up process. Alternatively, if you backed up the installation directory, restore the installation directory.

Restore Sterling Integrator after a Planned Database Outage

To restore Sterling Integrator after a planned database outage, perform the following steps:

1. Shut down Sterling Integrator.
2. Afer the database is back up, restart Sterling Integrator.

Miscellaneous

Start and Stop Commands

See the Sterling Integrator Installation or Upgrade documentation for the appropriate command format.

Customize Date and Time Formats

After you work with Sterling Commerce Customer Support to complete your query, you can export the results in different formats to send them to Sterling Commerce Customer Support or for archival purposes.

Date and time formats in Sterling Integrator can be customized to use international formats for field input and display.

Before performing this procedure, see *Working with Property Files* for important cautions.

To customize date and time formats:

1. Navigate to the installation directory.
2. Navigate to the properties directory.
3. Open the *ui.properties.in* file in a text editor, and move to the Input/Display date/time formats section:

```
#####  
# Input/Display date/time formats  
#####  
  
PlatformDateFormat.Date.SHORT=MM/dd/yy  
PlatformDateFormat.Date.MEDIUM=MMM d,yyyy  
PlatformDateFormat.Date.LONG=MMMM d,yyyy  
PlatformDateFormat.Date.FULL=EEEE,MMMM d,yyyy  
PlatformDateFormat.Time.SHORT=h:mm a  
PlatformDateFormat.Time.MEDIUM=h:mm:ss a  
PlatformDateFormat.Time.LONG=h:mm:ss a z  
PlatformDateFormat.Time.FULL=h:mm:ss a z
```

Note: During operation, Sterling Integrator uses the *ui.properties* file, not the *ui.properties.in* file. The date/time edit is performed on the *ui.properties.in* file to keep the edited values from being overwritten during system initialization and setup.

4. Edit the date/time pattern strings, using the characters and syntax specified for the Java SimpleDateFormat class as documented at <http://java.sun.com>.
5. Save and close the *ui.properties.in* file.
6. Stop Sterling Integrator.
7. Run the *setupfiles* script using one of the following steps:
 - (UNIX, Linux, or iSeries) – From the `install_dir/bin` directory, run the `setupfiles.sh` command.
 - (Windows) – From the `install_dir\bin` directory, run the `setupfiles.cmd` command.
8. Start Sterling Integrator.

Configure Keystore Pathname or Password

When importing CA (trusted root) certificates from the Java Key Store (JKS) that is shipped with the JVM, a password is required. This password appears as a prepopulated default in the user interface.

If Sun Microsystems changes this password or the JKS pathname, modify the *ui.properties* file to modify the default password that appears in the UI.

To configure a keystore pathname or password:

1. Navigate to the installation directory.
2. Navigate to the properties directory.
3. Open the *ui.properties* file and locate this line:

```
JVMcacertsFilePath = install_dir/jdk/jre/lib/security/cacerts
```

4. Modify the *JVMcacertsFilePath* entry to reflect the new pathname.
5. To change the keystore default password that appears in the interface, locate this line:

```
JVMcacertsFilePass =
```

6. Modify the *JVMcacertsFilePass* entry to reflect the new password.
7. Save and close the *ui.properties* file.
8. Stop Sterling Integrator.
9. Run the *setupfiles* script using one of the following steps:
 - (UNIX, Linux, or iSeries) – From the `install_dir/bin` directory, run the `setupfiles.sh` command.
 - (Windows) – From the `install_dir\bin` directory, run the `setupfiles.cmd` command.
10. Start Sterling Integrator.

System Log Messages

System Log Messages

Sterling Integrator uses enhanced system logging for EDI and translator messages. Each system message related to EDI or translation now contains a unique code number in addition to the text of the message.

Log files are created in the `install_dir/logs` directory. To prevent the system log files from taking up necessary storage space and memory allocations, Sterling Integrator only generates a log file when a component runs (a log file is generated to monitor the activities of each system component), which improves the performance of the system.

See *Managing System Logs* for information on log file naming conventions, log file types, and how to manage the system logs.

Note: If you receive the following code in a system log, it indicates that a basic logging method was used and notifies you of a message that has not yet been converted to use the enhanced logging (in the future all these messages will be converted):

```
000000000000 GLOBAL_SCOPE N/A
```

Format of Error Codes Without Parameters

The new error code numbers use the following format:

```
Scope.Subsystem.Name=000110020789
```

The format used is parsed and described in the following table:

Number of Error Code Number Digits	Description
1 - 4	The first four digits specify the scope of the component (for example, EDI).
5	The next one digit specifies the log severity level. The convention is: <ul style="list-style-type: none">• 1 = error/exception• 2 = debug messages

Number of Error Code Number Digits	Description
	<ul style="list-style-type: none"> • 3 = warnings • 4 = information/all messages
6 - 8	The next three digits specify the subsystem of the component (for example, EDI_EDIFACTDEENVELOPING).
9 -12	The next four digits specify the unique error number (this number is unique in conjunction with the rest of the error code format (such as the scope and so forth).

For example, this is an EDIFACT deenveloping system message:

```
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACTServiceImpl_start=000520040001
```

The format used in this message (to the left of the equals sign) is parsed and described in the following table:

Parameter	Description
Scope	EDI
Subsystem	EDI_EDIFACTDEENVELOPING (the EDIFACT deenveloping subsystem, which is a subset of EDI in the system)
Name	DEB_DeenvelopeEDIFACTServiceImpl_start This is the name of the error message which, when translated into the system log, reads DeenvelopeEDIFACTServiceImpl processData() starting...

The format used in this message (to the right of the equals sign) is parsed and described in the following table:

Number of Error Code Number Digits	Description
1 - 4	The first four digits (0005) specify the scope of the component (EDI).
5	The next one digit (2) specifies the log severity level, indicating that this is a debug message (DEB).
6 - 8	The next three digits (004) specify the subsystem of the component (EDI_EDIFACTDEENVELOPING).
9 -12	The next four digits (0001) specify the unique error number (this number is unique in conjunction with the entire error code format).

Format of Error Codes With Parameters

Additionally, the system message codes may include parameters, such as:

```
Scope.Subsystem.Name={0}000110020789{3}
```

The format used is parsed and described in the same manner as messages without parameters.

For example, this is an EDIFACT deenveloping system message with a parameter:

```
EDI.EDI_EDIFACTDEENVELOPING.EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACTServiceImpl_ExceptionFindingContract={0}0005200400010{3}
```

The format used in this message (to the left of the equals sign) is parsed and described in the following table:

Parameter	Description
Scope	EDI
Subsystem	EDI_EDIFACTDEENVELOPING (the EDIFACT deenveloping subsystem, which is a subset of EDI in the system)
Name	EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACTServiceImpl_ExceptionFindingContract This is the name of the error message which, when translated into the system log, reads [DeenvelopeEDIFACTServiceImpl] Exception finding contract {0} Note: The first parameter [DeenvelopeEDIFACTServiceImpl], indicates the service implementation. The second parameter {0}, indicates the specific contract.

The format used is in this message (to the right of the equals sign) parsed and described in the following table:

Number of Error Code Number Digits	Description
1 - 4	The first four digits (0005) specify the scope of the component (EDI).
5	The next one digit (2) specifies the log severity level, indicating that this is a debug message (DEB).
6 - 8	The next three digits (004) specify the subsystem of the component (EDI_EDIFACTDEENVELOPING).
9 -12	The next four digits (0001) specify the unique error number (this number is unique in conjunction with the entire error code format).

ASC X12 Deenveloping System Log Messages

The following system log messages are used for ASC X12 deenveloping:

Message Code	Log Message
EDI.EDI_X12DEENVELOPING.DEB_DeenvelopeX12ServiceImpl_ExceptionFindingContract = 0005200200 04	[DeenvelopeX12ServiceImpl] Exception finding contract {0}
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception1 = 000510020001	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception2 = 000510020002	DeenvelopeX12ServiceImpl - Error saving interchange correlation
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception3 = 000510020003	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception4 = 000510020004	DeenvelopeX12ServiceImpl - Error saving group correlations

Message Code	Log Message
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception5 = 000510020005	DeenvelopeX12 - Error EDI encoding 997 document for group control no. {0}
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception6 = 000510020006	DeenvelopeX12 - Error creating 997
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception7 = 000510020007	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception8 = 000510020008	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception9 = 000510020009	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception10 = 000510020010	DeenvelopeX12ServiceImpl - Error generating TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception11 = 000510020011	DeenvelopeX12ServiceImpl - Error enveloping 997
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception12 = 000510020012	DeenvelopeX12ServiceImpl - Error generating TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception13 = 000510020013	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception14 = 000510020014	DeenvelopeX12ServiceImpl - Error saving transaction correlation
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception15 = 000510020015	DeenvelopeX12ServiceImpl - Error generating TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception16 = 000510020016	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception17 = 000510020017	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception18 = 000510020018	Error reconciling TA1s
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception19 = 000510020019	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception20 = 000510020020	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception21 = 000510020021	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception22 = 000510020022	Exception while de-enveloping ISA/IEA

Message Code	Log Message
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception23 = 000510020023	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception24 = 000510020024	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception25 = 000510020025	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception26 = 000510020026	Exception attempting to close output stream in DeenvelopeX12ServiceImpl
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception27 = 000510020027	Exception while de-enveloping GS/GE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception28 = 000510020028	Exception while de-enveloping GS/GE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception29 = 000510020029	Exception while de-enveloping GS/GE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception30 = 000510020030	Exception while removing GS/GE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception31 = 000510020031	Exception while removing GS/GE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception32 = 000510020032	Exception while removing GS/GE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception33 = 000510020033	Exception while removing GS/GE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception34 = 000510020034	Exception while looking up a contract
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception35 = 000510020035	DeenvelopeX12ServiceImpl - Error reconciling 997
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception36 = 000510020036	Exception while de-enveloping ST/SE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception37 = 000510020037	Exception while de-enveloping ST/SE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception38 = 000510020038	Exception while de-enveloping ST/SE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception39 = 000510020039	Exception while removing ST/SE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception40 = 000510020040	Exception while removing ST/SE envelope

Message Code	Log Message
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception41 = 000510020041	Exception while removing ST/SE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception42 = 000510020042	Exception while removing ST/SE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_str1 = 000510020043	Unable to match ISA/IEA Envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_str2 = 000510020044	Unable to match ISA/IEA Envelope, lookup returned multiple envelopes
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_str3 = 000510020045	Unable to match GS/GE Envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_str4 = 000510020046	Unable to match GS/GE Envelope, lookup returned multiple envelopes
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception43 = 000510020047	ProcessTransactions: IOException while closing streams
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception44 = 000510020048	DeenvelopeX12ServiceImpl - Error loading BP
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception45 = 000510020049	[DeenvelopeX12ServiceImpl] Exception finding contract
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_str5 = 000510020050	Unable to match ST/SE Envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_str6 = 000510020051	Unable to match ST/SE Envelope, lookup returned multiple envelopes
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception46 = 000510020051	DeenvelopeX12ServiceImpl unable to start workflow for TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception47 = 510020052	DeenvelopeX12ServiceImpl - Error enveloping TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception48 = 000510020054	DeenvelopeX12ServiceImpl - Error setting up deferred sequence/duplicate control number checking
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception49 = 000510020055	DeenvelopeX12ServiceImpl - Error saving transaction correlations
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception50 = 000510020056	[DeenvelopeX12ServiceImpl] Error in Correlation
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception51 = 000510020057	DeenvelopeX12ServiceImpl - Error saving transaction correlations

Message Code	Log Message
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception52 = 000510020058	Exception while de-enveloping ISA/IEA

ASC X12 Enveloping System Log Messages

The following system log messages are used for ASC X12 enveloping:

Message Code	Log Message
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12ServiceImpl_start = 000520010001	EnvelopeX12.envelope() starting...
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12ServiceImpl_TranslationLargeFile = 000520010002	Translation large file support enabled /= {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12ServiceImpl_end = 000520010003	EnvelopeX12.envelope() ending...
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12ServiceImpl_stControlNumber = 000520010004	Loading st control number for {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12ServiceImpl_gsControlNumber = 000520010005	Loading gs control number for {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12ServiceImpl_isaControlNumber = 000520010006	Loading isa control number for {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12ServiceImpl_ExceptionFindingContract1 = 000520010007	EnvelopeX12.lookupSTContract(): Exception on finding contract {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12ServiceImpl_ExceptionFindingContract2 = 000520010008	EnvelopeX12.lookupSTContract(): Exception finding contract {0}
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception1 = 000510010001	EnvelopeGeneric.envelope() encountered exception:
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception2 = 000510010002	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_str1 = 000510010003	Document has not been processed by the EDI Encoder service
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception3 = 000510010004	Exception while looking up a contract
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception4 = 000510010005	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception5 = 000510010006	A SQL Exception occurred while retrieving the document extension.

Message Code	Log Message
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception6 = 000510010007	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception7 = 000510010008	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception8 = 000510010009	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception9 = 000510010010	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception10 = 000510010011	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception11 = 000510010012	EnvelopeX12.envelope() encountered exception
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception12 = 000510010013	EnvelopeX12.envelope() encountered exception:
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception13 = 000510010014	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception14 = 000510010015	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception15 = 000510010016	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_info = 000510010017	{0}
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception16 = 000510010018	Exception attempting to close output or input streams in EnvelopeX12.envelope()
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception17 = 000510010019	X12EnvelopeServiceImpl - Error loading control number
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception18 = 000510010020	X12EnvelopeServiceImpl - Error loading control number
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception19 = 000510010021	X12EnvelopeServiceImpl - Error loading control number
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception20 = 000510010022	[X12 Envelope Service] Error saving correlations.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception21 = 000510010023	EnvelopeX12.envelope() encountered exception:

Message Code	Log Message
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception22 = 000510010024	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception23 = 000510010025	X12EnvelopeServiceImpl - Error loading control number
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception24 = 000510010026	Exception while writing ISA/IEA envelope
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception25 = 000510010027	Exception while writing ISA/IEA envelope
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception26 = 000510010028	Exception while writing ISA/IEA envelope
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception27 = 000510010029	EnvelopeX12ServiceImpl - Exception loading outbound envelope values from correlations
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception28 = 000510010030	EnvelopeX12ServiceImpl - Exception loading outbound envelope values from correlations
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_ERR_EnvelopeX12ServiceImpl_ControlNumberNames = 000510010031	EnvelopeX12ServiceImpl - Error generating control number names - {0}
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception29 = 000510010031	Error generating ISA resource name
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception30 = 000510010032	[EnvelopeX12Service] exception finding document. The requiresEnvelope correlation was not changed

Block Processor Translation System Log Messages

The following system log messages are used for block processor translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDInputBinBlockHandler_exception1 = 000610060001	[Translator] Unable to encode overridden delimiters using encoding {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDInputBinBlockHandler_exception2 = 000610060002	[Translator] Unable to encode overridden delimiters using default encoding
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDInputCharBlockHandler_exception1 = 000610060003	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDInputCharBlockHandler_exception2 = 000610060004	TRANSLATOR: The specified input encoding is not supported.

Message Code	Log Message
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDIOutputBlockHandler_exception1 = 000610060005	TRANSLATOR: The specified output encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDIOutputBlockHandler_exception2 = 000610060006	TRANSLATOR: The specified output encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_PositionInputBlockHandler_exception1 = 000610060007	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_PositionInputBlockHandler_exception2 = 000610060008	TRANSLATOR: The specified output encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_PositionInputBlockHandler_exception3 = 000610060009	TRANSLATOR: Failed to convert multibyte char to bytes
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_PositionInputBlockHandler_exception4 = 000610060010	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_PositionInputBlockHandler_exception5 = 000610060011	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception1 = 000610060012	TRANSLATOR: SQL exception while opening JDBC connection
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception2 = 000610060013	TRANSLATOR: jdbc driver \ {0} \ does not support scrolling, defaulting to forward only while executing \ {1} \ in {2}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception3 = 000610060014	TRANSLATOR: jdbc driver \ {0} \ does not support scrolling, defaulting to forward only while executing \ {1} \ in {2}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception4 = 000610060015	TRANSLATOR: SQL exception while executing \ {0} \ in {1}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception5 = 000610060016	TRANSLATOR: SQL exception while executing \ {0} \ in {1}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception6 = 000610060017	TRANSLATOR: SQL exception performing MOVEFIRST on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception7 = 000610060018	TRANSLATOR: SQL exception performing MOVELAST on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception8 = 000610060019	TRANSLATOR: SQL exception performing MOVENEXT on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception9 = 000610060020	TRANSLATOR: SQL exception performing MOVEPREV on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception10 = 000610060021	TRANSLATOR: SQL exception performing CLOSE on result of {0}

Message Code	Log Message
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception11 = 000610060022	TRANSLATOR: SQL exception while closing JDBC resultset
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception12 = 000610060023	TRANSLATOR: SQL exception while rolling back transaction in {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception13 = 000610060024	TRANSLATOR: SQL exception while committing transaction in " {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SQLBlockHandler_exception14 = 000610060025	Caught exception in finishTranslation()
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SWIFTInputBlockHandler_exception1 = 000610060026	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SWIFTInputBlockHandler_exception2 = 000610060027	TRANSLATOR: Error closing the input stream.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SWIFTInputBlockHandler_exception3 = 000610060028	TRANSLATOR: I/O exception.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SWIFTInputBlockHandler_exception4 = 000610060029	TRANSLATOR: Error compiling a syntax.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_SWIFTInputBlockHandler_exception5 = 000610060030	TRANSLATOR: Data conversion error.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_VarDelimInputBlockHandler_exception1 = 000610060031	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_XMLErrorHandler_exception1 = 000610060032	SAX Parser Exception:
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.DEB_SQLBlockHandler_dbPool = 000620060001	[SQLBlockHandler] dbPool \= {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.WAR_PositionInputBlockHandler_dataEncoding = 000630060001	TRANSLATOR: The {0} data encoding overrides the {1} specified encoding

Document Extraction System Log Messages

The following system log messages are used for document extraction:

Message Code	Log Message
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_str1 = 000610050001	Document Extraction Service - New Behavior = saving array list into content.
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_DocExtraction1 = 000610050002	Document Extraction Service - Parser exception:{0}

Message Code	Log Message
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_DocExtraction2 = 000610050003	Document Extraction Service - Handler or parser-initialization exception:{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_DocExtraction3 = 000610050004	Document Extraction Service - Parser with specified options can't be built:{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_DocExtraction4 = 000610050005	Document Extraction Service - IO error while splitting compound XML document:{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_str2 = 000610050006	Document Extraction Service - No XML subdocuments found
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_exception1 = 000610050007	Document Extraction Service - Error writing unrecognized data
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_exception2 = 000610050008	{0} : {1}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_exception3 = 000610050009	Document Extraction Service - Error enveloping document
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_exception4 = 000610050010	Document Extraction Service - Error enveloping documents
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_exception5 = 000610050011	Document Extraction Service - IOException occurred
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_exception6 = 000610050012	Document Extraction Service - SQLException occurred
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_DocumentExtractionService_MapList = 000610050013	DocumentExtractionService.getMapList():{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception1 = 000610050014	XML Document Extraction Handler - SQLException occurred: Initialize()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception2 = 000610050015	XML Document Extraction Handler - Unrecognized encoding in XML Declaration: {0} defaulting to UTF-8
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception3 = 000610050016	XML Document Extraction Handler - IOException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception4 = 000610050017	XML Document Extraction Handler - SQLException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception5 = 000610050018	XML Document Extraction Handler - IOException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception6 = 000610050019	XML Document Extraction Handler - IOException occurred: startElement()

Message Code	Log Message
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception7 = 000610050020	XML Document Extraction Handler - IOException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception8 = 000610050021	XML Document Extraction Handler - IOException occurred: characters()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception9 = 000610050022	XML Document Extraction Handler - IOException occurred: endElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception10 = 000610050023	XML Document Extraction Handler - IOException occurred: endElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception11 = 000610050024	XML Document Extraction Handler - IOException occurred: comment()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception12 = 000610050025	XML Document Extraction Handler - IOException occurred: startCDATA()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception13 = 000610050026	XML Document Extraction Handler - IOException occurred: endCDATA()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.DEB_DocumentExtractionService_LargeFile = 000620050001	Document Extraction Service - translation large file support enabled \={0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.DEB_DocumentExtractionService_str1 = 000620050002	DocumentExtractService: Save unrecognized document into PD
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.DEB_DocumentExtractionService_WFContent = 000620050003	Set WFContent Document Extraction Service - total\={0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str1 = 000630050001	[DocumentExtractionService] DocExtractMapList parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str2 = 000630050002	[DocumentExtractionService] XMLEDIEnvelopeStandard parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str3 = 000630050003	[DocumentExtractionService] XMLSenderIDPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str4 = 000630050004	[DocumentExtractionService] XMLSenderIDQualifierPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str5 = 000630050005	[DocumentExtractionService] XMLReceiverIDPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str6 = 000630050006	[DocumentExtractionService] XMLReceiverIDQualifierPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str7 = 000630050007	[DocumentExtractionService] XMLAcceptorLookupAliasPath parameter ignored

Message Code	Log Message
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_ DocumentExtractionService_str8 = 000630050008	[DocumentExtractionService] XMLEDIEnvelopeStandard parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_ DocumentExtractionService_str9 = 000630050009	[DocumentExtractionService] XMLRootTag parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_ DocumentExtractionService_str10 = 000630050010	[DocumentExtractionService] XMLSenderIDPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_ DocumentExtractionService_str11 = 000630050011	[DocumentExtractionService] XMLReceiverIDPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_ DocumentExtractionService_str12 = 000630050012	[DocumentExtractionService] XMLAcceptorLookupAliasPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_ DocumentExtractionService_str13 = 000630050013	[DocumentExtractionService] XMLEDIEnvelopeStandard parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_ DocumentExtractionService_str14 = 000630050014	[DocumentExtractionService] Empty substring in path string

EDI Control Report System Log Messages

The following system log messages are used for the EDI Control Report:

Message Code	Log Message
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception1 = 000510120001	Exception creating EDIFACT CONTRL report
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception2 = 000510120002	IO Exception creating EDIFACT CONTRL report
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception3 = 000510120003	Exception attempting to close output stream in EDIFACTCONTRL report
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception4 = 000510120004	EDI.EDI_EDICONTRLREPORT.ERR_ EDICONTRLReport_exception4 = Exception in GenerateCONTRL
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception5 = 000510120005	EDI.EDI_EDICONTRLREPORT.ERR_ EDICONTRLReport_exception5 = Exception in GenerateCONTRL
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception6 = 000510120006	EDI.EDI_EDICONTRLREPORT.ERR_ EDICONTRLReport_exception6 = Exception in GenerateCONTRL

Message Code	Log Message
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception7 = 000510120007	EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception7 = Exception in GenerateCONTRL
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception8 = 000510120008	EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception8 = Exception in GenerateCONTRL
EDI.EDI_EDICONTRLREPORT.ERR_GenerateCONTRLServicImpl_str1 = 000510120009	EDI.EDI_EDICONTRLREPORT.ERR_GenerateCONTRLServicImpl_str1 = GenerateCONTRL processData() A SQL Exception occurred while retrieving the document extension.
EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception9 = 000510120010	EDI.EDI_EDICONTRLREPORT.ERR_EDICONTRLReport_exception9 = Exception in GenerateCONTRL
EDI.EDI_EDICONTRLREPORT.DEB_GenerateCONTRLServicImpl_start = 000520120001	EDI.EDI_EDICONTRLREPORT.DEB_GenerateCONTRLServicImpl_start = GenerateCONTRL processData() starting...
EDI.EDI_EDICONTRLREPORT.DEB_GenerateCONTRLServicImpl_end = 000520120002	EDI.EDI_EDICONTRLREPORT.DEB_GenerateCONTRLServicImpl_end = GenerateCONTRL processData() ending...

EDIFACT Deenvolving System Log Messages

The following system log messages are used for EDIFACT deenvolving:

Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvolveEDIFACTServicImpl_start = 000520040001	DeenvolveEDIFACTServicImpl processData() starting...
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvolveEDIFACTServicImpl_end = 000520040002	DeenvolveEDIFACTServicImpl processData() ending...
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvolveEDIFACTServicImpl_translationLargeFileSupportEnabled = 000520040003	DeenvolveEdifactServicImpl - translation large file support enabled \={0}
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvolveEDIFACTServicImpl_str1 = 000520040004	Security Header Segment Missing.
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvolveEDIFACTServicImpl_str2 = 000520040005	Security Trailer Segment is null

Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeveloppeEDIFACTServiceImpl_str3 = 000520040006	Security Trailer Segment Missing.
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeveloppeEDIFACTServiceImpl_str4 = 000520040007	Non-repudiation of origin succeeded
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeveloppeEDIFACTServiceImpl_str5 = 000520040008	Non-repudiation of origin verification failed.
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeveloppeEDIFACTServiceImpl_str6 = 000520040009	Non-repudiation of origin verification failed because digital signature data is missing.
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeveloppeEDIFACTServiceImpl_ExceptionFindingContract = 000520040010	[DeveloppeEDIFACTServiceImpl] Exception finding contract {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception1 = 000510040001	EDIFACTServiceImpl_Exception while deenvolving UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception2 = 000510040002	DeveloppeEDIFACTServiceImpl - Error saving interchange correlations
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception3 = 000510040003	DeveloppeEDIFACTServiceImpl - Error saving group correlations
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception4 = 000510040004	DeveloppeEDIFACTServiceImpl - Error enveloping CONTRL
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception5 = 000510040005	DeveloppeEDIFACT - Error EDI encoding CONTRL document for interchange control no. {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception6 = 000510040006	DeveloppeEDIFACT - Error creating CONTRL document for interchange control no. {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception7 = 000510040007	EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception7 = DeveloppeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception8 = 000510040008	DeveloppeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception9 = 000510040009	DeveloppeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception10 = 000510040010	EDIFACT Developpe Service - error parsing interchange to find first message type for CONTRL envelope acceptor lookup alias generation
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeveloppeEDIFACTServiceImpl_exception11 = 000510040011	EDIFACT Developpe Service - error parsing interchange to find first message type for CONTRL envelope acceptor lookup alias generation

Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception12 = 000510040012	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception13 = 000510040013	DeenvelopeEDIFACTServiceImpl - Error saving transaction correlation
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception14 = 000510040014	DeenvelopeEDIFACTServiceImpl - Error enveloping CONTRL
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception15 = 000510040015	DeenvelopeEDIFACT - Error EDI encoding CONTRL document for interchange control no. {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception16 = 000510040016	DeenvelopeEDIFACT - Error creating CONTRL document for interchange control no. {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception17 = 000510040017	DeenvelopeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception18 = 000510040018	DeenvelopeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception19 = 000510040019	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception20 = 000510040020	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception21 = 000510040021	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception22 = 000510040022	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception23 = 000510040023	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception24 = 000510040024	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception25 = 000510040025	Exception while de-enveloping GS/GE
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception26 = 000510040026	Exception while de-enveloping GS/GE
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception27 = 000510040027	Exception while de-enveloping GS/GE
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception28 = 000510040028	Exception while removing GS/GE envelope

Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception29 = 000510040029	Exception while removing GS/GE envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception30 = 000510040030	Exception while removing GS/GE envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception31 = 000510040031	Exception while removing GS/GE envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception32 = 000510040032	Exception while looking up a contract
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception33 = 000510040033	Exception attempting to close output stream in DeenvelopeEDIFACTServiceImpl
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception34 = 000510040034	Exception attempting to close output stream in DeenvelopeEDIFACTServiceImpl
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception35 = 000510040035	Exception while de-enveloping UNH/UNT
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception36 = 000510040036	Exception while de-enveloping UNH/UNT
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception37 = 000510040037	Exception while de-enveloping UNH/UNT
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception38 = 000510040038	Exception while removing UNH/UNT envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception39 = 000510040039	Exception while removing UNH/UNT envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception40 = 000510040040	Exception while removing UNH/UNT envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_str1 = 000510040041	Unable to match UNB/UNZ Envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_str2 = 000510040042	Unable to match UNB/UNZ Envelope, lookup returned multiple envelopes
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_str3 = 000510040043	Unable to match UNG/UNE Envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_str4 = 000510040044	Unable to match UNG/UNE Envelope, lookup returned multiple envelopes
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception41 = 000510040045	DeenvelopeEDIFACTServiceImpl - Error loading BP

Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.ERR_DevelopeEDIFACTServiceImpl_exception42 = 000510040046	[DevelopeEDIFACTServiceImpl] Exception finding contract
EDI.EDI_EDIFACTDEENVELOPING.ERR_DevelopeEDIFACTServiceImpl_str5 = 000510040047	Unable to match UNH/UNT Envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DevelopeEDIFACTServiceImpl_str6 = 000510040048	Unable to match UNH/UNT Envelope, lookup returned multiple envelopes
EDI.EDI_EDIFACTDEENVELOPING.ERR_DevelopeEDIFACTServiceImpl_exception43 = 000510040049	DevelopeEDIFACTServiceImpl - Error setting up deferred sequence/duplicate control number checking
EDI.EDI_EDIFACTDEENVELOPING.ERR_DevelopeEDIFACTServiceImpl_exception44 = 000510040050	DevelopeEDIFACTServiceImpl - Error saving transaction correlations
EDI.EDI_EDIFACTDEENVELOPING.ERR_DevelopeEDIFACTServiceImpl_exception45 = 000510040051	[DevelopeEDIFACTServiceImpl] Error in Correlation
EDI.EDI_EDIFACTDEENVELOPING.ERR_DevelopeEDIFACTServiceImpl_exception46 = 000510040052	[DevelopeEDIFACTServiceImpl] Error in Correlation

EDIFACT Enveloping System Log Messages

The following system log messages are used for EDIFACT enveloping:

Message Code	Log Message
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACTServiceImpl_start = 000520030001	EnvelopeEDIFACT.envelope() starting...
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACTServiceImpl_end = 000520030002	EnvelopeEDIFACT.envelope() ending...
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACTServiceImpl_UnhControlNumber = 000520030003	Loading unh control number for {0}
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACTServiceImpl_TranslationLargeFileSupportEnabled = 000520030004	EnvelopeEDIFACT.envelope() translation large file support enabled \={0}
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACTServiceImpl_unhControlNumber = 000520030005	Loading unh control number for
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACTServiceImpl_ExceptionFindingContract1 = 000520030006	EnvelopeEDIFACT.lookupUNHContract(): Exception finding contract {0}
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACTServiceImpl_ExceptionFindingContract2 = 000520030007	EnvelopeEDIFACT.lookupUNHContract(): Exception finding contract {0}

Message Code	Log Message
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception1 = 000510030001	Exception in EnvelopeEDIFACTServiceImpl
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception2 = 000510030002	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_str1 = 000510030003	Document has not been processed by the EDI Encoder service
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception3 = 000510030004	Exception while looking up a contract
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception4 = 000510030005	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception5 = 000510030006	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception6 = 000510030007	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception7 = 000510030008	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception8 = 000510030009	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception9 = 000510030010	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception10 = 000510030011	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception11 = 000510030012	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception12 = 000510030013	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception13 = 000510030014	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception14 = 000510030015	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_info = 000510030016	{0}
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception15 = 000510030017	Exception attempting to close output or input streams in EnvelopeEDIFACT .envelope()

Message Code	Log Message
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception16 = 000510030018	EDIFACTEnvelopeServiceImpl - Error loading control number
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception17 = 000510030019	EDIFACTEnvelopeServiceImpl - Error loading control number
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception18 = 000510030020	EDIFACTEnvelopeServiceImpl - Error loading control number
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception19 = 000510030021	Exception in EDIFACTSecurity.buildNonRepudiationOfOrigin()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception20 = 000510030022	Exception in EDIFACTSecurity.buildNonRepudiationOfOrigin()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_str2 = 000510030023	EnvelopeEDIFACT.createOutboundInterchange(): No transaction count available
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception21 = 000510030024	[EDIFACT Envelope Service] Error saving correlations.
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception22 = 000510030025	Exception attempting to close output or input streams in EnvelopeEDIFACT .createOutboundInterchange()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception23 = 000510030026	EnvelopeEDIFACTServiceImpl - Exception loading outbound envelope values from correlations
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_ControlNumberNames1 = 000510030027	EnvelopeEDIFACTServiceImpl - Error generating control number names -{0}
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_ControlNumberNames2 = 000510030028	EnvelopeEDIFACTServiceImpl - Error generating control number names - {0}
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception24 = 000510030029	EnvelopeEDIFACTServiceImpl - Error loading WFD
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception25 = 000510030030	EnvelopeEDIFACT.loadUNBEnvelopeParms()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception26 = 000510030031	EnvelopeEDIFACTService] exception: Cannot update the requiresEnvelope correlation because the document cannot be found.

EDI Encoding System Log Messages

The following system log messages are used for EDI encoding:

Message Code	Log Message
EDI.EDI_ENCODING.ERR_EDIEncoder_str1 = 000510070001	Mandatory parameter <AcceptorLookupAlias> is missing.
EDI.EDI_ENCODING.ERR_EDIEncoder_str2 = 000510070002	Mandatory parameter <SenderID> is missing
EDI.EDI_ENCODING.ERR_EDIEncoder_str3 = 000510070003	Mandatory parameter <ReceiverID> is missing
EDI.EDI_ENCODING.ERR_EDIEncoder_str4 = 000510070004	EnvelopeGeneric.envelope() starting...
EDI.EDI_ENCODING.ERR_EDIEncoder_str5 = 000510070014	EDIEncoder: Couldn't find the envelope
EDI.EDI_ENCODING.ERR_EDIEncoder_str6 = 000510070015	EDIEncoder: Envelope lookup returned multiple envelopes
EDI.EDI_ENCODING.ERR_EDIEncoder_str7 = 000510070016	EDIEncoder: Ambiguous ISA/EDIFACT envelopes.
EDI.EDI_ENCODING.ERR_EDIEncoder_exception1 = 000510070005	Exception in EDIEncode
EDI.EDI_ENCODING.ERR_EDIEncoder_exception2 = 000510070006	Exception in EDIEncode
EDI.EDI_ENCODING.ERR_EDIEncoder_exception3 = 000510070007	Exception in EDIEncode
EDI.EDI_ENCODING.ERR_EDIEncoder_exception4 = 000510070008	Exception in EDIEncode
EDI.EDI_ENCODING.ERR_EDIEncoder_exception5 = 000510070009	EDIEncoder: Couldn't find the envelope
EDI.EDI_ENCODING.ERR_EDIEncoder_exception6 = 000510070010	EDIEncoder: Envelope lookup returned multiple envelopes
EDI.EDI_ENCODING.ERR_EDIEncoder_exception7 = 000510070011	EDIEncoder: Ambiguous ISA/EDIFACT envelopes.
EDI.EDI_ENCODING.ERR_EDIEncoderServiceImpl_exception1 = 000510070012	Error during EDI Encoding process
EDI.EDI_ENCODING.ERR_EDIEncoderServiceImpl_exception2 = 000510070013	Error during EDI Encoding process
EDI.EDI_ENCODING.DEB_EDIEncoder_AddingEnvelope1 = 000520070002	EDIEncoder adding envelope {0}
EDI.EDI_ENCODING.DEB_EDIEncoder_AddingEnvelope2 = 000520070003	EDIEncoder adding envelope {0}
EDI.EDI_ENCODING.DEB_EDIEncoder_str1 = 000520070004	EDIEncoder processData() ending...
EDI.EDI_ENCODING.DEB_EDIEncoderServiceImpl_str1 = 000520070005	EDI Encoder processData() starting...
EDI.EDI_ENCODING.DEB_EDIEncoderServiceImpl_str2 = 000520070006	EDIEncoder processData() ending...

EDI Enveloping System Log Messages

The following system log messages are used for EDI enveloping:

Message Code	Log Message
EDI.EDI_ENVELOPING.DEB_EDIEvelopeServiceImpl_start = 000520080001	[EDIEvelope] processData() starting...
EDI.EDI_ENVELOPING.DEB_EDIEvelopeServiceImpl_end = 000520080002	[EDIEvelope] processData() ending...
EDI.EDI_ENVELOPING.ERR_EDIEveloper_exception1 = 000510080001	EDIEvelopeService: bad workflow id {0}
EDI.EDI_ENVELOPING.ERR_EDIEveloper_str1 = 000510080002	No document to envelope
EDI.EDI_ENVELOPING.ERR_EDIEveloper_exception2 = 000510080003	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_ENVELOPING.ERR_EDIEveloper_str2 = 000510080004	Document has not been processed by the EDI Encoder service
EDI.EDI_ENVELOPING.ERR_EDIEveloper_exception3 = 000510080005	[EDIEvelope] Error in Correlation
EDI.EDI_ENVELOPING.ERR_EDIEveloper_NoEnvelopingProcessDefined = 000510080006	No enveloping process defined for {0}
EDI.EDI_ENVELOPING.ERR_EDIEveloper_NoWorkflowProcessDefined = 000510080007	[EDIEvelope] no workflow defined for {0}
EDI.EDI_ENVELOPING.ERR_EDIEveloper_InvalidParmForWFD_NAME = 000510080008	EDIEvelopeServiceEJBBean.processData() invalid parm for WFD_NAME {0} (no matching found)
EDI.EDI_ENVELOPING.ERR_EDIEveloper_exception3 = 000510080009	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_ENVELOPING.ERR_EDIEveloper_exception4 = 000510080010	[EDIEvelope] unable to load document, skipping {0}
EDI.EDI_ENVELOPING.ERR_EDIEveloper_exception5 = 000510080011	[EDIEvelope] unable to update RequiresEnvelope to " {0} for document'{1}'. This document will be picked up again by EDIDevelope Deferred
EDI.EDI_ENVELOPING.ERR_EDIEveloper_unableToUpdateRequiresEnvelope = 000510080012	[EDIEvelope] unable to update RequiresEnvelope to " {0} for document'{1}'. This document will be picked up again by EDIDevelope Deferred
EDI.EDI_ENVELOPING.ERR_EDIEveloper_str3 = 000510080013	No document to envelope
EDI.EDI_ENVELOPING.ERR_EDIEveloper_exception6 = 000510080014	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_ENVELOPING.ERR_EDIEveloper_str4 = 000510080015	Document has not been processed by the EDI Encoder service
EDI.EDI_ENVELOPING.ERR_EDIEveloper_noWorkflowDefined = 000510080016	[EDIEvelope] no workflow defined for {0}
EDI.EDI_ENVELOPING.ERR_EDIEveloper_invalidWFD_NAME = 000510080017	EDIEvelope.processDocuments() invalid parm for WFD_NAME {0} (no matching id found)

Message Code	Log Message
EDI.EDI_ENVELOPING.ERR_EDIEvelope_exception7 = 000510080018	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_ENVELOPING.ERR_EDIEvelopeServiceImpl_exception8 = 000510080019	[EDIEvelope] unable to get a JDBC connection
EDI.EDI_ENVELOPING.ERR_EDIEvelopeServiceImpl_exception9 = 000510080020	[EDIEvelope] encountered a SQL exception
EDI.EDI_ENVELOPING.ERR_EDIEvelopeServiceImpl_exception10 = 000510080021	[EDIEvelope] unable to start workflow
EDI.EDI_ENVELOPING.INFO_EDIEvelope_UpdatedRequiresEnvelope = 000540080001	Updated RequiresEnvelope to -100 for CORRELATION_ID \= {0} who se document (OBJECT_ID\= {1}) does not exist

EDI Post-processing System Log Messages

The following system log messages are used for EDI post-processing:

Message Code	Log Message
EDI.EDI_POSTPROCESSING.DEB_EDIPostProcessorServiceImpl_start = 000520090001	SequenceCheck processData() starting...
EDI.EDI_POSTPROCESSING.DEB_EDIPostProcessorServiceImpl_end = 000520090002	SequenceCheck processData() ending...
EDI.EDI_POSTPROCESSING.DEB_EDIPostProcessorServiceImpl_EDIPostProcessor1 = 000520090003	[EDIPostProcessor:{0}] Failed to load document with id '{1}'. SQLException: {2}
EDI.EDI_POSTPROCESSING.DEB_EDIPostProcessorServiceImpl_EDIPostProcessor2 = 000520090004	[EDIPostProcessor:{0}] Failed to load document with id '{1}'. DocumentNotFoundException: {2}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception1 = 000510090001	EDIPostProcessorServiceImpl - Error retrieving document with id " {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception2 = 000510090002	EDIPostProcessorServiceImpl - error removing interchange from sequence check queue.
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception3 = 000510090003	EDIPostProcessorServiceImpl - Error storing updated control number for envelope.
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception4 = 000510090004	EDIPostProcessorServiceImpl - Error storing updated control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception5 = 000510090005	EDIPostProcessorServiceImpl - An EDI error occurred

Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception6 = 000510090006	SequenceCheckService error
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception7 = 000510090007	EDIPostProcessorServiceImpl - Error creating 997.
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception8 = 000510090008	EDIPostProcessorServiceImpl - Error EDI encoding 997 document for group control no. {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception9 = 000510090009	EDI Post Processor - Error generating TA1
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception10 = 000510090010	EDI Post Processor - Error enveloping 997
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception11 = 000510090011	EDI Post Processor - Error generating TA1
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception12 = 000510090012	EDIPostProcessorServiceImpl - Error creating CONTRL.
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception13 = 000510090013	EDIPostProcessorServiceImpl - Error enveloping CONTRL message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception14 = 000510090014	EDIPostProcessorServiceImpl - Error EDI encoding CONTRL document for interchange control no.{0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception15 = 000510090015	EDI Post Processor Service - Error loading control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception16 = 000510090016	EDIPostProcessorServiceImpl - Error loading interchange control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception17 = 000510090017	EDIPostProcessorServiceImpl - Error loading Control Number History for
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception18 = 000510090018	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception19 = 000510090019	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception20 = 000510090020	EDIPostProcessorServiceImpl - TransactionRegisterException occurred while trying to save Control Number History for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception21 = 000510090021	EDIPostProcessorServiceImpl - SQLException occurred while trying to save Control Number History for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception22 = 000510090022	EDI Post Processor Service - Error loading control number

Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception23 = 000510090023	EDIPostProcessorServiceImpl - Error loading group control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception24 = 000510090024	EDIPostProcessorServiceImpl - SQLException while trying to load control number history for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception25 = 000510090025	EDIPostProcessorServiceImpl - TransactionRegisterException while trying to save control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception26 = 000510090026	[EDIPostProcessorService: {0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception27 = 000510090027	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception28 = 000510090028	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception29 = 000510090029	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception30 = 000510090030	EDI Post Processor Service - Error loading control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception31 = 000510090031	EDIPostProcessorServiceImpl - Error loading interchange control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception32 = 000510090032	EDIPostProcessorServiceImpl - Error loading control number history data for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception33 = 000510090033	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception34 = 000510090034	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception35 = 000510090035	EDIPostProcessorServiceImpl - TransactionRegisterException occurred while trying to save Control Number History for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception36 = 000510090036	EDIPostProcessorServiceImpl - SQLException occurred while trying to save Control Number History for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception37 = 000510090037	EDI Post Processor Service - Error loading control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception38 = 000510090038	EDIPostProcessorServiceImpl - Error loading group control number for envelope {0}

Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception39 = 000510090039	EDIPostProcessorServiceImpl - SQLException while trying to load control number history for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception40 = 000510090040	EDIPostProcessorServiceImpl - TransactionRegisterException while trying to save control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception41 = 000510090041	[EDIPostProcessorService: {0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception42 = 000510090042	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception43 = 000510090043	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception44 = 000510090044	EDI Post Processor Service - Error loading control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception45 = 000510090045	EDIPostProcessorServiceImpl - Error loading transaction control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception46 = 000510090046	EDIPostProcessorServiceImpl - Error loading control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception47 = 000510090047	Exception
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception48 = 000510090048	Exception
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception49 = 000510090049	EDIPostProcessorServiceImpl - TransactionRegisterException while adding control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception50 = 000510090050	EDIPostProcessorServiceImpl - SQLException while adding control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception51 = 000510090051	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception52 = 000510090052	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception53 = 000510090053	EDIPostProcessorServiceImpl - Error reconciling 997
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception54 = 000510090054	EDIPostProcessorServiceImpl - Error loading CONTRL to reconcile
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception55 = 000510090055	EDIPostProcessorServiceImpl - Error loading CONTRL to reconcile

Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception56 = 000510090056	[EDIPostProcessorService: {0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception57 = 000510090057	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception58 = 000510090058	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception59 = 000510090059	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception60 = 000510090060	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception61 = 000510090061	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception62 = 000510090062	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception63 = 000510090063	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception64 = 000510090064	EDIPostProcessorServiceImpl - Error reconciling 997
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception65 = 000510090065	EDIPostProcessorServiceImpl - Error retrieving transaction document with id {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception66 = 000510090066	EDIPostProcessorServiceImpl - Error retrieving transaction document with id {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception67 = 000510090067	EDIPostProcessorServiceImpl - Error loading control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception68 = 000510090068	EDIPostProcessorServiceImpl - TransactionRegisterException while adding control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception69 = 000510090069	EDIPostProcessorServiceImpl - Error retrieving transaction document with id {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception70 = 000510090070	EDIPostProcessorServiceImpl - Error retrieving transaction document with id {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception71 = 000510090071	EDIPostProcessorServiceImpl - IO error extracting non-compliant transaction from batch
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception72 = 000510090072	EDIPostProcessorServiceImpl - Error enveloping TA1

Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception73 = 000510090073	EDI Post Processor Service unable to create develope process to child process workflow linkage
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception74 = 000510090074	EDI Post Processor Service unable to start workflow
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_InterchangeComplianceReport = 000510090075	EDIPostProcessorServiceImpl - Error retrieving InterchangeCompliance Report for document {0}

EDI Report System Log Messages

The following system log messages are used for the EDI report:

Message Code	Log Message
EDI.EDI_REPORT.ERR_ReportEntry_exception1 = 000510170001	Exception
EDI.EDI_REPORT.ERR_CompilanceReport_exception2 = 000510170002	Exception
EDI.EDI_REPORT.ERR_EntryInfo_exception3 = 000510170003	Exception

Field Processor Translation System Log Messages

The following system log messages are used for field processor translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_FIELDPROCESSOR.ERR_PositionalInputFieldHandler_exception1 = 000610080001	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_FIELDPROCESSOR.ERR_PositionalInputFieldHandler_exception2 = 000610080002	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_FIELDPROCESSOR.ERR_PositionalInputFieldHandler_exception3 = 000610080003	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_FIELDPROCESSOR.ERR_SQLInputFieldHandler_exception1 = 000610080004	TRANSLATOR: SQL Exception while getting {0} from result of {1}
TRANSLATION.TRANSLATION_FIELDPROCESSOR.ERR_SWIFTInputFieldHandler_exception1 = 000610080005	TRANSLATOR: Error building
TRANSLATION.TRANSLATION_FIELDPROCESSOR.ERR_SWIFTInputFieldHandler_exception2 = 000610080006	TRANSLATOR: The field syntax is not valid. block data using encoding.The default encoding will be used.
TRANSLATION.TRANSLATION_FIELDPROCESSOR.ERR_SWIFTInputFieldHandler_exception3 = 000610080007	TRANSLATOR: Data conversion exception.

Message Code	Log Message
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTOutputFieldHandler_str1 = 000610080008	TRANSLATOR: SWIFTOutputFieldHandler handled ClassCastException for packed decimal processing.
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTOutputFieldHandler_exception1 = 000610080009	TRANSLATOR: Error building block data using encoding. The default encoding will be used.
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTOutputFieldHandler_exception2 = 000610080010	TRANSLATOR: Data conversion exception.

Generate 997 System Log Messages

The following system log messages are used when generating 997 acknowledgements:

Message Code	Log Message
EDI.EDI_GENERATE997.DEB_Generate997ServiceImpl_start = 000520110001	Generate997 processData() starting...
EDI.EDI_GENERATE997.DEB_Generate997ServiceImpl_end = 000520110002	Generate997 processData() ending..
EDI.EDI_GENERATE997.ERR_Generate997ServiceImpl_start = 000510110001	Generate997ServiceImpl.processData() A SQL Exception occurred while retrieving the document extension
EDI.EDI_GENERATE997.ERR_Generate997ServiceImpl_exception1 = 000510110002	Exception in Generate997ServiceImpl

Generate TA1 Acknowledgement System Log Messages

The following system log messages are used when generating TA1 acknowledgements:

Message Code	Log Message
EDI.EDI_GENERATETA1.DEB_GenerateTA1ServiceImpl_start = 000520130001	GenerateTA1 processData() starting...
EDI.EDI_GENERATETA1.DEB_GenerateTA1ServiceImpl_end = 000520130002	GenerateTA1 processData() ending...
EDI.EDI_GENERATETA1.ERR_TA1_InfoEntry = 000510130001	TA1: ComplianceReport contains unknown information entry: {0}
EDI.EDI_GENERATETA1.ERR_GenerateTA1ServiceImpl_str1 = 000510130002	GenerateTA1 processData() A SQL Exception occurred while retrieving the document extension
EDI.EDI_GENERATETA1.ERR_GenerateTA1ServiceImpl_exception1 = 000510130003	Caught exception in GenerateTA1ServiceEJBBean.processData():
EDI.EDI_GENERATETA1.ERR_GenerateTA1ServiceImpl_exception2 = 000510130004	Caught exception in GenerateTA1ServiceEJBBean.processData():

Generic Deenveloping System Log Messages

The following system log messages are used for generic deenveloping:

Message Code	Log Message
EDI.EDI_GENERICDEENVELOPING.DEB_DeenvelopeGenericServiceImpl_str1 = 000520060001	DeenvelopeGeneric processData() starting...
EDI.EDI_GENERICDEENVELOPING.DEB_DeenvelopeGenericServiceImpl_mapName = 000520060002	TranslationServiceEJBBean map_name is {0}
EDI.EDI_GENERICDEENVELOPING.DEB_DeenvelopeGenericServiceImpl_str2 = 000520060003	DevelopeGeneric processData() ending...
EDI.EDI_GENERICDEENVELOPING.DEB_DeenvelopeGenericServiceImpl_EntityID = 000520060004	Sender Entity ID: {0}, Receiver Entity ID: {1}
EDI.EDI_GENERICDEENVELOPING.DEB_DeenvelopeGenericServiceImpl_ExceptionFindingContract1 = 000520060005	[DeenvelopeGeneric] Exception finding contract {0}
EDI.EDI_GENERICDEENVELOPING.DEB_DeenvelopeGenericServiceImpl_ExceptionFindingContract2 = 000520060006	[DeenvelopeGeneric] Exception finding contract {0}
EDI.EDI_GENERICDEENVELOPING.ERR_eenvelopeGenericServiceImpl_exception1 = 000510060001	Exception while looking up a contract
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_str1 = 000510060002	Unable to find Envelope
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_DuplicateControlNumber = 000510060003	Duplicate Control Number encountered {0}
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_ControlNumberHistory = 000510060004	Error while adding control number history to database. {0}
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_ControlNumberOutOfSequence = 000510060005	Control Number Out of Sequence: expected {0}, received {1}
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception2 = 000510060006	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception3 = 000510060007	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception4 = 000510060008	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception5 = 000510060009	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception6 = 000510060010	Exception while de-enveloping

Message Code	Log Message
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception7 = 000510060011	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception8 = 000510060012	Exception while unlocking control number
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception9 = 000510060013	Exception while unlocking envelope
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_str2 = 000510060014	Unable to match Envelope
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_str3 = 000510060015	Unable to match Envelope, lookup returned multiple envelopes
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception10 = 000510060016	Exception
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception11 = 000510060017	Exception
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception12 = 000510060018	[DeenvelopeGenericServiceImpl] Exception finding contract
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception13 = 000510060019	[DeenvelopeGenericServiceImpl] loadEnvelopeParms
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception14 = 000510060020	SQL Error generating map name
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception15 = 000510060021	License error
EDI.EDI_GENERICDEENVELOPING.INFO_DeenvelopeGenericServiceImpl_MapObjectForMap = 000540060001	Unable to load MapObject for map: {0}

Generic Enveloping System Log Messages

The following system log messages are used for generic enveloping:

Message Code	Log Message
EDI.EDI_GENERICENVELOPING.DEB_EnvelopeGenericServiceImpl_str1 = 000520050001	EnvelopeGeneric.envelope() starting...
EDI.EDI_GENERICENVELOPING.DEB_EnvelopeGenericServiceImpl_str2 = 000520050002	EnvelopeGeneric.envelope() ending...
EDI.EDI_GENERICENVELOPING.DEB_EnvelopeGenericServiceImpl_str3 = 000520050003	EnvelopeGeneric.applyOuterEnvelope() starting...

Message Code	Log Message
EDI.EDI_GENERICENVELOPING.DEB_EnvelopeGenericServiceImpl_str4 = 000520050004	EnvelopeGeneric.applyOuterEnvelope() ending..
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_str1 = 000510050001	EnvelopeGenericServiceImpl.envelope(): A SQL Exception occurred while retrieving the document extension.
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_str2 = 000510050002	Document has not been processed by the EDI Encoder service
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_str3 = 000510050013	Generic Envelope Service: Error during enveloping or pre-envelope translation.
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception1 = 000510050003	EnvelopeGeneric.envelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception2 = 000510050004	EnvelopeGeneric.envelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception3 = 000510050005	EnvelopeGeneric.envelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception4 = 000510050006	Exception while looking up a contract
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception5 = 000510050007	EnvelopeGenericServiceImpl.envelope() A SQL Exception occurred while retrieving the document extension
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception6 = 000510050008	EnvelopeGenericServiceImpl.envelope() A SQL Exception occurred while retrieving the document extension
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception7 = 000510050009	Exception while looking up a contract
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception8 = 000510050010	EnvelopeGeneric.applyOuterEnvelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception9 = 000510050011	EnvelopeGeneric.applyOuterEnvelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception10 = 000510050012	EnvelopeGeneric.applyOuterEnvelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception11 = 000510050014	Exception while enveloping document
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception12 = 000510050015	Exception while enveloping document
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception13 = 000510050016	EnvelopeGeneric.envelope() encountered exception

Message Code	Log Message
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception14 = 000510050017	EnvelopeGenericServiceImpl.envelope() encountered a License error
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_invalidWorkflowName = 000510050018	EnvelopeGenericServiceImpl.spawnBusProcess(): invalid workflow name {0} (no matching id found)
EDI.EDI_GENERICENVELOPING.INFO_EnvelopeGenericServiceImpl_type = 000540050001	***** type \= {0}
EDI.EDI_GENERICENVELOPING.INFO_EnvelopeGenericServiceImpl_standard = 000540050002	***** type \= {0}

JDBC Translation System Log Messages

The following system log messages are used for JDBC translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_exception1 = 000610020001	Required 'map_name' parameter not found
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_str1 = 000610020002	Unable to load MapObject for map: {0}
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_str2 = 000610020003	Unable to load TranslationObject for map: {0}
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_MapObject = 000610020004	{0} is not a valid SQL map file
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_TranslationObject = 000610020005	Exception trying to start business process:{0}
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_SQLmap = 000610020006	Caught TranslationException in processData():
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_exception2 = 000610020007	Caught exception in processData():
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_exception3 = 000610020008	JDBC query returns no data
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_exception4 = 000610020009	There are more rows remaining in the ResultSet of the SQL query
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_str3 = 000610020010	Exception
TRANSLATION.TRANSLATION_JDBC.WAR_JdbcAdapaterImpl_str1 = 000630020001	Exception

Message Code	Log Message
TRANSLATION.TRANSLATION_JDBC.ERR_JDBCService_exception1 = 000610020011	Exception
TRANSLATION.TRANSLATION_JDBC.ERR_JDBCService_exception2 = 000610020012	Exception

Overdue Acknowledgement System Log Messages

The following system log messages are used for overdue acknowledgements:

Message Code	Log Message
EDI.EDI_OVERDUEACK.DEB_OverdueAckServiceImpl_start = 000520140001	OverdueAck] processData() starting...
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception1 = 000510140001	[OverdueAck] exception finding overdue ack documents
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception2 = 000510140002	OverdueAck] exception finding overdue ack documents
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception3 = 000510140003	[OverdueAck] exception
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception4 = 000510140004	[OverdueAck] Unable to load document
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_FindingQuery = 000510140005	Error finding named query {0} in db pool {1}
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception5 = 000510140006	[OverdueAckServiceImpl] Error in Correlation
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception6 = 000510140007	[OverdueAckServiceImpl] Error in Correlation
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_str1 = 000510140008	OverdueAck setOverdueAckByDocState() A SQL Exception occurred while retrieving the document extension.
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception7 = 000510140009	Caught exception

Reconcile 997 Acknowledgement System Log Messages

The following system log messages are used for ASC X12 997 acknowledgement reconciliation:

Message Code	Log Message
EDI.EDI_RECONCILE997.DEB_Reconcile997_str1 = 000520150001	[Reconcile997] Processing 997
EDI.EDI_RECONCILE997.DEB_Reconcile997_str2 = 000520150002	[Reconcile997] Reconciling group
EDI.EDI_RECONCILE997.DEB_Reconcile997_str3 = 000520150003	[Reconcile997] Reconciling transaction set
EDI.EDI_RECONCILE997.DEB_Reconcile997_ackstatus = 000520150004	[Reconcile997] Updated ackstatus of document {0}
EDI.EDI_RECONCILE997.DEB_Reconcile997ServiceImpl_start = 000520150005	[Reconcile997] processData() starting...
EDI.EDI_RECONCILE997.DEB_Reconcile997ServiceImpl_end = 000520150006	[Reconcile997] processData() ending...
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception1 = 000510150001	Reconcile997 - Exception while reconciling 997
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception2 = 000510150002	Reconcile997 - SQL Exception while reconciling 997
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception3 = 000510150003	Reconcile997 IOException while trying to close streams
EDI.EDI_RECONCILE997.ERR_Reconcile997_str1 = 000510150004	[Reconcile997] Could not find AK1
EDI.EDI_RECONCILE997.ERR_Reconcile997_str2 = 000510150005	[Reconcile997] Could not find AK9
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception4 = 000510150006	[Reconcile997] Exception while reconciling group
EDI.EDI_RECONCILE997.ERR_Reconcile997_str3 = 000510150007	Reconcile997.updateGroupDocState(...) A SQL Exception occurred while retrieving the document extension.
EDI.EDI_RECONCILE997.ERR_Reconcile997_GroupDetails = 000510150008	[Reconcile997] Unable to reconcile 997 group details {0}
EDI.EDI_RECONCILE997.ERR_Reconcile997_str4 = 000510150009	[Reconcile997] Unable to reconcile 997 group details
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception6 = 000510150010	[Reconcile997] Unable to load document
EDI.EDI_RECONCILE997.ERR_Reconcile997ServiceImpl_exception6 = 000510150011	[Reconcile997] Exception while reconciling 997
EDI.EDI_RECONCILE997.WAR_Reconcile997_MutipleDocuments = 000530150001	[Reconcile997] Multiple documents found when one expected for {0}
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception5 = 000510150012	[Reconcile997] Error in Correlation

Reconcile CONTRL Acknowledgement System Log Messages

The following system log messages are used for EDIFACT CONTRL acknowledgement reconciliation:

Message Code	Log Message
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str1 = 000520160001	ReconcileCONTRL] Processing CONTRL
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str2 = 000520160002	ReconcileCONTRLSERVICEEJBBean Processing UCI
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str3 = 000520160003	ReconcileCONTRLSERVICEEJBBean Reconciling UCI
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str4 = 000520160004	[ReconcileCONTRL] Reconciling group
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str5 = 000520160005	[ReconcileCONTRL] Reconciling message
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_ackstatus = 000520160006	ReconcileCONTRL Updated ackstatus of document
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_ackstatus2 = 000520160007	[ReconcileCONTRL] Updated ackstatus of document
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROLServiceImpl_start = 000520160008	[ReconcileCONTRL] processData() starting...
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROLServiceImpl_end = 000520160009	[ReconcileCONTRL] processData() ending...
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception1 = 000510160001	[ReconcileCONTRL] Exception while reconciling CONTRL
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception2 = 000510160002	[ReconcileCONTRL] SQL Exception while reconciling CONTRL
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception3 = 000510160003	[ReconcileCONTRL] IOException while trying to close streams
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_CONTRLmessage = 000510160004	[ReconcileCONTRL] Unrecognized segment in CONTRL message:
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_str1 = 000510160005	[ReconcileCONTRL] Could not find UCI
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception4 = 000510160006	[ReconcileCONTRL] Exception while reconciling interchange
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception5 = 000510160007	[ReconcileCONTRL] Exception while reconciling group
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception6 = 000510160008	[ReconcileCONTRL] Error updating correlation
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception7 = 000510160009	[ReconcileCONTRL] Error updating correlation

Message Code	Log Message
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_str2 = 000510160010	ReconcileCONTRLupdateInterchangeDocState(...) A SQL Exception occurred
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_UCI1 = 000510160011	[ReconcileCONTRL] Unable to reconcile UCI {0}
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_UCI2 = 000510160012	[ReconcileCONTRL] Unable to reconcile UCI {0}
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception8 = 000510160013	ReconcileTA1ServiceEJBBean Unable to load document
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_str3 = 000510160014	ReconcileCONTRLupdateGroupDocState(...) A SQL Exception occurred
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception9 = 000510160015	ReconcileTA1ServiceEJBBean Unable to load document
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_CONTRLgroupDetails1 = 000520160016	[ReconcileCONTRL] Unable to reconcile CONTRL group details {0}
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_CONTRLgroupDetails2 = 000520160017	[ReconcileCONTRL] Unable to reconcile CONTRL group
EDI.EDI_RECONCILECONTROL.WAR_ReconcileCONTROL_MultipleDocuments1 = 000530160001	[ReconcileCONTRL] Multiple documents found when one expected for {0}
EDI.EDI_RECONCILECONTROL.WAR_ReconcileCONTROL_MultipleDocuments2 = 000530160002	[ReconcileCONTRL] Multiple documents found when one expected for {0}

Report Translation System Log Messages

The following system log message is used for report translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_REPORT.ERR_TranslationReport_exception1 = 000610090001	[Translator] Exception parsing translation report entry limit property

Standards Translation System Log Messages

The following system log messages are used for standards translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_STANDARD.DEB_TranslationServiceImpl_str1 = 000620010001	[TranslationServiceImpl] processData() starting...

Message Code	Log Message
TRANSLATION.TRANSLATION_STANDARD.DEB_TranslationServiceImpl_str2 = 000620010002	[TranslationServiceImpl] map_name is {0}
TRANSLATION.TRANSLATION_STANDARD.DEB_TranslationServiceImpl_largeFileSupport = 000620010003	[TranslationServiceImpl] large file support \= {0}
TRANSLATION.TRANSLATION_STANDARD.DEB_TranslationServiceImpl_TranslationReport = 000620010004	Translation Report: {0} {1}
TRANSLATION.TRANSLATION_STANDARD.DEB_TranslationServiceImpl_str3 = 000620010005	[TranslationServiceImpl] processData() completed ...
TRANSLATION.TRANSLATION_STANDARD.ERR_TranslationServiceImpl_exception1 = 000610010001	{0} {1} is not valid
TRANSLATION.TRANSLATION_STANDARD.ERR_TranslationServiceImpl_SOAPAttachment=000610010002	Caught exception while attempting to load map \ SOAPAttachment1\ for MapTest in TranslationServiceImpl::processData:
TRANSLATION.TRANSLATION_STANDARD.ERR_TranslationServiceImpl_exception2 = 000610010003	[TranslationService] Tracking error. It will be ignored
TRANSLATION.TRANSLATION_STANDARD.ERR_TranslationServiceImpl_exception3 = 000610010004	Caught exception in TranslationServiceEJBBean.processData():
TRANSLATION.TRANSLATION_STANDARD.ERR_TranslationServiceImpl_exception4 = 000610010005	Caught exception in TranslationServiceEJBBean.processData():
TRANSLATION.TRANSLATION_STANDARD.ERR_TranslationServiceImpl_exception5 = 000610010006	Caught exception in TranslationServiceEJBBean.processData():
TRANSLATION.TRANSLATION_STANDARD.ERR_TranslationServiceImpl_exception6 = 000610010007	Caught exception closing input stream
TRANSLATION.TRANSLATION_STANDARD.ERR_TranslationServiceImpl_exception7 = 000610010008	Caught exception closing output stream
TRANSLATION.TRANSLATION_STANDARD.LOG_TranslationServiceImpl_str1 = 000640010001	Unable to load \"SOAPAttachment\" for MapTest.
TRANSLATION.TRANSLATION_STANDARD.LOG_TranslationServiceImpl_MapObject = 000640010002	Unable to load MapObject for map:{0}
TRANSLATION.TRANSLATION_STANDARD.LOG_TranslationServiceImpl_str2 = 000640010003	There is no Primary Document

TA1 Acknowledgement Reconciliation System Log Messages

The following system log messages are used for TA1 acknowledgement reconciliation:

Message Code	Log Message
EDI.EDI_TA1RECONCILER.DEB_ReconcileTA1ServiceImpl_start = 000520100001	ReconcileTA1ServiceImpl processData() starting...
EDI.EDI_TA1RECONCILER.DEB_ReconcileTA1ServiceImpl_str1 = 000520100002	ReconcileTA1ServiceImpl No TA1s to reconcile
EDI.EDI_TA1RECONCILER.DEB_ReconcileTA1ServiceImpl_str2 = 000520100003	ReconcileTA1ServiceImpl Found TA1 document to reconcile
EDI.EDI_TA1RECONCILER.DEB_ReconcileTA1ServiceImpl_end = 000520100004	ReconcileTA1ServiceImpl processData() ending...
EDI.EDI_TA1RECONCILER.DEB_TA1Reconciler_str3 = 000520100005	TA1Reconciler Found TA1 document to reconcile
EDI.EDI_TA1RECONCILER.DEB_TA1Reconciler_str4 = 000520100006	ReconcileTA1ServiceImpl Processing TA1
EDI.EDI_TA1RECONCILER.DEB_TA1Reconciler_str5 = 000520100007	ReconcileTA1ServiceImpl Reconciling TA1
EDI.EDI_TA1RECONCILER.DEB_TA1Reconciler_AckstatusOfDocument = 000510100008	ReconcileTA1 Updated ackstatus of document {}
EDI.EDI_TA1RECONCILER.ERR_ReconcileTA1ServiceImpl_exception1 = 000510100001	Exception
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler_exception2 = 000510100002	ReconcileTA1ServiceEJBBean Exception while reconciling TA1s
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler_exception3 = 000510100003	ReconcileTA1ServiceEJBBean Exception while reconciling TA1s
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler_exception4 = 000510100004	[TA1Reconciler] Error in Correlation
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler_str1 = 000510100005	TA1Reconciler.updateInterchangeDocState(...) A SQL Exception occurred while retrieving the document extension.
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler_str2 = 000510100006	ReconcileTA1ServiceEJBBean Unable to reconcile TA1 {}
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler_str3 = 000510100007	ReconcileTA1ServiceEJBBean Unable to reconcile TA1 {}
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler_exception5 = 000510100008	ReconcileTA1ServiceEJBBean Unable to load document
EDI.EDI_TA1RECONCILER.WAR_TA1Reconciler_str1 = 000530100001	[ReconcileTA1] Multiple documents found when one expected for

Translation Engine System Log Messages

The following system log messages are used for the translation rules:

Message Code	Log Message
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngine_LargeFile = 000620070001	translation large file support threshold \={0}
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngine_str1 = 000720060002	translation large file support threshold not present in properties, setting to 1
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngine_fileSize = 000620070003	input file size \={0}
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngine_duration = 000620070004	execution time \={0} seconds
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngine_duration2 = 000620070005	execution time \={0} seconds
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_map = 000620070017	Translating using map {0} ...
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_str1 = 000620070006	Translation complete
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_str2 = 000620070007	Reading input...
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_str3 = 000620070008	Writing output...
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_ExecutionTime = 000620070009	finished input translation phase - execution time {0} seconds
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_NumberEntries = 000620070010	number entries paged in \={0}
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_NumberEntries2 = 000620070011	number entries paged out \={0}
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_NumberSort = 000720060012	number sorts \=0
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_executionTime2 = 000620070013	finished output translation phase - execution time {0} seconds
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_numberEntries2 = 000620070014	number entries paged in \={0}
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_numberEntries3 = 000620070015	number entries paged out \={0}
TRANSLATION.TRANSLATION_ENGINE.DEB_TranslationEngineImpl_numberSorts2 = 000620070016	number sorts \={0}

Translation Object System Log Messages

The following system log messages are used for translation objects:

Message Code	Log Message
TRANSLATION.TRANSLATION_TRANSLATIONOBJECT.ERR_Constants_exception1 = 000610120001	Translator: access to invalid constant
TRANSLATION.TRANSLATION_TRANSLATIONOBJECT.ERR_SyntaxManager_className = 000610120002	TRANSLATOR: invalid syntax factory {0}
TRANSLATION.TRANSLATION_TRANSLATIONOBJECT.ERR_SyntaxManager_exception1 = 000610120003	TRANSLATOR: error loading syntax factory {0}
TRANSLATION.TRANSLATION_TRANSLATIONOBJECT.DEB_TranslationObject_str1 = 000620120001	TranslationObject.initialize(String) is now deprecated, you may remove this call

Translation Rules System Log Messages

The following system log messages are used for the translation rules:

Message Code	Log Message
TRANSLATION.TRANSLATION_RULES.ERR_BasicOpcodes_exception1 = 000610100001	TRANSLATOR: missing opcode implementation
TRANSLATION.TRANSLATION_RULES.ERR_BasicOpcodes_exception2 = 000610100002	TRANSLATOR: SLEEP opcode interrupted
TRANSLATION.TRANSLATION_RULES.ERR_BasicOpcodes_exception3 = 000610100003	TRANSLATOR: SLEEP opcode interrupted
TRANSLATION.TRANSLATION_RULES.ERR_DBOpcodes_exception1 = 000610100004	TRANSLATOR: SLEEP opcode interrupted
TRANSLATION.TRANSLATION_RULES.ERR_dateOpcodes_exception1 = 000610100005	TRANSLATOR: missing opcode implementation
TRANSLATION.TRANSLATION_RULES.ERR_ExtendedRuleExecuter_str1 = 000610100006	Translator extended rule InvocationTargetException - see appserver log for stack trace
TRANSLATION.TRANSLATION_RULES.ERR_ExtendedRuleExecuter_exception1 = 000610100007	Translator extended rule IllegalAccessException
TRANSLATION.TRANSLATION_RULES.ERR_ExtendedRuleExecuter_NoMethod = 000610100008	Translator extended rule NoSuchMethodError {0}
TRANSLATION.TRANSLATION_RULES.ERR_ExtendedRuleExecuter_exception2 = 000610100009	Translator extended rule NullPointerException

Message Code	Log Message
TRANSLATION.TRANSLATION_RULES.ERR_IOpcodes_exception1 = 000610100010	TRANSLATOR: missing opcode implementation
TRANSLATION.TRANSLATION_RULES.ERR_IOpcodes_exception2 = 000610100011	TRANSLATION.TRANSLATION_RULES.ERR_IOpcodes_exception2 = TRANSLATOR: attempt to READBLOCK on non-stream syntax
TRANSLATION.TRANSLATION_RULES.ERR_IOpcodes_exception3 = 000610100012	TRANSLATOR: attempt to WRITEBLOCK on non-stream syntax
TRANSLATION.TRANSLATION_RULES.ERR_StandardRuleLoopCount_exception1 = 000610100013	TRANSLATOR: unable to get loop count on field {0}
TRANSLATION.TRANSLATION_RULES.ERR_StandardRuleSelect_str1 = 000610100014	[StandardRuleSelect] undefined failure
TRANSLATION.TRANSLATION_RULES.ERR_StringOpcodes_exception1 = 000610100015	TRANSLATOR: missing opcode implementation
TRANSLATION.TRANSLATION_RULES.ERR_TransactionRegister_exception1 = 000610100016	Caught exception while trying to add Transaction Register to the transaction register table
TRANSLATION.TRANSLATION_RULES.ERR_TransactionRegister_exception2 = 000610100017	Caught exception while trying to add Transaction Register to the transaction register table
TRANSLATION.TRANSLATION_RULES.ERR_TransactionRegister_exception3 = 000610100018	Caught exception while trying to add Transaction Register to the transaction register table
TRANSLATION.TRANSLATION_RULES.ERR_TransactionRegister_exception4 = 000610100019	TransactionRegister: SQL Exception Encountered
TRANSLATION.TRANSLATION_RULES.ERR_TransactionRegister_exception5 = 000610100020	Caught exception freeing JDBC resources
TRANSLATION.TRANSLATION_RULES.ERR_TransactionRegister_exception6 = 000610100021	Caught exception while trying to get Transaction Registers from the transaction register table
TRANSLATION.TRANSLATION_RULES.ERR_TransactionRegister_exception7 = 000610100022	Caught exception while trying to delete Transaction Registers from the transaction register table
TRANSLATION.TRANSLATION_RULES.DEB_TransactionRegister_tr = 000620100001	Added the transactionRegister {0}
TRANSLATION.TRANSLATION_RULES.DEB_TransactionRegister_str1 = 000620100002	Found transaction registers that need to be added to the database
TRANSLATION.TRANSLATION_RULES.DEB_TransactionRegister_tr2 = 000620100003	Added the transaction register {0}

Message Code	Log Message
TRANSLATION.TRANSLATION_RULES.DEB_TransactionRegister_tr3 = 000620100004	Found a duplicate transaction register {0}
TRANSLATION.TRANSLATION_RULES.DEB_TransactionRegister_tr4 = 000620100005	[TransactionRegister]: Executed {0}
TRANSLATION.TRANSLATION_RULES.DEB_TransactionRegister_tr5 = 000620100006	[TransactionRegister]: Executed {0}
TRANSLATION.TRANSLATION_RULES.WAR_UnsupportedOpcodes_opcode = 000630100001	TRANSLATOR: call to unsupported opcode {0}
TRANSLATION.TRANSLATION_RULES.LOG_StringOpcodes_msg1 = 000640100001	{0}
TRANSLATION.TRANSLATION_RULES.LOG_StringOpcodes_msg2 = 000640100002	{0}
TRANSLATION.TRANSLATION_RULES.LOG_TransactionRegister_TruncatedFiled = 000640100003	Truncated the field {0}. The maximum allowable width of this field is {1}

Translation Storage System Log Messages

The following system log messages are used for translation storage:

Message Code	Log Message
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_tmp = 000610110001	[DiskHashMap] Could not create directory {0}
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception1 = 000610110002	[DiskHashMap] error reading from key file
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception2 = 000610110003	[DiskHashMap] error removing entry from key file
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception3 = 000610110004	[DiskHashMap] error accessing key file while executing count extended rule
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception4 = 000610110005	[DiskHashMap] error accessing keyfile while executing delete extended rule
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_str1 = 000610110006	[DiskHashMap] error accessing key file in deleteAllInstances method
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception5 = 000610110007	[DiskHashMap] error accessing key file in readKeyFile() method
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception6 = 000610110008	[DiskHashMap] error accessing keyfile while executing delete extended rule

Message Code	Log Message
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception7 = 000610110009	[DiskHashMap] error accessing keyfile while executing sort extended rule
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception8 = 000610110010	[DiskHashMap] error accessing keyfile while executing sort extended rule
TRANSLATION.TRANSLATION_STORAGE.ERR_Index_exception1 = 000610110011	TRANSLATOR: error cloning Index
TRANSLATION.TRANSLATION_STORAGE.ERR_VirtualGroupStore_tmpdir = 000610110012	[VirtualGroupStore] Could not create directory {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_guardBytes = 000620110001	[DiskHashMap] guard bytes \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_cacheDir = 000620110002	[DiskHashMap] cache dir \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_hashCapacity = 000620110003	[DiskHashMap] hash capacity \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_hashEntries = 000620110015	[DiskHashMap] hash entries to page \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_keyBatch = 000620110004	[DiskHashMap] key batch size \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_collisionCount = 000620110005	[DiskHashMap] for storage group {0} collision count {1}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_keyList = 000620110012	[DiskHashMap] readKeyFile(), number of keys in file \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_getAbsolutePath = 000620110006	[DiskHashMap] create storage page file {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_collision = 000620110007	[DiskHashMap] writeRecord() collision between key to write {0} and existing key {1} at offset {2} in key file, collision count \={3}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_readKey = 000620110008	[DiskHashMap] writeRecord() updating read key "{0}" setting next key ptr \={1}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_batch = 000620110009	[KeyBatch] writing {0} keys (key length\={1}) to key file {2} at offset {3}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_cacheDir = 000620110010	[VirtualGroupStore] cache dir \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_batch = 000620110011	[VirtualGroupStore] data batch size \={0}

Message Code	Log Message
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_getAbsolutePath = 000620110012	[VirtualGroupStore] create storage page file {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_count = 000620110013	[VirtualGroupStore] paged in count \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_count2 = 000620110014	[VirtualGroupStore] paged out count \={0}
TRANSLATION.TRANSLATION_STORAGE.LOG_DiskHashMap_tmp = 000640110001	[DiskHashMap] The storage.cache_dir is null, setting to java.io.tmpdir {0}
TRANSLATION.TRANSLATION_STORAGE.LOG_VirtualGroupStore_tmpdir = 000640110002	[DiskHashMap] The storage.cache_dir is null, setting to java.io.tmpdir {0}

Typing Service System Log Messages

The following system log messages are used for the Typing service:

Message Code	Log Message
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_MapNotFound = 000610030001	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_MapDISABLED = 000610030002	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_InvalidTypingServiceMapTYPE = 000610030003	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_UNREGISTEREDMap = 000610030004	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_InvalidMapOutput = 000610030005	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_RequiredParametersNotFound = 000610030006	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_TransformerException = 000610030007	{0}
TRANSLATION.TRANSLATION_TYPING.DEB_TypingService_TranslationLargeFile = 000620030001	TypingService.locateValidMap(): translation large file support enabled \={0}
TRANSLATION.TRANSLATION_TYPING.DEB_TypingService_TRXreport = 000620030002	TypingService.locateValidMap(): DEBUG TRX report: {0} {1}

Utility Translation System Log Messages

The following system log messages are used for Utility translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.ERR_DataConvert_exception1 = 000610130001	Exception parsing two digit year start property, defaulting to 1970
TRANSLATION.TRANSLATION_UTIL.ERR_DataConvert_exception2 = 000610130002	[Translator] Invalid format passed to DataConverter. The format: {0} is not valid
TRANSLATION.TRANSLATION_UTIL.ERR_DataConvert_exception3 = 000610130003	TRANSLATOR: The specified output encoding is not supported
TRANSLATION.TRANSLATION_UTIL.ERR_FuncDocToDOM_exception1 = 000710130004	dumpit method
TRANSLATION.TRANSLATION_UTIL.ERR_FuncSecurityContext_exception1 = 000610130005	Exception
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_str1 = 000610130006	sql.statement.MaximumBatchSize property value is not valid. Default maximum batch size will be used.
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception1 = 000610130007	TRANSLATOR: SQL Exception while closing PreparedStatment in SQLWriter
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_curBlock = 000610130008	TRANSLATOR: Batch execution error while performing batch operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception2 = 000610130009	TRANSLATOR: Batch Update Exception while performing batch operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception3 = 000610130010	TRANSLATOR: SQL Exception while performing batch operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception4 = 000610130011	TRANSLATOR: SQL Exception while performing batch operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception5 = 000610130012	TRANSLATOR: SQL Exception while performing operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception6 = 000610130013	TRANSLATOR: SQL Exception performing retry for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception7 = 000610130014	TRANSLATOR: SQL Exception while performing operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception1 = 000610130015	TRANSLATOR: The field syntax is not valid.

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception2 = 000610130016	TRANSLATOR: The field syntax is not valid
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception3 = 000610130017	TRANSLATOR: The field syntax is not valid
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception4 = 000610130018	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception5 = 000610130019	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception6 = 000610130020	TRANSLATOR: The field syntax is not valid
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception7 = 000610130021	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception8 = 000610130022	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception9 = 000610130023	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception10 = 000610130024	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception11 = 000610130025	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception12 = 000610130026	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception13 = 000610130027	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception14 = 000610130028	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception15 = 000610130029	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception16 = 000610130030	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception17 = 000610130031	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception18 = 000610130032	TRANSLATOR: Data conversion exception
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception19 = 000610130033	TRANSLATOR: Data conversion exception.

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception20 = 000610130034	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTValidator_exception1 = 000610130035	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTValidator_exception2 = 000610130036	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SmartDate_exception1 = 000610130037	TRANSLATOR: error cloning SmartDate
TRANSLATION.TRANSLATION_UTIL.ERR_SyntaxValidator_TokenFunction = 000610130038	TRANSLATOR: Function End token not found for field syntax \ {0} \ at index {1} .
TRANSLATION.TRANSLATION_UTIL.ERR_SyntaxValidator_TokenText = 000610130039	TRANSLATOR: Literal Text token not found for field syntax \ {0} \ at index {1}.
TRANSLATION.TRANSLATION_UTIL.ERR_SyntaxValidator_TokenREGEX = 000610130040	TRANSLATOR: REGEX token not found for field syntax \ {0} \ at index {1}.
TRANSLATION.TRANSLATION_UTIL.ERR_SyntaxValidator_exception1 = 000610130041	TRANSLATOR: The field syntax \ \ {0} \ at index {1} .
TRANSLATION.TRANSLATION_UTIL.ERR_SyntaxValidator_exception2 = 000610130042	TRANSLATOR: The field syntax \ \ {0} \ at index {1} .
TRANSLATION.TRANSLATION_UTIL.ERR_TxByteArrayOutputStream_exception1 = 000610130043	TRANSLATOR: The specified encoding is not supported.
TRANSLATION.TRANSLATION_UTIL.ERR_TxByteArrayOutputStream_exception2 = 000610130044	TRANSLATOR: The specified encoding is not supported.
TRANSLATION.TRANSLATION_UTIL.ERR_XMLDOMWriter_exception1 = 000610130045	TRANSLATOR: Error getting parent node for current element in setCurrentElementToParent.
TRANSLATION.TRANSLATION_UTIL.ERR_XpathHelper_exception1 = 000610130046	(DEBUG) XPathHelper.executeXPath: Exception testing xpath string: {0}
TRANSLATION.TRANSLATION_UTIL.ERR_XpathHelper_exception2 = 000610130047	XPathHelper.executeXPath: Exception optimizing xpath string: {0}
TRANSLATION.TRANSLATION_UTIL.ERR_XpathHelper_exception3 = 000610130048	XPathHelper.executeXPath: Exception for target ' {0} ' executing xpath: {1}
TRANSLATION.TRANSLATION_UTIL.ERR_XpathStatusRpt_str1 = 000610130049	Wfc is null in xpathStatusRpt
TRANSLATION.TRANSLATION_UTIL.ERR_XpathStatusRpt_wfId = 000610130050	DOM is null for wf_id {0}

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.ERR_XpathStatusRpt_str2 = 000610130051	Only one text parm is required
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath = 000620130001	[XPathHelper] executeXPath original xpath:
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath2 = 000620130002	[XPathHelper] cache based xpath query starts with some-function(/ProcessData/ : {0})
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath3 = 000620130003	[XPathHelper] cache based xpath query starts with /ProcessData/ : {0})
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath4 = 000620130004	[XPathHelper] attempting cache based xpath processing: {0}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath5 = 000620130005	[XPathHelper] executeXPath function type xpath cache query token: {0} : {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath6 = 000620130006	[XPathHelper] executeXPath non-function type xpath cache query token: {0} : {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath7 = 000620130007	[XPathHelper] executeXPath found cacheable node: {0} xpath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath8 = 000620130008	[XPathHelper] creating new cached xpath for document for document {0} xpath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath9 = 000620130009	[XPathHelper] NOT creating new cached xpath for document {0} placing null into cache: {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath10 = 000620130010	[XPathHelper] executeXPath evaluating with cached xpath: {0}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath11 = 000620130011	[XPathHelper] failed to find cacheable node, executing normal xpath: {0}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath12 = 000620130012	[XPathHelper] cache not available; executing normal xpath: {0}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath13 = 000620130013	[XPathHelper] executeXPath predicate query: begin \ = {0} end \ = {1} {2}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath14 = 000620130014	[XPathHelper] executeXPath, subXPath: {0} orXPath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath15 = 000620130015	[XPathHelper] executeXPath final predicate; executing xpath query, subXPath: {0} orXPath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath16 = 000620130016	[XPathHelper] executeXPath predicate, single return type, subXPath: {0} orXPath: {1}

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath17 = 000620130017	[XPathHelper] executeXPath predicate, multiple node return; perform operation: {0}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath18 = 000620130018	[XPathHelper] executeXPath predicate result: {0}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath19 = 000620130019	[XPathHelper] executeXPath not executing pre-predicate processing returning: {0} level: {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath20 = 000620130020	[XPathHelper] next loop predicate query, pre change: begin \ = {0} end \ = {1} {2}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath21 = 000620130021	[XPathHelper] next loop predicate query, postchange, begin: {0} end: {1} subXPath: {2} orXPath: {3}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath22 = 000620130022	[XPathHelper] executeXPath final xpath, orXPath: {0} newXPath: {1} level: {2}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathHelper_xpath23 = 000620130023	[XPathHelper] calling executeXPath,newXPath: {0} level: {1}
TRANSLATION.TRANSLATION_UTIL.DEB_XpathStatusRpt_str1 = 000620130024	create CDatasection for status_rpt
TRANSLATION.TRANSLATION_UTIL.WAR_XpathHelper_xpath = 000630130001	Predicate XPath query failed; falling back to slower full query.If this is a caching scheme, the results may be incorrect. Examine this xpath query: {0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_dumpit = 000640130001	{0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_saXPath = 000640130002	saXPath before\ = {0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_saXPath = 000640130003	saXPath after\ = {0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_xpt = 000640130004	token\ = {0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_str1 = 000640130005	dump of XPathTree:
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_XPathTree = 000640130006	{0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_str2 = 000640130007	=====
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_str3 = 000640130008	got a last-in-tree match or wildcard

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_str4 = 000640130009	incrementing tree index
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_mHits = 000640130010	##### HITS\ = {0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncDocToDOM_debugElement = 000640130011	{0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncSecurityContext_contextID = 000640130012	contextID is {0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncSecurityContext_contextName = 000640130013	contextName is {0}
TRANSLATION.TRANSLATION_UTIL.LOG_FuncSecurityContext_ret = 000640130014	Password is {0}

XML Encoding Translation System Log Messages

The following system log messages are used for XML encoding:

Message Code	Log Message
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_MapObject = 000610040001	Unable to load MapObject for map: {0}
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_exception1 = 000610040002	Exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_exception2 = 000610040003	Exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_exception3 = 000610040004	Caught exception in LightweightTxServiceEJBBean.processData():
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_exception4 = 000610040005	Unable to pass namespace-schema mappings to XML parser
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_exception5 = 000610040006	Unable to set XML parser validation feature
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_exception6 = 000610040007	MLEncoder.xmlToProcessData caught SQL exception while parsing the document : {0}
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_exception7 = 000610040008	Error while reading document with supplied encoding.
TRANSLATION.TRANSLATION_XMLENCODING.ERR_LightweightServiceImpl_exception8 = 000610040009	{0}

Message Code	Log Message
TRANSLATION.TRANSLATION_XMLENCODING.ERR_ LightweightServiceImpl_exception9 = 000610040010	XMLEncoder.xmlToProcessData caught parser exception while parsing the document :{0}
TRANSLATION.TRANSLATION_XMLENCODING.ERR_ LightweightServiceImpl_exception10 = 000610040011	Exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR_ LightweightServiceImpl_XMLEncoder = 000610040012	XMLEncoder.processdataToDocument failed. Object {0} returned from wfc.getWFEElement is of type {1} . Must be of type NodeList
TRANSLATION.TRANSLATION_XMLENCODING.ERR_ LightweightServiceImpl_exception11 = 000610040013	XMLEncoder.processdataToDocument caught unsupported encoding exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR_ LightweightServiceImpl_exception12 = 000610040014	XMLEncoder.processdataToDocument caught IO exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR_ LightweightServiceImpl_exception13 = 000610040015	XML parsing warning occurred
TRANSLATION.TRANSLATION_XMLENCODING.DEB_ LightweightServiceImpl_TranslationReport = 000620040001	Translation Report: {0} {1}
TRANSLATION.TRANSLATION_XMLENCODING.DEB_LightweightServiceImpl_str1 = 000720040002	LightweightTxServiceImpl.translate() completed

System Maintenance

System Maintenance

See the Sterling Integrator Installation or Upgrade documentation for system maintenance activities you may need to perform. These activities might include:

- Applying a Patch
- Applying a Hot-fix
- Performing a Checksum
- Generating a Patch Change Report
- Modifying the License Files
- Uninstalling the Software

Copyright

© Copyright 2012 Sterling Commerce, Inc. All rights reserved.

Additional copyright information is located on the Sterling Integrator 5.0 Documentation Library:

<http://www-01.ibm.com/support/docview.wss?uid=swg27023835>