

Sterling B2B Integrator



# System Administration

*Version 5.2*



Sterling B2B Integrator



# System Administration

*Version 5.2*

**Note**

Before using this information and the product it supports, read the information in "Notices" on page 55.

**Copyright**

This edition applies to Version 5 Release 2 of Sterling B2B Integrator and to all subsequent releases and modifications until otherwise indicated in new editions.

© **Copyright IBM Corporation 2000, 2015.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

---

# Contents

<b>System Administration . . . . .</b>	<b>1</b>	JDBC Translation System Log Messages . . . . .	33
System Maintenance . . . . .	1	Overdue Acknowledgement System Log Messages . . . . .	34
License Information . . . . .	1	Reconcile 997 Acknowledgement System Log Messages . . . . .	34
View License Information . . . . .	1	Reconcile CONTRL Acknowledgement System Log Messages . . . . .	35
License Modification. . . . .	1	Report Translation System Log Messages . . . . .	37
Support Tools . . . . .	2	Standards Translation System Log Messages . . . . .	37
Support Case Tool . . . . .	2	TA1 Acknowledgement Reconciliation System Log Messages . . . . .	38
SQL Manager Tool . . . . .	5	Translation Engine System Log Messages . . . . .	39
Back Up and Restore . . . . .	6	Translation Object System Log Messages. . . . .	39
Back Up Sterling B2B Integrator . . . . .	6	Translation Rules System Log Messages . . . . .	40
Restore Sterling B2B Integrator . . . . .	7	Translation Storage System Log Messages . . . . .	41
System Log Messages . . . . .	8	Typing Service System Log Messages. . . . .	43
Format of Error Codes Without Parameters . . . . .	8	Utility Translation System Log Messages . . . . .	43
Format of Error Codes With Parameters . . . . .	9	XML Encoding Translation System Log Messages	47
ASC X12 Deenveloping System Log Messages..	10	Start and Stop Commands . . . . .	48
ASC X12 Enveloping System Log Messages. . . . .	12	Customize Date and Time Formats . . . . .	48
Block Processor Translation System Log Messages	14	Customizing the Sterling B2B Integrator user interface . . . . .	49
Document Extraction System Log Messages . . . . .	16	Restart Sterling B2B Integrator after Time Change	52
EDI Control Report System Log Messages . . . . .	18	Configure Keystore Pathname or Password. . . . .	52
EDIFACT Deenveloping System Log Messages . . . . .	18	EBICS Client . . . . .	53
EDIFACT Enveloping System Log Messages . . . . .	21	<b>Notices . . . . .</b>	<b>55</b>
EDI Encoding System Log Messages . . . . .	23	Trademarks . . . . .	57
EDI Enveloping System Log Messages . . . . .	24	Terms and conditions for product documentation..	58
EDI Post-processing System Log Messages . . . . .	25		
EDI Report System Log Messages . . . . .	29		
Field Processor Translation System Log Messages	29		
Generate 997 System Log Messages . . . . .	30		
Generate TA1 Acknowledgement System Log Messages . . . . .	30		
Generic Deenveloping System Log Messages . . . . .	31		
Generic Enveloping System Log Messages . . . . .	32		



---

## System Administration

There are several system administration tasks you can perform to ensure Sterling B2B Integrator performs according to your business needs.

---

## System Maintenance

See the Sterling B2B Integrator Installation or Upgrade documentation for system maintenance activities you may need to perform. These activities might include:

- Applying a Patch
- Applying a Hot-fix
- Performing a Checksum Calculation
- Generating a Patch Change Report
- Modifying the License Files
- Uninstalling the Software

---

## License Information

See the Sterling B2B Integrator Installation or Upgrade documentation for information about system licenses.

### View License Information

#### About this task

You may find it useful to list and view the following information about currently installed licenses:

- License status - Valid or invalid.
- Component name - Component that the license is valid for.
- IP address - IP address that the license is valid on.
- Valid dates - Start and end dates that the license is valid.

To list all installed licenses:

#### Procedure

1. From the Administration Menu, select **Operations > System > Licenses**.
2. On the Licenses page, under List, next to List All Licenses, click **Go!** All of the installed licenses are listed.
3. To refresh the license page, click **Reload Licenses**.

### License Modification

#### About this task

See the Sterling B2B Integrator Installation or Upgrade documentation for the appropriate command format.

---

## Support Tools

Sterling B2B Integrator provides you with a support case and an SQL manager tool to help you communicate with and troubleshoot operational issues with IBM® Customer Support.

A support case is a situation where you contact IBM Customer Support for help. IBM Customer Support opens a support case to record all activities through resolution.

### Support Case Tool

The Support Case tool enables you to create and add information to a support case directly from the Sterling B2B Integrator interface.

This reduces the communications effort between you and IBM Customer Support.

#### Creating a Support Case (5.2.0 - 5.2.4.2)

After you have created a support case, you can attach database queries, system information, properties files and other information to help communicate issues to IBM Customer Support.

#### Before you begin

The information is bundled together using the PackageSupportInfo business process, which creates a .jar file, a compressed java file, and then sends the .jar file to IBM Customer Support using the FTP adapter.

The .jar file is also stored in your `install_dir/supportcasejars` directory under the following name formats:

- `c#case_no#filename.jar`, if you selected support case.
- `s#case_no#filename.jar`, if you selected support request.

Using the support case tool should be reserved for the system administrator or the system administrator's delegate. You must have permissions for the Support Case tool to use it.

**Note:** A support case may also be called a Service Request (SR) or a Problem Management Record (PMR). The term "trouble ticket" is also used sometimes.

Before using the Support Case tool:

- Have the support case or support request number you are referencing available.
- Create a support case on the Support Center, if you do not have a support case or support request number.

#### About this task

To use the Support Case Tool:

#### Procedure

1. From the Administration menu, select **Operations > System > Support Tools > Support Case**.
2. On the Support Case page, in the Case Number field, type the case number of the support case you are referencing.

Case Number is a required field and cannot accept special characters.



**Note:** If you do not have a case number assigned, click **SOD site** to go to the Support Center and create a new case.

3. Select whether the case number you are referencing is a:
  - Support Case – References a case number. Case numbers begin with the letter c.
  - Support Request – References a support request number. Support Request numbers begin with the letters sr.
4. In the Output Jar Name field, type the filename that becomes the bundled .jar file when you complete this procedure. For example, if you type IBM in the Output Jar Name field, the bundled .jar file becomes IBM.jar when you finish this procedure.
5. Select the **FTP** check box if you want to send the case information to IBM Customer Support.
6. In the Steps To reproduce field, type the steps to reproduce the issue that led to the support case.

Provide detailed information including all steps leading up to the issue and any error messages received in this field to help support provide a quicker resolution to your issue.

This information is available in the support .jar file in the StepsToReproduce.txt file.
7. In the Description field, type a description for the support case.

This information is available in the support .jar file in the ProblemDescription.txt file.
8. Click **Next**.
9. On the Case Data page, in the Data File field, type the path or browse to the location of the data file you want to attach to the case. The data files you upload are available in the support .jar file in the SuppCase.jar file.
10. In the Description field, type a brief, unique description of the file being attached.
11. Click **Attach**.

**Note:** You can attach multiple files in multiple formats in one support case bundle. Repeat steps 9 through 11 to attach multiple files.

12. On the Confirm page, complete the following actions: Providing the system information and properties files in the .jar bundle provides the greatest amount of information about your system and situation to IBM Customer Support and helps to expedite the case to resolution.
  - a. Select **Include System Information** to include information about the server, memory and other components in the bundle.
  - b. Select **Include Property Files** to include properties files from your Sterling B2B Integrator installation.
  - c. Review the information and click **Finish**.

## Results

The information is bundled into the .jar file you named in the Output Jar Name field. If you selected the option, the information is sent to IBM Customer Support.

## Collecting data for a PMR (5.2.5 or higher)

You can use the Support Case tool to automatically collect and post system data associated with a Problem Management Record (PMR) to help Customer Support analyze and fix the issue.

## Before you begin

Before using the Support Case tool:

- Have the Problem Management Record (PMR) number you are referencing available.
- If you do not have a PMR number, create a PMR on the IBM Support Center.

**Note:** A PMR may also be called a Service Request (SR). The terms "support case" and "trouble ticket" are also used sometimes.

## About this task

Using the support case tool should be reserved for the system administrator or the system administrator's delegate. You must have permissions for the Support Case tool to use it.

To use the Support Case Tool:

## Procedure

1. From the Administration Menu, select **Operations > System > Support Tools > Support Case**.
2. On the Case Details page, in the **PMR Number** field, type the PMR number of the support case you are referencing.

This is a required field. Do not include any special characters except spaces. Although you can use spaces, they will automatically be removed. The number supplied here becomes part of the Output Jar file name.

If you do not have a PMR number assigned, click **IBM Support Center** to go to the Support Center and create a PMR.

3. In the **Output Jar Name** field, type any text you would like included in the file name of the output JAR file when you complete this procedure. The text will be preceded by a period. This field is optional and may be left blank.

The naming convention for the output JAR file name is `PMR<PMR Number><.Output Jar Name>.jar`

For example, if the PMR Number is 12345 678 901 and you enter myData in the **Output Jar Name** field, the output JAR file will be named `PMR12345678901.myData.jar`.

If the PMR Number is 12345 678 901 and you leave the **Output Jar Name** field blank, the output JAR file will be named `PMR12345678901.jar`.

4. In the **Description** field, type a description for the support case.  
This field is required.
5. Click **Next**.
6. On the Case Data page, attach any additional files or test data that will help debug the issue. Next to **Data File**, browse to the location of the data file you want to attach to the case. The data files you upload will be included in the output JAR file.
7. In the Description field, type a brief, unique description of the file being attached. This field is optional.
8. Click **Attach**.

**Note:** You can attach multiple files in multiple formats. Repeat steps 6 through 8 to attach additional files.

9. Click **Next**.

10. On the Confirm page:
  - a. Select **Include System Information** to include information about the server, memory and other components in the output JAR file.
  - b. Select **Include Property Files** to include properties files from your Sterling B2B Integrator installation. Providing the system information and properties files in the output JAR file provides the greatest amount of information about your system and situation to IBM Customer Support and helps to expedite resolution of the case.
  - c. Confirm the information and click **Finish**.

## Results

The Support Case tool analyzes the system and collects all data according to the options provided. The data is bundled into the output JAR file. The name of the output JAR file is based on the PMR number and your entry in the **Output Jar Name** field. The output JAR file is sent to the Enhanced Customer Data Repository (ECuRep) to aid IBM Customer Support in resolving your PMR. You will also be provided the option to download and save the output JAR file.

## SQL Manager Tool

The SQL Manager tool in Sterling B2B Integrator enables IBM Customer Support to search your Sterling B2B Integrator database for information that may help in resolving your support case.

**Caution:** Use this tool only when IBM Customer Support directs you to use it and when a support representative guides you through the process. You can make permanent changes to your database, which may result in damage to your Sterling B2B Integrator configuration and loss of data.

**Note:** If you are manually entering the date in MySQL, do not enter a date with all zeroes, for example, 0000-00-00 00:00:00. Enter a valid date or NULL.

### Perform SQL Query from SQL Manager

#### About this task

To complete a query using the SQL Manager:

#### Procedure

1. From the Administration Menu, select **Operations > System > Support Tools > SQL Manager**.
2. Enter your SQL query and click **Execute**. The query results display directly under the SQL Manager tool.

#### What to do next

You can use the **Command History** link at the top of the SQL Manager tool to view the commands you have entered during the most current session. You can copy and paste the commands from the history page to the SQL Manager. Once you log out, or your session times out, all previous command history entries are lost.

## Export SQL Query Results from SQL Manager

### About this task

After you work with IBM Customer Support to complete your query, you can export the results in different formats to send them to IBM Customer Support or for archival purposes.

To export the query results from the SQL Manager:

#### Procedure

1. In the SQL Manager tool, complete your query.
2. At the top-center of the results table, next to Export, click the format for the file:
  - xls – Microsoft Excel spreadsheet file
  - csv – Comma separated values file
  - xml – XML file
3. In the File Download window, click **Save** and select the location to save the file to.

#### What to do next

You can now e-mail the file to IBM, Customer Support or attach the file to your case opened using the Support Case tool in Sterling B2B Integrator.

---

## Back Up and Restore

It is good practice to back up Sterling B2B Integrator on a regular basis to protect your data in the event of hardware failure, system failure or a catastrophic event.

The Back Up and Restore tasks contain general instructions. Your installation may require other steps not identified in the tasks. These are system level instructions. Ensure that you have sufficient access and file permissions before attempting to back up or restore Sterling B2B Integrator. If you encounter problems with these tasks contact IBM Customer Support.

## Back Up Sterling B2B Integrator

### About this task

You may find it useful to list and view the following information about currently installed licenses:

To back up Sterling B2B Integrator, perform the following steps:

#### Procedure

1. Back up the database used with Sterling B2B Integrator. If you are using MySQL, this is part of the Sterling B2B Integrator installation directory structure. Take the following precautions:
  - If you are using MySQL, stop Sterling B2B Integrator before backing up the file system.
  - If you are using another database, perform one of the following:
    - Stop Sterling B2B Integrator before backing up the database.

- Use a database backup tool that allows you to back up the database while it is live. Never attempt to back up a live database otherwise.
- 2. Back up the entire Sterling B2B Integrator installation directory, include all files and subdirectories.  
  
**Note:** Be sure to include any service configurations that point to directories that are not within the installation directories. These include:
  - Command Line Adapter - `install_dir/install/client/cmdline/CLA2Client.jar`
  - Command Line Adapter2 - `install_dir/install/client/cmdline2/CLA2Client.jar`
- 3. Back up external resources, including any external locations used by any service configurations. For example:
  - Collection/extraction directories for FSA instances
  - Document directory for File System storage
  - Resources such as scripts
- 4. If you use perimeter services, perform the following steps:
  - a. Back up your *perimeter.properties* file.
  - b. For perimeter services in the DMZ, record your installation parameters. You will need them during the restore process. Alternatively, back up the installation directory.
  - c. Back up DMZ deployments and resources.

## Restore Sterling B2B Integrator

### About this task

If you restore a system because of total failure, review the following requirements:

- The system must be restored with the same IP address.
- The user account must match the system that failed.
- The JDK on the new system must be the exact same version and installed in the same location.

To restore Sterling B2B Integrator, perform the following steps:

### Procedure

1. Restore the database used with Sterling B2B Integrator.

**Note:** If you are using MySQL, this is part of the Sterling B2B Integrator installation directory structure.

2. Restore the Sterling B2B Integrator installation directory, including all files and subdirectories, to the same directory path where it was originally installed.
3. Restore external resources to the same directory path where they were originally installed.

**Note:** The host information (IP address or hostname) must remain the same on the restored system.

4. (Windows only) From the installation directory, install windows services by running the *command installWindowsService.cmd*.
5. If you use perimeter services, perform the following steps:
  - a. Restore your *perimeter.properties* file.

- b. Restore DMZ deployments and resources, if required and perimeter services installations. Use the installation parameters you recorded during the back up process. Alternatively, if you backed up the installation directory, restore the installation directory.

---

## System Log Messages

Sterling B2B Integrator uses enhanced system logging for EDI and translator messages. Each system message related to EDI or translation now contains a unique code number in a addition to the text of the message.

Log files are created in the `install_dir/logs` directory. To prevent the system log files from taking up necessary storage space and memory allocations, Sterling B2B Integrator only generates a log file when a component runs (a log file is generated to monitor the activities of each system component), which improves the performance of the system.

See *Managing System Logs* for information on log file naming conventions, log file types, and how to manage the system logs.

**Note:** If you receive the following code in a system log, it indicates that a basic logging method was used and notifies you of a message that has not yet been converted to use the enhanced logging (in the future all these messages will be converted):

```
000000000000 GLOBAL_SCOPE N/A
```

## Format of Error Codes Without Parameters

The new error code numbers use the following format:

```
Scope.Subsystem.Name=000110020789
```

The format used is parsed and described in the following table:

Number of Error Code Number Digits	Description
1 - 4	The first four digits specify the scope of the component (for example, EDI).
5	The next one digit specifies the log severity level. The convention is: <ul style="list-style-type: none"> <li>• 1 = error/exception</li> <li>• 2 = debug messages</li> <li>• 3 = warnings</li> <li>• 4 = information/all messages</li> </ul>
6 - 8	The next three digits specify the subsystem of the component (for example, EDI_EDIFACTDEENVELOPING).
9 -12	The next four digits specify the unique error number (this number is unique in conjunction with the rest of the error code format (such as the scope and so forth).

For example, this is an EDIFACT deenvolving system message:

```
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvolveEDIFACTServiceImpl_start=000520040001
```

The format used in this message (to the left of the equals sign) is parsed and described in the following table:

Parameter	Description
Scope	EDI
Subsystem	EDI_EDIFACTDEENVELOPING (the EDIFACT deenveloping subsystem, which is a subset of EDI in the system)
Name	DEB_DeenvelopeEDIFACTServiceImpl_start  This is the name of the error message which, when translated into the system log, reads DeenvelopeEDIFACTServiceImpl processData() starting...

The format used in this message (to the right of the equals sign) is parsed and described in the following table:

Number of Error Code Number Digits	Description
1 - 4	The first four digits (0005) specify the scope of the component (EDI).
5	The next one digit (2) specifies the log severity level, indicating that this is a debug message (DEB).
6 - 8	The next three digits (004) specify the subsystem of the component (EDI_EDIFACTDEENVELOPING).
9 -12	The next four digits (0001) specify the unique error number (this number is unique in conjunction with the entire error code format).

## Format of Error Codes With Parameters

Additionally, the system message codes may include parameters, such as:

Scope.Subsystem.Name={0}000110020789{3}

The format used is parsed and described in the same manner as messages without parameters.

For example, this is an EDIFACT deenveloping system message with a parameter:

EDI.EDI\_EDIFACTDEENVELOPING.EDI.EDI\_EDIFACTDEENVELOPING.  
DEB\_DeenvelopeEDIFACTServiceImpl\_ExceptionFindingContract={0}000520040010{3}

The format used in this message (to the left of the equals sign) is parsed and described in the following table:

Parameter	Description
Scope	EDI
Subsystem	EDI_EDIFACTDEENVELOPING (the EDIFACT deenveloping subsystem, which is a subset of EDI in the system)
Name	EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACTServiceImpl_ExceptionFindingContract  This is the name of the error message which, when translated into the system log, reads [DeenvelopeEDIFACTServiceImpl] Exception finding contract {0} <b>Note:</b> The first parameter [DeenvelopeEDIFACTServiceImpl], indicates the service implementation. The second parameter {0}, indicates the specific contract.

The format used in this message (to the right of the equals sign) is parsed and described in the following table:

Number of Error Code Number Digits	Description
1 - 4	The first four digits (0005) specify the scope of the component (EDI).
5	The next one digit (2) specifies the log severity level, indicating that this is a debug message (DEB).
6 - 8	The next three digits (004) specify the subsystem of the component (EDI_EDIFACTDEENVELOPING).
9 -12	The next four digits (0001) specify the unique error number (this number is unique in conjunction with the entire error code format).

## ASC X12 Deenveloping System Log Messages

The following system log messages are used for ASC X12 deenveloping:

Message Code	Log Message
EDI.EDI_X12DEENVELOPING.DEB_DeenvelopeX12 ServiceImpl_ExceptionFindingContract=0005200200 04	[DeenvelopeX12ServiceImpl] Exception finding contract {0}
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception1=000510020001	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception2=000510020002	DeenvelopeX12ServiceImpl - Error saving interchange correlation
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception3=000510020003	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception4=000510020004	DeenvelopeX12ServiceImpl - Error saving group correlations
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception5=000510020005	DeenvelopeX12 - Error EDI encoding 997 document for group control no. {0}
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception6=000510020006	DeenvelopeX12 - Error creating 997
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception7=000510020007	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception8=000510020008	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception9=000510020009	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception10=000510020010	DeenvelopeX12ServiceImpl - Error generating TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception11=000510020011	DeenvelopeX12ServiceImpl - Error enveloping 997
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception12=000510020012	DeenvelopeX12ServiceImpl - Error generating TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception13=000510020013	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception14=000510020014	DeenvelopeX12ServiceImpl - Error saving transaction correlation
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception15=000510020015	DeenvelopeX12ServiceImpl - Error generating TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception16=000510020016	DeenvelopeX12ServiceImpl - Error starting business process



Message Code	Log Message
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception17=000510020017	DeenvelopeX12ServiceImpl - Error starting business process
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception18=000510020018	Error reconciling TA1s
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception19=000510020019	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception20=000510020020	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception21=000510020021	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception22=000510020022	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception23=000510020023	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception24=000510020024	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception25=000510020025	Exception while de-enveloping ISA/IEA
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception26=000510020026	Exception attempting to close output stream in DeenvelopeX12ServiceImpl
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception27=000510020027	Exception while de-enveloping GS/GE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception28=000510020028	Exception while de-enveloping GS/GE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception29=000510020029	Exception while de-enveloping GS/GE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception30=000510020030	Exception while removing GS/GE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception31=000510020031	Exception while removing GS/GE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception32=000510020032	Exception while removing GS/GE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception33=000510020033	Exception while removing GS/GE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception34=000510020034	Exception while looking up a contract
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception35=000510020035	DeenvelopeX12ServiceImpl - Error reconciling 997
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception36=000510020036	Exception while de-enveloping ST/SE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception37=000510020037	Exception while de-enveloping ST/SE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception38=000510020038	Exception while de-enveloping ST/SE
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception39=000510020039	Exception while removing ST/SE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12ServiceImpl_exception40=000510020040	Exception while removing ST/SE envelope

Message Code	Log Message
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception41=000510020041	Exception while removing ST/SE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception42=000510020042	Exception while removing ST/SE envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_str1=000510020043	Unable to match ISA/IEA Envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_str2=000510020044	Unable to match ISA/IEA Envelope, lookup returned multiple envelopes
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_str3=000510020045	Unable to match GS/GE Envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_str4=000510020046	Unable to match GS/GE Envelope, lookup returned multiple envelopes
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception43=000510020047	ProcessTransactions: IOException while closing streams
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception44=000510020048	DeenvelopeX12ServiceImpl - Error loading BP
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception45=000510020049	[DeenvelopeX12ServiceImpl] Exception finding contract
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_str5=000510020050	Unable to match ST/SE Envelope
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_str6=000510020051	Unable to match ST/SE Envelope, lookup returned multiple envelopes
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception46=000510020051	DeenvelopeX12ServiceImpl unable to start workflow for TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception47=510020052	DeenvelopeX12ServiceImpl - Error enveloping TA1
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception48=000510020054	DeenvelopeX12ServiceImpl - Error setting up deferred sequence/duplicate control number checking
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception49=000510020055	DeenvelopeX12ServiceImpl - Error saving transaction correlations
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception50=000510020056	[DeenvelopeX12ServiceImpl] Error in Correlation
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception51=000510020057	DeenvelopeX12ServiceImpl - Error saving transaction correlations
EDI.EDI_X12DEENVELOPING.ERR_DeenvelopeX12 ServiceImpl_exception52=000510020058	Exception while de-enveloping ISA/IEA

## ASC X12 Enveloping System Log Messages

The following system log messages are used for ASC X12 enveloping:

Message Code	Log Message
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12 ServiceImpl_start=000520010001	EnvelopeX12.envelope() starting...
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12 ServiceImpl_TranslationLargeFile=000520010002	Translation large file support enabled /= {0}

Message Code	Log Message
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12 ServiceImpl_end=000520010003	EnvelopeX12.envelope() ending...
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12 ServiceImpl_stControlNumber=000520010004	Loading st control number for {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12 ServiceImpl_gsControlNumber=000520010005	Loading gs control number for {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12 ServiceImpl_isaControlNumber=000520010006	Loading isa control number for {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12 ServiceImpl_exceptionFindingContract1=000520010007	EnvelopeX12.lookupSTContract(): Exception on finding contract {0}
EDI.EDI_X12ENVELOPING.DEB_EnvelopeX12 ServiceImpl_exceptionFindingContract2=000520010008	EnvelopeX12.lookupSTContract(): Exception finding contract {0}
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception1=000510010001	EnvelopeGeneric.envelope() encountered exception:
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception2=000510010002	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_str1=000510010003	Document has not been processed by the EDI Encoder service
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception3=000510010004	Exception while looking up a contract
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception4=000510010005	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception5=000510010006	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception6=000510010007	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception7=000510010008	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception8=000510010009	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception9=000510010010	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception10=000510010011	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception11=000510010012	EnvelopeX12.envelope() encountered exception
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception12=000510010013	EnvelopeX12.envelope() encountered exception:
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception13=000510010014	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception14=000510010015	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception15=000510010016	Exception while enveloping document
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_info=000510010017	{0}
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12 ServiceImpl_exception16=000510010018	Exception attempting to close output or input streams in EnvelopeX12.envelope()

Message Code	Log Message
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception17=000510010019	X12EnvelopeServiceImpl - Error loading control number
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception18=000510010020	X12EnvelopeServiceImpl - Error loading control number
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception19=000510010021	X12EnvelopeServiceImpl - Error loading control number
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception20=000510010022	[X12 Envelope Service] Error saving correlations.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception21=000510010023	EnvelopeX12.envelope() encountered exception:
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception22=000510010024	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception23=000510010025	X12EnvelopeServiceImpl - Error loading control number
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception24=000510010026	Exception while writing ISA/IEA envelope
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception25=000510010027	Exception while writing ISA/IEA envelope
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception26=000510010028	Exception while writing ISA/IEA envelope
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception27=000510010029	EnvelopeX12ServiceImpl - Exception loading outbound envelope values from correlations
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception28=000510010030	EnvelopeX12ServiceImpl - Exception loading outbound envelope values from correlations
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_ERR_EnvelopeX12ServiceImpl_ControlNumberNames=000510010031	EnvelopeX12ServiceImpl - Error generating control number names - {0}
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception29=000510010031	Error generating ISA resource name
EDI.EDI_X12ENVELOPING.ERR_EnvelopeX12ServiceImpl_exception30=000510010032	[EnvelopeX12Service] exception finding document. The requiresEnvelope correlation was not changed

## Block Processor Translation System Log Messages

The following system log messages are used for block processor translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDIIInputBinBlockHandler_exception1=000610060001	[Translator] Unable to encode overridden delimiters using encoding {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDIIInputBinBlockHandler_exception2=000610060002	[Translator] Unable to encode overridden delimiters using default encoding
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDIIInputCharBlockHandler_exception1=000610060003	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDIIInputCharBlockHandler_exception2=000610060004	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR.ERR_EDIIOutputBlockHandler_exception1=000610060005	TRANSLATOR: The specified output encoding is not supported.

Message Code	Log Message
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_EDIOutputBlockHandler_exception2=000610060006	TRANSLATOR: The specified output encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_PositionInputBlockHandler_exception1=000610060007	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_PositionInputBlockHandler_exception2=000610060008	TRANSLATOR: The specified output encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_PositionInputBlockHandler_exception3=000610060009	TRANSLATOR: Failed to convert multibyte char to bytes
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_PositionInputBlockHandler_exception4=000610060010	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_PositionInputBlockHandler_exception5=000610060011	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception1=000610060012	TRANSLATOR: SQL exception while opening JDBC connection
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception2=000610060013	TRANSLATOR: jdbc driver \ {0} \ does not support scrolling, defaulting to forward only while executing \ {1} \ in {2}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception3=000610060014	TRANSLATOR: jdbc driver \ {0} \ does not support scrolling, defaulting to forward only while executing \ {1} \ in {2}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception4=000610060015	TRANSLATOR: SQL exception while executing \ {0} \ in {1}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception5=000610060016	TRANSLATOR: SQL exception while executing \ {0} \ in {1}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception6=000610060017	TRANSLATOR: SQL exception performing MOVEFIRST on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception7=000610060018	TRANSLATOR: SQL exception performing MOVELAST on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception8=000610060019	TRANSLATOR: SQL exception performing MOVENEXT on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception9=000610060020	TRANSLATOR: SQL exception performing MOVEPREV on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception10=000610060021	TRANSLATOR: SQL exception performing CLOSE on result of {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception11=000610060022	TRANSLATOR: SQL exception while closing JDBC resultset
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception12=000610060023	TRANSLATOR: SQL exception while rolling back transaction in {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception13=000610060024	TRANSLATOR: SQL exception while committing transaction in " {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SQLBlockHandler_exception14=000610060025	Caught exception in finishTranslation()
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SWIFTInputBlockHandler_exception1=000610060026	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SWIFTInputBlockHandler_exception2=000610060027	TRANSLATOR: Error closing the input stream.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SWIFTInputBlockHandler_exception3=000610060028	TRANSLATOR: I/O exception.

Message Code	Log Message
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SWIFTInputBlockHandler_exception4=000610060029	TRANSLATOR: Error compiling a syntax.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_SWIFTInputBlockHandler_exception5=000610060030	TRANSLATOR: Data conversion error.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_VarDelimInputBlockHandler_exception1=000610060031	TRANSLATOR: The specified input encoding is not supported.
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. ERR_XMLErrorHandler_exception1=000610060032	SAX Parser Exception:
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. DEB_SQLBlockHandler_dbPool=000620060001	[SQLBlockHandler] dbPool \= {0}
TRANSLATION.TRANSLATION_BLOCKPROCESSOR. WAR_PositionInputBlockHandler_dataEncoding=000630060001	TRANSLATOR: The {0} data encoding overrides the {1} specified encoding

## Document Extraction System Log Messages

The following system log messages are used for document extraction:

Message Code	Log Message
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_str1=000610050001	Document Extraction Service - New Behavior = saving array list into content.
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_DocExtraction1=000610050002	Document Extraction Service - Parser exception:{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_DocExtraction2=000610050003	Document Extraction Service - Handler or parser-initialization exception:{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_DocExtraction3=000610050004	Document Extraction Service - Parser with specified options can't be built:{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_DocExtraction4=000610050005	Document Extraction Service - IO error while splitting compound XML document:{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_str2=000610050006	Document Extraction Service - No XML subdocuments found
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_exception1=000610050007	Document Extraction Service - Error writing unrecognized data
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_exception2=000610050008	{0} : {1}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_exception3=000610050009	Document Extraction Service - Error enveloping document
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_exception4=000610050010	Document Extraction Service - Error enveloping documents
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_exception5=000610050011	Document Extraction Service - IOException occurred
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_exception6=000610050012	Document Extraction Service - SQLException occurred
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_DocumentExtractionService_MapList=000610050013	DocumentExtractionService.getMapList():{0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_XMLDocExtractHandler_exception1=000610050014	XML Document Extraction Handler - SQLException occurred: Initialize()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION. ERR_XMLDocExtractHandler_exception2=000610050015	XML Document Extraction Handler - Unrecognized encoding in XML Declaration: {0} defaulting to UTF-8

Message Code	Log Message
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception3=000610050016	XML Document Extraction Handler - IOException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception4=000610050017	XML Document Extraction Handler - SQLException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception5=000610050018	XML Document Extraction Handler - IOException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception6=000610050019	XML Document Extraction Handler - IOException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception7=000610050020	XML Document Extraction Handler - IOException occurred: startElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception8=000610050021	XML Document Extraction Handler - IOException occurred: characters()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception9=000610050022	XML Document Extraction Handler - IOException occurred: endElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception10=000610050023	XML Document Extraction Handler - IOException occurred: endElement()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception11=000610050024	XML Document Extraction Handler - IOException occurred: comment()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception12=000610050025	XML Document Extraction Handler - IOException occurred: startCDATA()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.ERR_XMLDocExtractHandler_exception13=000610050026	XML Document Extraction Handler - IOException occurred: endCDATA()
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.DEB_DocumentExtractionService_LargeFile=000620050001	Document Extraction Service - translation large file support enabled \={0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.DEB_DocumentExtractionService_str1=000620050002	DocumentExtractService: Save unrecognized document into PD
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.DEB_DocumentExtractionService_WFContent=000620050003	Set WFContent Document Extraction Service - total\={0}
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str1=000630050001	[DocumentExtractionService] DocExtractMapList parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str2=000630050002	[DocumentExtractionService] XMLEDIEnvelopeStandard parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str3=000630050003	[DocumentExtractionService] XMLSenderIDPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str4=000630050004	[DocumentExtractionService] XMLSenderIDQualifierPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str5=000630050005	[DocumentExtractionService] XMLReceiverIDPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str6=000630050006	[DocumentExtractionService] XMLReceiverIDQualifierPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str7=000630050007	[DocumentExtractionService] XMLAcceptorLookupAliasPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str8=000630050008	[DocumentExtractionService] XMLEDIEnvelopeStandard parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str9=000630050009	[DocumentExtractionService] XMLRootTag parameter ignored

Message Code	Log Message
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str10=000630050010	[DocumentExtractionService] XMLSenderIDPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str11=000630050011	[DocumentExtractionService] XMLReceiverIDPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str12=000630050012	[DocumentExtractionService] XMLAcceptorLookupAliasPath parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str13=000630050013	[DocumentExtractionService] XMLEDIEnvelopeStandard parameter ignored
TRANSLATION.TRANSLATION_DOCUMENTEXTRACTION.WAR_DocumentExtractionService_str14=000630050014	[DocumentExtractionService] Empty substring in path string

## EDI Control Report System Log Messages

The following system log messages are used for the EDI Control Report:

Message Code	Log Message
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception1=000510120001	Exception creating EDIFACT CONTRL report
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception2=000510120002	IO Exception creating EDIFACT CONTRL report
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception3=000510120003	Exception attempting to close output stream in EDIFACTCONTRL report
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception4=000510120004	EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception4=Exception in GenerateCONTRL
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception5=000510120005	EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception5=Exception in GenerateCONTRL
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception6=000510120006	EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception6=Exception in GenerateCONTRL
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception7=000510120007	EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception7=Exception in GenerateCONTRL
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception8=000510120008	EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception8=Exception in GenerateCONTRL
EDI.EDI_EDICONTLREPORT.ERR_GenerateCONTRLSERVICEImpl_str1=000510120009	EDI.EDI_EDICONTLREPORT.ERR_GenerateCONTRL ServiceImpl_str1=GenerateCONTRL processData() A SQL Exception occurred while retrieving the document extension.
EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception9=000510120010	EDI.EDI_EDICONTLREPORT.ERR_EDICONTL Report_exception9=Exception in GenerateCONTRL
EDI.EDI_EDICONTLREPORT.DEB_GenerateCONTRL ServiceImpl_start=000520120001	EDI.EDI_EDICONTLREPORT.DEB_GenerateCONTRL ServiceImpl_start=GenerateCONTRL processData() starting...
EDI.EDI_EDICONTLREPORT.DEB_GenerateCONTRL ServiceImpl_end=000520120002	EDI.EDI_EDICONTLREPORT.DEB_GenerateCONTRL ServiceImpl_end=GenerateCONTRL processData() ending...

## EDIFACT Deenveloping System Log Messages

The following system log messages are used for EDIFACT deenveloping:

Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_start=000520040001	DeenvelopeEDIFACTServiceImpl processData() starting...
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_end=000520040002	DeenvelopeEDIFACTServiceImpl processData() ending...



Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_translationLargeFileSupportEnabled=000520040003	DeenvelopeEdifactServiceImpl - translation large file support enabled \={0}
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_str1=000520040004	Security Header Segment Missing.
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_str2=000520040005	Security Trailer Segment is null
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_str3=000520040006	Security Trailer Segment Missing.
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_str4=000520040007	Non-repudiation of origin succeeded
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_str5=000520040008	Non-repudiation of origin verification failed.
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_str6=000520040009	Non-repudiation of origin verification failed because digital signature data is missing.
EDI.EDI_EDIFACTDEENVELOPING.DEB_DeenvelopeEDIFACT ServiceImpl_ExceptionFindingContract=000520040010	[DeenvelopeEDIFACTServiceImpl] Exception finding contract {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception1=000510040001	EDIFACTServiceImpl_Exception while deenveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception2=000510040002	DeenvelopeEDIFACTServiceImpl - Error saving interchange correlations
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception3=000510040003	DeenvelopeEDIFACTServiceImpl - Error saving group correlations
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception4=000510040004	DeenvelopeEDIFACTServiceImpl - Error enveloping CONTRL
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception5=000510040005	DeenvelopeEDIFACT - Error EDI encoding CONTRL document for interchange control no. {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception6=000510040006	DeenvelopeEDIFACT - Error creating CONTRL document for interchange control no. {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception7=000510040007	EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACTServiceImpl_exception7=DeenvelopeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception8=000510040008	DeenvelopeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception9=000510040009	DeenvelopeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception10=000510040010	EDIFACT Deenvelope Service - error parsing interchange to find first message type for CONTRL envelope acceptor lookup alias generation
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception11=000510040011	EDIFACT Deenvelope Service - error parsing interchange to find first message type for CONTRL envelope acceptor lookup alias generation

Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception12=000510040012	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception13=000510040013	DeenvelopeEDIFACTServiceImpl - Error saving transaction correlation
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception14=000510040014	DeenvelopeEDIFACTServiceImpl - Error enveloping CONTRL
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception15=000510040015	DeenvelopeEDIFACT - Error EDI encoding CONTRL document for interchange control no. {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception16=000510040016	DeenvelopeEDIFACT - Error creating CONTRL document for interchange control no. {0}
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception17=000510040017	DeenvelopeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception18=000510040018	DeenvelopeEDIFACTServiceImpl - Error starting business process
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception19=000510040019	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception20=000510040020	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception21=000510040021	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception22=000510040022	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception23=000510040023	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception24=000510040024	Exception while de-enveloping UNB/UNZ
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception25=000510040025	Exception while de-enveloping GS/GE
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception26=000510040026	Exception while de-enveloping GS/GE
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception27=000510040027	Exception while de-enveloping GS/GE
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception28=000510040028	Exception while removing GS/GE envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception29=000510040029	Exception while removing GS/GE envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception30=000510040030	Exception while removing GS/GE envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception31=000510040031	Exception while removing GS/GE envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception32=000510040032	Exception while looking up a contract
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception33=000510040033	Exception attempting to close output stream in DeenvelopeEDIFACTServiceImpl

Message Code	Log Message
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception34=000510040034	Exception attempting to close output stream in DeenvelopeEDIFACTServiceImpl
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception35=000510040035	Exception while de-enveloping UNH/UNT
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception36=000510040036	Exception while de-enveloping UNH/UNT
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception37=000510040037	Exception while de-enveloping UNH/UNT
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception38=000510040038	Exception while removing UNH/UNT envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception39=000510040039	Exception while removing UNH/UNT envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception40=000510040040	Exception while removing UNH/UNT envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_str1=000510040041	Unable to match UNB/UNZ Envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_str2=000510040042	Unable to match UNB/UNZ Envelope, lookup returned multiple envelopes
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_str3=000510040043	Unable to match UNG/UNE Envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_str4=000510040044	Unable to match UNG/UNE Envelope, lookup returned multiple envelopes
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception41=000510040045	DeenvelopeEDIFACTServiceImpl - Error loading BP
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception42=000510040046	[DeenvelopeEDIFACTServiceImpl] Exception finding contract
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_str5=000510040047	Unable to match UNH/UNT Envelope
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_str6=000510040048	Unable to match UNH/UNT Envelope, lookup returned multiple envelopes
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception43=000510040049	DeenvelopeEDIFACTServiceImpl - Error setting up deferred sequence/duplicate control number checking
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception44=000510040050	DeenvelopeEDIFACTServiceImpl - Error saving transaction correlations
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception45=000510040051	[DeenvelopeEDIFACTServiceImpl] Error in Correlation
EDI.EDI_EDIFACTDEENVELOPING.ERR_DeenvelopeEDIFACT ServiceImpl_exception46=000510040052	[DeenvelopeEDIFACTServiceImpl] Error in Correlation

## EDIFACT Enveloping System Log Messages

The following system log messages are used for EDIFACT enveloping:

Message Code	Log Message
EDI.EDI_EDIFACTENVELOPING_DEB_EnvelopeEDIFACT ServiceImpl_start=000520030001	EnvelopeEDIFACT.envelope() starting...

Message Code	Log Message
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACT ServiceImpl_end=000520030002	EnvelopeEDIFACT.envelope() ending...
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACT ServiceImpl_UnhControlNumber=000520030003	Loading unh control number for {0}
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACT ServiceImpl_TranslationLargeFileSupportEnabled=000520030004	EnvelopeEDIFACT.envelope() translation large file support enabled \= {0}
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACT ServiceImpl_unhControlNumber=000520030005	Loading unh control number for
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACT ServiceImpl_ExceptionFindingContract1=000520030006	EnvelopeEDIFACT.lookupUNHContract(): Exception finding contract {0}
EDI.EDI_EDIFACTENVELOPING.DEB_EnvelopeEDIFACT ServiceImpl_ExceptionFindingContract2=000520030007	EnvelopeEDIFACT.lookupUNHContract(): Exception finding contract {0}
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception1=000510030001	Exception in EnvelopeEDIFACTServiceImpl
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception2=000510030002	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_str1=000510030003	Document has not been processed by the EDI Encoder service
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception3=000510030004	Exception while looking up a contract
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception4=000510030005	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception5=000510030006	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception6=000510030007	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception7=000510030008	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception8=000510030009	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception9=000510030010	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception10=000510030011	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception11=000510030012	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception12=000510030013	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception13=000510030014	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception14=000510030015	Exception while enveloping document
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_info=000510030016	{0}
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception15=000510030017	Exception attempting to close output or input streams in EnvelopeEDIFACT .envelope()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACT ServiceImpl_exception16=000510030018	EDIFACTEnvelopeServiceImpl - Error loading control number

Message Code	Log Message
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception17=000510030019	EDIFACTEnvelopeServiceImpl - Error loading control number
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception18=000510030020	EDIFACTEnvelopeServiceImpl - Error loading control number
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception19=000510030021	Exception in EDIFACTSecurity.buildNonRepudiationOfOrigin()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception20=000510030022	Exception in EDIFACTSecurity.buildNonRepudiationOfOrigin()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_str2=000510030023	EnvelopeEDIFACT.createOutboundInterchange(): No transaction count available
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception21=000510030024	[EDIFACT Envelope Service] Error saving correlations.
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception22=000510030025	Exception attempting to close output or input streams in EnvelopeEDIFACT .createOutboundInterchange()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception23=000510030026	EnvelopeEDIFACTServiceImpl - Exception loading outbound envelope values from correlations
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_ControlNumberNames1=000510030027	EnvelopeEDIFACTServiceImpl - Error generating control number names -{0}
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_ControlNumberNames2=000510030028	EnvelopeEDIFACTServiceImpl - Error generating control number names - {0}
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception24=000510030029	EnvelopeEDIFACTServiceImpl - Error loading WFD
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception25=000510030030	EnvelopeEDIFACT.loadUNBEnvelopeParms()
EDI.EDI_EDIFACTENVELOPING.ERR_EnvelopeEDIFACTServiceImpl_exception26=000510030031	EnvelopeEDIFACTService] exception: Cannot update the requiresEnvelope correlation because the document cannot be found.

## EDI Encoding System Log Messages

The following system log messages are used for EDI encoding:

Message Code	Log Message
EDI.EDI_ENCODING.ERR_EDIEncoder_str1=000510070001	Mandatory parameter <AcceptorLookupAlias> is missing.
EDI.EDI_ENCODING.ERR_EDIEncoder_str2=000510070002	Mandatory parameter <SenderID> is missing
EDI.EDI_ENCODING.ERR_EDIEncoder_str3=000510070003	Mandatory parameter <ReceiverID> is missing
EDI.EDI_ENCODING.ERR_EDIEncoder_str4=000510070004	EnvelopeGeneric.envelope() starting...
EDI.EDI_ENCODING.ERR_EDIEncoder_str5=000510070014	EDIEncoder: Couldn't find the envelope
EDI.EDI_ENCODING.ERR_EDIEncoder_str6=000510070015	EDIEncoder: Envelope lookup returned multiple envelopes
EDI.EDI_ENCODING.ERR_EDIEncoder_str7=000510070016	EDIEncoder: Ambiguous ISA/EDIFACT envelopes.

Message Code	Log Message
EDI.EDI_ENCODING.ERR_EDIEncoder_exception1=000510070005	Exception in EDIEncode
EDI.EDI_ENCODING.ERR_EDIEncoder_exception2=000510070006	Exception in EDIEncode
EDI.EDI_ENCODING.ERR_EDIEncoder_exception3=000510070007	Exception in EDIEncode
EDI.EDI_ENCODING.ERR_EDIEncoder_exception4=000510070008	Exception in EDIEncode
EDI.EDI_ENCODING.ERR_EDIEncoder_exception5=000510070009	EDIEncoder: Couldn't find the envelope
EDI.EDI_ENCODING.ERR_EDIEncoder_exception6=000510070010	EDIEncoder: Envelope lookup returned multiple envelopes
EDI.EDI_ENCODING.ERR_EDIEncoder_exception7=000510070011	EDIEncoder: Ambiguous ISA/EDIFACT envelopes.
EDI.EDI_ENCODING.ERR_EDIEncoderServiceImpl_exception1=000510070012	Error during EDI Encoding process
EDI.EDI_ENCODING.ERR_EDIEncoderServiceImpl_exception2=000510070013	Error during EDI Encoding process
EDI.EDI_ENCODING.DEB_EDIEncoder_AddingEnvelope1=000520070002	EDIEncoder adding envelope {0}
EDI.EDI_ENCODING.DEB_EDIEncoder_AddingEnvelope2=000520070003	EDIEncoder adding envelope {0}
EDI.EDI_ENCODING.DEB_EDIEncoder_str1=000520070004	EDIEncoder processData() ending...
EDI.EDI_ENCODING.DEB_EDIEncoderServiceImpl_str1=000520070005	EDI Encoder processData() starting...
EDI.EDI_ENCODING.DEB_EDIEncoderServiceImpl_str2=000520070006	EDIEncoder processData() ending...

## EDI Enveloping System Log Messages

The following system log messages are used for EDI enveloping:

Message Code	Log Message
EDI.EDI_ENVELOPING.DEB_EDIEnvelope ServiceImpl_start=000520080001	[EDIEnvelope] processData() starting...
EDI.EDI_ENVELOPING.DEB_EDIEnvelope ServiceImpl_end=000520080002	[EDIEnvelope] processData() ending...
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_exception1=000510080001	EDIEnvelopeService: bad workflow id {0}
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_str1=000510080002	No document to envelope
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_exception2=000510080003	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_str2=000510080004	Document has not been processed by the EDI Encoder service
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_exception3=000510080005	[EDIEnvelope] Error in Correlation
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_NoEnvelopingProcessDefined=000510080006	No enveloping process defined for {0}
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_NoWorkflowProcessDefined=000510080007	[EDIEnvelope] no workflow defined for {0}
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_InvalidParmForWFD_NAME=000510080008	EDIEnvelopeServiceEJBBean.processData() invalid parm for WFD_NAME {0} (no matching found)

Message Code	Log Message
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_exception3=000510080009	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_exception4=000510080010	[EDIEnvelope] unable to load document, skipping {0}
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_exception5=000510080011	[EDIEnvelope] unable to update RequiresEnvelope to " {0} for document'{1}'. This document will be picked up again by EDIDeenvelope Deferred
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_unableToUpdateRequiresEnvelope=000510080012	[EDIEnvelope] unable to update RequiresEnvelope to " {0} for document'{1}'. This document will be picked up again by EDIDeenvelope Deferred
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_str3=000510080013	No document to envelope
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_exception6=000510080014	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_str4=000510080015	Document has not been processed by the EDI Encoder service
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_noWorkflowDefined=000510080016	[EDIEnvelope] no workflow defined for {0}
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_invalidWFD_NAME=000510080017	EDIEnvelope.processDocuments() invalid parm for WFD_NAME {0} (no matching id found)
EDI.EDI_ENVELOPING.ERR_EDIEnveloper_exception7=000510080018	A SQL Exception occurred while retrieving the document extension.
EDI.EDI_ENVELOPING.ERR_EDIEnvelopeServiceImpl_exception8=000510080019	[EDIEnvelope] unable to get a JDBC connection
EDI.EDI_ENVELOPING.ERR_EDIEnvelopeServiceImpl_exception9=000510080020	[EDIEnvelope] encountered a SQL exception
EDI.EDI_ENVELOPING.ERR_EDIEnvelopeServiceImpl_exception10=000510080021	[EDIEnvelope] unable to start workflow
EDI.EDI_ENVELOPING.INFO_EDIEnveloper_UpdatedRequiresEnvelope=000540080001	Updated RequiresEnvelope to -100 for CORRELATION_ID \= {0} who se document (OBJECT_ID\= {1}) does not exist

## EDI Post-processing System Log Messages

The following system log messages are used for EDI post-processing:

Message Code	Log Message
EDI.EDI_POSTPROCESSING.DEB_EDIPostProcessorServiceImpl_start=000520090001	SequenceCheck processData() starting...
EDI.EDI_POSTPROCESSING.DEB_EDIPostProcessorServiceImpl_end=000520090002	SequenceCheck processData() ending...
EDI.EDI_POSTPROCESSING.DEB_EDIPostProcessorServiceImpl_EDIPostProcessor1=000520090003	[EDIPostProcessor:{0}] Failed to load document with id '{1} '. SQLException: {2}
EDI.EDI_POSTPROCESSING.DEB_EDIPostProcessorServiceImpl_EDIPostProcessor2=000520090004	[EDIPostProcessor:{0}] Failed to load document with id '{1} '. DocumentNotFoundException: {2}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception1=000510090001	EDIPostProcessorServiceImpl - Error retrieving document with id " {0}

Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception2=000510090002	EDIPostProcessorServiceImpl - error removing interchange from sequence check queue.
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception3=000510090003	EDIPostProcessorServiceImpl - Error storing updated control number for envelope.
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception4=000510090004	EDIPostProcessorServiceImpl - Error storing updated control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception5=000510090005	EDIPostProcessorServiceImpl - An EDI error occurred
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception6=000510090006	SequenceCheckService error
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception7=000510090007	EDIPostProcessorServiceImpl - Error creating 997.
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception8=000510090008	EDIPostProcessorServiceImpl - Error EDI encoding 997 document for group control no. {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception9=000510090009	EDI Post Processor - Error generating TA1
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception10=000510090010	EDI Post Processor - Error enveloping 997
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception11=000510090011	EDI Post Processor - Error generating TA1
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception12=000510090012	EDIPostProcessorServiceImpl - Error creating CONTRL.
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception13=000510090013	EDIPostProcessorServiceImpl - Error enveloping CONTRL message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception14=000510090014	EDIPostProcessorServiceImpl - Error EDI encoding CONTRL document for interchange control no.{0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception15=000510090015	EDI Post Processor Service - Error loading control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception16=000510090016	EDIPostProcessorServiceImpl - Error loading interchange control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception17=000510090017	EDIPostProcessorServiceImpl - Error loading Control Number History for
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception18=000510090018	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception19=000510090019	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception20=000510090020	EDIPostProcessorServiceImpl - TransactionRegisterException occurred while trying to save Control Number History for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception21=000510090021	EDIPostProcessorServiceImpl - SQLException occurred while trying to save Control Number History for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception22=000510090022	EDI Post Processor Service - Error loading control number



Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception23=000510090023	EDIPostProcessorServiceImpl - Error loading group control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception24=000510090024	EDIPostProcessorServiceImpl - SQLException while trying to load control number history for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception25=000510090025	EDIPostProcessorServiceImpl - TransactionRegisterException while trying to save control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception26=000510090026	[EDIPostProcessorService: {0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception27=000510090027	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception28=000510090028	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception29=000510090029	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception30=000510090030	EDI Post Processor Service - Error loading control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception31=000510090031	EDIPostProcessorServiceImpl - Error loading interchange control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception32=000510090032	EDIPostProcessorServiceImpl - Error loading control number history data for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception33=000510090033	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception34=000510090034	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception35=000510090035	EDIPostProcessorServiceImpl - TransactionRegisterException occurred while trying to save Control Number History for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception36=000510090036	EDIPostProcessorServiceImpl - SQLException occurred while trying to save Control Number History for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception37=000510090037	EDI Post Processor Service - Error loading control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception38=000510090038	EDIPostProcessorServiceImpl - Error loading group control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception39=000510090039	EDIPostProcessorServiceImpl - SQLException while trying to load control number history for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception40=000510090040	EDIPostProcessorServiceImpl - TransactionRegisterException while trying to save control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception41=000510090041	[EDIPostProcessorService: {0}]

Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception42=000510090042	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception43=000510090043	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception44=000510090044	EDI Post Processor Service - Error loading control number
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception45=000510090045	EDIPostProcessorServiceImpl - Error loading transaction control number for envelope {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception46=000510090046	EDIPostProcessorServiceImpl - Error loading control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception47=000510090047	Exception
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception48=000510090048	Exception
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception49=000510090049	EDIPostProcessorServiceImpl - TransactionRegisterException while adding control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception50=000510090050	EDIPostProcessorServiceImpl - SQLException while adding control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception51=000510090051	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception52=000510090052	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception53=000510090053	EDIPostProcessorServiceImpl - Error reconciling 997
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception54=000510090054	EDIPostProcessorServiceImpl - Error loading CONTRL to reconcile
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception55=000510090055	EDIPostProcessorServiceImpl - Error loading CONTRL to reconcile
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception56=000510090056	[EDIPostProcessorService: {0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception57=000510090057	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception58=000510090058	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception59=000510090059	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception60=000510090060	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception61=000510090061	[EDIPostProcessorService:{0}]
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception62=000510090062	EDIPostProcessorServiceImpl - Error saving correlation data
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception63=000510090063	[EDIPostProcessorService:{0}]

Message Code	Log Message
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception64=000510090064	EDIPostProcessorServiceImpl - Error reconciling 997
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception65=000510090065	EDIPostProcessorServiceImpl - Error retrieving transaction document with id {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception66=000510090066	EDIPostProcessorServiceImpl - Error retrieving transaction document with id {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception67=000510090067	EDIPostProcessorServiceImpl - Error loading control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception68=000510090068	EDIPostProcessorServiceImpl - TransactionRegisterException while adding control number history for {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception69=000510090069	EDIPostProcessorServiceImpl - Error retrieving transaction document with id {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception70=000510090070	EDIPostProcessorServiceImpl - Error retrieving transaction document with id {0}
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception71=000510090071	EDIPostProcessorServiceImpl - IO error extracting non-compliant transaction from batch
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception72=000510090072	EDIPostProcessorServiceImpl - Error enveloping TA1
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception73=000510090073	EDI Post Processor Service unable to create develope process to child process workflow linkage
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_exception74=000510090074	EDI Post Processor Service unable to start workflow
EDI.EDI_POSTPROCESSING.ERR_EDIPostProcessorServiceImpl_InterchangeComplianceReport=000510090075	EDIPostProcessorServiceImpl - Error retrieving InterchangeCompliance Report for document {0}

## EDI Report System Log Messages

The following system log messages are used for the EDI report:

Message Code	Log Message
EDI.EDI_REPORT.ERR_ReportEntry_exception1=000510170001	Exception
EDI.EDI_REPORT.ERR_CompilanceReport_exception2=000510170002	Exception
EDI.EDI_REPORT.ERR_EntryInfo_exception3=000510170003	Exception

## Field Processor Translation System Log Messages

The following system log messages are used for field processor translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_FIELDPROCESSOR.ERR_PositionalInputFieldHandler_exception1=000610080001	Translator Positional Field Handler Error

Message Code	Log Message
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_PositionalInputFieldHandler_exception2=000610080002	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_PositionalInputFieldHandler_exception3=000610080003	Translator Positional Field Handler Error
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SQLInputFieldHandler_exception1=000610080004	TRANSLATOR: SQL Exception while getting {0} from result of {1}
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTInputFieldHandler_exception1=000610080005	TRANSLATOR: Error building
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTInputFieldHandler_exception2=000610080006	TRANSLATOR: The field syntax is not valid. block data using encoding.The default encoding will be used.
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTInputFieldHandler_exception3=000610080007	TRANSLATOR: Data conversion exception.
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTOutputFieldHandler_str1=000610080008	TRANSLATOR: SWIFTOutputFieldHandler handled ClassCastException for packed decimal processing.
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTOutputFieldHandler_exception1=000610080009	TRANSLATOR: Error building block data using encoding. The default encoding will be used.
TRANSLATION.TRANSLATION_FIELDPROCESSOR. ERR_SWIFTOutputFieldHandler_exception2=000610080010	TRANSLATOR: Data conversion exception.

## Generate 997 System Log Messages

The following system log messages are used when generating 997 acknowledgements:

Message Code	Log Message
EDI.EDI_GENERATE997.DEB_Generate997 ServiceImpl_start=000520110001	Generate997 processData() starting...
EDI.EDI_GENERATE997.DEB_Generate997 ServiceImpl_end=000520110002	Generate997 processData() ending..
EDI.EDI_GENERATE997.ERR_Generate997 ServiceImpl_start=000510110001	Generate997ServiceImpl.processData() A SQL Exception occurred while retrieving the document extension
EDI.EDI_GENERATE997.ERR_Generate997 ServiceImpl_exception1=000510110002	Exception in Generate997ServiceImpl

## Generate TA1 Acknowledgement System Log Messages

The following system log messages are used when generating TA1 acknowledgements:

Message Code	Log Message
EDI.EDI_GENERATETA1.DEB_GenerateTA1 ServiceImpl_start=000520130001	GenerateTA1 processData() starting...
EDI.EDI_GENERATETA1.DEB_GenerateTA1 ServiceImpl_end=000520130002	GenerateTA1 processData() ending...
EDI.EDI_GENERATETA1.ERR_TA1_InfoEntry=000510130001	TA1: ComplianceReport contains unknown information entry: {0}

Message Code	Log Message
EDI.EDI_GENERATETA1.ERR_ GenerateTA1ServiceImpl_str1=000510130002	GenerateTA1 processData() A SQL Exception occurred while retrieving the document extension
EDI.EDI_GENERATETA1.ERR_ GenerateTA1ServiceImpl_exception1=000510130003	Caught exception in GenerateTA1ServiceEJBBean.processData():
EDI.EDI_GENERATETA1.ERR_ GenerateTA1ServiceImpl_exception2=000510130004	Caught exception in GenerateTA1ServiceEJBBean.processData():

## Generic Deenveloping System Log Messages

The following system log messages are used for generic deenveloping:

Message Code	Log Message
EDI.EDI_GENERICDEENVELOPING. DEB_DeenvelopeGenericServiceImpl_str1=000520060001	DeenvelopeGeneric processData() starting...
EDI.EDI_GENERICDEENVELOPING.DEB_ DeenvelopeGenericServiceImpl_mapName=000520060002	TranslationServiceEJBBean map_name is {0}
EDI.EDI_GENERICDEENVELOPING.DEB_ DeenvelopeGenericServiceImpl_str2=000520060003	DenvelopeGeneric processData() ending...
EDI.EDI_GENERICDEENVELOPING.DEB_ DeenvelopeGenericServiceImpl_EntityID=000520060004	Sender Entity ID: {0}, Receiver Entity ID\.: {1}
EDI.EDI_GENERICDEENVELOPING.DEB_ DeenvelopeGenericServiceImpl_ExceptionFindingContract1=000520060005	[DeenvelopeGeneric] Exception finding contract {0}
EDI.EDI_GENERICDEENVELOPING.DEB_ DeenvelopeGenericServiceImpl_ExceptionFindingContract2=000520060006	[DeenvelopeGeneric] Exception finding contract {0}
EDI.EDI_GENERICDEENVELOPING.ERR_ DeenvelopeGenericServiceImpl_exception1=000510060001	Exception while looking up a contract
EDI.EDI_GENERICDEENVELOPING.ERR_ DeenvelopeGenericServiceImpl_str1=000510060002	Unable to find Envelope
EDI.EDI_GENERICDEENVELOPING.ERR_ DeenvelopeGenericServiceImpl_DuplicateControlNumber=000510060003	Duplicate Control Number encountered {0}
EDI.EDI_GENERICDEENVELOPING.ERR_ DeenvelopeGenericServiceImpl_ControlNumberHistory=000510060004	Error while adding control number history to database. {0}
EDI.EDI_GENERICDEENVELOPING.ERR_ DeenvelopeGenericServiceImpl_ControlNumberOutOfSequence=000510060005	Control Number Out of Sequence: expected {0}, received {1}
EDI.EDI_GENERICDEENVELOPING.ERR_ DeenvelopeGenericServiceImpl_exception2=000510060006	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception3=000510060007	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception4=000510060008	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception5=000510060009	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception6=000510060010	Exception while de-enveloping
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception7=000510060011	Exception while de-enveloping

Message Code	Log Message
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception8=000510060012	Exception while unlocking control number
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception9=000510060013	Exception while unlocking envelope
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_str2=000510060014	Unable to match Envelope
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_str3=000510060015	Unable to match Envelope, lookup returned multiple envelopes
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception10=000510060016	Exception
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception11=000510060017	Exception
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception12=000510060018	[DeenvelopeGenericServiceImpl] Exception finding contract
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception13=000510060019	[DeenvelopeGenericServiceImpl] loadEnvelopeParms
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception14=000510060020	SQL Error generating map name
EDI.EDI_GENERICDEENVELOPING.ERR_DeenvelopeGenericServiceImpl_exception15=000510060021	License error
EDI.EDI_GENERICDEENVELOPING.INFO_DeenvelopeGenericServiceImpl_MapObjectForMap=000540060001	Unable to load MapObject for map\{: {0}

## Generic Enveloping System Log Messages

The following system log messages are used for generic enveloping:

Message Code	Log Message
EDI.EDI_GENERICENVELOPING.DEB_EnvelopeGenericServiceImpl_str1=000520050001	EnvelopeGeneric.envelope() starting...
EDI.EDI_GENERICENVELOPING.DEB_EnvelopeGenericServiceImpl_str2=000520050002	EnvelopeGeneric.envelope() ending...
EDI.EDI_GENERICENVELOPING.DEB_EnvelopeGenericServiceImpl_str3=000520050003	EnvelopeGeneric.applyOuterEnvelope() starting...
EDI.EDI_GENERICENVELOPING.DEB_EnvelopeGenericServiceImpl_str4=000520050004	EnvelopeGeneric.applyOuterEnvelope() ending..
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_str1=000510050001	EnvelopeGenericServiceImpl.envelope(): A SQL Exception occurred while retrieving the document extension.
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_str2=000510050002	Document has not been processed by the EDI Encoder service
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_str3=000510050013	Generic Envelope Service: Error during enveloping or pre-envelope translation.
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception1=000510050003	EnvelopeGeneric.envelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception2=000510050004	EnvelopeGeneric.envelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception3=000510050005	EnvelopeGeneric.envelope() encountered exception

Message Code	Log Message
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception4=000510050006	Exception while looking up a contract
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception5=000510050007	EnvelopeGenericServiceImpl.envelope() A SQL Exception occurred while retrieving the document extension
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception6=000510050008	EnvelopeGenericServiceImpl.envelope() A SQL Exception occurred while retrieving the document extension
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception7=000510050009	Exception while looking up a contract
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception8=000510050010	EnvelopeGeneric.applyOuterEnvelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception9=000510050011	EnvelopeGeneric.applyOuterEnvelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception10=000510050012	EnvelopeGeneric.applyOuterEnvelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception11=000510050014	Exception while enveloping document
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception12=000510050015	Exception while enveloping document
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception13=000510050016	EnvelopeGeneric.envelope() encountered exception
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_exception14=000510050017	EnvelopeGenericServiceImpl.envelope() encountered a License error
EDI.EDI_GENERICENVELOPING.ERR_EnvelopeGenericServiceImpl_invalidWorkflowName=000510050018	EnvelopeGenericServiceImpl.spawnBusProcess(): invalid workflow name {0} (no matching id found)
EDI.EDI_GENERICENVELOPING.INFO_EnvelopeGenericServiceImpl_type=000540050001	***** type \= {0}
EDI.EDI_GENERICENVELOPING.INFO_EnvelopeGenericServiceImpl_standard=000540050002	***** type \= {0}

## JDBC Translation System Log Messages

The following system log messages are used for JDBC translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_exception1=000610020001	Required 'map_name' parameter not found
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_str1=000610020002	Unable to load MapObject for map: {0}
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_str2=000610020003	Unable to load TranslationObject for map: {0}
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_MapObject=000610020004	{0} is not a valid SQL map file
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_TranslationObject=000610020005	Exception trying to start business process:{0}
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_SQLmap=000610020006	Caught TranslationException in processData():

Message Code	Log Message
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_exception2=000610020007	Caught exception in processData():
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_exception3=000610020008	JDBC query returns no data
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_exception4=000610020009	There are more rows remaining in the ResultSet of the SQL query
TRANSLATION.TRANSLATION_JDBC.ERR_JdbcAdapaterImpl_str3=000610020010	Exception
TRANSLATION.TRANSLATION_JDBC.WAR_JdbcAdapaterImpl_str1=000630020001	Exception
TRANSLATION.TRANSLATION_JDBC.ERR_JDBCService_exception1=000610020011	Exception
TRANSLATION.TRANSLATION_JDBC.ERR_JDBCService_exception2=000610020012	Exception

## Overdue Acknowledgement System Log Messages

The following system log messages are used for overdue acknowledgements:

Message Code	Log Message
EDI.EDI_OVERDUEACK.DEB_OverdueAckServiceImpl_start=000520140001	OverdueAck] processData() starting...
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception1=000510140001	[OverdueAck] exception finding overdue ack documents
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception2=000510140002	OverdueAck] exception finding overdue ack documents
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception3=000510140003	[OverdueAck] exception
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception4=000510140004	[OverdueAck] Unable to load document
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_FindingQuery=000510140005	Error finding named query {0} in db pool {1}
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception5=000510140006	[OverdueAckServiceImpl] Error in Correlation
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception6=000510140007	[OverdueAckServiceImpl] Error in Correlation
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_str1=000510140008	OverdueAck setOverdueAckByDocState() A SQL Exception occurred while retrieving the document extension.
EDI.EDI_OVERDUEACK.ERR_OverdueAckServiceImpl_exception7=000510140009	Caught exception

## Reconcile 997 Acknowledgement System Log Messages

The following system log messages are used for ASC X12 997 acknowledgement reconciliation:



Message Code	Log Message
EDI.EDI_RECONCILE997.DEB_Reconcile997_str1=000520150001	[Reconcile997] Processing 997
EDI.EDI_RECONCILE997.DEB_Reconcile997_str2=000520150002	[Reconcile997] Reconciling group
EDI.EDI_RECONCILE997.DEB_Reconcile997_str3=000520150003	[Reconcile997] Reconciling transaction set
EDI.EDI_RECONCILE997.DEB_Reconcile997_ackstatus=000520150004	[Reconcile997] Updated ackstatus of document {0}
EDI.EDI_RECONCILE997.DEB_Reconcile997ServiceImpl_start=000520150005	[Reconcile997] processData() starting...
EDI.EDI_RECONCILE997.DEB_Reconcile997ServiceImpl_end=000520150006	[Reconcile997] processData() ending...
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception1=000510150001	Reconcile997 - Exception while reconciling 997
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception2=000510150002	Reconcile997 - SQL Exception while reconciling 997
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception3=000510150003	Reconcile997 IOException while trying to close streams
EDI.EDI_RECONCILE997.ERR_Reconcile997_str1=000510150004	[Reconcile997] Could not find AK1
EDI.EDI_RECONCILE997.ERR_Reconcile997_str2=000510150005	[Reconcile997] Could not find AK9
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception4=000510150006	[Reconcile997] Exception while reconciling group
EDI.EDI_RECONCILE997.ERR_Reconcile997_str3=000510150007	Reconcile997.updateGroupDocState(...) A SQL Exception occurred while retrieving the document extension.
EDI.EDI_RECONCILE997.ERR_Reconcile997_GroupDetails=000510150008	[Reconcile997] Unable to reconcile 997 group details {0}
EDI.EDI_RECONCILE997.ERR_Reconcile997_str4=000510150009	[Reconcile997] Unable to reconcile 997 group details
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception6=000510150010	[Reconcile997] Unable to load document
EDI.EDI_RECONCILE997.ERR_Reconcile997ServiceImpl_exception6=000510150011	[Reconcile997] Exception while reconciling 997
EDI.EDI_RECONCILE997.WAR_Reconcile997_MutipleDocuments=000530150001	[Reconcile997] Multiple documents found when one expected for {0}
EDI.EDI_RECONCILE997.ERR_Reconcile997_exception5=000510150012	[Reconcile997] Error in Correlation

## Reconcile CONTRL Acknowledgement System Log Messages

The following system log messages are used for EDIFACT CONTRL acknowledgement reconciliation:

Message Code	Log Message
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str1=000520160001	ReconcileCONTROL] Processing CONTRL

Message Code	Log Message
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str2=000520160002	ReconcileCONTRLServiceEJBBean Processing UCI
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str3=000520160003	ReconcileCONTRLServiceEJBBean Reconciling UCI
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str4=000520160004	[ReconcileCONTRL] Reconciling group
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_str5=000520160005	[ReconcileCONTRL] Reconciling message
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_ackstatus=000520160006	ReconcileCONTRL Updated ackstatus of document
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROL_ackstatus2=000520160007	[ReconcileCONTRL] Updated ackstatus of document
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROLServiceImpl_start=000520160008	[ReconcileCONTRL] processData() starting...
EDI.EDI_RECONCILECONTROL.DEB_ReconcileCONTROLServiceImpl_end=000520160009	[ReconcileCONTRL] processData() ending...
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception1=000510160001	[ReconcileCONTRL] Exception while reconciling CONTRL
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception2=000510160002	[ReconcileCONTRL] SQL Exception while reconciling CONTRL
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception3=000510160003	[ReconcileCONTRL] IOException while trying to close streams
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_CONTRLmessage=000510160004	[ReconcileCONTRL] Unrecognized segment in CONTRL message:
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_str1=000510160005	[ReconcileCONTRL] Could not find UCI
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception4=000510160006	[ReconcileCONTRL] Exception while reconciling interchange
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception5=000510160007	[ReconcileCONTRL] Exception while reconciling group
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception6=000510160008	[ReconcileCONTRL] Error updating correlation
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception7=000510160009	[ReconcileCONTRL] Error updating correlation
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_str2=000510160010	ReconcileCONTRL.updateInterchange DocState(...) A SQL Exception occurred
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_UCI1=000510160011	[ReconcileCONTRL] Unable to reconcile UCI {0}
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_UCI2=000510160012	[ReconcileCONTRL] Unable to reconcile UCI {0}
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception8=000510160013	ReconcileTA1ServiceEJBBean Unable to load document
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_str3=000510160014	ReconcileCONTRL.updateGroupDocState(...) A SQL Exception occurred
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_exception9=000510160015	ReconcileTA1ServiceEJBBean Unable to load document
EDI.EDI_RECONCILECONTROL.ERR_ReconcileCONTROL_CONTRLgroupDetails1=000520160016	[ReconcileCONTRL] Unable to reconcile CONTRL group details {0}

Message Code	Log Message
EDI.EDI_RECONCILECONTROL.ERR_ ReconcileCONTROL_CONTRLgroupDetails2=000520160017	[ReconcileCONTRL] Unable to reconcile CONTRL group
EDI.EDI_RECONCILECONTROL.WAR_ ReconcileCONTROL_MulitpleDocuments1=000530160001	[ReconcileCONTRL] Multiple documents found when one expected for {0}
EDI.EDI_RECONCILECONTROL.WAR_ ReconcileCONTROL_MulitpleDocuments2=000530160002	[ReconcileCONTRL] Multiple documents found when one expected for {0}

## Report Translation System Log Messages

The following system log message is used for report translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_REPORT.ERR_TranslationReport_ exception1=000610090001	[Translator] Exception parsing translation report entry limit property

## Standards Translation System Log Messages

The following system log messages are used for standards translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_STANDARD. DEB_TranslationServiceImpl_str1=000620010001	[TranslationServiceImpl] processData() starting...
TRANSLATION.TRANSLATION_STANDARD. DEB_TranslationServiceImpl_str2=000620010002	[TranslationServiceImpl] map_name is {0}
TRANSLATION.TRANSLATION_STANDARD. DEB_TranslationServiceImpl_largeFileSupport=000620010003	[TranslationServiceImpl] large file support \= {0}
TRANSLATION.TRANSLATION_STANDARD. DEB_TranslationServiceImpl_TranslationReport= 000620010004TRANSLATION.TRANSLATION_STANDARD.DEB _TranslationServiceImpl_TranslationReport=000620010004	Translation Report: {0} {1}
TRANSLATION.TRANSLATION_STANDARD. DEB_TranslationServiceImpl_str3=000620010005	[TranslationServiceImpl] processData() completed ...
TRANSLATION.TRANSLATION_STANDARD.ERR _TranslationServiceImpl_exception1=000610010001	{0} {1} is not valid
TRANSLATION.TRANSLATION_STANDARD.ERR _TranslationServiceImpl_SOAPAttachment=000610010002	Caught exception while attempting to load map \ SOAPAttachment1 \ for MapTest in TranslationServiceImpl::processData:
TRANSLATION.TRANSLATION_STANDARD.ERR _TranslationServiceImpl_exception2=000610010003	[TranslationService] Tracking error. It will be ignored
TRANSLATION.TRANSLATION_STANDARD.ERR _TranslationServiceImpl_exception3=000610010004	Caught exception in TranslationServiceEJBBean.processData():
TRANSLATION.TRANSLATION_STANDARD.ERR _TranslationServiceImpl_exception4=000610010005	Caught exception in TranslationServiceEJBBean.processData():
TRANSLATION.TRANSLATION_STANDARD.ERR _TranslationServiceImpl_exception5=000610010006	Caught exception in TranslationServiceEJBBean.processData():
TRANSLATION.TRANSLATION_STANDARD.ERR _TranslationServiceImpl_exception6=000610010007	Caught exception closing input stream
TRANSLATION.TRANSLATION_STANDARD.ERR _TranslationServiceImpl_exception7=000610010008	Caught exception closing output stream

Message Code	Log Message
TRANSLATION.TRANSLATION_STANDARD.LOG _TranslationServiceImpl_str1=000640010001	Unable to load \"SOAPAttachment\" for MapTest.
TRANSLATION.TRANSLATION_STANDARD.LOG _TranslationServiceImpl_MapObject=000640010002	Unable to load MapObject for map:{0}
TRANSLATION.TRANSLATION_STANDARD.LOG _TranslationServiceImpl_str2=000640010003	There is no Primary Document

## TA1 Acknowledgement Reconciliation System Log Messages

The following system log messages are used for TA1 acknowledgement reconciliation:

Message Code	Log Message
EDI.EDI_TA1RECONCILER.DEB_ReconcileTA1ServiceImpl _start=000520100001	ReconcileTA1ServiceImpl processData() starting...
EDI.EDI_TA1RECONCILER.DEB_ReconcileTA1ServiceImpl _str1=000520100002	ReconcileTA1ServiceImpl No TA1s to reconcile
EDI.EDI_TA1RECONCILER.DEB_ReconcileTA1ServiceImpl _str2=000520100003	ReconcileTA1ServiceImpl Found TA1 document to reconcile
EDI.EDI_TA1RECONCILER.DEB_ReconcileTA1ServiceImpl _end=000520100004	ReconcileTA1ServiceImpl processData() ending...
EDI.EDI_TA1RECONCILER.DEB_TA1Reconciler _str3=000520100005	TA1Reconciler Found TA1 document to reconcile
EDI.EDI_TA1RECONCILER.DEB_TA1Reconciler _str4=000520100006	ReconcileTA1ServiceImpl Processing TA1
EDI.EDI_TA1RECONCILER.DEB_TA1Reconciler _str5=000520100007	ReconcileTA1ServiceImpl Reconciling TA1
EDI.EDI_TA1RECONCILER.DEB_TA1Reconciler _AckstatusOfDocument=000510100008	ReconcileTA1 Updated ackstatus of document {}
EDI.EDI_TA1RECONCILER.ERR_ReconcileTA1ServiceImpl _exception1=000510100001	Exception
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler _exception2=000510100002	ReconcileTA1ServiceEJBBean Exception while reconciling TA1s
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler _exception3=000510100003	ReconcileTA1ServiceEJBBean Exception while reconciling TA1s
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler _exception4=000510100004	[TA1Reconciler] Error in Correlation
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler tr1=000510100005	TA1Reconciler.updateInterchangeDocState(...) A SQL Exception occurred while retrieving the document extension.
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler _str2=000510100006	ReconcileTA1ServiceEJBBean Unable to reconcile TA1 {}
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler _str3=000510100007	ReconcileTA1ServiceEJBBean Unable to reconcile TA1 {}
EDI.EDI_TA1RECONCILER.ERR_TA1Reconciler _exception5=000510100008	ReconcileTA1ServiceEJBBean Unable to load document
EDI.EDI_TA1RECONCILER.WAR_TA1Reconciler _str1=000530100001	[ReconcileTA1] Multiple documents found when one expected for

## Translation Engine System Log Messages

The following system log messages are used for the translation rules:

Message Code	Log Message
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngine_LargeFile=000620070001	translation large file support threshold \= {0}
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngine_str1=000720060002	translation large file support threshold not present in properties, setting to 1
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngine_fileSize=000620070003	input file size \= {0}
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngine_duration=000620070004	execution time \= {0} seconds
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngine_duration2=000620070005	execution time \= {0} seconds
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_map=000620070017	Translating using map {0} ...
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_str1=000620070006	Translation complete
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_str2=000620070007	Reading input...
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_str3=000620070008	Writing output...
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_ExecutionTime=000620070009	finished input translation phase - execution time {0} seconds
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_NumberEntries=000620070010	number entries paged in \={0}
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_NumberEntries2=000620070011	number entries paged out \={0}
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_NumberSort=000720060012	number sorts \=0
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_executionTime2=000620070013	finished output translation phase - execution time {0} seconds
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_numberEntries2=000620070014	number entries paged in \= {0}
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_numberEntries3=000620070015	number entries paged out \= {0}
TRANSLATION.TRANSLATION_ENGINE.DEB _TranslationEngineImpl_numberSorts2=000620070016	number sorts \={0}

## Translation Object System Log Messages

The following system log messages are used for translation objects:

Message Code	Log Message
TRANSLATION.TRANSLATION_TRANSLATIONOBJECT.ERR _Constants_exception1=000610120001	Translator: access to invalid constant
TRANSLATION.TRANSLATION_TRANSLATIONOBJECT.ERR _SyntaxManager_className=000610120002	TRANSLATOR: invalid syntax factory {0}
TRANSLATION.TRANSLATION_TRANSLATIONOBJECT.ERR _SyntaxManager_exception1=000610120003	TRANSLATOR: error loading syntax factory {0}

Message Code	Log Message
TRANSLATION.TRANSLATION_TRANSLATIONOBJECT.DEB _TranslationObject_str1=000620120001	TranslationObject.initialize(String) is now deprecated, you may remove this call

## Translation Rules System Log Messages

The following system log messages are used for the translation rules:

Message Code	Log Message
TRANSLATION.TRANSLATION_RULES.ERR_BasicOpcodes _exception1=000610100001	TRANSLATOR: missing opcode implementation
TRANSLATION.TRANSLATION_RULES.ERR_BasicOpcodes _exception2=000610100002	TRANSLATOR: SLEEP opcode interrupted
TRANSLATION.TRANSLATION_RULES.ERR_BasicOpcodes _exception3=000610100003	TRANSLATOR: SLEEP opcode interrupted
TRANSLATION.TRANSLATION_RULES.ERR_DBOpcodes _exception1=000610100004	TRANSLATOR: SLEEP opcode interrupted
TRANSLATION.TRANSLATION_RULES.ERR_dateOpcodes _exception1=000610100005	TRANSLATOR: missing opcode implementation
TRANSLATION.TRANSLATION_RULES.ERR_ExtendedRuleExecuter _str1=000610100006	Translator extended rule InvocationTargetException - see appserver log for stack trace
TRANSLATION.TRANSLATION_RULES.ERR_ExtendedRuleExecuter _exception1=000610100007	Translator extended rule IllegalAccessException
TRANSLATION.TRANSLATION_RULES.ERR_ExtendedRuleExecuter _NoMethod=000610100008	Translator extended rule NoSuchMethodError {0}
TRANSLATION.TRANSLATION_RULES.ERR_ExtendedRuleExecuter _exception2=000610100009	Translator extended rule NullPointerException
TRANSLATION.TRANSLATION_RULES.ERR_IOOpcodes _exception1=000610100010	TRANSLATOR: missing opcode implementation
TRANSLATION.TRANSLATION_RULES.ERR_IOOpcodes _exception2=000610100011	TRANSLATION.TRANSLATION_RULES. ERR_IOOpcodes_exception2= TRANSLATOR: attempt to READBLOCK on non-stream syntax
TRANSLATION.TRANSLATION_RULES.ERR_IOOpcodes _exception3=000610100012	TRANSLATOR: attempt to WRITEBLOCK on non-stream syntax
TRANSLATION.TRANSLATION_RULES.ERR _StandardRuleLoopCount_exception1=000610100013	TRANSLATOR: unable to get loop count on field {0}
TRANSLATION.TRANSLATION_RULES.ERR _StandardRuleSelect_str1=000610100014	[StandardRuleSelect] undefined failure
TRANSLATION.TRANSLATION_RULES.ERR _StringOpcodes_exception1=000610100015	TRANSLATOR: missing opcode implementation
TRANSLATION.TRANSLATION_RULES.ERR _TransactionRegister_exception1=000610100016	Caught exception while trying to add Transaction Register to the transaction register table
TRANSLATION.TRANSLATION_RULES.ERR _TransactionRegister_exception2=000610100017	Caught exception while trying to add Transaction Register to the transaction register table

Message Code	Log Message
TRANSLATION.TRANSLATION_RULES.ERR _TransactionRegister_exception3=000610100018	Caught exception while trying to add Transaction Register to the transaction register table
TRANSLATION.TRANSLATION_RULES.ERR _TransactionRegister_exception4=000610100019	TransactionRegister: SQL Exception Encountered
TRANSLATION.TRANSLATION_RULES.ERR _TransactionRegister_exception5=000610100020	Caught exception freeing JDBC resources
TRANSLATION.TRANSLATION_RULES.ERR _TransactionRegister_exception6=000610100021	Caught exception while trying to get Transaction Registers from the transaction register table
TRANSLATION.TRANSLATION_RULES.ERR _TransactionRegister_exception7=000610100022	Caught exception while trying to delete Transaction Registers from the transaction register table
TRANSLATION.TRANSLATION_RULES.DEB _TransactionRegister_tr=000620100001	Added the transactionRegister {0}
TRANSLATION.TRANSLATION_RULES.DEB _TransactionRegister_str1=000620100002	Found transaction registers that need to be added to the database
TRANSLATION.TRANSLATION_RULES.DEB _TransactionRegister_tr2=000620100003	Added the transaction register {0}
TRANSLATION.TRANSLATION_RULES.DEB _TransactionRegister_tr3=000620100004	Found a duplicate transaction register {0}
TRANSLATION.TRANSLATION_RULES.DEB _TransactionRegister_tr4=000620100005	[TransactionRegister]: Executed {0}
TRANSLATION.TRANSLATION_RULES.DEB _TransactionRegister_tr5=000620100006	[TransactionRegister]: Executed {0}
TRANSLATION.TRANSLATION_RULES.WAR _UnsupportedOpcodes_opcode=000630100001	TRANSLATOR: call to unsupported opcode {0}
TRANSLATION.TRANSLATION_RULES.LOG _StringOpCodes_msg1=000640100001	{0}
TRANSLATION.TRANSLATION_RULES.LOG _StringOpCodes_msg2=000640100002	{0}
TRANSLATION.TRANSLATION_RULES.LOG _TransactionRegister_TruncatedFiled=000640100003	Truncated the field {0}. The maximum allowable width of this field is {1}

## Translation Storage System Log Messages

The following system log messages are used for translation storage:

Message Code	Log Message
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap _tmp=000610110001	[DiskHashMap] Could not create directory {0}
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap _exception1=000610110002	[DiskHashMap] error reading from key file
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap _exception2=000610110003	[DiskHashMap] error removing entry from key file
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap _exception3=000610110004	[DiskHashMap] error accessing key file while executing count extended rule
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap _exception4=000610110005	[DiskHashMap] error accessing keyfile while executing delete extended rule

Message Code	Log Message
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_str1=000610110006	[DiskHashMap] error accessing key file in deleteAllInstances method
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception5=000610110007	[DiskHashMap] error accessing key file in readKeyFile() method
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception6=000610110008	[DiskHashMap] error accessing keyfile while executing delete extended rule
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception7=000610110009	[DiskHashMap] error accessing keyfile while executing sort extended rule
TRANSLATION.TRANSLATION_STORAGE.ERR_DiskHashMap_exception8=000610110010	[DiskHashMap] error accessing keyfile while executing sort extended rule
TRANSLATION.TRANSLATION_STORAGE.ERR_Index_exception1=000610110011	TRANSLATOR: error cloning Index
TRANSLATION.TRANSLATION_STORAGE.ERR_VirtualGroupStore_tmpdir=000610110012	[VirtualGroupStore] Could not create directory {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_guardBytes=000620110001	[DiskHashMap] guard bytes \= {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_cacheDir=000620110002	[DiskHashMap] cache dir \= {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_hashCapacity=000620110003	[DiskHashMap] hash capacity \= {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_hashEntries=000620110015	[DiskHashMap] hash entries to page \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_keyBatch=000620110004	[DiskHashMap] key batch size \= {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_collisionCount=000620110005	[DiskHashMap] for storage group {0} collision count {1}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_keyList=000620110012	[DiskHashMap] readKeyFile(), number of keys in file \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_getAbsolutePath=000620110006	[DiskHashMap] create storage page file {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_collision=000620110007	[DiskHashMap] writeRecord() collision between key to write {0} and existing key {1} at offset {2} in key file, collision count \= {3}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_readKey=000620110008	[DiskHashMap] writeRecord() updating read key "{0} setting next key ptr \= {1}
TRANSLATION.TRANSLATION_STORAGE.DEB_DiskHashMap_batch=000620110009	[KeyBatch] writing {0} keys (key length\={1}) to key file {2} at offset {3}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_cacheDir=000620110010	[VirtualGroupStore] cache dir \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_batch=000620110011	[VirtualGroupStore] data batch size \= {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_getAbsolutePath=000620110012	[VirtualGroupStore] create storage page file {0}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_count=000620110013	[VirtualGroupStore] paged in count \={0}
TRANSLATION.TRANSLATION_STORAGE.DEB_VirtualGroupStore_count2=000620110014	[VirtualGroupStore] paged out count \={0}



Message Code	Log Message
TRANSLATION.TRANSLATION_STORAGE.LOG_DiskHashMap_tmp=000640110001	[DiskHashMap] The storage.cache_dir is null, setting to java.io.tmpdir {0}
TRANSLATION.TRANSLATION_STORAGE.LOG_VirtualGroupStore_tmpdir=000640110002	[DiskHashMap] The storage.cache_dir is null, setting to java.io.tmpdir {0}

## Typing Service System Log Messages

The following system log messages are used for the Typing service:

Message Code	Log Message
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_MapNotFound=000610030001	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_MapDISABLED=000610030002	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_InvalidTypingServiceMapTYPE=000610030003	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_UNREGISTEREDMap=000610030004	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_InvalidMapOutput=000610030005	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_RequiredParametersNotFound=000610030006	{0}
TRANSLATION.TRANSLATION_TYPING.ERR_TypingService_TransformerException=000610030007	{0}
TRANSLATION.TRANSLATION_TYPING.DEB_TypingService_TranslationLargeFile=000620030001	TypingService.locateValidMap(): translation large file support enabled \={0}
TRANSLATION.TRANSLATION_TYPING.DEB_TypingService_TRXreport=000620030002	TypingService.locateValidMap(): DEBUG TRX report: {0} {1}

## Utility Translation System Log Messages

The following system log messages are used for Utility translation:

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.ERR_DataConvert_exception1=000610130001	Exception parsing two digit year start property, defaulting to 1970
TRANSLATION.TRANSLATION_UTIL.ERR_DataConvert_exception2=000610130002	[Translator] Invalid format passed to DataConverter. The format: {0} is not valid
TRANSLATION.TRANSLATION_UTIL.ERR_DataConvert_exception3=000610130003	TRANSLATOR: The specified output encoding is not supported
TRANSLATION.TRANSLATION_UTIL.ERR_FuncDocToDOM_exception1=000710130004	dumpit method
TRANSLATION.TRANSLATION_UTIL.ERR_FuncSecurityContext_exception1=000610130005	Exception
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_str1=000610130006	sql.statement.MaximumBatchSize property value is not valid. Default maximum batch size will be used.

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception1=000610130007	TRANSLATOR: SQL Exception while closing PreparedStatement in SQLWriter
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_curBlock=000610130008	TRANSLATOR: Batch execution error while performing batch operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception2=000610130009	TRANSLATOR: Batch Update Exception while performing batch operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception3=000610130010	TRANSLATOR: SQL Exception while performing batch operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception4=000610130011	TRANSLATOR: SQL Exception while performing batch operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception5=000610130012	TRANSLATOR: SQL Exception while performing operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception6=000610130013	TRANSLATOR: SQL Exception performing retry for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SQLWriter_exception7=000610130014	TRANSLATOR: SQL Exception while performing operation for {0}
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception1=000610130015	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception2=000610130016	TRANSLATOR: The field syntax is not valid
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception3=000610130017	TRANSLATOR: The field syntax is not valid
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception4=000610130018	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception5=000610130019	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception6=000610130020	TRANSLATOR: The field syntax is not valid
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception7=000610130021	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception8=000610130022	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception9=000610130023	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception10=000610130024	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception11=000610130025	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception12=000610130026	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception13=000610130027	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception14=000610130028	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception15=000610130029	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR_SWIFTComponentValidator_exception16=000610130030	TRANSLATOR: The field syntax is not valid.

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.ERR _SWIFTComponentValidator_exception17=000610130031	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR _SWIFTComponentValidator_exception18=000610130032	TRANSLATOR: Data conversion exception
TRANSLATION.TRANSLATION_UTIL.ERR _SWIFTComponentValidator_exception19=000610130033	TRANSLATOR: Data conversion exception.
TRANSLATION.TRANSLATION_UTIL.ERR _SWIFTComponentValidator_exception20=000610130034	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR _SWIFTValidator_exception1=000610130035	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR _SWIFTValidator_exception2=000610130036	TRANSLATOR: The field syntax is not valid.
TRANSLATION.TRANSLATION_UTIL.ERR _SmartDate_exception1=000610130037	TRANSLATOR: error cloning SmartDate
TRANSLATION.TRANSLATION_UTIL.ERR _SyntaxValidator_TokenFunction=000610130038	TRANSLATOR: Function End token not found for field syntax \ {0} \ at index {1} .
TRANSLATION.TRANSLATION_UTIL.ERR _SyntaxValidator_TokenText=000610130039	TRANSLATOR: Literal Text token not found for field syntax \ {0} \ at index {1}.
TRANSLATION.TRANSLATION_UTIL.ERR _SyntaxValidator_TokenREGEX=000610130040	TRANSLATOR: REGEX token not found for field syntax \ {0} \ at index {1}.
TRANSLATION.TRANSLATION_UTIL.ERR _SyntaxValidator_exception1=000610130041	TRANSLATOR: The field syntax \ \ {0} \ at index {1} .
TRANSLATION.TRANSLATION_UTIL.ERR _SyntaxValidator_exception2=000610130042	TRANSLATOR: The field syntax \ \ {0} \ at index {1} .
TRANSLATION.TRANSLATION_UTIL.ERR _TxByteArrayOutputStream_exception1=000610130043	TRANSLATOR: The specified encoding is not supported.
TRANSLATION.TRANSLATION_UTIL.ERR _TxByteArrayOutputStream_exception2=000610130044	TRANSLATOR: The specified encoding is not supported.
TRANSLATION.TRANSLATION_UTIL.ERR _XMLDOMWriter_exception1=000610130045	TRANSLATOR: Error getting parent node for current element in setCurrentElementToParent.
TRANSLATION.TRANSLATION_UTIL.ERR _XPathHelper_exception1=000610130046	(DEBUG) XPathHelper.executeXPath: Exception testing xpath string: {0}
TRANSLATION.TRANSLATION_UTIL.ERR _XPathHelper_exception2=000610130047	XPathHelper.executeXPath: Exception optimizing xpath string: {0}
TRANSLATION.TRANSLATION_UTIL.ERR _XPathHelper_exception3=000610130048TRANSLATION. TRANSLATION_UTIL.ERR_XpathHelper_exception3=000610130048	XPathHelper.executeXPath: Exception for target ' {0} ' executing xpath: {1}
TRANSLATION.TRANSLATION_UTIL.ERR _XPathStatusRpt_str1=000610130049	Wfc is null in xpathStatusRpt
TRANSLATION.TRANSLATION_UTIL.ERR _XPathStatusRpt_wfId=000610130050	DOM is null for wf_id {0}
TRANSLATION.TRANSLATION_UTIL.ERR _XPathStatusRpt_str2=000610130051	Only one text parm is required
TRANSLATION.TRANSLATION_UTIL.DEB _XPathHelper_xpath=000620130001	[XPathHelper] executeXPath original xpath:

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath2=000620130002	[XPathHelper] cache based xpath query starts with some-function(/ProcessData/ : {0} )
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath3=000620130003	[XPathHelper] cache based xpath query starts with /ProcessData/ : {0} )
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath4=000620130004	[XPathHelper] attempting cache based xpath processing: {0}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath5=000620130005	[XPathHelper] executeXPath function type xpath cache query token: {0} : {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath6=000620130006	[XPathHelper] executeXPath non-function type xpath cache query token: {0} : {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath7=000620130007	[XPathHelper] executeXPath found cacheable node: {0} xpath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath8=000620130008	[XPathHelper] creating new cached xpath for document for document {0} xpath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath9=000620130009	[XPathHelper] NOT creating new cached xpath for document {0} placing null into cache: {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath10=000620130010	[XPathHelper] executeXPath evaluating with cached xpath: {0}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath11=000620130011	[XPathHelper] failed to find cacheable node, executing normal xpath: {0}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath12=000620130012	[XPathHelper] cache not available; executing normal xpath: {0}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath13=000620130013	[XPathHelper] executeXPath predicate query: begin \ = {0} end \ = {1} {2}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath14=000620130014	[XPathHelper] executeXPath, subXPath: {0} orXPath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath15=000620130015	[XPathHelper] executeXPath final predicate; executing xpath query, subXPath: {0} orXPath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath16=000620130016	[XPathHelper] executeXPath predicate, single return type, subXPath: {0} orXPath: {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath17=000620130017	[XPathHelper] executeXPath predicate, multiple node return; perform operation: {0}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath18=000620130018	[XPathHelper] executeXPath predicate result: {0}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath19=000620130019	[XPathHelper] executeXPath not executing pre-predicate processing returning: {0} level: {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath20=000620130020	[XPathHelper] next loop predicate query, pre change: begin \ = {0} end \ = {1} {2}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath21=000620130021	[XPathHelper] next loop predicate query, postchange, begin: {0} end: {1} subXPath: {2} orXPath: {3}
TRANSLATION.TRANSLATION_UTIL.DEB _XpathHelper_xpath22=000620130022	[XPathHelper] executeXPath final xpath, orXPath: {0} newXPath: {1} level: {2}

Message Code	Log Message
TRANSLATION.TRANSLATION_UTIL.DEB _XPathHelper_xpath23=000620130023	[XPathHelper] calling executeXPath,newXPath: {0} level: {1}
TRANSLATION.TRANSLATION_UTIL.DEB _XPathStatusRpt_str1=000620130024	create CDataSection for status_rpt
TRANSLATION.TRANSLATION_UTIL.WAR _XPathHelper_xpath=000630130001	Predicate XPath query failed; falling back to slower full query.If this is a caching scheme, the results may be incorrect. Examine this XPath query: {0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_dumpit=000640130001	{0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_saXPath=000640130002	saXPath before\ = {0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_saXPath=000640130003	saXPath after\ = {0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_xpt=000640130004	token\ = {0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_str1=000640130005	dump of XPathTree:
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_XPathTree=000640130006	{0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_str2=000640130007	=====
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_str3=000640130008	got a last-in-tree match or wildcard
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_str4=000640130009	incrementing tree index
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_mHits=000640130010	##### HITS\ = {0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncDocToDOM_debugElement=000640130011	{0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncSecurityContext_contextID=000640130012	contextID is {0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncSecurityContext_contextName=000640130013	contextName is {0}
TRANSLATION.TRANSLATION_UTIL.LOG _FuncSecurityContext_ret=000640130014	Password is {0}

## XML Encoding Translation System Log Messages

The following system log messages are used for XML encoding:

Message Code	Log Message
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_MapObject=000610040001	Unable to load MapObject for map: {0}
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception1=000610040002	Exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception2=000610040003	Exception

Message Code	Log Message
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception3=000610040004	Caught exception in LightweightTxServiceEJBBean.processData():
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception4=000610040005	Unable to pass namespace-schema mappings to XML parser
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception5=000610040006	Unable to set XML parser validation feature
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception6=000610040007	MLEncoder.ditaToProcessData caught SQL exception while parsing the document : {0}
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception7=000610040008	Error while reading document with supplied encoding.
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception8=000610040009	{0}
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception9=000610040010	XMLEncoder.ditaToProcessData caught parser exception while parsing the document :{0}
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception10=000610040011	Exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_XMLEncoder=000610040012	XMLEncoder.processdataToDocument failed. Object {0} returned from wfc.getWFElement is of type {1} . Must be of type NodeList
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception11=000610040013	XMLEncoder.processdataToDocument caught unsupported encoding exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception12=000610040014	XMLEncoder.processdataToDocument caught IO exception
TRANSLATION.TRANSLATION_XMLENCODING.ERR _LightweightServiceImpl_exception13=000610040015	XML parsing warning occurred
TRANSLATION.TRANSLATION_XMLENCODING.DEB _LightweightServiceImpl_TranslationReport=000620040001	Translation Report: {0} {1}
TRANSLATION.TRANSLATION_XMLENCODING.DEB _LightweightServiceImpl_str1=000720040002	LightweightTxServiceImpl.translate() completed .....

---

## Start and Stop Commands

See the Sterling B2B Integrator Installation or Upgrade documentation for the appropriate command format.

---

## Customize Date and Time Formats

### About this task

Date and time formats in Sterling B2B Integrator can be customized to use international formats for field input and display.

Before performing this procedure, see *Working with Property Files* for important cautions.

To customize date and time formats:

### Procedure

1. Navigate to the installation directory.
2. Navigate to the properties directory.

- Open the *ui.properties.in* file in a text editor, and locate the Input/Display date/time formats section:

```
#####
# Input/Display date/time formats
#####
PlatformDateFormat.Date.SHORT=MM/dd/yy
PlatformDateFormat.Date.MEDIUM=MMM d,yyyy
PlatformDateFormat.Date.LONG=MMMM d,yyyy
PlatformDateFormat.Date.FULL=EEEE,MMMM d,yyyy
PlatformDateFormat.Time.SHORT=h:mm a
PlatformDateFormat.Time.MEDIUM=h:mm:ss a
PlatformDateFormat.Time.LONG=h:mm:ss a z
PlatformDateFormat.Time.FULL=h:mm:ss a z
```

**Note:** During operation, Sterling B2B Integrator uses the *ui.properties* file, not the *ui.properties.in* file. The date/time edit is performed on the *ui.properties.in* file to keep the edited values from being overwritten during system initialization and setup.

- Edit the date/time pattern strings, using the characters and syntax specified for the Java SimpleDateFormat class as documented at <http://java.sun.com>.
- Save and close the *ui.properties.in* file.
- Stop Sterling B2B Integrator.
- Run the *setupfiles* script using one of the following formats:
  - (UNIX, Linux, or iSeries) – From the *install\_dir/install/bin* directory, run the *setupfiles.sh* command.
  - (Windows) – From the *install\_dir\install\bin* directory, run the *setupfiles.cmd* command.
- Start Sterling B2B Integrator.

---

## Customizing the Sterling B2B Integrator user interface

You can customize the appearance of the Sterling B2B Integrator user interface. Basic page colors and fonts can be changed by revising their properties.

### About this task

**Tip:** In Sterling B2B Integrator V5.2.6 or earlier, you can also make these changes using the skin editor in MESA Developer Studio.

To edit a template:

### Procedure

- Open the *skins.properties\_style\_ext* file in the *install\_dir/properties* directory.
- Edit the user interface colors or fonts as desired by editing the appropriate properties in the *skins.properties\_style\_ext* file.

#### **style.cmmTreeHdrFontColor.value**

Specifies the font color for tree headers. Default setting is `style.cmmTreeHdrFontColor.value=RGB(255,255,255)`.

#### **style.sectionHeader.value**

Specifies the font for section headers. Default setting is `style.sectionHeader.value=Arial`.

**style.sectionBg.value**

Specifies the background color for sections. Default setting is `style.sectionBg.value=rgb(117,145,221)` .

**style.pageBg.value**

Specifies the background color for pages. Default setting is `style.pageBg.value=rgb(255,255,255)` .

**style.loginFormFont.value**

Specifies the font for login forms . Default setting is `style.loginFormFont.value=Verdana,Arial,Helvetica,sans-serif` .

**style.tblBorder.value**

Specifies the color for table borders. Default setting is `style.tblBorder.value=rgb(117,145,221)` .

**style.sectionContent.value**

Specifies the font for section content. Default setting is `style.sectionContent.value=Verdana,Arial,Helvetica,sans-serif` .

**style.sectionHeaderFontColor.value**

Specifies the font color for section headers. Default setting is `style.sectionHeaderFontColor.value=RGB(255,255,255)` .

**style.sectionContentColor.value**

Specifies the color for section content. Default setting is `style.sectionContentColor.value=rgb(102,102,102)` .

**style.loginForm.value**

Specifies the color for login forms. Default setting is `style.loginForm.value=RGB(193,214,235)` .

**style.headerColor.value**

Specifies the color for headers. Default setting is `style.headerColor.value=rgb(89,89,89)` .

**style.cmmTreeBg.value**

Specifies the background color for trees. Default setting is `style.cmmTreeBg.value=RGB(182,182,189)` .

**style.contentBorder.value**

Specifies the color for border content. Default setting is `style.contentBorder.value=rgb(128,128,128)` .

**style.selectedTabColor.value**

Specifies the color for tabs when selected. Default setting is `style.selectedTabColor.value=RGB(192,192,192)` .

**style.td.value**

Specifies the font for table cells.. Default setting is `style.td.value=Helvetica,Verdana,Arial,sans-serif` .

**style.sectionSubHeader.value**

Specifies the font for section sub-headers. Default setting is `style.sectionSubHeader.value=Helvetica,Sans-serif` .

**style.cmmTreeLinkHover.value**

Specifies the font color for links when hovered over. Default setting is `style.cmmTreeLinkHover.value=rgb(255,255,0)` .

**style.cmmTreeHdr.value**

Specifies the color for tree headers. Default setting is `style.cmmTreeHdr.value=RGB(117,145,221)` .



**style.pageHeaderBg.value**

Specifies the background color for page headers. Default setting is `style.pageHeaderBg.value=RGB(117,145,221)` .

**style.sectionTextColor.value**

Specifies the font color for section text. Default setting is `style.sectionTextColor.value=rgb(255,255,255)` .

**style.cmmTreeHeaderBorder.value**

Specifies the border color for tree headers. Default setting is `style.cmmTreeHeaderBorder.value=rgb(128,128,128)` .

**style.header.value**

Specifies the font for headers. Default setting is `style.header.value=Arial,Tahoma,Verdana` .

**style.cmmTreeLink.value**

Specifies the font color for links in trees. Default setting is `style.cmmTreeLink.value=RGB(0,0,0)` .

3. Save the `skins.properties_style_ext` file.
4. Navigate to the `install_dir/install/bin` directory and perform one of the following:

**UNIX or Linux**

- a. Run the `setupfiles.sh` file.
- b. Run the `deployer.sh` file.

**Windows**

- a. Run the `setupfiles.cmd` file.
- b. Run the `deployer.cmd` file.

For information about the `setupfiles` and `deployer` scripts, see `bin Directory Files`.

5. Restart Sterling B2B Integrator for the changes to take effect.

**Results**

The `skins.properties_style_ext` file is uploaded into the Sterling B2B Integrator instance and the new skin settings are used after restarting the instance.

**Example skins.properties\_style\_ext file**

```
#Default Values
#Tue Aug 04 18:22:04 EDT 2015
style.cmmTreeHdrFontColor.value=RGB(255,255,255)
style.sectionHeader.value=Arial
style.sectionBg.value=rgb(117,145,221)
style.pageBg.value=rgb(255, 255, 255)
style.loginFormFont.value=Verdana, Arial, Helvetica, sans-serif
style.tblBorder.value=rgb(117, 145, 221)
style.sectionContent.value=Verdana, Arial, Helvetica, sans-serif
style.sectionHeaderFontColor.value=RGB(255,255,255)
style.sectionContentColor.value=rgb(102, 102, 102)
style.loginForm.value=RGB(193,214,235)
style.headerColor.value=rgb(89, 89, 89)
style.cmmTreeBg.value=RGB(182,182,189)
style.contentBorder.value=rgb(128, 128, 128)
style.selectedTabColor.value=RGB(192,192,192)
style.cmmTreeBorder.value=rgb(128, 128, 128)
style.selectedTabFontColor.value=RGB(255,255,255)
style.td.value=Helvetica, Verdana, Arial, sans-serif
style.sectionSubHeader.value=Helvetica, Sans-serif
style.cmmTreeLinkHover.value=rgb(255,255,0)
```

```
style.cmmTreeHdr.value=RGB(117,145,221)
style.pageHeaderBg.value=RGB(117,145,221)
style.sectionTextColor.value=rgb(255, 255, 255)
style.cmmTreeHeaderBorder.value=rgb(128, 128, 128)
style.header.value=Arial, Tahoma, Verdana
style.cmmTreeLink.value=RGB(0,0,0)
```

## What to do next

The `skins.properties_style_ext` file can be manually copied to another installation or upgrade installation of Sterling B2B Integrator. After copying the file, you can apply the changes to the new Sterling B2B Integrator instance by running the `setupfiles` script and then the `deployer` script, and afterward restarting Sterling B2B Integrator. This can be done with both single node and cluster node installations and upgrades.

For information about the `setupfiles` and `deployer` scripts, see `bin Directory Files`.

---

## Restart Sterling B2B Integrator after Time Change

You must restart both Sterling B2B Integrator and its database for seasonal changes to your system time. For example, when the time changes between British Summer Time and Greenwich Mean Time, or, in the United States, between Standard Time and Daylight Savings Time.

This ensures that both Sterling B2B Integrator and the database are using the same new time settings. It helps prevent problems with database queries that compare timestamp values in database tables with the time of the database server.

---

## Configure Keystore Pathname or Password

### About this task

When importing CA (trusted root) certificates from the Java Key Store (JKS) that is shipped with the JVM, a password is required. This password appears as a prepopulated default in the user interface.

If this password or the JKS pathname changes, modify the `ui.properties` file to modify the default password that appears in the UI.

To configure a keystore pathname or password:

### Procedure

1. Navigate to the installation directory.
2. Navigate to the `properties` directory.
3. Open the `ui.properties` file and locate this line:  
`JVMcacertsFilePath = install_dir/jdk/jre/lib/security/cacerts`
4. Modify the `JVMcacertsFilePath` entry to reflect the new pathname.
5. To change the keystore default password that appears in the interface, locate this line:  
`JVMcacertsFilePass =`
6. Modify the `JVMcacertsFilePass` entry to reflect the new password.
7. Save and close the `ui.properties` file.
8. Stop Sterling B2B Integrator.

9. Run the *setupfiles* script using one of the following steps:
    - (UNIX, Linux, or iSeries) – From the `install_dir/bin` directory, run the `setupfiles.sh` command.
    - (Windows) – From the `install_dir\bin` directory, run the `setupfiles.cmd` command.
  10. Start Sterling B2B Integrator.
- 

## EBICS Client

If you are upgrading to Sterling B2B Integrator version 5.2.4 from a previous 5.2.x release, you must manually install the EBICS client. See the information about installing the EBICS client module manually in the *EBICS Client User Guide* for more information



---

## Notices

This information was developed for products and services offered in the US. This material might be available from IBM in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing  
IBM Corporation  
North Castle Drive, MD-NC119  
Armonk, NY 10504-1785  
US*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing  
Legal and Intellectual Property Law  
IBM Japan Ltd.  
19-21, Nihonbashi-Hakozakicho, Chuo-ku  
Tokyo 103-8510, Japan*

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those

websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Director of Licensing  
IBM Corporation  
North Castle Drive, MD-NC119  
Armonk, NY 10504-1785  
US*

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data and client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

All IBM prices shown are IBM's suggested retail prices, are current and are subject to change without notice. Dealer prices may vary.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

#### COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to

IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work must include a copyright notice as shown in the next column.

© 2015.

Portions of this code are derived from IBM Corp. Sample Programs.

© Copyright IBM Corp. 2015.

---

## Trademarks

IBM, the IBM logo, and [ibm.com](http://ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at [www.ibm.com/legal/copytrade.shtml](http://www.ibm.com/legal/copytrade.shtml).

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

IT Infrastructure Library is a registered trademark of the Central Computer and Telecommunications Agency which is now part of the Office of Government Commerce.

Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

ITIL is a registered trademark, and a registered community trademark of the Office of Government Commerce, and is registered in the U.S. Patent and Trademark Office.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java™ and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Cell Broadband Engine is a trademark of Sony Computer Entertainment, Inc. in the United States, other countries, or both and is used under license therefrom.

Linear Tape-Open, LTO, the LTO Logo, Ultrium and the Ultrium Logo are trademarks of HP, IBM Corp. and Quantum in the U.S. and other countries.

Connect Control Center<sup>®</sup>, Connect:Direct<sup>®</sup>, Connect:Enterprise<sup>®</sup>, Gentran<sup>®</sup>, Gentran<sup>®</sup>:Basic<sup>®</sup>, Gentran:Control<sup>®</sup>, Gentran:Director<sup>®</sup>, Gentran:Plus<sup>®</sup>, Gentran:Realtime<sup>®</sup>, Gentran:Server<sup>®</sup>, Gentran:Viewpoint<sup>®</sup>, Sterling Commerce<sup>™</sup>, Sterling Information Broker<sup>®</sup>, and Sterling Integrator<sup>®</sup> are trademarks or registered trademarks of Sterling Commerce<sup>®</sup>, Inc., an IBM Company.

Other company, product, and service names may be trademarks or service marks of others.

---

## Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

### Applicability

These terms and conditions are in addition to any terms of use for the IBM website.

### Personal use

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

### Commercial use

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

### Rights

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.







Product Number:

Printed in USA