

# Communication Bandwidth Requirements

\*SPP=Seconds Per Page,  
numbers in parentheses show  
usable attachment bytes per second

Printer	IPM	SPP*	56 (6,000)	128 (13,500)	256 (27,000)	T1 (150,000)	10BaseT (1M)	100BaseT (10M)
1116	16	3.750	22,500	50,625	101,250	562,500	3,750,000	37,500,000
1120	20	3.000	18,000	40,500	81,000	450,000	3,000,000	30,000,000
1125	25	2.400	14,400	32,400	64,800	360,000	2,400,000	24,000,000
1130	30	2.000	12,000	27,000	54,000	300,000	2,000,000	20,000,000
1140	40	1.500	9,000	20,250	40,500	225,000	1,500,000	15,000,000
1145	45	1.333	7,998	17,996	35,991	199,950	1,333 000	13,330,000
Infoprint 62	62	.968	5,808	13,068	26,136	145,200	968,000	9,680,000
Infoprint 70	70	.857	5,142	11,570	23,139	128,550	857,000	8,570,000
Infoprint 2000	110	.545	3,270	7,358	14,715	81,750	545,000	5,450,000
Infoprint Color 130+	138	.435	2,610	5,873	11,745	65,250	435,000	4,350,000
3000-ES1, 2-up	172	.349	2,094	4,712	9,423	52,350	349,000	3,490,000
3000-ED1/2, 1-up	224	.268	1,608	3,618	7,236	40,200	268,000	2,680,000
3000-ED1/2, 2-up	344	.174	1,044	2,349	4,698	26,100	174,000	1,740,000
4000-IS1, 2-up	354	.169	1,014	2,282	4,563	25,350	169,000	1,690,000
4100-XS1, 2-up	381	.157	942	2,120	4,239	23,550	157,000	1,570,000
4000-ID1/2, 1-up	458	.131	786	1,769	3,537	19,650	131,000	1,310,000
4100-XD1/2, 1-up	494	.121	726	1,634	3,267	18,150	121,000	1,210,000
4000-IS2, 2-up	501	.120	720	1,620	3,240	18,000	120,000	1,200,000
4000-ID3/4+5/6, 1-up	648	.093	558	1,256	2,511	13,950	93,000	930,000
4000-ID1/2, 2-up	708	.085	510	1,148	2,295	12,750	85,000	850,000
4100-XD1/2, 2-up	762	.079	474	1,067	2,133	11,850	79,000	790,000
4000-ID3/4+5/6, 2-up	1002	.060	360	810	1,620	9,000	60,000	600,000
4100-XD1/2, 3-up	1400	.043	258	581	1,161	6,450	43,000	430,000