



IBM MobileFirst Platform Foundation

IBM MobileFirst Platform Foundation V6.3.0

C# client-side API for native Windows Phone 8 apps

5 December 2014

Copyright Notice

© Copyright IBM Corp. 2014
US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Trademarks

IBM, the IBM logo, ibm.com®, and Worklight® are trademarks or registered trademarks of International Business Machines Corporation, registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "[Copyright and trademark information](http://www.ibm.com/legal/copytrade.shtml)" at www.ibm.com/legal/copytrade.shtml.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company products or service names may be trademarks or service marks of others.

This document may not be reproduced in whole or in part without the prior written permission of IBM.

About IBM

See <http://www.ibm.com/ibm/us/en/>.

Contents

| | | |
|----------|---|----------|
| 1 | API overview | 1 |
| 2 | API reference | 3 |
| 2.1 | Example Code..... | 3 |
| 2.1.1 | Example: connecting to the MobileFirst Server and calling a procedure | 3 |
| 2.2 | Class WLClient..... | 4 |
| 2.2.1 | Method getInstance | 4 |
| 2.2.2 | Method connect | 4 |
| 2.2.3 | Method invokeProcedure | 5 |
| 2.2.4 | Method logActivity..... | 5 |
| 2.2.5 | Method setHeartBeatInterval | 6 |
| 2.2.6 | Method getPush..... | 6 |
| 2.2.7 | Method setServerUrl..... | 7 |
| 2.2.8 | Method getServerUrl..... | 7 |
| 2.3 | Class WLProcedureInvocationData..... | 7 |
| 2.3.1 | Method setParameters..... | 8 |
| 2.4 | Class WLRequestOptions | 8 |
| 2.4.1 | Method addParameter | 8 |
| 2.4.2 | Method addParameters | 9 |
| 2.4.3 | Method getParameter | 9 |
| 2.4.4 | Method getParameters | 9 |
| 2.4.5 | Method getResponseListener..... | 9 |
| 2.4.6 | Method addHeader | 10 |
| 2.4.7 | Method setHeaders..... | 10 |
| 2.4.8 | Method getHeaders | 10 |
| 2.4.9 | Methods getInvocationContext, setInvocationContext | 10 |
| 2.5 | Interface WLResponseListener | 11 |
| 2.5.1 | Method onSuccess | 11 |
| 2.5.2 | Method onFailure | 11 |
| 2.6 | Class WLResponse..... | 12 |
| 2.6.1 | Method getStatus..... | 12 |
| 2.6.2 | Method getInvocationContext..... | 12 |
| 2.6.3 | Method getResponseText..... | 12 |
| 2.6.4 | Method getResponseJSON | 12 |
| 2.7 | Class WLFailResponse | 13 |
| 2.7.1 | Method getErrorCode | 13 |
| 2.7.2 | Method getErrorMsg | 13 |
| 2.8 | Class WLProcedureInvocationResult | 13 |
| 2.8.1 | Method getResult..... | 13 |
| 2.8.2 | Method isSuccessful..... | 13 |
| 2.9 | Class WLProcedureInvocationFailResponse..... | 13 |
| 2.9.1 | Method getProcedureInvocationErrors | 14 |
| 2.9.2 | Method getResult..... | 14 |

| | | |
|--------|---|----|
| 2.10 | Class WLErrorCode | 14 |
| 2.10.1 | Method getDescription | 14 |
| 2.10.2 | Method valueOf | 14 |
| 2.11 | Class BaseChallengeHandler | 15 |
| 2.11.1 | Constructor | 15 |
| 2.11.2 | Method handleChallenge(T challenge) | 15 |
| 2.11.3 | Method submitFailure(WLResponse wLResponse) | 15 |
| 2.12 | Class ChallengeHandler | 16 |
| 2.12.1 | Constructor | 16 |
| 2.12.2 | Method isCustomResponse | 16 |
| 2.12.3 | Method submitSuccess | 16 |
| 2.12.4 | Method submitLoginForm | 16 |
| 2.12.5 | Method submitAdapterAuthentication | 17 |
| 2.13 | Class WLChallengeHandler | 17 |
| 2.13.1 | Constructor | 18 |
| 2.13.2 | Method submitChallengeAnswer | 18 |
| 2.14 | Class WLPush | 18 |
| 2.14.1 | Method registerEventSourceCallback | 19 |
| 2.14.2 | Method subscribe | 19 |
| 2.14.3 | Method unsubscribe | 20 |
| 2.14.4 | Method isSubscribed | 20 |
| 2.14.5 | Method subscribeTag | 21 |
| 2.14.6 | Method unsubscribeTag | 21 |
| 2.14.7 | Method isTagSubscribed | 22 |
| 2.14.8 | Property onReadyToSubscribeListener | 22 |
| 2.14.9 | Property notificationListener | 22 |
| 2.15 | Interface WLOnReadyToSubscribeListener | 22 |
| 2.15.1 | Method onReadyToSubscribe | 23 |
| 2.16 | Interface WLEventSourceListener | 23 |
| 2.16.1 | Method onReceive | 23 |
| 2.17 | Interface WLNotificationListener | 23 |
| 2.17.1 | Method onMessage | 23 |
| 2.18 | Class WLPushOptions | 24 |
| 2.18.1 | Constructor | 24 |
| 2.18.2 | Method AddSubscriptionParameter | 24 |
| 2.18.3 | Method GetSubscriptionParameter | 24 |
| 2.18.4 | Property subscriptionParameters | 25 |
| 2.19 | Interface WLActionReceiver | 25 |
| 2.19.1 | Method onActionReceived | 25 |
| 2.20 | Class WL | 26 |
| 2.20.1 | Method showSplashScreen | 26 |
| 2.20.2 | Method hideSplashScreen WL | 26 |
| 2.20.3 | Method sendActionToJS | 26 |
| 2.20.4 | Method sendActionToJS | 27 |
| 2.20.5 | Method addActionReceiver | 27 |
| 2.20.6 | Method removeActionReceiver | 28 |
| 2.20.7 | Method setServerUrl | 28 |

| | |
|---|-----------|
| 2.20.8 Method getServerUrl..... | 29 |
| Appendix A - Notices..... | 30 |
| Appendix B - Support and comments..... | 33 |

Tables

| | |
|--|----|
| Table 1-1: IBM MobileFirst Platform Foundation C# client-side API for Windows Phone 8 applications – packages, classes, interfaces, and files..... | 2 |
| Table 2-1: Method connect parameters..... | 5 |
| Table 2-2: Method invokeProcedure parameters..... | 5 |
| Table 2-3: Method logActivity parameters..... | 6 |
| Table 2-4: Method setHeartBeatInterval parameters..... | 6 |
| Table 2-5: Method setServerURL parameters..... | 7 |
| Table 2-6: Method setParameters parameters..... | 8 |
| Table 2-7: Method addParameter parameters..... | 8 |
| Table 2-8: Method addParameters parameters..... | 9 |
| Table 2-9: Method getParameter parameters..... | 9 |
| Table 2-10: Method addHeader parameters..... | 10 |
| Table 2-11: Method setHeaders parameters..... | 10 |
| Table 2-12: Methods getInvocationContext, setInvocationContext parameters..... | 11 |
| Table 2-13: Method onSuccess parameters..... | 11 |
| Table 2-14: Method onFailure parameters..... | 12 |
| Table 2-15: Method submitLoginForm parameters..... | 17 |
| Table 2-16: Method submitAdapterAuthentication parameters..... | 17 |
| Table 2-17: Method registerEventSourceCallback parameters..... | 19 |
| Table 2-18: Method subscribe parameters..... | 20 |
| Table 2-19: Method unsubscribe parameters..... | 20 |
| Table 2-20: Method isSubscribed parameters..... | 21 |
| Table 2-21: Method subscribeTag parameters..... | 21 |
| Table 2-22: Method unsubscribeTag parameters..... | 22 |
| Table 2-23: Method isTagSubscribed parameters..... | 22 |
| Table 2-24: Method onReceive parameters..... | 23 |
| Table 2-25: Method onMessage parameters..... | 24 |
| Table 2-26: Method AddSubscriptionParameter parameters..... | 24 |
| Table 2-27: Method GetSubscriptionParameter parameters..... | 25 |
| Table 2-28: Method onActionReceived parameters..... | 25 |
| Table 2-29: Method sendActionToJS parameters..... | 27 |
| Table 2-30: Method sendActionToJS parameters..... | 27 |
| Table 2-31: Method addActionReceiver parameters..... | 28 |
| Table 2-32: Method removeActionReceiver parameters..... | 28 |
| Table 2-33: Method setServerUrl parameters..... | 29 |

About this document

This document is intended for Windows Phone 8 developers who want to access IBM MobileFirst Platform Foundation services from Windows Phone 8 applications written in C#. The document guides you through the available classes and methods.

1 API overview

The IBM MobileFirst Platform Foundation C# client-side API for native Windows Phone 8 applications exposes two main capabilities:

- Calling back-end services to retrieve data and perform back-end transactions.
- Writing custom log lines for reporting and auditing purposes.

The IBM MobileFirst Platform Foundation C# client-side API for native Windows Phone 8 applications is available as part of the IBM MobileFirst Platform Studio.

| Type | Name | Description | Implemented By |
|-----------------|---------------------------|---|-----------------------|
| Properties file | wlclient.properties | Properties file that contains the necessary data to connect to IBM MobileFirst Platform Server. | IBM |
| Class | WLClient | Singleton class that exposes methods to communicate with the MobileFirst Server, in particular <code>invokeProcedure</code> for calling a back-end service. | IBM |
| Class | WLProcedureInvocationData | Class that contains all data necessary to call a procedure. | IBM |
| Class | WLRequestOptions | Class that you use to add request parameters, headers, and invocation context. | IBM |
| Interface | WLResponseListener | Interface that defines methods that a listener for the <code>WLClient.invokeProcedure</code> method implements to receive notifications about the success or failure of the method call. | Application developer |
| Class | WLResponse | Class that contains the result of a procedure invocation. | IBM |
| Class | WLFailResponse | Class that extends <code>WLResponse</code> . This class contains error codes, messages, and the status in <code>WLResponse</code> . This class also contains the original response <code>DataObject</code> from the server. | IBM |

| Type | Name | Description | Implemented By |
|-----------|----------------------------------|--|-----------------------|
| Class | WProcedureInvocationResult | Class that extends WResponse. This class contains the result of calling a back-end service, which includes statuses and data items that the adapter function retrieves from the server. | IBM |
| Class | WProcedureInvocationFailResponse | Class that extends WFailResponse and that you can use to retrieve the invocation error messages. | IBM |
| Class | WErrorCode | Class that contains an error code and its message that arrive from the MobileFirst Server. | IBM |
| Class | BaseChallengeHandler | Abstract base class for all Challenge Handlers. | IBM |
| Class | ChallengeHandler | Abstract class that you must extend to create custom challenge handlers. | Application Developer |
| Class | WChallengeHandler | Abstract base class for MobileFirst challenge handlers. You must extend it to implement your own version of a MobileFirst challenge handler. | IBM |
| Interface | WActionReceiver | Interface that allows every implementing object to receive actions and data from the MobileFirst framework | Application Developer |
| Class | WL | Class that contains the various methods that are related to mixed hybrid features: actionsender, splashscreen, and changeserver API. You can get reference of WL object by using WL.getInstance(). | IBM |

Table 1-1: IBM MobileFirst Platform Foundation C# client-side API for Windows Phone 8 applications – packages, classes, interfaces, and files

2 API reference

2.1 Example Code

The following code samples show how to use the IBM MobileFirst Platform Foundation C# client-side API for native Windows Phone 8 applications.

2.1.1 Example: connecting to the MobileFirst Server and calling a procedure

Initializing the MobileFirst client

```
WLClient client = WLClient.getInstance();
client.connect(new MyConnectResponseListener());
```

Implementation of a Response Listener for connect

```
public class MyConnectResponseListener : WLResponseListener{
    public void onFailure(WLFailResponse response) {
        Debug.WriteLine("Response fail: " + response.getErrorMsg());
    }
    public void onSuccess(WLResponse response) {
        WLProcedureInvocationData invocationData = new
WLProcedureInvocationData("myAdapterName", "myProcedureName");
        invocationData.setParameters(new Object[]{"stringParam"});
        String myContextObject = new String("This is my context object");
        WLRequestOptions options = new WLRequestOptions();
        options.setInvocationContext(myContextObject);
        WLClient.getInstance().invokeProcedure(invocationData, new
MyInvokeListener(), options);
    }
}
```

Implementation of a Response Listener for Procedure Invocation

```
public class MyInvokeListener : WLResponseListener {
    public void onFailure(WLFailResponse response) {
        Debug.WriteLine("Response failed: " + response.getErrorMsg());
    }
}
```

```
public void onSuccess(WLResponse response) {
    WLProcedureInvocationResult invocationResponse =
((WLProcedureInvocationResult) response);
    JObject items;
    try {
        items = invocationResponse.getResponseJSON();
        // do something with the items
    } catch (JSONException e) {
    }
}
}
```

2.2 Class WLClient

This singleton class exposes methods that you use to communicate with the MobileFirst Server.

2.2.1 Method getInstance

Syntax

```
public static WLClient getInstance()
```

Description

This method gets the singleton instance of WLClient.

2.2.2 Method connect

Syntax

```
public void connect(WLResponseListener
responseListener)
```

Description

This method sends an initialization request to the MobileFirst Server, establishes a connection with the server, and validates the application version.

Important: You must call this method before any other WLClient methods that communicate with the MobileFirst Server.

Parameters

| Type | Name | Description |
|---------------------------|------------------|---|
| WLResponseListener | responseListener | When the server returns a successful response, the <code>WLResponseListener</code> <code>onSuccess</code> method is called. If an error occurs, the <code>onFailure</code> method is called |

Table 2-1: Method connect parameters

2.2.3 Method invokeProcedure

Syntax

```
public void invokeProcedure(
    WLProcedureInvocationData invocationData,
    WLResponseListener responseListener,
    WLRequestOptions requestOptions)
```

```
public void invokeProcedure(
    WLProcedureInvocationData invocationData,
    WLResponseListener listener)
```

Description

This method sends an asynchronous call to an adapter procedure. The response is returned to the callback functions of the provided [responseListener](#).

If the invocation succeeds, the `onSuccess` method is called. If the invocation fails, the `onFailure` method is called.

Parameters

| Type | Name | Description |
|----------------------------------|------------------|--|
| WLProcedureInvocationData | invocationData | The invocation data for the procedure call. |
| WLResponseListener | responseListener | The listener object whose callback methods <code>onSuccess</code> and <code>onFailure</code> are called. |
| WLRequestOptions | requestOptions | Optional. Invocation options . |

Table 2-2: Method invokeProcedure parameters

2.2.4 Method logActivity

Syntax

```
public void logActivity(String activityType)
```

Description

This method reports a user activity for auditing or reporting purposes. The activity is stored in the raw table.

Important: Ensure that `reports.exportRawData` is set to `true` in the `worklight.properties` file, else the activity is not stored in the database. Also, ensure that the following properties are entered appropriately in the `worklight.properties` file:

- `wl.reports.db.type`
 - `wl.reports.db.url`
 - `wl.reports.db.username`
 - `wl.reports.db.password`
-

Parameters

| Type | Name | Description |
|---------------------|---------------------------|--|
| <code>String</code> | <code>activityType</code> | A string that identifies the activity. |

Table 2-3: Method `logActivity` parameters

2.2.5 Method `setHeartBeatInterval`

Syntax

```
public void setHeartBeatInterval(int value)
```

Description

This method sets the interval, in seconds, at which the MobileFirst Server sends the heartbeat signal. You use the heartbeat signal to ensure that the session with the server is kept alive when the app does not issue any call to the server, such as `invokeProcedure`.

By default, the interval is set to 7 minutes.

Parameters

| Type | Name | Description |
|------------------|--------------------|--|
| <code>int</code> | <code>value</code> | An interval value in seconds, at which the heartbeat signal is sent to MobileFirst Server. |

Table 2-4: Method `setHeartBeatInterval` parameters

2.2.6 Method `getPush`

Syntax

```
public WLPush getPush()
```

Description

This method returns a `WL.Push` object that the application can use to perform actions such as subscribing and unsubscribing to Push notifications.

2.2.7 Method setServerUrl

Syntax

```
public void setServerUrl(Uri url)
```

Description

Use this method to set the MobileFirst Server URL to the specified URL

This method changes the MobileFirst Server URL to the new URL and cleans the HTTP client context. After you call this method, the application is not logged in to any server. The responsibility for checking the validity of the URL is on the developer. If the app uses push notification, it is the developer's responsibility to unsubscribe from the previous server and subscribe to the new server.

Parameters

| Type | Name | Description |
|------|------|---|
| Uri | url | Mandatory. The URL of the new server, including protocol, IP, port, and context Example: <code>WLClient.getInstance().setServerUrl(new URL("http://<ip>:<port>/context"));</code> |

Table 2-5: Method setServerURL parameters

2.2.8 Method getServerUrl

Syntax

```
public Uri getServerUrl()
```

Description

This method returns the URL of the current MobileFirst Server.

Example

```
WLClient.getInstance().getServerUrl();
```

2.3 Class WLProcedureInvocationData

This class contains all data necessary to call a procedure, including the following elements:

- The names of the adapter and procedure to call.
- The parameters that the procedure requires.

2.3.1 Method setParameters

Syntax

```
public void setParameters(Object [] parameters)
```

Description

This method set the request parameters.

Parameters

| Type | Name | Description |
|-----------|------------|---|
| Object [] | parameters | An array of objects of primitive types (String, Integer, Float, Boolean, Double). The order of the objects in the array is the order in which they are sent to the adapter. |

Table 2-6: Method setParameters parameters

Example

```
invocationData.setParameters(new Object[]{"stringParam", true, 1.0, 1});
```

2.4 Class WLRequestOptions

This class contains the request parameters, headers, and invocation context.

2.4.1 Method addParameter

Syntax

```
public void addParameter(String name,String value)
```

Description

This method adds a request parameter with the given name and value.

Parameters

| Type | Name | Description |
|--------|-------|-----------------------------|
| String | name | The name of the parameter. |
| String | value | The value of the parameter. |

Table 2-7: Method addParameter parameters

2.4.2 Method addParameters

Syntax

```
public void addParameters(Dictionary<String,
String> parameters)
```

Description

This method adds a table of request parameters.

Parameters

| Type | Name | Description |
|--------------------------------|------------|--------------------------|
| Dictionary <String, String> | parameters | Request parameters table |

Table 2-8: Method addParameters parameters

2.4.3 Method getParameter

Syntax

```
public String getParameter(String name)
```

Description

This method returns the value of the parameter that is set.

Parameters

| Type | Name | Description |
|--------|------|----------------------------|
| String | name | The name of the parameter. |

Table 2-9: Method getParameter parameters

2.4.4 Method getParameters

Syntax

```
public Dictionary<String, String> getParameters()
```

Description

This method returns the parameters table.

2.4.5 Method getResponseListener

Syntax

```
public WLResponseListener getResponseListener()
```

Description

This method returns the response listener for this request.

2.4.6 Method addHeader

Syntax

```
public void addHeader(String name,String value)
```

Description

This method adds a header with the given name and value.

Parameters

| Type | Name | Description |
|--------|-------|--------------------------|
| String | name | The name of the header. |
| String | value | The value of the header. |

Table 2-10: Method addHeader parameters

2.4.7 Method setHeaders

Syntax

```
public void setHeaders(WebHeaderCollection
extraHeaders)
```

Description

This method sets the request with the given headers.

Parameters

| Type | Name | Description |
|---------------------|--------------|------------------------|
| WebHeaderCollection | extraHeaders | The headers to be set. |

Table 2-11: Method setHeaders parameters

2.4.8 Method getHeaders

Syntax

```
public WebHeaderCollection getHeaders()
```

Description

This method returns the headers that are set for this request.

2.4.9 Methods getInvocationContext, setInvocationContext

Syntax

```
public Object getInvocationContext()
```

```
public void setInvocationContext(Object
invocationContext)
```

Parameters

| Type | Name | Description |
|--------|-------------------|--|
| Object | invocationContext | An object that is returned with <code>WLResponse</code> to the listener methods <code>onSuccess</code> and <code>onFailure</code> . You can use this object to identify and distinguish different <code>invokeProcedure</code> calls. This object is returned as is to the listener methods. |

Table 2-12: Methods `getInvocationContext`, `setInvocationContext` parameters

2.5 Interface `WLResponseListener`

This interface defines methods that the listener for the `WLClient.invokeProcedure` method implements to receive notifications about the success or failure of the method call.

2.5.1 Method `onSuccess`

Syntax

```
public void onSuccess (WLResponse response)
```

Description

This method is called after successful calls to the `WLClient` `connect` or `invokeProcedure` methods.

Parameters

| Type | Name | Description |
|-------------------------|----------|--|
| <code>WLResponse</code> | response | The response that the server returns, along with any invocation context object and status. |

Table 2-13: Method `onSuccess` parameters

2.5.2 Method `onFailure`

Syntax

```
public void onFailure (WLFailResponse response)
```

Description

This method is called if any failure occurred during the execution of the `WLClient` `connect` or `invokeProcedure` methods.

Parameters

| Type | Name | Description |
|-----------------------|----------|--|
| WLFailResponse | response | A response that contains the error code and error message. Optionally, this response contains the results from the server, and any invocation context object and status. |

Table 2-14: Method onFailure parameters

2.6 Class WLResponse

This class contains the result of a procedure invocation. IBM MobileFirst Platform Foundation passes this class as an argument to the listener methods of the `WLClient` `invokeProcedure` method.

2.6.1 Method getStatus

Syntax

```
public HttpStatusCode getStatus()
```

Description

This method retrieves the HTTP status from the response.

2.6.2 Method getInvocationContext

Syntax

```
public Object getInvocationContext()
```

Description

This method retrieves the invocation context object that is passed when the `invokeProcedure` method is called.

2.6.3 Method getResponseText

Syntax

```
public String getResponseText()
```

Description

This method retrieves the original response text from the server.

2.6.4 Method getResponseJSON

Syntax

```
public JObject getResponseJSON()
```

Description

This method retrieves the response text from the server in JSON format.

2.7 Class `WLFailResponse`

This class extends `WLResponse`. This class contains error codes, messages, the status in `WLResponse`, and the original response `DataObject` from the server.

2.7.1 Method `getErrorCode`

Syntax

```
public WLErrorCode getErrorCode()
```

Description

The `WLErrorCode` section describes the possible errors.

2.7.2 Method `getErrorMsg`

Syntax

```
public String getErrorMsg()
```

Description

This method returns an error message that is for the developer and not necessarily suitable for the user.

2.8 Class `WLProcedureInvocationResult`

This class extends `WLResponse`. This class contains statuses and data that an adapter procedure retrieves.

2.8.1 Method `getResult`

Syntax

```
public JObject getResult()
```

Description

This method returns a `JObject` that represents the JSON response from the server.

2.8.2 Method `isSuccessful`

Syntax

```
public boolean isSuccessful()
```

Description

This method returns `true` if the procedure invocation was technically successful. Application errors are returned as part of the retrieved data, and not in this flag.

2.9 Class `WLProcedureInvocationFailResponse`

This class extends `WLFailResponse`. This class contains statuses and data that an adapter procedure retrieves.

2.9.1 Method `getProcedureInvocationErrors`

Syntax

```
public List<String> getProcedureInvocationErrors()
```

Description

This method returns a list of applicative error messages that are collected while the procedure is called.

2.9.2 Method `getResult`

Syntax

```
public JObject getResult()
```

Description

This method returns a `JObject` that represents the JSON response from the server.

2.10 Class `WLErrorCode`

This class contains the error code and its description that the server returns.

2.10.1 Method `getDescription`

Syntax

```
public String getDescription()
```

Description

This method returns the description of this error code instance.

2.10.2 Method `valueOf`

Syntax

```
public static WLErrorCode valueOf(String errorCode)
```

Description

This method returns the error code instance of the `errorCode` that is given.

Error Codes

UNEXPECTED_ERROR - Unexpected `errorCode` occurred. Please try again.

REQUEST_TIMEOUT - Request timed out.

UNRESPONSIVE_HOST - The service is currently unavailable.

PROCEDURE_ERROR - Procedure invocation errorCode.

PROCEDURE_PROTECTED_ERROR - Procedure is protected.

APP_VERSION_ACCESS_DENIAL - Application version denied.

APP_VERSION_ACCESS_NOTIFY - Notify application version changed.

2.11 Class BaseChallengeHandler

This class is an abstract base class for all challenge handlers.

2.11.1 Constructor

Syntax

```
public BaseChallengeHandler(String realm)
```

Description

This method creates a `BaseChallengeHandler` object for a particular `realm`.

2.11.2 Method handleChallenge(T challenge)

Syntax

```
public abstract void handleChallenge(T challenge)
```

Description

This method must be implemented by the subclass to handle the challenge logic. For example, show a login form in a challenge from a `FormBasedAuthenticator`.

2.11.3 Method submitFailure(WLResponse wlResponse)

Syntax

```
protected void submitFailure(WLResponse wlResponse)
```

Description

You must call this method when the challenge is answered with an error. The method is inherited from `BaseChallengeHandler`. Calling this method tells IBM MobileFirst Platform Foundation that the challenge was unsuccessful and that you no longer want to take any actions to attempt to resolve the problem. This method returns control to IBM MobileFirst Platform Foundation for further handling. For example, call this method only when you know that several

authentication attempts were unsuccessful and you do not want the user to continue attempting to authenticate into the realm.

2.12 Class ChallengeHandler

This class is an abstract class that you must extend to create custom challenge handlers.

2.12.1 Constructor

Syntax

```
public ChallengeHandler(String realmName)
```

Description

This method creates a ChallengeHandler object for a particular realm.

2.12.2 Method isCustomResponse

Syntax

```
public abstract bool isCustomResponse(WLResponse response)
```

Description

You must implement this method and parse the response to determine whether the response from the server is a challenge for this ChallengeHandler. For example, a ChallengeHandler for a realm with a form-based authenticator must parse the response to search for the `j_security_test` parameter and return `true` if found.

2.12.3 Method submitSuccess

Syntax

```
protected void submitSuccess(WLResponse response)
```

Description

You must call this method from the subclass within the `onSuccess` of your ChallengeHandler.

2.12.4 Method submitLoginForm

Syntax

```
protected void submitLoginForm(String requestURL,  
Dictionary<String, String> requestParameters,  
Dictionary<String, String> requestHeaders, int  
requestTimeoutInMs, String requestMethod)
```

Description

This helper method submits a login form by making an HTTP request to the specified `requestURL`.

Parameters

| Type | Name | Description |
|-----------------------------------|---------------------------------|---|
| String | <code>requestURL</code> | The full or relative URL to which the request must be made. |
| Dictionary <String, String> | <code>requestParameters</code> | A Dictionary object with name-value pairs of request parameters. |
| Dictionary <String, String> | <code>requestHeaders</code> | A Dictionary object consisting of the additional headers that must be sent along with the HTTP request. |
| int | <code>requestTimeoutInMs</code> | The time in milliseconds the request must wait before timing out. |
| String | <code>requestMethod</code> | The method to use. Specify GET or POST. |

Table 2-15: Method `submitLoginForm` parameters

2.12.5 Method `submitAdapterAuthentication`

Syntax

```
protected void submitAdapterAuthentication(String
WLProcedureInvocationData invocationData,
WLRequestOptions requestOptions)
```

Description

This helper method submits a response to a challenge made by an `AdapterAuthenticator` by using an `invokeProcedure` call to the adapter procedure.

Parameters

| Type | Name | Description |
|---------------------------|-----------------------------|--|
| WLProcedureInvocationData | <code>invocationData</code> | The <code>WLProcedureInvocationData</code> object that contains the name of the adapter and the procedure. |
| WLRequestOptions | <code>requestOptions</code> | A <code>WLRequestOptions</code> object with request options. |

Table 2-16: Method `submitAdapterAuthentication` parameters

2.13 Class `WLChallengeHandler`

This class is an abstract base class for MobileFirst challenge handlers. You must extend it to implement your own version of a

MobileFirst challenge handler. For example, the `RemoteDisableChallengeHandler`.

2.13.1 Constructor

Syntax

```
public WLChallengeHandler(String realm)
```

Description

This method creates a `WLChallengeHandler` object for a particular realm.

2.13.2 Method `submitChallengeAnswer`

Syntax

```
public void submitChallengeAnswer(Object answer)
```

Description

This method sends the answer back to the server.

2.14 Class `WLPush`

This class contains all the methods that are required to work with Push notifications. You cannot instantiate this class directly. To get a reference to this class, use the [getPush\(\)](#) method of `WLClient`.

To enable Push notifications, add the `pushSender` element to the application descriptor of your Native API application.

```
<nativeWindowsPhone8App>
  ...
  <pushSender>
    <authenticatedPush serviceName="service_name"
keyAlias="key_alias" keyAliasPassword="key_password" />
  </pushSender>
  ...
</nativeWindowsPhone8App>
```

MPNS provides two ways to send push notifications to devices. One, is a non-authenticated mode where the Push requests are throttled. The second is an authenticated mode where push requests are not throttled. Sending authenticated push notification requires authenticating IBM MobileFirst Platform Foundation with MPNS by using an SSL certificate. For more information, see [http://msdn.microsoft.com/en-us/library/windowsphone/develop/ff941099\(v=vs.105\).aspx](http://msdn.microsoft.com/en-us/library/windowsphone/develop/ff941099(v=vs.105).aspx)

If you are not using authenticated push notifications, you can leave the `pushSender` tag empty.

Open the `WMAppManifest.xml` file of your application and under the capabilities section, select `ID_CAP_PUSH_NOTIFICATION`.

2.14.1 Method `registerEventSourceCallback`

Syntax

```
public void registerEventSourceCallback(String alias, String adapter, String eventSource,
WLEventSourceListener eventSourceListener)
```

Description

This method registers a [WLEventSourceListener](#) that is called whenever a notification arrives from the specified event source.

Parameters

| Type | Name | Description |
|-----------------------|---------------------|---|
| String | alias | Mandatory string. A short ID that you use to identify the event source when the push notification arrives. You can provide a short alias, rather than the full names of the adapter and event source. This action frees space in the notification text, which is limited in length. |
| String | adapter | Mandatory string. The name of the adapter that contains the event source. |
| String | eventSource | Mandatory string. The name of the event source. |
| WLEventSourceListener | eventSourceListener | Mandatory listener class. When a notification arrives, the <code>WLEventSourceListener.onReceive</code> method is called. |

Table 2-17: Method `registerEventSourceCallback` parameters

2.14.2 Method `subscribe`

Syntax

```
public void subscribe(String alias, WLPushOptions pushOptions, WLResponseListener respListener)
```

Description

This method subscribes the user to the event source with the specified alias.

Parameters

| Type | Name | Description |
|--------------------|--------------|---|
| String | alias | Mandatory string. The event source alias, as defined in registerEventSourceCallback . |
| WLPushOptions | pushOptions | This instance contains the custom subscription parameters that the event source in the adapter supports. |
| WLResponseListener | respListener | The listener object whose callback methods are called by the MobileFirst runtime when a subscribe call succeeds or fails. |

Table 2-18: Method subscribe parameters

2.14.3 Method unsubscribe

Syntax

```
public void unsubscribe(String alias,
    WLResponseListener respListener)
```

Description

This method unsubscribes the user from the event source with the specified alias.

Parameters

| Type | Name | Description |
|--------------------|--------------|---|
| String | alias | Mandatory string. The event source alias, as defined in registerEventSourceCallback . |
| WLResponseListener | respListener | The listener object whose callback methods are called by the MobileFirst runtime when a subscribe call succeeds or fails. |

Table 2-19: Method unsubscribe parameters

2.14.4 Method isSubscribed

Syntax

```
public void isSubscribed(String alias)
```

Description

This method returns whether the currently logged-in user is subscribed to the specified event source alias.

Parameters

| Type | Name | Description |
|--------|-------|---|
| String | alias | Mandatory string. The event source alias. |

Table 2-20: Method `isSubscribed` parameters

2.14.5 Method `subscribeTag`

Syntax

```
public void subscribeTag(String tagName,
    WLPushOptions pushOptions, WLResponseListener
    respListener)
```

Description

This method subscribes the device to the tag.

Parameters

| Type | Name | Description |
|--------------------|--------------|---|
| String | tagName | Mandatory string. The name of the tag. |
| WLPushOptions | pushOptions | This instance contains the custom subscription parameters that the event source in the adapter supports. |
| WLResponseListener | respListener | The listener object whose callback methods are called by the MobileFirst runtime when a subscribe call succeeds or fails. |

Table 2-21: Method `subscribeTag` parameters

2.14.6 Method `unsubscribeTag`

Syntax

```
public void unsubscribeTag(String tagName,
    WLResponseListener respListener)
```

Description

This method unsubscribes the device from the tag.

Parameters

| Type | Name | Description |
|--------------------|--------------|---|
| String | tagName | Mandatory string. The name of the tag. |
| WLResponseListener | respListener | The listener object whose callback methods are called by the MobileFirst runtime when a subscribe call succeeds or fails. |

Table 2-22: Method `unsubscribeTag` parameters

2.14.7 Method `isTagSubscribed`

Syntax

```
public void isTagSubscribed(String tagName)
```

Description

This method returns whether the device is subscribed to the specified tag.

Parameters

| Type | Name | Description |
|--------|---------|--|
| String | tagName | Mandatory string. The name of the tag. |

Table 2-23: Method `isTagSubscribed` parameters

2.14.8 Property `onReadyToSubscribeListener`

Type

WLOnReadyToSubscribeListener

Access

Read/Write

Description

This property sets the `WLOnReadyToSubscribeListener` callback to be notified when the device is ready to subscribe to push notifications.

2.14.9 Property `notificationListener`

Type

WLNotificationListener

Access

Read/Write

Description

This property sets the `WLNotificationListener` callback to be notified when the push notification arrives.

2.15 Interface `WLOnReadyToSubscribeListener`

This interface defines the method that is notified when a device is ready to subscribe.

2.15.1 Method onReadyToSubscribe

Syntax

```
void onReadyToSubscribe()
```

Description

This method is called when the device is ready to subscribe to push notifications.

2.16 Interface WLEventSourceListener

This interface defines the method that receives the notification message.

2.16.1 Method onReceive

Syntax

```
void onReceive(String properties, String payload)
```

Description

This method is called when the notification arrives from the subscribed event source.

Parameters

| Type | Name | Description |
|--------|------------|---|
| String | properties | A JSON block that contains the notifications properties of the platform. |
| String | payload | A JSON block that contains other data that is sent from the MobileFirst Server. |

Table 2-24: Method onReceive parameters

2.17 Interface WLNotificationListener

This interface defines the method that receives the notification message.

2.17.1 Method onMessage

Syntax

```
void onMessage(String properties, String payload)
```

Description

This method is called when a push notification arrives.

Parameters

| Type | Name | Description |
|--------|------------|---|
| String | properties | A JSON block that contains the notifications properties of the platform. |
| String | payload | A JSON block that contains other data that is sent from the MobileFirst Server. It also contains the tag name for tag and broadcast notification. The tag name appears in the "tag" element. The default tag name for broadcast notification is <code>Push.ALL</code> . |

Table 2-25: Method `onMessage` parameters

2.18 Class `WLPushOptions`

This class contains the subscription parameters that can be specified while subscribing to push notifications.

2.18.1 Constructor

Syntax

```
public WLPushOptions()
```

Description

This method creates a `WLPushOptions` object.

2.18.2 Method `AddSubscriptionParameter`

Syntax

```
public void AddSubscriptionParameter(String name,
String value)
```

Description

Use this method to add a subscription parameter.

Parameters

| Type | Name | Description |
|--------|-------|---|
| String | name | Mandatory. The name of the subscription parameter. |
| String | value | Mandatory. The value of the subscription parameter. |

Table 2-26: Method `AddSubscriptionParameter` parameters

2.18.3 Method `GetSubscriptionParameter`

Syntax


```
public void GetSubscriptionParameter(String name)
```

Description

This method returns the map that contains the subscription parameters.

Parameters

| Type | Name | Description |
|--------|------|--|
| String | name | Mandatory. The name of the subscription parameter. |

Table 2-27: Method `GetSubscriptionParameter` parameters

2.18.4 Property `subscriptionParameters`

Type

Dictionary <String, String>

Access

Read/Write

Description

This property gets/sets the subscription parameters.

2.19 Interface `WLActionReceiver`

This interface allows every implementing object to receive actions and data from the MobileFirst framework.

2.19.1 Method `onActionReceived`

Syntax

```
void onActionReceived(string action, JObject data)
```

Description

This method is called when an action and data arrives.

Parameters

| Type | Name | Description |
|---------|--------|---|
| String | action | Mandatory. Custom String representing an action |
| JObject | data | Optional, custom JObject instance containing key-value pairs. |

Table 2-28: Method `onActionReceived` parameters

Example

```
Class MyReceiver implements WLActionReceiver{
    void onActionReceived(String action, JObject data){
        // process received action
    }
}
```

2.20 Class WL

This class contains the various methods that are related to mixed hybrid features: `actionsender`, `splashscreen`, and `changeserver` API. You can get reference of WL object by using `WL.getInstance()`.

2.20.1 Method showSplashScreen

Syntax

```
public void showSplashScreen()
```

Description

This method shows the default MobileFirst splash screen.

2.20.2 Method hideSplashScreen WL

Syntax

```
public void hideSplashScreen()
```

Description

This method hides the default MobileFirst splash screen if it is shown. This method does nothing if the default MobileFirst splash screen is already hidden.

2.20.3 Method sendActionToJS

Syntax

```
public void sendActionToJS(String action)
```

Description

This method sends action to JavaScript action receivers.

Note: if there is no JavaScript action receiver registered, the action is queued until a JavaScript action receiver is registered.

Parameters

| Type | Name | Description |
|--------|--------|---|
| String | action | Mandatory. Custom String representing an action Example: <code>WL.getInstance().sendActionToJS("doSomething");</code> |

Table 2-29: Method `sendActionToJS` parameters

2.20.4 Method `sendActionToJS`

Syntax

```
public void sendActionToJS(String action, JObject data)
```

Description

Use this method to send action to JavaScript action receivers.

Note: if there is no JavaScript action receiver registered, the action is queued until a JavaScript action receiver is registered.

Parameters

| Type | Name | Description |
|---------|--------|--|
| String | action | Mandatory. Custom String representing an action |
| JObject | data | Optional, custom JObject instance containing key-value pairs. Example: <code>WL.getInstance().sendActionToJS("doSomething");</code> <code>JObject data = new JObject();</code> <code>data.put("customData", 12345);</code> <code>WL.getInstance().sendActionToJS("doSomething", data);</code> |

Table 2-30: Method `sendActionToJS` parameters

2.20.5 Method `addActionReceiver`

Syntax

```
public void addActionReceiver(WLActionReceiver wLActionReceiver)
```

Description

This method registers a new native action receiver with the MobileFirst framework.

Parameters

| Type | Name | Description |
|-------------------------|------------------|---|
| WLActionReceiver | wlActionReceiver | <p>Mandatory. ActionReceiver object that implements the WLActionReceiver interface</p> <p>Example:</p> <pre>MyReceiver myReceiver = new MyReceiver(); WL.getInstance().addActionReceiver(my Receiver);</pre> |

*Table 2-31: Method addActionReceiver parameters***2.20.6 Method removeActionReceiver****Syntax**

```
public void removeActionReceiver(WLActionReceiver
wlActionReceiver)
```

Description

This method unregisters a receiver from receiving actions. After you call this API, the receiver will no longer receive actions.

Parameters

| Type | Name | Description |
|-------------------------|------------------|---|
| WLActionReceiver | wlActionReceiver | <p>Mandatory. ActionReceiver object that implements the WLActionReceiver interface</p> <p>Example:</p> <pre>WL.getInstance().removeActionReceiver (myReceiver);</pre> |

*Table 2-32: Method removeActionReceiver parameters***2.20.7 Method setServerUri****Syntax**

```
public void setServerUri(Uri url)
```

Description

Use this method to set the MobileFirst Server URL to the specified URL.

This method changes the MobileFirst Server URL to the new URL and cleans the HTTP client context. After you call this method, the application is not logged in to any server. The responsibility for checking the validity of the URL is on the developer. If the app uses

push notification, it is the developer's responsibility to unsubscribe from the previous server and subscribe to the new server.

Parameters

| Type | Name | Description |
|------|------|---|
| Uri | url | Mandatory. The URL of the new server, including protocol, IP, port, and context Example: <code>WL.GetInstance().setServerUrl(new URL("http://<ip>:<port>/context"));</code> |

Table 2-33: Method `setServerUrl` parameters

2.20.8 Method `getServerUrl`

Syntax

```
public Uri getServerUrl()
```

Description

This method returns the current MobileFirst Server URL.

Example

```
WL.GetInstance().getServerUrl();
```

Appendix A - Notices

Permission for the use of these publications is granted subject to these terms and conditions.

This information was developed for products and services offered in the U.S.A.

IBM® may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
1623-14, Shimotsuruma, Yamato-shi
Kanagawa 242-8502 Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites

are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Dept F6, Bldg 1
294 Route 100
Somers NY 10589-3216
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs.

Each copy or any portion of these sample programs or any derivative work, must include a copyright notice as follows:

© (your company name) (year). Portions of this code are derived from IBM Corp. Sample Programs. © Copyright IBM Corp. _enter the year or years_. All rights reserved.

Privacy Policy Considerations

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session cookies that collect session information (generated by the application server). These cookies contain no personally identifiable information and are required for session management. Additionally, persistent cookies may be randomly generated to recognize and manage anonymous users. These cookies also contain no personally identifiable information and are required.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent. For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at <http://www.ibm.com/privacy> and IBM's Online Privacy Statement at <http://www.ibm.com/privacy/details> the section entitled "Cookies, Web Beacons and Other Technologies" and the "IBM Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.

Appendix B - Support and comments

For the entire IBM® MobileFirst Platform documentation set, training material and online forums where you can post questions, see the IBM website at:

<http://www.ibm.com/mobile-docs>

Support

Software Subscription and Support (also referred to as Software Maintenance) is included with licenses purchased through Passport Advantage® and Passport Advantage Express. For additional information about the International Passport Advantage Agreement and the IBM International Passport Advantage Express Agreement, visit the Passport Advantage website at:

<http://www.ibm.com/software/passportadvantage>

If you have a Software Subscription and Support in effect, IBM provides you assistance for your routine, short duration installation and usage (how-to) questions, and code-related questions. For additional details, consult your IBM Software Support Handbook at:

<http://www.ibm.com/support/handbook>

Comments

We appreciate your comments about this publication. Please comment on specific errors or omissions, accuracy, organization, subject matter, or completeness of this document. The comments you send should pertain to only the information in this manual or product and the way in which the information is presented.

For technical questions and information about products and prices, please contact your IBM branch office, your IBM business partner, or your authorized remarketer.

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute your comments in any way it believes appropriate without incurring any obligation to you. IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you state.

Thank you for your support.

If you would like a response from IBM, please provide the following information:

- Name
- Address
- Company or Organization
- Phone No.
- Email address

