



Gateways Installation Note

**TIVOLI® NETCOOL® GATEWAY FRAMEWORK
GATEWAYS INSTALLATION NOTE**

Note: Before using this information and the product it supports, read the information in on page 15.

This edition applies to Version 3.5 of IBM® Tivoli® Netcool® Gateway Framework and to all subsequent releases and modifications until otherwise indicated in new editions.

© Copyright International Business Machines Corporation, 2011. All rights reserved.

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Table of Contents

1	Introduction	4
2	Intended Audience	4
2.1	Prerequisites	4
3	Gateway Package Naming Convention	5
4	Installation Procedure	6
4.1	Gateway Framework Installation.....	6
4.2	Vendor Gateway Installation	6
4.3	Gateway Configuration Installation	7
5	Installation layout	8
5.1	Gateway Framework layout	8
5.2	Vendor Gateway layout.....	9
5.3	Gateway Configuration layout	9
6	Post-Installation Procedure	10
7	Upgrade Procedures	11
7.1	Software Requirement	11
7.2	New Configuration Structure	11
7.3	Configuration of properties file	12
8	Running Gateway.....	13
9	Associated Tasks.....	13
10	Removing Gateway Packages	14
Appendix A	Notices and Trademarks.....	15

1 Introduction

This document describes the steps required to install and run a Gateway. The steps described here are generic to all Productised Gateways from version 3.4 and above.

The layout of the Gateways installation was altered at the 3.4 release, and this document only applies to releases from this point.

As well as this document, readers should refer to the following documents before proceeding to install the Gateway:

- the Gateway Configuration Distribution Note
- the appropriate Vendor Gateway Distribution Note
- the Gateway Framework Distribution Note

2 Intended Audience

This document is intended for Vallent Consultants and partners deploying the Gateway.

2.1 Prerequisites

The Gateway Framework requires Perl version 5.6.1 installed. Perl is not included with the Gateways package. Download the appropriate Perl version and build Perl on a supported architecture. Refer to the Perl Build Instructions for more details. The following are the supported Perl build architecture for the platforms respectively.

Operatin System Version(s)	Chipset	Perl Build Architecture
HP-UX 11.11	PA-RISC2.0	PA-RISC2.0
Solaris 9 & 10	SPARC	sun4-solaris
Tru64 UNIX 5.0	DEC-ALPHA	alpha-dec_osf
Red Hat Enterprise Linux Server 4 & 5	x86-32, and x86-64	i686-linux
	PPC64	ppc64-linux
AIX 5.3	PPC64	aix

Note: x86-64 includes EM64T (Xeon) and AMD64 (Opteron); x86-32 is Intel 32-bit and AMD Athlon

3 Gateway Package Naming Convention

The Gateway Framework package has the following naming convention:

`gways-gateway-framework-3.w.x.p.tar.Z`

e.g.

`gways-gateway-framework-3.5.1.9.tar.Z`

A Vendor Gateway package has the following naming convention:

`gways-<vendor/data>-<network/format>-3.w.y.p.tar.Z`

e.g.

`gways-ericsson-gsm-3.5.0.1.tar.Z`

`gways-3gpp-xml-3.5.0.1.tar.Z`

A Gateway Configuration package has the following naming convention:

`gways-cfg-<techpack-name>-<techpack_version>.tar.Z`

e.g.

`gways-cfg-gsm-siemens-nss-sr13-3.4.0.2.tar.Z`

`gways-cfg-umts-ericsson-sgsn-r8-1.0.0.1.tar.Z`

where:

`<vendor/data>` is the name of the network vendor e.g. nokia, ericsson or standards body
data type e.g. xml, asn1

`<network/format>` is the network e.g. gprs, cdma, or the data format e.g. XML.

The version numbers are described in the table below:

Version Numbers	Description
Major – w	Gateway major release number
Minor – x	Gateway Framework minor release number
Point - y	Vendor Gateway minor release number
Point - p	Patch release number

NOTE: Older Gateway Configuration packages will have `vallent-vt-` prefix before `<gways-cfg-techpack-name>`

4 Installation Procedure

The installation procedure is broken into 3 stages:

1. Installation of the Gateway Framework,
2. Installation of the Vendor Gateway,
3. Installation of the Gateway Configuration.

Step 1 and 2 only needs to be completed if a version of the Gateway Framework and Vendor Gateway has not already been installed on the server.

Create a Gateways root directory where all the Gateway Framework, Vendor Gateways and Gateway Configurations will be installed. A common name that can be used is “gways”. The full path to gways must be set for the environment variable **GATEWAY_ROOT**.

NOTE: If a package is being redeployed, it is important to remove the previously installed package. Procedures for removing an installed gateway package are defined in a later chapter of this document.

4.1 Gateway Framework Installation

Within the **GATEWAY_ROOT** directory, the Gateway Framework is installed in the “gateway-framework” directory. This directory will be referenced by all Gateway Configurations. This path will be set for the environment variable **GATEWAY_FRAMEWORK** by default.

1. Uncompress the package:

```
zcat gways-gateway-framework-3.w.x.p.tar.Z | tar xf -
```

Please refer to Section 5.1 for the Gateway Framework layout. These directories contain the common modules and functions of the Gateway Framework, and will be referenced by the Gateway Configuration Installation.

4.2 Vendor Gateway Installation

The following steps should be undertaken to install a Vendor Gateway. Within the **GATEWAY_ROOT** directory, all Vendor Gateways are installed in the “modules” directory with their respective vendor technology directory name. This directory will be referenced by all Gateway Configurations that requires it. This path will be set for the environment variable **VENDOR_GATEWAY** by default.

1. Uncompress the package:

```
zcat gways-<vendor/data>-<network/format>-3.w.y.p.tar.Z | tar xf -
```

Please refer to Section 5.2 for the Vendor Gateways layout. These directories contain the vendor gateway modules and functions of the Vendor Gateways, and will be referenced by the Gateway Framework start script.

4.3 Gateway Configuration Installation

The following steps should be undertaken to install a Gateway Configuration. Within the `GATEWAY_ROOT` directory, the Gateway Configuration is installed in the “`config`” directory with each respective vendor sub-system and release directory. These directories name are a unique for each vendor sub-system and release.

1. Uncompress the package:

```
zcat gways-cfg-<techpack-name>-<techpack_version>.tar.Z | tar xf -
```

Please refer to Section 5.3 for the Vendor Gateways layout. This directory contains the gateway configuration files of the Gateways Configuration, and will be referenced by the Gateway Framework start script.

For additional configurations of the Gateway Configuration, please follow the instructions in the Gateway Framework User Guide, and the respective Vendor Gateway User Guide for the Gateway Configuration.

If the the `StatisticsConfig.pm` script is configured, then create the `file_statistics` and `block_statistics` directory in the `config` directory.

eg. `$GATEWAT_ROOT/config/<vendor-subsys>/file_statistics`
 `$GATEWAT_ROOT config/<vendor-subsys>/block_statistics`

5 Installation layout

A Gateway installation is split into 3 stages:

- The installation of the Gateway Framework,
- The installation of the Vendor Gateways,
- The installation of the Gateway Configuration, and post installation setup.

This allows a single Gateway Framework and Vendor Gateways installation to be used by multiple Gateway Configuration solutions, with subsequent ease of maintenance and version control.

5.1 Gateway Framework layout

Within the Gateway Framework there are 5 subdirectories. None of these directories need to be edited or amended in any way during installation.

These directories and their contents are described below:

1. The `perl_extensions` contains the Gateway Framework modules used by both the Framework and Vendor Gateway.
2. The `parsersrc` directory contains the perl script that controls the Gateway execution.
3. The `example` directory contains examples of configuration files and usage of the Gateway.
4. The `docs` directory contains documentation on the configuration and use of the Gateway Framework.
5. The `vstart` directory contains 4 main files (`EngineConfig.pm`, `UserConfig.pm`, `gateway_start.sh` and `gateway_version.sh`). It can also contain configuration files for each network type of the Gateway.
 - `EngineConfig.pm` is the configuration file of the first stage of the Gateway.
 - `UserConfig.pm` that is a user configurable Perl module for configuring the Gateway Post Parser.
 - `TransferConfig.pm` that can be used to configure the transfer in of raw files, and transfer out of processed LIF files.
 - The `gateway_start.sh` script that is used to start the Gateway.

5.2 Vendor Gateway layout

Within the Vendor Gateway there are 4 subdirectories. They will be contained within a directory called `modules`. None of these directories need to be edited or amended in any way during installation.

These directories and their contents are described below:

1. The `parsersrc` directory contains the parser modules for the Vendor Gateway, which contains the specific functionality to parse the specific format of the vendor's data. You should NOT change anything under this directory.
2. The `docs` directory contains documentation on the configuration and use of the Vendor Gateway and its specific Post Parser rules.
3. The `perl_extensions` only exists for certain Vendor Gateways. It contains the compiled libraries of any Vendor Gateway modules which require them.
4. The `vstart` directory may contain a combination of default configuration files specific to the Vendor Gateway. (e.g. `EngineConfig.pm`, `UserConfig.pm`, `StatisticsConfig.pm`, `TransferConfig.pm`). The `StatisticsConfig.pm` and `TransferConfig.pm` file can be obtained from the gateway framework example directory.

5.3 Gateway Configuration layout

Within the Gateway Configuration there are configuration directories specific for every vendor sub-system and data revision. They will be contained within a directory called `config`. The contents of these are described below

1. The `docs` directory contains documentation on the configuration for each vendor data revision supported.
2. The configuration directories are named based on the vendor sub-system, e.g. `ericsson-bss`. Within each vendor sub-system directory contains the directories for each data revision supported, e.g. `r12_ascii`, `r12_asn1`. These directories contain the configuration files that are to be referenced by the Gateway Framework to parse the vendor data accordingly. (e.g. `EngineConfig.pm`, `UserConfig.pm`, `StatisticsConfig.pm`, `TransferConfig.pm`, `NotificationConfig.pm`). The `StatisticsConfig.pm`, `TransferConfig.pm` and `NotificationConfig.pm` file can be obtained from the gateway framework example directory.
3. If the Statistics Configuration is configured, the `file_statistics` and `block_statistics` directory must be created manually by the user, and the path specified in the `StatisticsConfig.pm`.

6 Post-Installation Procedure

Gateway Framework

Set the following environment variables accordingly.

- GATEWAY_ROOT: the base path to where all Gateway components have been installed

```
GATEWAY_ROOT=${WMCROOT}/gways
```

- TZ: the time zone as defined in RFC 822

```
Universal:  GMT, UT
```

```
US zones  :  EST, EDT, CST, CDT, MST, MDT, PST, PDT
```

```
Military  :  A to Z (except J)
```

```
Other     :  +HHMM or -HHMM
```

```
ISO 8601  :  +HH:MM, +HH, -HH:MM, -HH
```

- PERL5_BASE: the full path to where Perl base is installed, which contains the `bin` and `lib` directories.

```
PERL5_BASE=/usr
```

- PERL5: the path of the perl command, which is commonly in the `bin` directory of PERL5_BASE. Please set it if otherwise.

```
PERL5=${PERL5_BASE}/bin/perl
```

Gateway Configuration

The Gateway Framework will make use of properties file for its operation. This file must exist within the Gateway Configuration release directory and updated accordingly, for example :

```
$GATEWAY_ROOT/config/siemens-bss/br10/properties
```

where `siemens-bss` is the vendor and `br10` is the release version. A copy of properties file is available within `$GATEWAY_ROOT/gateway-framework/vstart` directory as a template.

Create the spool directories for input files, intermediate files, and loader files. Set the directories accordingly in the `properties` file for the variables below:

```
IN_DIR=./spool/input_d
```

```
INT_DIR=./spool/inter_d
```

```
OUT_DIR=./spool/output_d
```

Create the `file_statistics` and `block_statistics` directories within the `vendor-subsys` directory if the `StatisticsConfig.pm` is configured for the Gateway Configuration.

To enable notification for monitoring services, copy the `NotificationConfig.pm` from the Gateway Framework example directory and edit it return the relevant array rule for the respective monitoring service, i.e. either `@rules_NPR`, `@rules_MPM`, or `@rules_ITM`.

7 Upgrade Procedures

All Gateway Configurations that was previously configured for the Gateway release 3.3.1 and earlier must be migrated into the configuration structure for Gateway release 3.4 in order to be compatible with Gateway Framework 3.5.

7.1 Software Requirement

Gateway release 3.5 requires Perl version 5.6.1. Please refer to the Perl Build Instruction to compile and install Perl on your system.

7.2 New Configuration Structure

The new directory structure for the Gateway Configurations for Gateway release 3.4 and above is as follow:

```
$GATEWAY_ROOT
|-gateway-framework
|-modules
|   |-<vendor-gateways>
|-config
|   |-<vendor-subsys>
|       |-<data_version>
```

The following steps describe the procedures to upgrade Gateway configurations from Gateway release 3.3.1 and below into 3.4:

1. Create the new configuration directory for the Gateway configurations within the `GATEWAY_ROOT` directory:

```
$GATEWAY_ROOT/config/<vendor-subsys>/<data_version>
```

2. Copy the properties and configuration files from the old Gateway configuration into the new directory above, except for `gateway_start.sh`, `gateway_version.sh`, `cpan_check.pm` and `cpan_list`.
3. Update the `properties` file to include the log level and log filename in the following environment variables:

```
LOG_LEVEL=5
LOG_FILE=</log_path/log_filename>
```

These variables were defined in the old Gateway configurations `gateway_start.sh`.

7.3 Configuration of properties file

New environment variables are required in the `properties` file for each Gateway Configuration migrated from Gateway 3.4 and earlier. Below is the list of variables new in Gateway 3.5:

- `LOG_LEVEL` - specifies the log level which was previously defined in `gateway_start.sh`.
- `LOG_FILE` - specifies the path and file name of the log file which was previously defined in `gateway_start.sh`.
- `MAX_NUMBER_OF_PROCESSES` - specifies the number of Gateway processes allowed to be spawned for multiple independent blocks configured in the `UserConfig.pm`. By default this variable should be set to 1.

8 Running Gateway

To start the Gateway, run `gateway_start.sh` within the Gateway Framework `vstart` directory by passing in the Vendor Sub-system and Release of the vendor data as arguments:

```
gateway_start.sh -vendor <vendor-subsys> -release <data_version>
```

where:

<code><vendor-subsys></code>	The Vendor and Subsystem, e.g. 'ericsson-bss'. The name coincides with the Gateway Configuration directory name.
<code><data_version></code>	The data version for the Vendor Subsystem, e.g. 'r12_ascii'. The name coincides with the Gateway Configuration vendor release directory name.

Configure the crontab file for the `gateway_start.sh` command as above so that the Gateway runs at the required frequency.

9 Associated Tasks

House keeping scripts should be configured to remove '.bad' files from the input, intermediate and output directories, after these files have been there for a certain amount of time.

10 Removing Gateway Packages

The Gateway package removal scripts are typically found in the Tivoli Netcool Performance Manager for Wireless' Administration sub-directory for gateways:

```
${WMCROOT}/admin/software/gateways/
```

To remove a specific Gateway package, locate and run the `<gateway_package>.remove` script.

```
${WMCROOT}/admin/software/gateways/<gateway_package>.remove
```

Where `<gateway_package>` is the name of the gateway component package to be removed. The gateway package naming convention is outlined in a previous section.

For example, the following scripts are used:

- To remove the Gateway Framework package
`gways-gateway-framework.remove`
- To remove a Vendor Gateway package such as 3gpp-xml
`gways-3gpp-xml.remove`
- To remove a Gateway Configuration package such as siemens-bss
`gways-cfg-siemens-bss.remove`

Appendix A Notices and Trademarks

This appendix contains the following:

- Notices
- Trademarks

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in all countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk NY 10504-1785
U.S.A.*

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
1623-14, Shimotsuruma, Yamato-shi
Kanagawa 242-8502 Japan*

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
224A/101
11400 Burnet Road
Austin, TX 78758
U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Trademarks

IBM, the IBM logo and ibm.com are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at <http://www.ibm.com/legal/copytrade.shtml>.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.



Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other company, product or service names may be trademarks or service marks of others.



Printed in the U.S.A.