

# Release Notes

**Prospect® 8.0.4 P5 (8.0.4.5)**



## **DOCUMENT CONTROL**

Issue Number: 01

Issue Date: 11 April 2008

Version: 8.0.4 P5 (8.0.4.5)

Build: 8.0.4.5 b2

## **OWNERSHIP & CONFIDENTIALITY**

*No part of this document may be disclosed orally or in writing, including by reproduction, to any third party without the prior written consent of Vallent Corp. This document, its associated appendices, and any attachments remain the property of Vallent Corp. and shall be returned upon request.*

## Table of Contents

<b>1</b>	<b><i>Description</i></b>	<b>4</b>
<b>2</b>	<b><i>Resolved Issues</i></b>	<b>5</b>
<b>3</b>	<b><i>Installation and Upgrade Instructions</i></b>	<b>6</b>
<b>4</b>	<b><i>Useful Hints</i></b>	<b>9</b>
<b>5</b>	<b><i>Customer Support</i></b>	<b>12</b>
<b>6</b>	<b><i>Manifest</i></b>	<b>13</b>

## 1 Description

Prospect® 8.0.4 P5 is a patch release for Prospect. It is a cumulative release and can be applied to 8.0.4.1 release or to one of the Prospect patches, from 8.0.4 P2 through 8.0.4 P4, in order to bring a system up to the 8.0.4 P5 release point.

Check you have a prerequisite version installed on your system, by running the `show_installed` command. Notice that 8.0.4.1 release is displayed as 8.0.4.1, 8.0.4 P2 as 8.0.4.2, 8.0.4 P3 as 8.0.4.3 and 8.0.4 P4 as 8.0.4.4.

This patch contains the fixes to some issues faced during the BH job execution and an enhancement to the 'ps-mgr purge' command.

## 2 Resolved Issues

This release includes the following resolved issues:

<i>DDTS / SRS or APAR</i>	<i>Description</i>
SEADE66354	SOFT ALARM: Code cleanup needed to schedcheck.sql. We have areas where logging prep is performed ant then discarded.
SEADE66777	Ensure minimum enqueue times is 1 second to prevent flood status msg
SEADE67198 / SRS 39525	Summation performance enhancements - round 2
SEADE67258	Active Heartbeat Queue failures causing decrementing license IN_USE spawning more jobs to start when the current jobs are still running
SEADE67756	BH_DRIVER_TMP and its INDEX needs to be moved to TRAFFIC_LARGE tablespace
SEADE67708	Order of Copy in BH JOB is making it to run longer times
SEADE67118	AutoClean package for clean_ilot and clean_schedule share parameter AutoCleanMaxLoops. Need to make them independent for each feature.
SEADE67897 / SRS41749	SOFT ALARM: clean_ilot does not check for Job Type 2 (SA) before run causing ORA-01410
SEADE68331	BH Slices: ability to splice a table into sections for BH copy purposes
SEADE68461	Import/Export sometimes fails to import udcs
SEADE66544	SBH and reports fail due to fx dataserver restart
SEADE68574	Some percentage values incorrectly truncated in reports
SEADE68590 / IZ09131	Summation job does not work on ericsson ggu
SEADE68058	PartMaint enhancements
SEADE68839 / IZ14072	BH Slicing doesn't work properly, due to overlapping instance in slices
SEADE68933 / IZ15501	BH optimistic insert
SEADE68939 / IZ15512	Incremental Summation enhancement
SEADE69008 / IZ14162	Busy Hour Update Copy does not show in ps-mgr watch command
SEADE69134 / IZ15662	UDC computations incorrect in 8.0.4.x
SEADE68988 / IZ13905	Need rg_common.sql to set hash_area_size
SEADE69274 / IZ13925	BHUpdate log shows #INVALID# message during copy to BH table
SEADE69079 / IZ14994	ORA-01410 errors occur when reports and soft alarms run
SEADE69384	Improve the 'ps-mgr purge' command
SEADE69523 / IZ18779	pm_weekly summations take longer times as time progresses

## 3 Installation and Upgrade Instructions

This section describes how to install the Prospect patch, 8.0.4 P5. This patch can be uninstalled (see section 3.7).

### 3.1 Network Timeouts

If your system has a security policy in place such that a session is disconnected after a lengthy period of apparent inactivity, you should disable it during this upgrade. There is the possibility that an upgrade can take a while to run. Since no user input is required during the most of the upgrade, this can make the upgrade session appear idle. If timeouts are not disabled, the upgrade terminal could be disconnected during the upgrade.

### 3.2 Installation Privileges Required

Privilege	Required
Oracle flexpm user DBA role	Yes
UNIX flexpm user in DBA group	Yes
Root privilege required	No
Oracle sys user password set to default (change_on_install)	No

### 3.3 Install Procedure Syntax

```
install.sh [ -install | -uninstall | -help ]
-install : installs the wmn_pkgb.sql
-uninstall : removes the current hotfix file version and replaces
it with the previous version
-help : help
```

The scripts depend on \$DB\_CONNECT, make sure you have this setup correct.

### 3.4 Pre-Installation Instructions

#### 3.4.1 Pre-Install Procedure

1. Login as flexpm and source the profile from FLEXPY\_HOME directory.  
\$ ./.profile
2. Copy 8.0.4-PROSPECT-IF0005.tar.gz into this directory.
3. Uncompress the file.  
\$ gunzip 8.0.4-PROSPECT-IF0005.tar.gz
4. Untar the package. It will create a subdirectory  
(patches/Core8.0.4\_P5) in \$FLEXPY\_HOME and untar the files in

- ```
to this directory.  
$ tar -xvpf 8.0.4-PROSPECT-IF0005.tar  
5. Install the Patch by following the instructions in Section 3.5  
below.
```

### 3.5 Installation Instructions

**Important!** If there are no errors from the Pre-Installation section, then continue with the following steps:

1. Login as flexpm and source the profile from FLEXP\_M\_HOME directory.  
\$ ./.profile
2. Go to the Patch directory.  
\$ cd \$FLEXP\_M\_HOME/patches/Core8.0.4\_P5
3. If Prospect Web is accessing this Prospect installation, then use the admin tool to disable the corresponding datasource.
4. Install the Patch.  
\$ install.sh -install 2>&1 | tee install.log

Note: the patch installation program will automatically stop the middleware, install the patch files, and restart the middleware.

### 3.6 Post-Installation Instructions

#### 3.6.1 Resource the Profile

If you have not done so already, log off and log on as flexpm.

#### 3.6.2 Re-enable the datasource in Prospect Web

Once the installation has completed, re-enable the datasource in Prospect Web (if you disabled it before starting the patch installation)

1. If you disabled any datasources in step 3.5.3, then use the admin tool to re-enable them.

### 3.7 Uninstall Procedure

1. Log in as flexpm and source the profile from the FLEXP\_M\_HOME directory.  
\$ ./.profile
2. Go to \$FLEXP\_M\_HOME/patches/Core8.0.4\_P5 directory.  
\$ cd \$FLEXP\_M\_HOME/patches/Core8.0.4\_P5
3. If Prospect Web is accessing this Prospect installation, then use the admin tool to disable the corresponding datasource.
4. Remove the patch.  
\$ install.sh -uninstall 2>&1 | tee uninstall.log

Copyright 2008 IBM Corporation. All rights reserved.

- 
5. If you disabled any datasources in step 3.7.3, then use the admin tool to re-enable them.

Note: the patch un-installation program will automatically stop the middleware, uninstall the patch files, and restart the middleware.

## 4 Useful Hints

### 4.1 New Configuration Option

#### 4.1.1 PartMaintSessions

PartMaintSessions is the maximum number of slave sessions that can be created during the part\_maint job. The default is 1 session.

Part\_maint is currently designed as a single-session Prospect job. As the volume of work climbs due to an increase in the number of tables (i.e. pegs) and an increase in the volume of data (i.e. larger networks), we need to move to a higher throughput, multiple-session design. This new design allows part\_maint to take advantage of the increased number of CPU's available on these large systems. Part\_maint is enhanced to use a single master session and a configurable number of slave sessions to perform the operations.

The recommended value is 8 and can be incremented gradually up to a maximum value of 16, depending on the number of CPUs.

To set the number of sessions, do the following:

```
$ sqlplus $DB_CONNECT  
SQL> exec wm_sysval.forcesysval('PartMaintSessions', '8');  
SQL> commit;
```

To check the value:

```
SQL> select * from wm_system_values_v where name =  
'PartMaintSessions';  
NAME VALUE  
PartMaintSessions 8
```

#### 4.1.2 BHSessions

BHSessions is the maximum number of slave sessions that can be created during the BH job. The default is 1 session.

The typical values chosen range between 4 and 16 depending on the number of available CPUs. Each session requires its own CPU. Available CPUs vary depending on the configuration and load on the target box.

##### 4.1.2.1 How to set BHSessions parameter

To set the number of sessions , do the following:

```
$ sqlplus $DB_CONNECT  
SQL> exec wm_sysval.forcesysval('BHSessions', '4');  
SQL> commit;
```

To check the value:

Copyright 2008 IBM Corporation. All rights reserved.

---

```
SQL> select * from wm_system_values_v where name = 'BHSessions';
      NAME          VALUE
      BHSessions    4
```

### 4.1.3 BHSlices

BHSlices is the maximum number of sliced tasks that can be created during the BH job. The default is equal to the BHSessions parameter value.

#### 4.1.3.1 How to set BHSlices parameter

To enable the BH Slicing and set the number of slices, do the following:

```
$ sqlplus $DB_CONNECT
SQL> exec wm_sysval.forcesysval('BHSliceThreshold', '10000');
SQL> commit;

SQL> exec wm_sysval.forcesysval('BHSessions', '8');
SQL> commit;

SQL> exec wm_sysval.forcesysval('BHSlices', '8');
SQL> commit;
```

To check the values:

```
SQL> select * from wm_system_values_v where name =
'BHSliceThreshold';
      NAME          VALUE
      BHSliceThreshold 10000

SQL> select * from wm_system_values_v where name = 'BHSessions';
      NAME          VALUE
      BHSessions    8

SQL> select * from wm_system_values_v where name = 'BHSlices';
      NAME          VALUE
      BHSlices      8
```

For appropriate parameter values, please, contact IBM Customer support.

Copyright 2008 IBM Corporation. All rights reserved.

#### 4.1.4 SummationSessions

SummationSessions is the maximum number of slave sessions that can be created during the SUMMATION job. The default is 1 session.

The typical values chosen range between 4 and 16 depending on the number of available CPUs. Each session requires its own CPU. Available CPUs vary depending on the configuration and load on the target box.

##### 4.1.4.1 How to set SummationSessions parameter

To set the number of sessions, do the following:

```
$ sqlplus $DB_CONNECT  
SQL> exec wm_sysval.forcesysval('SummationSessions', '4');  
PL/SQL procedure successfully completed.  
SQL> commit;  
Commit complete.
```

To check the value:

```
SQL> select * from wm_system_values_v where name like 'Summ%';  
NAME                      VALUE  
-----  
SummationSessions          4
```

#### 4.1.5 SummationParallelHint

The Summation query has been modified to support a PARALLEL option as part of the INSERT/SELECT Summation query. This value is controlled by a new System Parameter, which can be tuned and set by the IBM support personnel.

#### 4.2 Soft Alarm Trigger

This patch fixes a known Soft Alarm issue introduced in code 8.0.4.1 which suppresses the trigger of soft alarms. Please apply this patch immediately to all 8.0.4.1 based applications which use the soft alarm feature.

---

## 5 Customer Support

Contact IBM Customer Support if a problem is encountered during the installation of this patch.

---

## 6 Manifest

Prospect 8.0.4 P5 contains:

```
patches
patches/Core8.0.4_P5
patches/Core8.0.4_P5/backup
patches/Core8.0.4_P5/backup/install
patches/Core8.0.4_P5/backup/install/db
patches/Core8.0.4_P5/backup/install/db/Oracle8i
patches/Core8.0.4_P5/backup/install/db/Oracle8i/bh
patches/Core8.0.4_P5/backup/install/db/Oracle8i/cfgtool
patches/Core8.0.4_P5/backup/install/db/Oracle8i/part_maint
patches/Core8.0.4_P5/backup/install/db/Oracle8i/rg
patches/Core8.0.4_P5/backup/install/db/Oracle8i/scheduler
patches/Core8.0.4_P5/backup/install/db/Oracle8i/scheduler/except
patches/Core8.0.4_P5/backup/install/db/Oracle8i/scheduler/sched
patches/Core8.0.4_P5/backup/install/db/Oracle8i/softalarm
patches/Core8.0.4_P5/backup/install/db/Oracle8i/softalarm/sacheck
patches/Core8.0.4_P5/backup/install/db/Oracle8i/summarize
patches/Core8.0.4_P5/backup/install/db/Oracle8i/utility
patches/Core8.0.4_P5/backup/install/db/Oracle8i/wmllib
patches/Core8.0.4_P5/backup/install/pm
patches/Core8.0.4_P5/backup/install/pm/adm
patches/Core8.0.4_P5/backup/install/pm/bin
patches/Core8.0.4_P5/backup/install/pm/lib
patches/Core8.0.4_P5/backup/install/pm/lib/wm
patches/Core8.0.4_P5/backup/install/pm/run
patches/Core8.0.4_P5/backup/install/sw
patches/Core8.0.4_P5/backup/install/sw/oracle
patches/Core8.0.4_P5/install
patches/Core8.0.4_P5/install/compile-schema.sql
patches/Core8.0.4_P5/install/Core8.0.4_P5.build
patches/Core8.0.4_P5/install/db
patches/Core8.0.4_P5/install/db/Oracle8i
patches/Core8.0.4_P5/install/db/Oracle8i/bh
```

```
patches/Core8.0.4_P5/install/db/Oracle8i/bh/BH_Driver_tmp.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/bh/BH_Update.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/bh/BH_UpdatePack.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/bh/busyhour_task.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/bh/busyhour_taskDrop.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/cfgtool  
patches/Core8.0.4_P5/install/db/Oracle8i/cfgtool/create_schema_objects.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/createTables.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/createTrigger.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/Makefile  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/part_maint.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/part_maintDrop.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/part_maintPack.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/part_stat.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/part_statDrop.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/part_task.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/part_maint/part_taskDrop.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/rg  
patches/Core8.0.4_P5/install/db/Oracle8i/rg/rg_common.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/scheduler  
patches/Core8.0.4_P5/install/db/Oracle8i/scheduler/except  
patches/Core8.0.4_P5/install/db/Oracle8i/scheduler/except/except.sql  
patches/Core8.0.4_P5/install/db/Oracle8i/scheduler/sched  
patches/Core8.0.4_P5/install/db/Oracle8i/scheduler/sched/schedule_maint
```

```
patches/Core8.0.4_P5/install/db/Oracle8i/softalarm
patches/Core8.0.4_P5/install/db/Oracle8i/softalarm/sacheck
patches/Core8.0.4_P5/install/db/Oracle8i/softalarm/sacheck/schedc
heck.sql
patches/Core8.0.4_P5/install/db/Oracle8i/summarize
patches/Core8.0.4_P5/install/db/Oracle8i/summarize/CreateSumTab.s
ql
patches/Core8.0.4_P5/install/db/Oracle8i/summarize/summarize.sql
patches/Core8.0.4_P5/install/db/Oracle8i/summarize/summarizePack.
sql
patches/Core8.0.4_P5/install/db/Oracle8i/summarize/summ_task.sql
patches/Core8.0.4_P5/install/db/Oracle8i/summarize/summ_taskDrop.
sql
patches/Core8.0.4_P5/install/db/Oracle8i/utility
patches/Core8.0.4_P5/install/db/Oracle8i/utility/autoclean.sql
patches/Core8.0.4_P5/install/db/Oracle8i/utility/autocleanPack.sq
l
patches/Core8.0.4_P5/install/db/Oracle8i/utility/sched_immediate_
pkg.sql
patches/Core8.0.4_P5/install/db/Oracle8i/utility/sched_immediate_
pkgb.sql
patches/Core8.0.4_P5/install/db/Oracle8i/wmlib
patches/Core8.0.4_P5/install/db/Oracle8i/wmlib/wm_sysval_pkg.sql
patches/Core8.0.4_P5/install/db/Oracle8i/wmlib/wm_sysval_pkgb.sql
patches/Core8.0.4_P5/install/dew_drops.sql
patches/Core8.0.4_P5/install/downgrade_summations.sql
patches/Core8.0.4_P5/install/patch.sql
patches/Core8.0.4_P5/install/pm
patches/Core8.0.4_P5/install/pm/adm
patches/Core8.0.4_P5/install/pm/adm/exp_udc_convert.pl
patches/Core8.0.4_P5/install/pm/adm/import_docs.sh
patches/Core8.0.4_P5/install/pm/adm/part_mask.sh
patches/Core8.0.4_P5/install/pm/adm/wmpm-init
patches/Core8.0.4_P5/install/pm/adm/wmpm.sh
patches/Core8.0.4_P5/install/pm/bin
```

Copyright 2008 IBM Corporation. All rights reserved.

```
patches/Core8.0.4_P5/install/pm/bin/rgp
patches/Core8.0.4_P5/install/pm/lib
patches/Core8.0.4_P5/install/pm/lib/wm
patches/Core8.0.4_P5/install/pm/lib/wm/libexpressions.so
patches/Core8.0.4_P5/install/pm/lib/wm/libReportEngine.so
patches/Core8.0.4_P5/install/pm/lib/wm/libWmGateway.so
patches/Core8.0.4_P5/install/pm/run
patches/Core8.0.4_P5/install/pm/run/bhd.sh
patches/Core8.0.4_P5/install/pm/run/bhrgp.sh
patches/Core8.0.4_P5/install/pm/run/download
patches/Core8.0.4_P5/install/pm/run/ps-mgr
patches/Core8.0.4_P5/install/pm/run/rgp.sh
patches/Core8.0.4_P5/install/pm/run/udr.sh
patches/Core8.0.4_P5/install/recompile_view.sh
patches/Core8.0.4_P5/install/schema_patch.sql
patches/Core8.0.4_P5/install/sw
patches/Core8.0.4_P5/install/sw/oracle
patches/Core8.0.4_P5/install/sw/oracle/compile-schema.sql
patches/Core8.0.4_P5/install/unpatch.sql
patches/Core8.0.4_P5/install/upgrade_summations.sql
patches/Core8.0.4_P5/install.sh
```

